



MPE REPORT

Product Name	Module
Model	TALONCV001
FCC ID	2AAQ6TALONCV001
Client	MONTAGE SYSTEMS, INC.
Manufacture	Asiatelco Technologies Co.
Date of issue	September 11, 2013

Approved by 杨伟忠

Director

Revised by 凌致远

Manager

Performed by 沈峰

Engineer

Test By

Company: TA Technology (Shanghai) Co., Ltd.
Address: No.145, Jintang Rd, Tangzhen Industry Park, Pudong Shanghai, China
Contact: Yang Weizhong
Telephone: +86-021-50791141/2/3
Fax: +86-021-50791141/2/3-8000
Website: <http://www.ta-shanghai.com>
E-mail: yangweizhong@ta-shanghai.com

TA Technology (Shanghai)Co.,Ltd.

Test Report

Report No.: RXA1307-0096MPE

Page 2 of 5

Maximum Permissible Exposure

Type of EUT: Module

FCC ID: 2AAQ6TALONCV001

Manufacturer: Asiatelco Technologies Co.

Model: TALONCV001

Maximum conducted output power (measured) and antenna Gain:

Band	Time-average maximum tune up procedure (dBm)	Antenna Gain (dBi)
CDMA 800	25	2
CDMA 1900	25	2

According to section 1.1310 of FCC 47 CFR Part 1, limits for maximum permissible exposure (MPE) are as following

TA Technology (Shanghai)Co.,Ltd.

Test Report

Report No.: RXA1307-0096MPE

Page 3 of 5

TABLE 1 – LIMITS FOR MAXIMUM PERMISSIBLE EXPOSURE (MPE)

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
(A) Limits for Occupational/Controlled Exposures				
0.3-3.0	614	1.63	*(100)	6
3-30	1842/f	4.89/f	*(900/f ²)	6
30-300	61.4	0.163	1.0	6
300-1500	f/300	6
1500-100,000	5	6
(B) Limits for General Population/Uncontrolled Exposure				
0.3-1.34	614	1.63	*(100)	30
1.34-30	824/f	2.19/f	*(180/f ²)	30
30-300	27.5	0.073	0.2	30
300-1500	f/1500	30
1500-100,000	1.0	30

f = frequency in MHz

* = Plane-wave equivalent power density

Note1. Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational / controlled limits apply provided he or she is made aware of the potential for exposure.

Note2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or can not exercise control over their exposure.

TA Technology (Shanghai)Co.,Ltd.

Test Report

Report No.: RXA1307-0096MPE

Page 4 of 5

The maximum permissible exposure for 300~1500MHz is f/1500, 1500~100,000MHz is 1. So

Band	The maximum permissible exposure
CDMA 800	0.55 mW/cm²
CDMA 1900	1 mW/cm²

IMPORTANT NOTE: To comply with the FCC RF exposure compliance requirements, the antenna(s) used for this transmitter must be installed to provide a separation distance of at least 20 cm from all persons and must not be co-located or operating in conjunction with any other antenna or transmitter. No change to the antenna or the device is permitted. Any change to the antenna or the device could result in the device exceeding the RF exposure requirements and void user's authority to operate the device.

TA Technology (Shanghai)Co.,Ltd.

Test Report

Report No.: RXA1307-0096MPE

Page 5 of 5

RF Exposure Calculations:

The following information provides the minimum separation distance for the highest gain antenna provided.

This calculation is based on the conducted power, considering maximum power and antenna gain. The formula shown in OET Bulletin 65 is used in the calculation.

Equation from OET Bulletin 65, Edition 97-01 is:

$$S = PG / 4\pi R^2$$

where: S = power density (in appropriate units, e.g. mW/cm^2)

P = Time-average maximum tune up procedure (in appropriate units, e.g., mW)

G = the numeric gain of the antenna

R = distance to the center of radiation of the antenna (20 cm = limit for MPE)

So, the numeric gain (G) of the antenna with a gain specified in dB is determined by

Numeric gain (G) = $10^{\text{antenna gain}/10} = 10^{(2/10)} = 1.58 \text{ dB}$

CDMA 800: $PG = 25\text{dBm} + (1.58\text{dB}) = 26.58\text{dBm} = 454.99\text{mW}$

CDMA1900 $PG = 25\text{dBm} + (1.58\text{dB}) = 26.58\text{dBm} = 454.99\text{mW}$

$R = 20 \text{ cm}$

$\pi = 3.1416$

Solving for S , the power density at 20 cm is

Band	Test Result (mW/cm^2)	Limit Value (mW/cm^2)
CDMA 800	0.091	0.55 mW/cm^2
CDMA1900	0.091	1 mW/cm^2

Note: For mobile or fixed location transmitters, minimum separation distance is 20cm, even if calculations

indicate MPE distance is less.