

# FCC RF Exposure

EUT Description: Wireless Bodypack Transmitter

Model No.: BP500

FCC ID: 2AAQC-BP500

Equipment type: Portable Device

## 1. Test Procedure

According to KDB 447498 D01 General RF Exposure Guidance v06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}$$

where

$f(\text{GHz})$  is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

## 2. Test Result of RF Exposure Evaluation

CH/Frequency		Output power (dBm/ mW)
516-541MHz		6.319/4.284

Turn-up power	
Mode	Peak power range(dBm)
Wireless Bodypack Transmitter	6.00-8.00

FCC exclusion condition as below:

[522.9MHz, 6.319dBm/4.28mW) output power]  
(4.28mW /5mm) \*[v0.5229(GHz)] =0.619<3.0 for 1-g SAR  
Conclusion: No SAR is required