

RF EXPOSURE EVALUATION METHOD

SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and ≤ 50 mm

Approximate SAR Test Exclusion Power Thresholds at Selected Frequencies and Test Separation

Distances are illustrated in the following Table.

MHz	5	10	15	20	25	mm
150	39	77	116	155	194	SAR Test Exclusion Threshold (mW)
300	27	55	82	110	137	
450	22	45	67	89	112	
835	16	33	49	66	82	
900	16	32	47	63	79	
1500	12	24	37	49	61	
1900	11	22	33	44	54	
2450	10	19	29	38	48	
3600	8	16	24	32	40	
5200	7	13	20	26	33	
5400	6	13	19	26	32	
5800	6	12	19	25	31	

Maximum measured transmitter power

1Mbps

Frequency (MHZ)	Max Antenna Gain (dBm)	EIRP (dBm)	EIRP (mW)
2402	0	0.532	1.13
2441	0	1.441	1.39
2480	0	1.841	1.53

2Mbps

Frequency (MHZ)	Max Antenna Gain (dBm)	EIRP (dBm)	EIRP (mW)
2402	0	0.113	1.020
2441	0	0.986	1.254
2480	0	1.515	1.417

3Mbps

Frequency (MHZ)	Max Antenna Gain (dBm)	EIRP (dBm)	EIRP (mW)
2402	0	0.483	1.117
2441	0	1.414	1.384
2480	0	1.860	1.535

Refer to 447498 25 D01 General RF Exposure Guidance v05 Appendix A, you see that for Maximum Conducted AV Output Power **1.535** mW(<10mW), so no SAR is required.