


Prüfbericht-Nr.: <i>Test report No.:</i>	50298527 001	Auftrags-Nr.: <i>Order No.:</i>	168131232	Seite 1 von 28 <i>Page 1 of 28</i>
Kunden-Referenz-Nr.: <i>Client reference No.:</i>	N/A	Auftragsdatum: <i>Order date.:</i>	11.10.2019	
Auftraggeber: <i>Client:</i>	UP Global Sourcing Ltd. UP Global Sourcing, Manor Mill, Victoria Street, Chadderton, Oldham, OL9 0DD, United Kingdom			
Prüfgegenstand: <i>Test item:</i>	Wireless charging headphones			
Bezeichnung / Typ-Nr.: <i>Identification / Type No.:</i>	EE5244			
Auftrags-Inhalt: <i>Order content:</i>	FCC approval			
Prüfgrundlage: <i>Test specification:</i>	CFR47 FCC Part 15: Subpart C Section 15.247 CFR47 FCC Part 15: Subpart B Section 15.107 CFR47 FCC Part 15: Subpart B Section 15.109 CFR47 FCC Part 2: Section 2.1093			
Wareneingangsdatum: <i>Date of receipt:</i>	12.10.2019	Please refer to photo documents		
Prüfmuster-Nr.: <i>Test sample No.:</i>	A001005193-001 to 002 A001005193-013 A000999740-005			
Prüfzeitraum: <i>Testing period:</i>	13.10.2019 - 12.11.2019			
Ort der Prüfung: <i>Place of testing:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüflaboratorium: <i>Testing laboratory:</i>	TÜV Rheinland (Shenzhen) Co., Ltd.			
Prüfergebnis*: <i>Test result*:</i>	Pass			
geprüft von / tested by:		kontrolliert von / reviewed by:		
				
13.11.2019	Jonathan Li / Project Manager	13.11.2019	Winnie Hou / Technical Certifier	
Datum <i>Date</i>	Name/Stellung <i>Name/Position</i>	Unterschrift <i>Signature</i>	Datum <i>Date</i>	Name/Stellung <i>Name/Position</i>
Sonstiges / Other:				
FCC ID: 2AAR2EE5244				
Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i>		Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged:</i>		
* Legende:	1 = sehr gut	2 = gut	3 = befriedigend	4 = ausreichend
	P(ass) = entspricht o.g. Prüfgrundlage(n)	F(ail) = entspricht nicht o.g. Prüfgrundlage(n)	N/A = nicht anwendbar	5 = mangelhaft
Legend:	1 = very good	2 = good	3 = satisfactory	4 = sufficient
	P(ass) = passed a.m. test specifications(s)	F(ail) = failed a.m. test specifications(s)	N/A = not applicable	5 = poor
				N/T = nicht getestet
				N/T = not tested
Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens.				
<i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i>				
V04				

Test Summary

5.1.1 ANTENNA REQUIREMENT*RESULT: Pass***5.1.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER***RESULT: Pass***5.1.3 99% BANDWIDTH***RESULT: Pass***5.1.4 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHZ BANDWIDTH***RESULT: Pass***5.1.5 RADIATED SPURIOUS EMISSION***RESULT: Pass***5.1.6 20dB BANDWIDTH***RESULT: Pass***5.1.7 CARRIER FREQUENCY SEPARATION***RESULT: Pass***5.1.8 NUMBER OF HOPPING FREQUENCY***RESULT: Pass***5.1.9 TIME OF OCCUPANCY***RESULT: Pass***5.1.10 CONDUCTED EMISSION ON AC MAINS***RESULT: Pass***5.1.11 RADIATED EMISSION***RESULT: Pass***6.1.1 ELECTROMAGNETIC FIELDS***RESULT: Pass*

Contents

1	GENERAL REMARKS	5
1.1	COMPLEMENTARY MATERIALS	5
2	TEST SITES	6
2.1	TEST FACILITIES	6
2.2	LIST OF TEST AND MEASUREMENT INSTRUMENTS.....	6
2.3	TRACEABILITY	8
2.4	CALIBRATION	8
2.5	MEASUREMENT UNCERTAINTY.....	8
2.6	LOCATION OF ORIGINAL DATA.....	8
2.7	STATUS OF FACILITY USED FOR TESTING.....	8
3	GENERAL PRODUCT INFORMATION	9
3.1	PRODUCT FUNCTION AND INTENDED USE.....	9
3.2	RATINGS AND SYSTEM DETAILS	9
3.3	INDEPENDENT OPERATION MODES	10
3.4	NOISE GENERATING AND NOISE SUPPRESSING PARTS.....	11
3.5	SUBMITTED DOCUMENTS.....	11
4	TEST SET-UP AND OPERATION MODES	12
4.1	PRINCIPLE OF CONFIGURATION SELECTION	12
4.2	TEST OPERATION AND TEST SOFTWARE.....	12
4.3	SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT.....	13
4.4	COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE.....	13
4.5	TEST SETUP DIAGRAM.....	14
5	TEST RESULTS	16
5.1	TRANSMITTER REQUIREMENT & TEST SUITES	16
<i>5.1.1</i>	<i>Antenna Requirement</i>	<i>16</i>
<i>5.1.2</i>	<i>Maximum Peak Conducted Output Power.....</i>	<i>17</i>
<i>5.1.3</i>	<i>99% Bandwidth</i>	<i>18</i>
<i>5.1.4</i>	<i>Conducted Spurious Emissions Measured in 100 kHz Bandwidth.....</i>	<i>19</i>
<i>5.1.5</i>	<i>Radiated Spurious Emission</i>	<i>20</i>
<i>5.1.6</i>	<i>20dB Bandwidth.....</i>	<i>21</i>
<i>5.1.7</i>	<i>Carrier Frequency Separation.....</i>	<i>22</i>
<i>5.1.8</i>	<i>Number of Hopping Frequency.....</i>	<i>23</i>
<i>5.1.9</i>	<i>Time of Occupancy</i>	<i>24</i>
<i>5.1.10</i>	<i>Conducted Emission on AC Mains</i>	<i>25</i>
<i>5.1.11</i>	<i>Radiated Emission.....</i>	<i>26</i>
6	SAFETY HUMAN EXPOSURE	27
6.1	RADIO FREQUENCY EXPOSURE COMPLIANCE	27
<i>6.1.1</i>	<i>Electromagnetic Fields.....</i>	<i>27</i>
7	PHOTOGRAPHS OF THE TEST SET-UP.....	28

8	LIST OF TABLES.....	28
----------	----------------------------	-----------

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Photographs of the Test Set-up

Appendix B: Test Results of Bluetooth

Appendix C: Test Results of Part 15B

2 Test Sites

2.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

1F East & 2-4F, Cybio Technology Building No. 1, No. 16 Kejibei 2nd Road, High-Tech Industrial Park North Nanshan District, Shenzhen, 518057

FCC accredited testing laboratory: CN1260

ISED wireless device testing laboratory: 25069

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment
TÜV Rheinland (Shenzhen) Co., Ltd.

Radio Spectrum Testing (TS8997)					
Equip. No.	Equipment	Manufacturer	Model	Serial No.	Cal. until
1825795	Signal Analyzer	Rohde & Schwarz	FSV 40	101441	20.08.2020
1825798	OSP	Rohde & Schwarz	OSP 150	101017	20.12.2019
1825799	Control PC	DELL	OptiPlex 7050	FTJZ9P2	N/A
1825800	Test Software	Rohde & Schwarz	WMS32 (V10.40.10)	N/A	N/A
1825801	Power Meter	Rohde & Schwarz	NRP2	107105	20.12.2019
1825802	Wideband Power Sensor	Rohde & Schwarz	NRP-Z81	105350	20.12.2019
1826431	Shielding Room 8#	Albatross	SR8	APC17151-SR8	23.07.2020
Unwanted Emission Testing (TS9975)					
Equip. No.	Equipment	Manufacturer	Model	Serial No.	Cal. until
1826021	EMI Test Receiver	Rohde & Schwarz	ESR 7	102021	19.08.2020
1826023	Signal Analyzer	Rohde & Schwarz	FSV 40	101439	21.08.2020
1826024	System Controller Interface	Rohde & Schwarz	SCI-100	S10010038	N/A
1826025	Filterbank	Rohde & Schwarz	Wlan	100759	21.08.2020
1826026	OSP	Rohde & Schwarz	OSP 120	102040	N/A
1826028	Pre-amplifier	Rohde & Schwarz	SCU08F1	08320031	20.08.2020
1826029	Amplifier	Rohde & Schwarz	SCU-18F	180070	20.08.2020
1826030	Amplifier	Rohde & Schwarz	SCU40A	100475	20.09.2020
1826031	Trilog Broadband Antenna (30 MHz - 7 GHz)	Schwarzbeck	VULB 9162	193	02.09.2020
1826032	Double-Ridged Antenna (1 -18 GHz)	ETS-LINDGREN	3117	00218717	02.09.2020
1826033	Wideband Ridged Horn Antenna (18-40 GHz)	Steatite	QMS-00880	19067	02.09.2020

1826034	Active Loop Antenna	Schwarzbeck	FMZB 1513	302	01.09.2020
1826035	Wideband Ridged Horn Antenna (12-18 GHz)	Steatite	QMS-00208	18313	02.09.2020
1826036	Test software	Rohde & Schwarz	V10.40.10-EMC32	N/A	N/A
1826037	Control PC	Dell	OptiPlex 7050	36NV9P2	N/A
1826433	3m Semi-Anechoic Chamber	Albatross	SAC-3m	APC17151-SAC	06.07.2020

Conducted Emission on AC Mains

Equip. No.	Equipment	Manufacturer	Model	Serial No.	Cal. until
1822625	EMI Test Receiver	R&S	ESR3	102428	03.09.2020
1822627	Artificial Mains Network	R&S	ENV216	102333	19.08.2020
1822626	Artificial Mains Network	R&S	ENV432	101411	19.08.2020
1822629	Attenuator	R&S	ESH2Z31	100300	19.08.2020
1825090	EMC32 test software	R&S	EMC32(Ver.10.50.01)	N/A	N/A

Radiated Emission (3m chamber)

Equip. No.	Equipment	Manufacturer	Model No.	Serial No.	Cali. until
1822620	3m SAC	ETS	SAC3	CT001632-Q1362	23.08.2021
1825044	EMI Test Receiver	R&S	ESR7	102111	23.01.2020
1825004	Horn Antenna	R&S	HF907	102706	01.09.2020
1825005	Preamplifier	FIT	SCU-18F	180077	19.08.2020
1825042	Trilog-Broadband antenna	SCHWARZBECK	VULB9168	0945	12.09.2020
1825072	Switching Controller Interface	R&S	OSP 120	102039	N/A
1825090	EMC32 test software	R&S	EMC32(Ver.10.50.01)	N/A	N/A

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

The estimated combined standard uncertainty for radiated emissions and conducted emissions measurements as below table.

Parameter	Uncertainty
Radio Frequency	$\pm 1 \times 10^{-7}$
RF Power (conducted)	± 2.5 dB
Radiated Emission of Transmitter, valid up to 26.5 GHz	± 6 dB
Radiated Emission of Receiver, valid up to 26.5 GHz	± 6 dB
Conducted Emission, (9kHz to 150kHz)/(150kHz to 30MHz)	± 3.70 dB / ± 3.30 dB
Radiated Emission (3m SAC), 30MHz to 1000MHz	± 4.52 dB
Radiated Emission (3m SAC), above 1000MHz	± 4.37 dB
Temperature	± 1 °C
Humidity	± 5 %
Voltage (DC)	± 1 %
Voltage (AC, <10kHz)	± 2 %

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B & C of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) Co., Ltd. file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at 1F East & 2-4F, Cybio Technology Building No. 1, No. 16 Kejibei 2nd Road, High-Tech Industrial Park North Nanshan District, Shenzhen, 518057 is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The EUT is a Wireless charging headphones, which support Bluetooth 5.0 technology.

Note: When the EUT is charged, other functions cannot be used.

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 2: Technical Specification of EUT

General Information of EUT	Value
Kind of Equipment	Wireless charging headphones
Type Designation	EE5244
FCC ID	2AAR2EE5244
Operating Voltage	DC 5.0V via USB port for charging DC 3.7V via internal rechargeable lithium battery
Battery #1	DC 3.7V@200mAh lithium battery
Technical Specification of Bluetooth	
Operating Frequency	2400 MHz to 2483.5 MHz
Type of Modulation	GFSK, $\pi/4$ -DQPSK
Channel Number	BDR & EDR mode:79 channels
Channel Separation	BDR & EDR mode:1MHz;
Antenna Type	Integral Antenna
Antenna Gain	0 dBi

Table 3: Operating Frequencies/Channels of EUT

Operating Mode	Description
Bluetooth [®]	<input checked="" type="checkbox"/> BDR/EDR $f_c = 2402 + k$ MHz, where $k = 0 \sim 78$ <input type="checkbox"/> Low Energy $f_c = 2402 + k*2$ MHz, where $k = 0 \sim 39$

Table 4: Frequency Hopping Information

Technical Specification	Description
Hopping Range	Hereby we declare that the frequency range of this device is: 2402-2480MHz. This is according the Bluetooth Core Specification V4.0 + EDR for devices which will be operated in the USA. This was checked during the Bluetooth Qualification tests (Test Case: TRM/CA/04-E).
Hopping Sequence	Example of a 79 hopping sequence in data mode: 33,04,21,44,23,42,53,46,55,48,40,59,72,29,76,31,08,73,07,75,09,45,60,39,58,13,47,11,77,52,35,50,65,54,67,56,69,62,71,64, 7,25,27,66,57,70,74,61,78,63,10,41,05,43,15,44,64,68,02,70,06,01,51,03,55,05,03,66,53,49,36,47,
Receiver input bandwidth	<p>The input bandwidth of the receiver is 1MHz. In every connection one Bluetooth device is the master and the other one is the slave. The master determines the hopping sequence. The slave follows this sequence. Both devices shift between RX and TX time slot according to the clock of the master.</p> <p>Additionally the type of connection is set up at the beginning of the connection. The master adapts its hopping frequency and its TX/RX timing according to the packet type of the connection. Also the slave of the connection will use these settings.</p> <p>Repeating of a packer has no influence on the hopping sequence. The hopping sequence generated by the master of the connection will be followed in any case.</p> <p>That means a repeated packet will not be send on the same frequency, it is send on the next frequency of the hopping sequence.</p>

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, Bluetooth transmitting mode (BDR & EDR mode)
 - 1) Low Channel
 - 2) Middle Channel
 - 3) High Channel
- B. On, Transmitting on Hopping channel
- C. On, Bluetooth connecting mode
- D. On, Charging mode
- E. On, Aux in playing mode
- F. On, TF card playing mode
- G. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- Block Diagram
- Schematics
- FCC/IC Label and Location Info
- User Manual

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All tests were performed according to the procedures in ANSI C63.10: 2013 and ANSI C63.4: 2014.

Table 5: List of Frequencies under Test

<input checked="" type="checkbox"/> Bluetooth				
Operation mode	Frequencies under Test (MHz)			Power Level setting (dBm)
	CH _{Low}	CH _{Mid}	CH _{High}	
<input checked="" type="checkbox"/> BDR/EDR	2402.0	2441.0	2480.0	10.0

4.3 Special Accessories and Auxiliary Equipment

Table 6: Auxiliary Equipment Used during Test

Description	Manufacturer	Model	S/N	Rating
Laptop	Lenovo	T480	PF-16A6N8	N/A
TF card	N/A	N/A	N/A	N/A
Adapter	N/A	N/A	N/A	DC 5V
Mobile Phone	N/A	N/A	N/A	N/A

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)




Diagram of Measurement Configuration for Mains Conduction Measurement





Diagram of Measurement Configuration for Conducted Transmitter Measurement



5 Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:

Pass

Test Specification

Test standard : FCC Part 15.247(b)(4) and Part 15.203

According to the manufacturer declared, the EUT has an internal antenna, the directional gain of antenna is 0 dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement. Therefore the EUT is considered sufficient to comply with the provision.

Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

5.1.2 Maximum Peak Conducted Output Power

RESULT:
Pass
Test Specification

Test standard	: FCC Part 15.247(b)(1)
Basic standard	: ANSI C63.10: 2013
Limits	: DSS < 0.125 Watts
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 23.10.2019
Input voltage	: Fully charged battery
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101 kPa

Table 7: Test Result of Maximum Peak Conducted Output Power, Bluetooth

Test Mode	Test Channel (MHz)	Measured Peak Power		Limit (W)
		(dBm)	(W)	
GFSK	2402.0	-7.63	0.0002	< 0.125
	2441.0	-7.50	0.0002	
	2480.0	-6.97	0.0002	
Maximum Measured Value		-6.97	0.0002	

Test Mode	Test Channel (MHz)	Measured Peak Power		Limit (W)
		(dBm)	(W)	
π/4DQPSK	2402.0	-7.86	0.0002	< 0.125
	2441.0	-7.69	0.0002	
	2480.0	-7.12	0.0002	
Maximum Measured Value		-7.12	0.0002	

Note:

- 1) The cable loss is taken into account in results.
- 2) Antenna gain(G): 0 dBi,

 The Maximum peak conducted output power (e.i.r.p.)= $P_{(Peak\ power)} + G$, which is far below the 4 W

5.1.3 99% Bandwidth

RESULT:**Pass****Test Specification**

Test standard : FCC Part 15.247(a)
Basic standard : ANSI C63.10: 2013
Kind of test site : Shielded Room

Test Setup

Date of testing : 23.10.2019
Input voltage : Fully charged battery
Operation mode : A
Test channel : Low / Middle / High
Ambient temperature : 25 °C
Relative humidity : 56 %
Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix B.

5.1.4 Conducted Spurious Emissions Measured in 100 kHz Bandwidth

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.247(d)
Basic standard	: ANSI C63.10: 2013
Limits	: 20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power); In addition, radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified in 15.209(a)
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 28.10.2019
Input voltage	: Fully charged battery
Operation mode	: A
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101 kPa

Test results of 100kHz Bandwidth of Frequency Band Edge by Conducted method refer to test plots, and compliance is achieved as well.

For the measurement records, refer to the appendix B.

5.1.5 Radiated Spurious Emission

RESULT:**Pass****Test Specification**

Test standard	:	FCC Part 15.247(d) & FCC Part 15.205
Basic standard	:	ANSI C63.10: 2013
Limits	:	Refer to 15.209(a) of FCC part 15.247(d)
Kind of test site	:	3m Semi-anechoic Chamber

Test Setup

Date of testing	:	Refer to test result
Input voltage	:	Fully charged battery
Operation mode	:	A
Test channel	:	Low / Middle / High
Ambient temperature	:	22 °C
Relative humidity	:	54 %
Atmospheric pressure	:	101 kPa

Remark:

Testing was carried out within frequency range 9kHz to the tenth harmonics. Only the worst case spurious emissions configuration of the each mode were reported.

For the measurement records, refer to the appendix B.

5.1.6 20dB Bandwidth

RESULT:**Pass****Test Specification**

Test standard : FCC Part 15.247(a)(1)
Basic standard : ANSI C63.10: 2013
Kind of test site : Shielded Room

Test Setup

Date of testing : 23.10.2019
Input voltage : Fully charged battery
Operation mode : A
Test channel : Low / Middle / High
Ambient temperature : 25 °C
Relative humidity : 56 %
Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix B.

5.1.7 Carrier Frequency Separation

RESULT:**Pass****Test Specification**

Test standard	: FCC Part 15.247(a)(1)
Basic standard	: ANSI C63.10: 2013
Limits	: $\geq 25\text{kHz}$ or 2/3 of 20dB bandwidth, whichever is greater
Kind of test site	: Shielded Room

Test Setup

Date of testing	: 23.10.2019
Input voltage	: Fully charged battery
Operation mode	: B
Test channel	: Low / Middle / High
Ambient temperature	: 25 °C
Relative humidity	: 56 %
Atmospheric pressure	: 101 kPa

For the measurement records, refer to the appendix B.

5.1.8 Number of Hopping Frequency

RESULT:**Pass****Test Specification**

Test standard	:	FCC part 15.247(a)(1)(iii)
Basic standard	:	ANSI C63.10: 2013
Limits	:	≥ 15 non-overlapping channels
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	23.10.2019
Input voltage	:	Fully charged battery
Operation mode	:	B
Ambient temperature	:	25 °C
Relative humidity	:	56 %
Atmospheric pressure	:	101 kPa

For the measurement records, refer to the appendix B.

5.1.9 Time of Occupancy

RESULT:**Pass****Test Specification**

Test standard	:	FCC part 15.247(a)(1)(iii)
Basic standard	:	ANSI C63.10: 2013
Limits	:	< 0.4s
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	23.10.2019
Input voltage	:	Fully charged battery
Operation mode	:	B
Test channel	:	Low / Middle / High
Ambient temperature	:	25 °C
Relative humidity	:	56 %
Atmospheric pressure	:	101 kPa

Note:

Dwell time = Pulse width x Number of channels in Period

Period = 0.4 (seconds/ channel) x 79 (channel) = 31.6 seconds

For the measurement records, refer to the appendix B.

5.1.10 Conducted Emission on AC Mains**RESULT:****Pass****Test Specification**

Test standard	:	FCC Part 15.107(a)
Basic standard	:	ANSI C63.4: 2014
Frequency range	:	0.15 – 30MHz
Limits	:	FCC Part 15.107(a)
Kind of test site	:	Shielded Room

Test Setup

Date of testing	:	Refer to test result
Input voltage	:	DC 5V input by the micro USB port
Operation mode	:	D
Earthing	:	Not connected
Ambient temperature	:	22 °C
Relative humidity	:	64 %
Atmospheric pressure	:	101 kPa

For the measurement records, refer to the appendix C.

5.1.11 Radiated Emission**RESULT:****Pass****Test Specification**

Test standard	:	FCC Part 15.109(a)
Basic standard	:	ANSI C63.4: 2014
Frequency range	:	30 - 6000MHz
Classification	:	Class B
Limits	:	FCC Part 15.109(a)
Kind of test site	:	3m Semi-anechoic Chamber

Test Setup

Date of testing	:	Refer to test result
Input voltage	:	DC 5V input by the micro USB port
Operation mode	:	D,E,F
Earthing	:	Not connected
Ambient temperature	:	24 °C
Relative humidity	:	50 %
Atmospheric pressure	:	101 kPa

For the measurement records, refer to the appendix C.

6 Safety Human Exposure

6.1 Radio Frequency Exposure Compliance

6.1.1 Electromagnetic Fields

RESULT:

Pass

Test Specification

Test standard

: CFR47 FCC Part 2: Section 2.1093

FCC KDB Publication 447498 D01 V06

FCC requirements

For 100 MHz to 6 GHz and *test separation distances* ≤ 50 mm, the 1-g and 10-g SAR test exclusion thresholds are determined by the following:

(*max. power of channel, including tune-up tolerance, mW*) / (*min. test separation distance, mm*) $\cdot [\sqrt{f(\text{GHz})}] \leq 3.0$ for 1-g SAR, and ≤ 7.5 for 10-g extremity SAR,30 where

- $f(\text{GHz})$ is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation
- The result is rounded to one decimal place for comparison
- The values 3.0 and 7.5 are referred to as *numeric thresholds* in step b) below

The test exclusions are applicable only when the minimum *test separation distance* is ≤ 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

Calculated result

The maximum peak output power of the transmitter is -6.97dBm and minimum test separation distance is 5mm, SAR test exclusion thresholds=0.06<3.0, so the SAR test is not required.

7 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix A.


8 List of Tables

Table 1: List of Test and Measurement Equipment.....	6
Table 2: Technical Specification of EUT	9
Table 3: Operating Frequencies/Channels of EUT	9
Table 4: Frequency Hopping Information.....	10
Table 5: List of Frequencies under Test.....	12
Table 6: Auxiliary Equipment Used during Test	13
Table 7: Test Result of Maximum Peak Conducted Output Power, Bluetooth.....	17

Appendix A: Photographs of the Test Set-Up

APPENDIX A: PHOTOGRAPHS OF THE TEST SET-UP	1
PHOTOGRAPH 1: SET-UP FOR RADIO SPECTRUM TEST	2
PHOTOGRAPH 3: SET-UP FOR RADIATED SPURIOUS EMISSION, 30MHz ~ 1GHz	2
PHOTOGRAPH 4: SET-UP FOR RADIATED SPURIOUS EMISSION, 1GHz ~ 18GHz	3
PHOTOGRAPH 6: SET-UP FOR CONDUCTED EMISSION ON AC MAINS.....	3
PHOTOGRAPH 7: SET-UP FOR RADIATED EMISSION, BELOW 1GHz	4
PHOTOGRAPH 8: SET-UP FOR RADIATED EMISSION, ABOVE 1GHz	4


Photograph 1: Set-up for Radio Spectrum Test



Photograph 2: Set-up for Radiated Spurious Emission, 30MHz ~ 1GHz




Photograph 3: Set-up for Radiated Spurious Emission, 1GHz ~ 18GHz




Photograph 4: Set-up for Conducted Emission on AC Mains





Photograph 5: Set-up for Radiated Emission, Below 1GHz



Photograph 6: Set-up for Radiated Emission, Above 1GHz





Appendix B: Test Results of Bluetooth

APPENDIX B: TEST RESULTS OF BLUETOOTH	1
APPENDIX B.1: TEST RESULTS OF 99% BANDWIDTH	3
B.1.1 Test Results of GFSK	3
Low Channel.....	3
Middle Channel.....	4
High Channel.....	5
B.1.2 Test Results of $\pi/4$DQPSK	6
Low Channel.....	6
Middle Channel.....	7
High Channel.....	8
APPENDIX B.2: TEST RESULTS OF 20DB BANDWIDTH	9
B.2.1 Test Results of GFSK	9
Low Channel.....	9
Middle Channel.....	10
High Channel.....	11
B.2.2 Test Results of $\pi/4$DQPSK	12
Low Channel.....	12
Middle Channel.....	13
High Channel.....	14
APPENDIX B.3: TEST RESULTS OF CARRIER FREQUENCY SEPARATION	15
B.3.1 Test Results of GFSK	15
Low Channel.....	15
Middle Channel.....	16
High Channel.....	17
B.3.2 Test Results of $\pi/4$DQPSK	18
Low Channel.....	18
Middle Channel.....	19
High Channel.....	20
APPENDIX B.4: TEST RESULTS OF NUMBER OF HOPPING FREQUENCY	21
B.4.1 Test Results of GFSK	21
All hopping channels.....	21
B.4.2 Test Results of $\pi/4$DQPSK	22
All hopping channels.....	22
APPENDIX B.5: TEST RESULTS OF TIME OF OCCUPANCY	23
B.5.1 Test Results of GFSK	23
B.5.2 Test Results of $\pi/4$DQPSK	29
APPENDIX B.6: TEST RESULTS OF CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHZ BANDWIDTH	35
B.6.1 Test Results of GFSK	35
Low Channel.....	35
Middle Channel.....	35
High Channel.....	36
Band Edge, Low Channel.....	37
Band Edge, High Channel.....	37
Band Edge, Hopping Mode, Low Channel.....	38
Band Edge, Hopping Mode, High Channle.....	38
B.6.2 Test Results of $\pi/4$DQPSK	39
Low Channel.....	39
Middle Channel.....	39
High Channel.....	40
Band Edge, Low Channel.....	41

<i>Band Edge, High Channel</i>	41
<i>Band Edge, Hopping Mode, Low Channel</i>	42
<i>Band Edge, Hopping Mode, High Channle</i>	42
APPENDIX B.7: TEST RESULTS OF RADIATED SPURIOUS EMISSIONS	43
<i>30MHz - 1GHz (Worst case)</i>	43
<i>1GHz - 18GHz</i>	47
APPENDIX B.8: TEST RESULTS OF RADIATED EMISSIONS IN RESTRICTED BANDS	53
<i>Low channel</i>	53
<i>High channel</i>	55

Appendix B.1: Test Results of 99% Bandwidth

B.1.1 Test Results of GFSK

Low Channel

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Occupied Channel Bandwidth 99% (2402 MHz; 10.000 dBm; 1 MHz; Test Mode)


Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	0.840000	—	—	2401.597500	2402.437500

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2402.000000	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40300 GHz	2.40300 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
StableValue	0.30 dB	0.30 dB
Run	6 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.18 dB	0.30 dB

Middle Channel

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Occupied Channel Bandwidth 99% (2441 MHz; 10.000 dBm; 1 MHz; Test Mode)


Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2441.000000	0.840000	—	—	2440.597500	2441.437500

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2441.000000	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.44000 GHz	2.44000 GHz
Stop Frequency	2.44200 GHz	2.44200 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
Sweeptime	189.648 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	5 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.10 dB	0.30 dB

High Channel

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Occupied Channel Bandwidth 99% (2480 MHz; 10.000 dBm; 1 MHz; Test Mode)


Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	0.840000	—	—	2479.597500	2480.437500

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2480.000000	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47900 GHz	2.47900 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
Sweeptime	189.648 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stable value	0.30 dB	0.30 dB
Run	10 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.06 dB	0.30 dB

B.1.2 Test Results of $\pi/4$ DQPSK

Low Channel

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Occupied Channel Bandwidth 99% (2402 MHz; 10.000 dBm; 1 MHz; Test Mode)


Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	1.170000	—	—	2401.432500	2402.602500

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2402.000000	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40300 GHz	2.40300 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 μ s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	6 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.15 dB	0.30 dB

Middle Channel

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Occupied Channel Bandwidth 99% (2441 MHz; 10.000 dBm; 1 MHz; Test Mode)


Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2441.000000	1.180000	—	—	2440.427500	2441.607500

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2441.000000	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.44000 GHz	2.44000 GHz
Stop Frequency	2.44200 GHz	2.44200 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	4 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.09 dB	0.30 dB

High Channel

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Occupied Channel Bandwidth 99% (2480 MHz; 10.000 dBm; 1 MHz; Test Mode)


Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

99 % Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	1.180000	—	—	2479.427500	2480.607500

(continuation of the "99 % Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Result
2480.000000	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47900 GHz	2.47900 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
Sweeptime	189.648 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	500	500
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.30 dB	0.30 dB
Run	8 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.06 dB	0.30 dB

Appendix B.2: Test Results of 20dB Bandwidth

B.2.1 Test Results of GFSK

Low Channel

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Emission Bandwidth 20 dB (2402 MHz; 10.000 dBm; 1 MHz; Test Mode)


Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	0.890000	--	--	2401.567500	2402.457500

(continuation of the "20 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2402.000000	-13.2	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40300 GHz	2.40300 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
StableValue	0.50 dB	0.50 dB
Run	9 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.04 dB	0.50 dB

Middle Channel

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Emission Bandwidth 20 dB (2441 MHz; 10.000 dBm; 1 MHz; Test Mode)


Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2441.000000	0.925000	—	—	2440.567500	2441.492500

(continuation of the "20 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2441.000000	-13.2	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.44000 GHz	2.44000 GHz
Stop Frequency	2.44200 GHz	2.44200 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	11 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.05 dB	0.50 dB

High Channel

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Emission Bandwidth 20 dB (2480 MHz; 10.000 dBm; 1 MHz; Test Mode)


Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	0.890000	—	—	2479.567500	2480.457500

(continuation of the "20 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2480.000000	-12.5	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47900 GHz	2.47900 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
Sweeptime	189.648 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stable value	0.50 dB	0.50 dB
Run	8 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.06 dB	0.50 dB

B.2.2 Test Results of $\pi/4$ DQPSK

Low Channel

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Emission Bandwidth 20 dB (2402 MHz; 10.000 dBm; 1 MHz; Test Mode)


Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2402.000000	1.205000	—	—	2401.417500	2402.622500

(continuation of the "20 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2402.000000	-13.2	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40300 GHz	2.40300 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 μ s	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	12 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.12 dB	0.50 dB

Middle Channel

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Emission Bandwidth 20 dB (2441 MHz; 10.000 dBm; 1 MHz; Test Mode)


Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2441.000000	1.210000	—	—	2440.417500	2441.627500

(continuation of the "20 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2441.000000	-13.2	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.44000 GHz	2.44000 GHz
Stop Frequency	2.44200 GHz	2.44200 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
Sweeptime	189.648 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	11 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.15 dB	0.50 dB

High Channel

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Emission Bandwidth 20 dB (2480 MHz; 10.000 dBm; 1 MHz; Test Mode)


Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

20 dB Bandwidth

DUT Frequency (MHz)	Bandwidth (MHz)	Limit Min (MHz)	Limit Max (MHz)	Band Edge Left (MHz)	Band Edge Right (MHz)
2480.000000	1.210000	—	—	2479.417500	2480.627500

(continuation of the "20 dB Bandwidth" table from column 6 ...)

DUT Frequency (MHz)	Max Level (dBm)	Result
2480.000000	-12.6	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47900 GHz	2.47900 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	2.000 MHz	2.000 MHz
RBW	10.000 kHz	>= 10.000 kHz
VBW	30.000 kHz	>= 30.000 kHz
SweepPoints	400	~ 400
SweepTime	189.648 µs	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	FFT	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	12 / max. 150	max. 150
Stable	5 / 5	5
Max Stable Difference	0.10 dB	0.50 dB

Appendix B.3: Test Results of Carrier Frequency Separation

B.3.1 Test Results of GFSK

Low Channel

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Carrier Frequency Separation (2402 MHz; 10.000 dBm; 1 MHz; Test Mode)


Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

Result

DUT Frequency (MHz)	Frequency Separation (MHz)	Limit Min (MHz)	Limit Max (MHz)	Center Frequency low Channel (MHz)	Center Frequency high Channel (MHz)
2402.000000	0.980198	0.593333	---	2402.024752	2403.004950

(continuation of the "Result" table from column 6 ...)

DUT Frequency (MHz)	Result
2402.000000	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40400 GHz	2.40400 GHz
Span	3.000 MHz	3.000 MHz
RBW	300.000 kHz	<= 300.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	101	~ 10
SweepTime	1.000 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
StableValue	0.50 dB	0.50 dB
Run	11 / max. 150	max. 150
Stable	10 / 10	10
Max Stable Difference	0.07 dB	0.50 dB

Middle Channel

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Carrier Frequency Separation (2441 MHz; 10.000 dBm; 1 MHz; Test Mode)


Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

Result

DUT Frequency (MHz)	Frequency Separation (MHz)	Limit Min (MHz)	Limit Max (MHz)	Center Frequency low Channel (MHz)	Center Frequency high Channel (MHz)
2441.000000	0.980198	0.616667	---	2441.024752	2442.004950

(continuation of the "Result" table from column 6 ...)

DUT Frequency (MHz)	Result
2441.000000	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.44000 GHz	2.44000 GHz
Stop Frequency	2.44300 GHz	2.44300 GHz
Span	3.000 MHz	3.000 MHz
RBW	300.000 kHz	<= 300.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	101	~ 10
SweepTime	1.000 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
StableValue	0.50 dB	0.50 dB
Run	11 / max. 150	max. 150
Stable	10 / 10	10
Max Stable Difference	0.10 dB	0.50 dB

High Channel

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Carrier Frequency Separation (2480 MHz; 10.000 dBm; 1 MHz; Test Mode)


Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

Result

DUT Frequency (MHz)	Frequency Separation (MHz)	Limit Min (MHz)	Limit Max (MHz)	Center Frequency low Channel (MHz)	Center Frequency high Channel (MHz)
2480.000000	0.980198	0.593333	---	2479.024752	2480.004950

(continuation of the "Result" table from column 6 ...)

DUT Frequency (MHz)	Result
2480.000000	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47800 GHz	2.47800 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	3.000 MHz	3.000 MHz
RBW	300.000 kHz	<= 300.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	101	~ 10
SweepTime	1.000 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	11 / max. 150	max. 150
Stable	10 / 10	10
Max Stable Difference	0.06 dB	0.50 dB

B.3.2 Test Results of $\pi/4$ DQPSK

Low Channel

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Carrier Frequency Separation (2402 MHz; 10.000 dBm; 1 MHz; Test Mode)


Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

Result

DUT Frequency (MHz)	Frequency Separation (MHz)	Limit Min (MHz)	Limit Max (MHz)	Center Frequency low Channel (MHz)	Center Frequency high Channel (MHz)
2402.000000	1.009900	0.803333	---	2401.995050	2403.004950

(continuation of the "Result" table from column 6 ...)

DUT Frequency (MHz)	Result
2402.000000	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40100 GHz	2.40100 GHz
Stop Frequency	2.40400 GHz	2.40400 GHz
Span	3.000 MHz	3.000 MHz
RBW	300.000 kHz	<= 300.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	101	~ 10
SweepTime	1.000 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	12 / max. 150	max. 150
Stable	10 / 10	10
Max Stable Difference	0.03 dB	0.50 dB

Middle Channel

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Carrier Frequency Separation (2441 MHz; 10.000 dBm; 1 MHz; Test Mode)


Test according to FCC title 47 part 15 § 15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

Result

DUT Frequency (MHz)	Frequency Separation (MHz)	Limit Min (MHz)	Limit Max (MHz)	Center Frequency low Channel (MHz)	Center Frequency high Channel (MHz)
2441.000000	1.009900	0.806667	---	2440.995050	2442.004950

(continuation of the "Result" table from column 6 ...)

DUT Frequency (MHz)	Result
2441.000000	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.44000 GHz	2.44000 GHz
Stop Frequency	2.44300 GHz	2.44300 GHz
Span	3.000 MHz	3.000 MHz
RBW	300.000 kHz	<= 300.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	101	~ 10
SweepTime	1.000 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
StableValue	0.50 dB	0.50 dB
Run	12 / max. 150	max. 150
Stable	10 / 10	10
Max Stable Difference	0.03 dB	0.50 dB

High Channel

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Carrier Frequency Separation (2480 MHz; 10.000 dBm; 1 MHz; Test Mode)


Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

Result

DUT Frequency (MHz)	Frequency Separation (MHz)	Limit Min (MHz)	Limit Max (MHz)	Center Frequency low Channel (MHz)	Center Frequency high Channel (MHz)
2480.000000	1.009900	0.806667	---	2478.995050	2480.004950

(continuation of the "Result" table from column 6 ...)

DUT Frequency (MHz)	Result
2480.000000	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.47800 GHz	2.47800 GHz
Stop Frequency	2.48100 GHz	2.48100 GHz
Span	3.000 MHz	3.000 MHz
RBW	300.000 kHz	<= 300.000 kHz
VBW	300.000 kHz	>= 300.000 kHz
SweepPoints	101	~ 10
SweepTime	1.000 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	200	200
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	Sweep
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	13 / max. 150	max. 150
Stable	10 / 10	10
Max Stable Difference	0.16 dB	0.50 dB

Appendix B.4: Test Results of Number of Hopping Frequency

B.4.1 Test Results of GFSK

All hopping channels


FCC Part 47 §15.247 2400-2483.5 MHz 2017

Hopping Frequencies (frequency independent; 10.000 dBm; 1 MHz)

Test according to FCC title 47 part 15 §15.247(a),(g), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

Channels

Channels	Limit Min	Limit Max	Result
79	15	---	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40000 GHz	2.40000 GHz
Stop Frequency	2.48350 GHz	2.48350 GHz
Span	83.500 MHz	83.500 MHz
RBW	200.000 kHz	<= 299.000 kHz
VBW	200.000 kHz	>= 200.000 kHz
SweepPoints	418	~ 418
SweepTime	1.060 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
SweepType	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	61 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.22 dB	0.50 dB

B.4.2 Test Results of $\pi/4$ DQPSK

All hopping channels


FCC Part 47 §15.247 2400-2483.5 MHz 2017

Hopping Frequencies (frequency independent; 10.000 dBm; 1 MHz)

Test according to FCC title 47 part 15 §15.247(a),(g), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

Channels

Channels	Limit Min	Limit Max	Result
82	15	--	PASS



Measurement

Setting	Instrument Value	Target Value
Start Frequency	2.40000 GHz	2.40000 GHz
Stop Frequency	2.48350 GHz	2.48350 GHz
Span	83.500 MHz	83.500 MHz
RBW	200.000 kHz	<= 299.000 kHz
VBW	200.000 kHz	>= 200.000 kHz
SweepPoints	418	~ 418
Sweeptime	1.060 ms	AUTO
Reference Level	0.000 dBm	0.000 dBm
Attenuation	20.000 dB	AUTO
Detector	MaxPeak	MaxPeak
SweepCount	100	100
Filter	3 dB	3 dB
Trace Mode	Max Hold	Max Hold
Sweeptype	Sweep	AUTO
Preamp	off	off
Stablemode	Trace	Trace
Stablevalue	0.50 dB	0.50 dB
Run	71 / max. 150	max. 150
Stable	3 / 3	3
Max Stable Difference	0.28 dB	0.50 dB

Appendix B.5: Test Results of Time of Occupancy

B.5.1 Test Results of GFSK

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Time of Channel Occupancy (2441 MHz; 10.000 dBm; 1 MHz)

Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

Result

DUT Frequency (MHz)	Result	Number of Hops	Average time of occupancy (ms)	Threshold (dBm)
2441.000000	PASS	319	122.410	-10.0

Periode


Min (ms)	Max (ms)	Mean (ms)
8.750	193.740	98.755

Transmit Time per Hop

Min (ms)	Max (ms)	Limit Max for Max (ms)	Limit Min for Max (ms)	Mean (ms)
0.35	0.39	400.000	0.000	0.383

DwellTime

Min (ms)	Max (ms)	Mean (ms)
0.380	0.390	0.384



FCC Part 47 §15.247 2400-2483.5 MHz 2017

Measurement

Setting	Instrument Value	Target Value
Center Frequency	2.44100 GHz	2.44100 GHz
Span	ZeroSpan	ZeroSpan
RBW	500.000 kHz	~ 500.000 kHz
VBW	1.000 MHz	~ 1.500 MHz
SweepPoints	30001	~ 30001
SweepTime	31.600 s	31.600 s
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	0.000 dB	0.000 dB
Detector	MaxPeak	MaxPeak
SweepCount	1	1
Filter	Channel	Channel
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamp	off	off
Trigger	External	External
Trigger Offset	0.000 s	0.000 s

OSP

Setting	Instrument Value	Target Value
Measurement Time	31.600 s	31.600 s
Tracepoints	31600000	31600000
Time resolution	1.000 µs	1.000 µs
Detector	RMS	RMS

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Time of Channel Occupancy(2) (2441 MHz; 10.000 dBm; 1 MHz)

Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

Result

DUT Frequency (MHz)	Result	Number of Hops	Average time of occupancy (ms)	Threshold (dBm)
2441.000000	PASS	105	173.400	-10.0

Periode


Min (ms)	Max (ms)	Mean (ms)
18.750	1162.470	297.431

Transmit Time per Hop

Min (ms)	Max (ms)	Limit Max for Max (ms)	Limit Min for Max (ms)	Mean (ms)
1.620	1.640	400.000	0.000	1.636

DwellTime

Min (ms)	Max (ms)	Mean (ms)
1.630	1.640	1.640



FCC Part 47 §15.247 2400-2483.5 MHz 2017

Measurement

Setting	Instrument Value	Target Value
Center Frequency	2.44100 GHz	2.44100 GHz
Span	ZeroSpan	ZeroSpan
RBW	500.000 kHz	~ 500.000 kHz
VBW	1.000 MHz	~ 1.500 MHz
SweepPoints	30001	~ 30001
SweepTime	31.600 s	31.600 s
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	0.000 dB	0.000 dB
Detector	MaxPeak	MaxPeak
SweepCount	1	1
Filter	Channel	Channel
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamp	off	off
Trigger	External	External
Trigger Offset	0.000 s	0.000 s

OSP

Setting	Instrument Value	Target Value
Measurement Time	31.600 s	31.600 s
Tracepoints	31600000	31600000
Time resolution	1.000 µs	1.000 µs
Detector	RMS	RMS

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Time of Channel Occupancy(3) (2441 MHz; 10.000 dBm; 1 MHz)

Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

Result

DUT Frequency (MHz)	Result	Number of Hops	Average time of occupancy (ms)	Threshold (dBm)
2441.000000	PASS	65	190.190	-10.0

Periode


Min (ms)	Max (ms)	Mean (ms)
25.000	1956.190	482.896

Transmit Time per Hop

Min (ms)	Max (ms)	Limit Max for Max (ms)	Limit Min for Max (ms)	Mean (ms)
2.860	2.890	400.000	0.000	2.882

DwellTime

Min (ms)	Max (ms)	Mean (ms)
2.880	2.890	2.888



FCC Part 47 §15.247 2400-2483.5 MHz 2017

Measurement

Setting	Instrument Value	Target Value
Center Frequency	2.44100 GHz	2.44100 GHz
Span	ZeroSpan	ZeroSpan
RBW	500.000 kHz	~ 500.000 kHz
VBW	1.000 MHz	~ 1.500 MHz
SweepPoints	30001	~ 30001
SweepTime	31.600 s	31.600 s
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	0.000 dB	0.000 dB
Detector	MaxPeak	MaxPeak
SweepCount	1	1
Filter	Channel	Channel
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamp	off	off
Trigger	External	External
Trigger Offset	0.000 s	0.000 s

OSP

Setting	Instrument Value	Target Value
Measurement Time	31.600 s	31.600 s
Tracepoints	31600000	31600000
Time resolution	1.000 µs	1.000 µs
Detector	RMS	RMS

B.5.2 Test Results of $\pi/4$ DQPSK

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Time of Channel Occupancy (2441 MHz; 10.000 dBm; 1 MHz)

Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

Result

DUT Frequency (MHz)	Result	Number of Hops	Average time of occupancy (ms)	Threshold (dBm)
2441.000000	PASS	320	66.320	-10.0

Periode


Min (ms)	Max (ms)	Mean (ms)
6.250	193.740	98.845

Transmit Time per Hop

Min (ms)	Max (ms)	Limit Max for Max (ms)	Limit Min for Max (ms)	Mean (ms)
0.14	0.28	400.000	0.000	0.207

DwellTime

Min (ms)	Max (ms)	Mean (ms)
0.140	0.400	0.347



FCC Part 47 §15.247 2400-2483.5 MHz 2017

Measurement

Setting	Instrument Value	Target Value
Center Frequency	2.44100 GHz	2.44100 GHz
Span	ZeroSpan	ZeroSpan
RBW	500.000 kHz	~ 500.000 kHz
VBW	1.000 MHz	~ 1.500 MHz
SweepPoints	30001	~ 30001
SweepTime	31.600 s	31.600 s
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	0.000 dB	0.000 dB
Detector	MaxPeak	MaxPeak
SweepCount	1	1
Filter	Channel	Channel
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamp	off	off
Trigger	External	External
Trigger Offset	0.000 s	0.000 s

OSP

Setting	Instrument Value	Target Value
Measurement Time	31.600 s	31.600 s
Tracepoints	31600000	31600000
Time resolution	1.000 µs	1.000 µs
Detector	RMS	RMS

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Time of Channel Occupancy(2) (2441 MHz; 10.000 dBm; 1 MHz)

Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

Result

DUT Frequency (MHz)	Result	Number of Hops	Average time of occupancy (ms)	Threshold (dBm)
2441.000000	PASS	118	68.760	-10.0

Periode


Min (ms)	Max (ms)	Mean (ms)
7.500	1597.450	265.345

Transmit Time per Hop

Min (ms)	Max (ms)	Limit Max for Max (ms)	Limit Min for Max (ms)	Mean (ms)
0.41	0.79	400.000	0.000	0.578

DwellTime

Min (ms)	Max (ms)	Mean (ms)
1.510	1.650	1.635



FCC Part 47 §15.247 2400-2483.5 MHz 2017

Measurement

Setting	Instrument Value	Target Value
Center Frequency	2.44100 GHz	2.44100 GHz
Span	ZeroSpan	ZeroSpan
RBW	500.000 kHz	~ 500.000 kHz
VBW	1.000 MHz	~ 1.500 MHz
SweepPoints	30001	~ 30001
SweepTime	31.600 s	31.600 s
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	0.000 dB	0.000 dB
Detector	MaxPeak	MaxPeak
SweepCount	1	1
Filter	Channel	Channel
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamp	off	off
Trigger	External	External
Trigger Offset	0.000 s	0.000 s

OSP

Setting	Instrument Value	Target Value
Measurement Time	31.600 s	31.600 s
Tracepoints	31600000	31600000
Time resolution	1.000 µs	1.000 µs
Detector	RMS	RMS

FCC Part 47 §15.247 2400-2483.5 MHz 2017

Time of Channel Occupancy(3) (2441 MHz; 10.000 dBm; 1 MHz)

Test according to FCC title 47 part 15 §15.247(a), KDB 558074 D01 DTS Meas Guidance v04 and ANSI C63.10-2013

Result

DUT Frequency (MHz)	Result	Number of Hops	Average time of occupancy (ms)	Threshold (dBm)
2441.000000	PASS	63	62.420	-10.0

Periode


Min (ms)	Max (ms)	Mean (ms)
25.000	1406.210	461.176

Transmit Time per Hop

Min (ms)	Max (ms)	Limit Max for Max (ms)	Limit Min for Max (ms)	Mean (ms)
0.75	1.890	400.000	0.000	0.977

DwellTime

Min (ms)	Max (ms)	Mean (ms)
2.770	9.150	3.073



FCC Part 47 §15.247 2400-2483.5 MHz 2017

Measurement

Setting	Instrument Value	Target Value
Center Frequency	2.44100 GHz	2.44100 GHz
Span	ZeroSpan	ZeroSpan
RBW	500.000 kHz	~ 500.000 kHz
VBW	1.000 MHz	~ 1.500 MHz
SweepPoints	30001	~ 30001
SweepTime	31.600 s	31.600 s
Reference Level	-10.000 dBm	-10.000 dBm
Attenuation	0.000 dB	0.000 dB
Detector	MaxPeak	MaxPeak
SweepCount	1	1
Filter	Channel	Channel
Trace Mode	Clear Write	Clear Write
SweepType	Sweep	AUTO
Preamp	off	off
Trigger	External	External
Trigger Offset	0.000 s	0.000 s


OSP

Setting	Instrument Value	Target Value
Measurement Time	31.600 s	31.600 s
Tracepoints	31600000	31600000
Time resolution	1.000 µs	1.000 µs
Detector	RMS	RMS


Appendix B.6: Test Results of Conducted Spurious Emissions Measured in 100 kHz Bandwidth

B.6.1 Test Results of GFSK


Low Channel



Middle Channel




High Channel




Date: 28.OCT.2019 02:55:06


Band Edge, Low Channel



Band Edge, High Channel




Band Edge, Hopping Mode, Low Channel



Date: 28.OCT.2019 02:58:22


Band Edge, Hopping Mode, High Channel




Date: 28.OCT.2019 02:57:49

B.6.2 Test Results of $\pi/4$ DQPSK

Low Channel




Middle Channel




Produkte
Products

High Channel




Date: 28.OCT.2019 03:15:35

Band Edge, Low Channel




Date: 28.OCT.2019 03:13:35

Band Edge, High Channel




Date: 28.OCT.2019 03:10:46

Band Edge, Hopping Mode, Low Channel



Date: 28.OCT.2019 03:01:43

Band Edge, Hopping Mode, High Channel



Date: 28.OCT.2019 03:02:08

Note: Testing was carried out within frequency range 9 kHz to the tenth harmonics. The measurement results below 30MHz and 18GHz - 26.5GHz were greater than 20dB below the limit, so only the radiated spurious emissions from 30MHz to 18GHz were reported.

Appendix B.7: Test Results of Radiated Spurious Emissions

30MHz - 1GHz (Worst case)


Test

1 / 1

Test Report

EUT Information

EUT Name:	Wireless charging headphone
Model:	EE5244
Test Mode:	TX BT Low Channel
Test Voltage:	Fully charged battery
Remark:	Temp:22; Humi:54%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
50.030500	17.10	--	40.00	22.90	100.0	H	324.0	-18.6
95.766000	10.48	--	43.50	33.02	100.0	H	54.0	-19.9


Test

1 / 1

Test Report

EUT Information

EUT Name:	Wireless charging headphone
Model:	EE5244
Test Mode:	TX BT Low Channel
Test Voltage:	Fully charged battery
Remark:	Temp:22; Humi:54%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
39.506000	24.61	---	40.00	15.39	100.0	V	264.0	-20.6
50.273000	28.59	---	40.00	11.41	100.0	V	190.0	-18.6
56.141500	29.88	---	40.00	10.12	100.0	V	6.0	-18.9

23/10/2019

4:44:59 PM


Test

1 / 1

Test Report

EUT Information

EUT Name:	Wireless charging headphone
Model:	EE5244
Test Mode:	TX BT High Channel
Test Voltage:	Fully charged battery
Remark:	Temp:22; Humi:54%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
49.109000	14.84	---	40.00	25.16	100.0	H	175.0	-18.6
62.446500	14.57	---	40.00	25.43	100.0	H	29.0	-19.8

23/10/2019

4:48:09 PM


Test

1 / 1

Test Report

EUT Information

EUT Name:	Wireless charging headphone
Model:	EE5244
Test Mode:	TX BT High Channel
Test Voltage:	Fully charged battery
Remark:	Temp:22; Humi:54%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
56.190000	29.84	---	40.00	10.16	100.0	V	223.0	-18.9
115.602500	11.90	---	43.50	31.60	100.0	V	190.0	-20.2

23/10/2019

4:51:08 PM

1GHz - 18GHz
Low Channel


Test

1 / 1

Test Report

EUT Information

EUT Name:	Wireless charging headphone
Model:	EE5244
Test Mode:	TX BT Low Channel
Test Voltage:	Fully charged battery
Remark:	Temp:22; Humi:54%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2402.000000	96.27	---	74.00	-22.27	100.0	H	6.0	7.0
2402.000000	---	95.94	54.00	-41.94	100.0	H	6.0	7.0
4804.000000	54.05	---	74.00	19.95	100.0	H	283.0	13.6
4804.000000	---	48.45	54.00	5.55	100.0	H	283.0	13.6
7204.966667	---	48.11	54.00	5.89	100.0	H	119.0	8.8
7205.458333	53.98	---	74.00	20.02	100.0	H	119.0	8.8


Test

1 / 1

Test Report

EUT Information

EUT Name:	Wireless charging headphone
Model:	EE5244
Test Mode:	TX BT Low Channel
Test Voltage:	Fully charged battery
Remark:	Temp:22; Humi:54%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2402.000000	---	101.69	54.00	-47.69	100.0	V	36.0	7.0
2402.000000	102.02	---	74.00	-28.02	100.0	V	36.0	7.0
4803.500000	53.33	---	74.00	20.67	100.0	V	304.0	13.6
4804.000000	---	47.37	54.00	6.63	100.0	V	48.0	13.6
7205.458333	59.83	---	74.00	14.17	100.0	V	303.0	8.8
7206.933333	---	47.17	54.00	6.83	100.0	V	303.0	8.8
9599.875000	---	41.26	54.00	12.74	100.0	V	177.0	10.4
9599.875000	46.39	---	74.00	27.61	100.0	V	177.0	10.4

24/10/2019

2:41:39 PM

Middle Channel


Test

1 / 1

Test Report

EUT Information

EUT Name:	Wireless charging headphone
Model:	EE5244
Test Mode:	TX BT Mid Channel
Test Voltage:	Fully charged battery
Remark:	Temp:22; Humi:54%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2441.000000	---	96.58	54.00	-42.58	100.0	H	190.0	7.4
2441.000000	96.98	---	74.00	-22.98	100.0	H	190.0	7.4
4882.000000	---	44.41	54.00	9.59	100.0	H	291.0	13.4
4882.000000	52.47	---	74.00	21.53	100.0	H	291.0	13.4
7322.475000	---	49.73	54.00	4.27	100.0	H	219.0	8.2
7322.475000	52.77	---	74.00	21.23	100.0	H	219.0	8.2


Test

1 / 1

Test Report

EUT Information

EUT Name:	Wireless charging headphone
Model:	EE5244
Test Mode:	TX BT Mid Channel
Test Voltage:	Fully charged battery
Remark:	Temp:22; Humi:54%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2441.000000	103.38	---	74.00	-29.38	100.0	V	29.0	7.4
2441.000000	---	103.00	54.00	-49.00	100.0	V	29.0	7.4
4881.500000	53.81	---	74.00	20.19	100.0	V	310.0	13.4
4882.000000	---	46.02	54.00	7.98	100.0	V	310.0	13.4
7321.983333	57.08	---	74.00	16.92	100.0	V	300.0	8.2
7323.950000	---	45.67	54.00	8.33	100.0	V	300.0	8.2
9755.733333	---	44.12	54.00	9.88	100.0	V	190.0	10.4
9755.733333	47.67	---	74.00	26.33	100.0	V	190.0	10.4

24/10/2019

3:08:04 PM

High Channel


Test

1 / 1

Test Report

EUT Information

EUT Name:	Wireless charging headphone
Model:	EE5244
Test Mode:	TX BT High Channel
Test Voltage:	Fully charged battery
Remark:	Temp:22; Humi:54%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2480.000000	---	95.50	54.00	-41.50	100.0	H	317.0	7.4
2480.000000	96.02	---	74.00	-22.02	100.0	H	317.0	7.4
4960.000000	---	44.55	54.00	9.45	100.0	H	356.0	13.2
4960.000000	52.19	---	74.00	21.81	100.0	H	356.0	13.2
7439.491667	---	44.21	54.00	9.79	100.0	H	70.0	8.4
7439.491667	47.82	---	74.00	26.18	100.0	H	70.0	8.4

24/10/2019

3:34:46 PM


Test

1 / 1

Test Report

EUT Information

EUT Name:	Wireless charging headphone
Model:	EE5244
Test Mode:	TX BT High Channel
Test Voltage:	Fully charged battery
Remark:	Temp:22; Humi:54%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2480.000000	101.53	---	74.00	-27.53	100.0	V	30.0	7.4
2480.000000	---	100.89	54.00	-46.89	100.0	V	30.0	7.4
4959.000000	52.60	---	74.00	21.40	100.0	V	52.0	13.2
4960.000000	---	47.86	54.00	6.14	100.0	V	52.0	13.2
7439.491667	56.24	---	74.00	17.76	100.0	V	353.0	8.4
7440.475000	---	49.55	54.00	4.45	100.0	V	353.0	8.4
9911.591667	---	40.86	54.00	13.14	100.0	V	195.0	10.8
9912.083333	46.98	---	74.00	27.02	100.0	V	195.0	10.8

24/10/2019

3:29:14 PM

Appendix B.8: Test Results of Radiated Emissions in Restricted Bands

Low channel


Test

1 / 1

Test Report

EUT Information

EUT Name:	Wireless charging headphone
Model:	EE5244
Test Mode:	TX BT Low Channel
Test Voltage:	Fully charged battery
Remark:	Temp:22; Humi:54%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Poi	Azimuth (deg)	Corr. (dB/m)
2322.451765	---	39.52	54.00	14.48	100.0	H	267.0	6.6
2322.501177	47.99	---	74.00	26.01	100.0	H	267.0	6.6


Test

1 / 1

Test Report

EUT Information

EUT Name:	Wireless charging headphone
Model:	EE5244
Test Mode:	TX BT Low Channel
Test Voltage:	Fully charged battery
Remark:	Temp:22; Humi:54%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2322.056471	—	43.89	54.00	10.11	100.0	V	200.0	6.6
2322.435294	50.01	—	74.00	23.99	100.0	V	80.0	6.6

24/10/2019

2:48:35 PM

High channel


Test

1 / 1

Test Report

EUT Information

EUT Name:	Wireless charging headphone
Model:	EE5244
Test Mode:	TX BT High Channel
Test Voltage:	Fully charged battery
Remark:	Temp:22; Humi:54%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2483.705882	55.36	---	74.00	18.64	100.0	H	229.0	7.4
2483.724265	---	48.10	54.00	5.90	100.0	H	229.0	7.4


Test

1 / 1

Test Report

EUT Information

EUT Name:	Wireless charging headphone
Model:	EE5244
Test Mode:	TX BT High Channel
Test Voltage:	Fully charged battery
Remark:	Temp:22; Humi:54%
Test Standard:	FCC 15.247
Tested By:	Kei Zhang
Reviewed By:	Terry Yin



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Height (cm)	Pol	Azimuth (deg)	Corr. (dB/m)
2483.511030	—	50.48	54.00	3.52	100.0	V	198.0	7.4
2483.636030	57.99	—	74.00	16.01	100.0	V	38.0	7.4

24/10/2019

3:45:09 PM

Appendix C: Test Results of FCC 15B

APPENDIX C: TEST RESULTS OF FCC 15B	1
APPENDIX C.1: TEST PLOTS OF CONDUCTED EMISSION ON AC MAINS	2
<i>Mode D, Charging mode.....</i>	<i>2</i>
APPENDIX C.2: TEST PLOTS OF RADIATED EMISSION, BELOW 1GHZ.....	4
<i>Mode D, Charging mode.....</i>	<i>4</i>
<i>Mode E, Aux in playing mode</i>	<i>6</i>
<i>Mode F, TF card playing mode.....</i>	<i>8</i>
APPENDIX C.3: TEST PLOTS OF RADIATED EMISSION, ABOVE 1GHZ	10
<i>Mode D, Charging mode.....</i>	<i>10</i>
<i>Mode E, Aux in playing mode</i>	<i>12</i>
<i>Mode F, TF card playing mode.....</i>	<i>14</i>

Appendix C.1: Test Plots of Conducted Emission on AC Mains

Mode D, Charging mode


FCC L

1 / 1

Test Report

EUT Information

EUT Name:	Wireless charging headphones
Model:	EE5244
Order No.:	168131232
Test Mode:	Charging mode
Test Voltage:	DC 5V
Test By:	Charlie Wang
Review By:	Gary Chen
Remark:	L



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.596000	---	28.00	46.00	18.00	---	---	L1	9.7
0.604000	36.47	---	56.00	19.53	---	---	L1	9.7
0.700000	43.05	---	56.00	12.95	---	---	L1	9.7
0.700000	---	34.73	46.00	11.27	---	---	L1	9.7
1.112000	---	26.81	46.00	19.19	---	---	L1	9.7
1.120000	36.15	---	56.00	19.85	---	---	L1	9.7
1.236000	---	26.97	46.00	19.03	---	---	L1	9.7
1.248000	36.67	---	56.00	19.33	---	---	L1	9.7
1.944000	---	25.96	46.00	20.04	---	---	L1	9.7
1.972000	35.03	---	56.00	20.97	---	---	L1	9.7
2.732000	---	25.58	46.00	20.42	---	---	L1	9.8
2.764000	34.81	---	56.00	21.19	---	---	L1	9.8


FCC N

1 / 1

Test Report

EUT Information

EUT Name:	Wireless charging headphones
Model:	EE5244
Order No.:	168131232
Test Mode:	Charging mode
Test Voltage:	DC 5V
Test By:	Charlie Wang
Review By:	Gary Chen
Remark:	N



Critical_Freqs

Frequency (MHz)	MaxPeak (dBµV)	Average (dBµV)	Limit (dBµV)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Line	Corr. (dB)
0.592000	---	27.99	46.00	18.01	---	---	N	9.7
0.592000	35.96	---	56.00	20.04	---	---	N	9.7
0.700000	40.83	---	56.00	15.17	---	---	N	9.7
0.700000	---	34.46	46.00	11.54	---	---	N	9.7
1.100000	34.49	---	56.00	21.51	---	---	N	9.7
1.112000	---	26.72	46.00	19.28	---	---	N	9.7
1.232000	---	26.92	46.00	19.08	---	---	N	9.7
1.244000	34.36	---	56.00	21.64	---	---	N	9.7
1.876000	32.39	---	56.00	23.61	---	---	N	9.7
1.948000	---	25.93	46.00	20.07	---	---	N	9.7
2.732000	---	25.33	46.00	20.67	---	---	N	9.8
2.752000	32.61	---	56.00	23.39	---	---	N	9.8

10/30/2019

3:11:12 PM

Appendix C.2: Test Plots of Radiated Emission, Below 1GHz

Mode D, Charging mode


FCC H

1 / 1

EMC32 Report

EUT Information

EUT Name:	Wireless charging headphones
Model:	EE5244
Order No:	168131232
Test Mode:	Charging mode
Test Voltage:	DC 5V
Test By:	Charlie Wang
Review By:	Gary Chen
Remark:	3M Chamber



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
194.900000	28.55	43.50	14.95	---	---	150.0	H	166.0
952.664000	33.42	46.00	12.58	---	---	150.0	H	245.0
595.413000	29.50	46.00	16.50	---	---	200.0	H	108.0
166.285000	24.14	43.50	19.36	---	---	200.0	H	220.0
85.872000	20.60	40.00	19.40	---	---	250.0	H	222.0
87.715000	22.61	40.00	17.39	---	---	250.0	H	222.0


FCC V

1 / 1

EMC32 Report

EUT Information

EUT Name:	Wireless charging headphones
Model:	EE5244
Order No:	168131232
Test Mode:	Charging mode
Test Voltage:	DC 5V
Test By:	Charlie Wang
Review By:	Gary Chen
Remark:	3M Chamber



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
64.338000	24.81	40.00	15.19	---	---	100.0	V	115.0
33.007000	26.13	40.00	13.87	---	---	100.0	V	131.0
48.527000	23.11	40.00	16.89	---	---	100.0	V	231.0
842.084000	34.80	46.00	11.20	---	---	150.0	V	176.0
694.256000	29.44	46.00	16.56	---	---	150.0	V	268.0
87.909000	23.37	40.00	16.63	---	---	150.0	V	324.0

Mode E, Aux in playing mode


FCC H

1 / 1

EMC32 Report

EUT Information

EUT Name:	Wireless charging headphones
Model:	EE5244
Order No:	168131232
Test Mode:	Aux in playing mode
Test Voltage:	DC 5V
Test By:	Charlie Wang
Review By:	Gary Chen
Remark:	3M Chamber



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
698.815000	30.29	46.00	15.71	---	---	100.0	H	102.0
299.951000	27.41	46.00	18.59	---	---	100.0	H	255.0
52.504000	19.84	40.00	20.16	---	---	150.0	H	190.0
914.058000	33.75	46.00	12.25	---	---	200.0	H	88.0
479.983000	35.32	46.00	10.68	---	---	200.0	H	332.0
87.909000	21.22	40.00	18.78	---	---	200.0	H	335.0


FCC V

1 / 1

EMC32 Report

EUT Information

EUT Name:	Wireless charging headphones
Model:	EE5244
Order No:	168131232
Test Mode:	Aux in playing mode
Test Voltage:	DC 5V
Test By:	Charlie Wang
Review By:	Gary Chen
Remark:	3M Chamber



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
890.390000	32.96	46.00	13.05	---	---	100.0	V	318.0
85.872000	22.53	40.00	17.47	---	---	150.0	V	210.0
87.327000	24.44	40.00	15.56	---	---	150.0	V	210.0
689.406000	29.20	46.00	16.80	---	---	200.0	V	63.0
45.132000	21.34	40.00	18.66	---	---	200.0	V	68.0
479.983000	28.25	46.00	17.75	---	---	200.0	V	218.0

Mode F, TF card playing mode


FCC H

1 / 1

EMC32 Report

EUT Information

EUT Name:	Wireless charging headphones
Model:	EE5244
Order No:	168131232
Test Mode:	TF card playing
Test Voltage:	DC 5V
Test By:	Charlie Wang
Review By:	Gary Chen
Remark:	3M Chamber



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
290.833000	35.21	46.00	10.79	---	---	100.0	H	304.0
939.763000	33.07	46.00	12.93	---	---	200.0	H	212.0
495.988000	32.68	46.00	13.32	---	---	200.0	H	297.0
479.983000	35.46	46.00	10.54	---	---	200.0	H	313.0
161.532000	32.29	43.50	11.21	---	---	250.0	H	205.0
87.715000	22.99	40.00	17.01	---	---	250.0	H	326.0


FCC V

1 / 1

EMC32 Report

EUT Information

EUT Name:	Wireless charging headphones
Model:	EE5244
Order No:	168131232
Test Mode:	TF card playing
Test Voltage:	DC 5V
Test By:	Charlie Wang
Review By:	Gary Chen
Remark:	3M Chamber



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol	Azimuth (deg)
53.862000	19.70	40.00	20.30	---	---	100.0	V	139.0
85.775000	22.33	40.00	17.67	---	---	100.0	V	291.0
87.715000	25.13	40.00	14.87	---	---	100.0	V	291.0
958.193000	33.54	46.00	12.46	---	---	150.0	V	115.0
479.983000	28.38	46.00	17.62	---	---	200.0	V	58.0
694.256000	30.09	46.00	15.91	---	---	200.0	V	212.0

Appendix C.3: Test Plots of Radiated Emission, Above 1GHz

Mode D, Charging mode


FCC H

1 / 1

EMC32 Report

EUT Information

EUT Name:	Wireless charging headphones
Model:	EE5244
Order No:	168131232
Test Mode:	Charging mode
Test Voltage:	DC 5V
Test By:	Charlie Wang
Review By:	Gary Chen
Standard:	3M Chamber



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol
2393.500000	---	33.50	54.00	20.50	---	---	100.0	H
2765.500000	---	35.51	54.00	18.49	---	---	100.0	H
2765.500000	36.77	---	74.00	37.23	---	---	100.0	H
2421.500000	34.42	---	74.00	39.58	---	---	100.0	H
4708.000000	---	40.94	54.00	13.06	---	---	100.0	H
4708.000000	41.86	---	74.00	32.14	---	---	100.0	H
3398.000000	---	36.48	54.00	17.52	---	---	100.0	H
4057.500000	---	38.40	54.00	15.60	---	---	100.0	H
4057.500000	39.28	---	74.00	34.72	---	---	100.0	H
5516.500000	---	37.67	54.00	16.33	---	---	100.0	H
3314.500000	37.70	---	74.00	36.30	---	---	100.0	H
5987.000000	38.41	---	74.00	35.59	---	---	100.0	H


FCC V

1 / 1

EMC32 Report

EUT Information

EUT Name:	Wireless charging headphones
Model:	EE5244
Order No:	168131232
Test Mode:	Charging mode
Test Voltage:	DC 5V
Test By:	Charlie Wang
Review By:	Gary Chen
Standard:	3M Chamber



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol
4180.500000	---	38.14	54.00	15.86	---	---	100.0	V
3644.000000	39.94	---	74.00	34.06	---	---	100.0	V
2284.000000	34.08	---	74.00	39.92	---	---	100.0	V
3393.500000	---	38.27	54.00	15.73	---	---	100.0	V
3393.500000	39.09	---	74.00	34.91	---	---	100.0	V
2679.000000	37.00	---	74.00	37.00	---	---	100.0	V
2679.000000	---	36.27	54.00	17.73	---	---	100.0	V
4715.500000	---	39.26	54.00	14.74	---	---	100.0	V
4693.000000	40.09	---	74.00	33.91	---	---	100.0	V
2425.500000	---	32.68	54.00	21.32	---	---	100.0	V
5987.000000	39.31	---	74.00	34.69	---	---	100.0	V
5997.000000	---	38.18	54.00	15.82	---	---	100.0	V

Mode E, Aux in playing mode


FCC H

1 / 1

EMC32 Report

EUT Information

EUT Name:	Wireless charging headphones
Model:	EE5244
Order No:	168131232
Test Mode:	Aux in playing mode
Test Voltage:	DC 5V
Test By:	Charlie Wang
Review By:	Gary Chen
Remark:	3M Chamber



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol
2752.000000	37.02	---	74.00	36.98	---	---	100.0	H
2444.000000	34.35	---	74.00	39.65	---	---	100.0	H
3796.000000	---	38.33	54.00	15.67	---	---	100.0	H
3796.000000	39.11	---	74.00	34.89	---	---	100.0	H
2442.000000	---	32.93	54.00	21.07	---	---	100.0	H
3465.000000	---	36.38	54.00	17.62	---	---	100.0	H
3392.500000	37.80	---	74.00	36.20	---	---	100.0	H
4404.000000	40.11	---	74.00	33.89	---	---	100.0	H
4404.000000	---	39.38	54.00	14.63	---	---	100.0	H
5992.500000	---	37.84	54.00	16.16	---	---	100.0	H
5992.500000	38.59	---	74.00	35.41	---	---	100.0	H
2650.000000	---	35.45	54.00	18.55	---	---	100.0	H


FCC V

1 / 1

EMC32 Report

EUT Information

EUT Name:	Wireless charging headphones
Model:	EE5244
Order No:	168131232
Test Mode:	Aux in playing mode
Test Voltage:	DC 5V
Test By:	Charlie Wang
Review By:	Gary Chen
Remark:	3M Chamber



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol
3952.500000	39.12	---	74.00	34.88	---	---	100.0	V
4516.500000	---	39.88	54.00	14.12	---	---	100.0	V
4516.500000	40.69	---	74.00	33.31	---	---	100.0	V
2772.500000	---	35.57	54.00	18.43	---	---	100.0	V
2772.500000	37.06	---	74.00	36.94	---	---	100.0	V
3263.000000	---	36.61	54.00	17.39	---	---	100.0	V
5948.500000	39.06	---	74.00	34.94	---	---	100.0	V
5948.500000	---	38.11	54.00	15.89	---	---	100.0	V
2389.000000	33.81	---	74.00	40.19	---	---	100.0	V
2224.500000	---	32.68	54.00	21.32	---	---	100.0	V
4031.000000	---	37.89	54.00	16.11	---	---	100.0	V
3453.500000	37.64	---	74.00	36.36	---	---	100.0	V

Mode F, TF card playing mode


FCC H

1 / 1

EMC32 Report

EUT Information

EUT Name:	Wireless charging headphones
Model:	EE5244
Order No:	168131232
Test Mode:	TF card playing
Test Voltage:	DC 5V
Test By:	Charlie Wang
Review By:	Gary Chen
Standard:	3M Chamber



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol
5994.500000	38.99	---	74.00	35.02	---	---	100.0	H
4359.000000	40.31	---	74.00	33.69	---	---	100.0	H
2422.000000	34.30	---	74.00	39.70	---	---	100.0	H
2422.000000	---	33.09	54.00	20.91	---	---	100.0	H
2689.000000	---	35.48	54.00	18.52	---	---	100.0	H
3225.500000	---	37.03	54.00	16.97	---	---	100.0	H
3225.500000	38.42	---	74.00	35.58	---	---	100.0	H
4709.500000	---	38.96	54.00	15.04	---	---	100.0	H
3845.000000	---	38.00	54.00	16.00	---	---	100.0	H
3845.000000	40.38	---	74.00	33.62	---	---	100.0	H
2580.000000	36.64	---	74.00	37.36	---	---	100.0	H
5995.000000	---	38.13	54.00	15.87	---	---	100.0	H


FCC V

1 / 1

EMC32 Report

EUT Information

EUT Name:	Wireless charging headphones
Model:	EE5244
Order No:	168131232
Test Mode:	TF card playing
Test Voltage:	DC 5V
Test By:	Charlie Wang
Review By:	Gary Chen
Standard:	3M Chamber



Critical Freqs

Frequency (MHz)	MaxPeak (dBµV/m)	Average (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Meas. Time (ms)	Bandwidth (kHz)	Height (cm)	Pol
3370.000000	---	36.36	54.00	17.64	---	---	100.0	V
3234.000000	37.39	---	74.00	36.61	---	---	100.0	V
4509.000000	41.82	---	74.00	32.18	---	---	100.0	V
4509.000000	---	39.51	54.00	14.49	---	---	100.0	V
2749.500000	---	36.02	54.00	17.98	---	---	100.0	V
5994.500000	---	38.23	54.00	15.77	---	---	100.0	V
5994.500000	39.56	---	74.00	34.44	---	---	100.0	V
3753.000000	---	37.25	54.00	16.75	---	---	100.0	V
2443.000000	---	33.43	54.00	20.57	---	---	100.0	V
2443.000000	34.42	---	74.00	39.58	---	---	100.0	V
2693.000000	37.99	---	74.00	36.01	---	---	100.0	V
3770.500000	38.56	---	74.00	35.44	---	---	100.0	V