

| | | | | | |
|--|---|--|--|--|--|
| Prüfbericht-Nr.: <i>Test report no.:</i> | CN22OG63 002 | Auftrags-Nr.: <i>Order no.:</i> | 168366486 | Seite 1 von 25 <i>Page 1 of 25</i> | |
| Kunden-Referenz-Nr.: <i>Client reference no.:</i> | N/A | Auftragsdatum: <i>Order date:</i> | 2022-04-08 | | |
| Auftraggeber: <i>Client:</i> | UP Global Sourcing Ltd. UP Global Sourcing, Manor Mill, Victoria Street, Chadderton, Oldham, United Kingdom | | | | |
| Prüfgegenstand: <i>Test item:</i> | True Wireless Earbud | | | | |
| Bezeichnung / Typ-Nr.: <i>Identification / Type no.:</i> | EE6011BLKPRIFOB, EE6011PNKPRIFOB, EE6011GRNPRIFOB | | | | |
| Auftrags-Inhalt: <i>Order content:</i> | Test Report | | | | |
| Prüfgrundlage: <i>Test specification:</i> | FCC CFR Title 47, Part 15, Subpart C, Section 15.247 | | | | |
| Wareneingangsdatum: <i>Date of sample receipt:</i> | 2022-04-12 | Please refer to Photo Document | | | |
| Prüfmuster-Nr.: <i>Test sample no.:</i> | A003239148-005~008 | | | | |
| Prüfzeitraum: <i>Testing period:</i> | 2022-04-13 - 2022-04-22 | | | | |
| Ort der Prüfung: <i>Place of testing:</i> | TÜV Rheinland (Shenzhen) Co., Ltd. | | | | |
| Prüflaboratorium: <i>Testing laboratory:</i> | TÜV Rheinland (Shenzhen) Co., Ltd. | | | | |
| Prüfergebnis*: <i>Test result*:</i> | Pass | | | | |
| geprüft von: <i>tested by:</i> |  Lin Lin | genehmigt von: <i>authorized by:</i> |  Hardy Suo | | |
| Datum: <i>Date:</i> | 2022-04-27 | Ausstellungsdatum: <i>Issue date:</i> | 2022-04-27 | | |
| Stellung / Position: | Senior Project Manager | Stellung / Position: | Reviewer | | |
| Sonstiges / Other: | FCC ID: 2AAR2EE6011 | | | | |
| Zustand des Prüfgegenstandes bei Anlieferung: <i>Condition of the test item at delivery:</i> | Prüfmuster vollständig und unbeschädigt <i>Test item complete and undamaged</i> | | | | |
| * Legende: | 1 = sehr gut P(ass) = entspricht o.g. Prüfgrundlage(n) | 2 = gut F(ail) = entspricht nicht o.g. Prüfgrundlage(n) | 3 = befriedigend F(ail) = entspricht nicht o.g. Prüfgrundlage(n) | 4 = ausreichend N/A = nicht anwendbar | 5 = mangelhaft N/T = nicht getestet |
| * Legend: | 1 = very good P(ass) = passed a.m. test specification(s) | 2 = good F(ail) = failed a.m. test specification(s) | 3 = satisfactory F(ail) = failed a.m. test specification(s) | 4 = sufficient N/A = not applicable | 5 = poor N/T = not tested |
| Dieser Prüfbericht bezieht sich nur auf das o.g. Prüfmuster und darf ohne Genehmigung der Prüfstelle nicht auszugsweise vervielfältigt werden. Dieser Bericht berechtigt nicht zur Verwendung eines Prüfzeichens. <i>This test report only relates to the a. m. test sample. Without permission of the test center this test report is not permitted to be duplicated in extracts. This test report does not entitle to carry any test mark.</i> | | | | | |

Test Summary

5.1.1 ANTENNA REQUIREMENT*RESULT: Pass***5.1.2 MAXIMUM PEAK CONDUCTED OUTPUT POWER***RESULT: Pass***5.1.3 CONDUCTED POWER SPECTRAL DENSITY***RESULT: Pass***5.1.4 6dB BANDWIDTH***RESULT: Pass***5.1.5 99% BANDWIDTH***RESULT: Reference only***5.1.6 20dB BANDWIDTH***RESULT: Pass***5.1.7 CARRIER FREQUENCY SEPARATION***RESULT: Pass***5.1.8 NUMBER OF HOPPING FREQUENCY***RESULT: Pass***5.1.9 TIME OF OCCUPANCY***RESULT: Pass***5.1.10 CONDUCTED SPURIOUS EMISSIONS MEASURED IN 100 KHZ BANDWIDTH***RESULT: Pass***5.1.11 RADIATED SPURIOUS EMISSION***RESULT: Pass*

Contents

| | | |
|---------------|--|-----------|
| 1 | GENERAL REMARKS | 4 |
| 1.1 | COMPLEMENTARY MATERIALS | 4 |
| 2 | TEST SITES | 5 |
| 2.1 | TEST FACILITIES | 5 |
| 2.2 | LIST OF TEST AND MEASUREMENT INSTRUMENTS..... | 5 |
| 2.3 | TRACEABILITY | 6 |
| 2.4 | CALIBRATION | 6 |
| 2.5 | MEASUREMENT UNCERTAINTY..... | 6 |
| 2.6 | LOCATION OF ORIGINAL DATA..... | 6 |
| 2.7 | STATUS OF FACILITY USED FOR TESTING..... | 6 |
| 3 | GENERAL PRODUCT INFORMATION | 7 |
| 3.1 | PRODUCT FUNCTION AND INTENDED USE..... | 7 |
| 3.2 | RATINGS AND SYSTEM DETAILS | 7 |
| 3.3 | INDEPENDENT OPERATION MODES | 9 |
| 3.4 | NOISE GENERATING AND NOISE SUPPRESSING PARTS..... | 9 |
| 3.5 | SUBMITTED DOCUMENTS..... | 9 |
| 4 | TEST SET-UP AND OPERATION MODES | 10 |
| 4.1 | PRINCIPLE OF CONFIGURATION SELECTION | 10 |
| 4.2 | TEST OPERATION AND TEST SOFTWARE..... | 10 |
| 4.3 | SPECIAL ACCESSORIES AND AUXILIARY EQUIPMENT..... | 10 |
| 4.4 | COUNTERMEASURES TO ACHIEVE EMC COMPLIANCE..... | 10 |
| 4.5 | TEST SETUP DIAGRAM..... | 11 |
| 5 | TEST RESULTS | 13 |
| 5.1 | TRANSMITTER REQUIREMENT & TEST SUITES | 13 |
| <i>5.1.1</i> | <i>Antenna Requirement</i> | <i>13</i> |
| <i>5.1.2</i> | <i>Maximum Peak Conducted Output Power.....</i> | <i>14</i> |
| <i>5.1.3</i> | <i>Conducted Power Spectral Density</i> | <i>16</i> |
| <i>5.1.4</i> | <i>6dB Bandwidth</i> | <i>17</i> |
| <i>5.1.5</i> | <i>99% Bandwidth</i> | <i>18</i> |
| <i>5.1.6</i> | <i>20dB Bandwidth.....</i> | <i>19</i> |
| <i>5.1.7</i> | <i>Carrier Frequency Separation.....</i> | <i>20</i> |
| <i>5.1.8</i> | <i>Number of Hopping Frequency.....</i> | <i>21</i> |
| <i>5.1.9</i> | <i>Time of Occupancy</i> | <i>22</i> |
| <i>5.1.10</i> | <i>Conducted Spurious Emissions Measured in 100 kHz Bandwidth.....</i> | <i>23</i> |
| <i>5.1.11</i> | <i>Radiated Spurious Emission.....</i> | <i>24</i> |
| 6 | PHOTOGRAPHS OF THE TEST SET-UP..... | 25 |
| 7 | LIST OF TABLES..... | 25 |

1 General Remarks

1.1 Complementary Materials

All attachments are integral parts of this test report. This applies especially to the following appendix:

Appendix A: Photographs of the Test Set-up

Appendix B: Test Results of Bluetooth BR/EDR

Appendix C: Test Results of Bluetooth Low Energy

2 Test Sites

2.1 Test Facilities

TÜV Rheinland (Shenzhen) Co., Ltd.

No. 362 Huanguan Road Middle, Longhua District, 518110, Shenzhen, P. R. China.

FCC Accreditation Designation No.: CN1260

2.2 List of Test and Measurement Instruments

Table 1: List of Test and Measurement Equipment

| Radio Spectrum Testing (SRD-Tonscend) | | | | |
|--|---------------------|-------------------|-------------------|-------------------|
| Equipment | Manufacturer | Model | Serial No. | Cal. until |
| EXA Signal Analyzer, Multi-touch | Keysight | N9010B | MY60241175 | 2022-09-28 |
| MXG X-Series RF Vector Signal Generator | Keysight | N5182B | MY61250137 | 2022-09-28 |
| EXG X-Series Microwave Analog Signal Generator | Keysight | N5173B | MY61250141 | 2022-09-28 |
| DC power supply | Keysight | E3642A | MY61276100 | 2022-09-28 |
| Power Control Unit | Tonscend | JS0806-4ADC | N/A | 2022-09-28 |
| Automation Control Unit | Tonscend | JS0806-2 | 21C8060396 | 2022-09-28 |
| Test Software | Tonscend | JS1120-3 | N/A | N/A |
| Control PC | Lenovo | TianYi510S-071MB | YLX23JMF | N/A |
| Shielding Room 8# | Albatross | SR8 | APC17151-SR8 | 2024-06-22 |
| Unwanted Emission Testing (TS9975) | | | | |
| Equipment | Manufacturer | Model | Serial No. | Cal. until |
| EMI Test Receiver | R&S | ESR 7 | 102021 | 2022-08-10 |
| Signal Analyzer | R&S | FSV 40 | 101439 | 2022-08-09 |
| System Controller Interface | R&S | SCI-100 | S10010038 | N/A |
| Filterbank | R&S | Wlan | 100759 | 2022-08-09 |
| OSP | R&S | OSP 120 | 102040 | N/A |
| Pre-amplifier | R&S | SCU08F1 | 08320031 | 2022-08-09 |
| Amplifier | R&S | SCU-18F | 180070 | 2022-08-09 |
| Amplifier | R&S | SCU40A | 100475 | 2022-08-09 |
| Trilog Broadband Antenna (30 MHz - 7 GHz) | Schwarzbeck | VULB 9162 | 193 | 2022-08-08 |
| Double-Ridged Antenna (1 -18 GHz) | ETS-LINDGREN | 3117 | 00218717 | 2022-08-08 |
| Wideband Ridged Horn Antenna (18-40 GHz) | Steatite | QMS-00880 | 19067 | 2022-08-08 |
| Active Loop Antenna | Schwarzbeck | FMZB 1513 | 302 | 2022-09-13 |
| Test software | R&S | EMC32 (V10.60.10) | N/A | N/A |
| Control PC | Dell | OptiPlex 7050 | 36NV9P2 | N/A |
| 3m Semi-Anechoic Chamber | Albatross | SAC-3m | APC17151-SAC | 2024-06-22 |

2.3 Traceability

All measurement equipment calibrations are traceable to NIM (National Institute of Metrology) or where calibration is performed in other countries, to equivalent nationally recognized standards organizations.

2.4 Calibration

Equipment requiring calibration is calibrated periodically by the manufacturer or according to manufacturer's specifications. Additionally all equipment is verified for proper performance on a regular basis using in house standards or comparisons.

2.5 Measurement Uncertainty

| Parameter | Uncertainty |
|--|------------------------|
| Radio Frequency | $\pm 1 \times 10^{-7}$ |
| RF Power (conducted) | ± 2.5 dB |
| Radiated Emission of Transmitter, valid up to 26.5 GHz | ± 6 dB |
| Radiated Emission of Receiver, valid up to 26.5 GHz | ± 6 dB |
| Temperature | ± 1 °C |
| Humidity | ± 5 % |
| Voltage (DC) | ± 1 % |
| Voltage (AC, <10kHz) | ± 2 % |

2.6 Location of Original Data

The original copies of all test data taken during actual testing were attached at Appendix A & B & C of this report and delivered to the applicant. A copy has been retained in the TÜV Rheinland (Shenzhen) Co., Ltd. file for certification follow-up purposes.

2.7 Status of Facility Used for Testing

The TÜV Rheinland (Shenzhen) Co., Ltd. Test facility located at No. 362 Huanguan Road Middle, Longhua District, 518110, Shenzhen, P. R. China. is listed on the US Federal Communications Commission list of facilities approved to perform measurements.

3 General Product Information

3.1 Product Function and Intended Use

The EUT is a True Wireless Earbud, which consist of a Charging case, a left earbud and a right earbud, both left and right earbuds support Bluetooth BR&EDR and Bluetooth LE wireless technology.

For details refer to the User Manual, Technical Description and Circuit Diagram.

3.2 Ratings and System Details

Table 2: Technical Specification of EUT

| General Information of EUT | Value |
|--|--|
| Kind of Equipment: | True Wireless Earbud |
| Type Designation: | EE6011BLKPRIFOB, EE6011PNKPRIFOB, EE6011GRNPRIFOB Note1: The above models are only different in appearance color. Note2: The left and right earbud are the same. |
| FCC ID: | 2AAR2EE6011 |
| Operating Voltage (Battery pack of charging base): | Internal battery operated (3.7Vdc, 200mAh) or USB operated (PC input voltage 120Vac, 60Hz) |
| Operating Voltage (Battery pack of earphone): | Internal battery operated (3.7Vdc, 30mAh) |
| Antenna Type: | Integral Antenna |
| Antenna Gain: | -0.58 dBi |
| Technical Specification of Bluetooth BR/EDR | |
| Operating Frequency: | 2402 MHz to 2480 MHz |
| Type of Modulation: | GFSK, $\pi/4$ -DQPSK, 8DPSK |
| Channel Number: | 79 channels |
| Channel Separation: | 1MHz |
| Technical Specification of Bluetooth LE | |
| Operating Frequency: | 2402 MHz to 2480 MHz |
| Type of Modulation: | GFSK |
| Channel Number: | 40 channels |
| Channel Separation: | 2MHz |
| Data Rate: | 1Mbps, 2Mbps |

Table 3: RF Channel and Frequency of Bluetooth BR/EDR

| RF Channel | Frequency (MHz) | RF Channel | Frequency (MHz) | RF Channel | Frequency (MHz) | RF Channel | Frequency (MHz) |
|------------|-----------------|------------|-----------------|------------|-----------------|------------|-----------------|
| 0 | 2402.00 | 20 | 2422.00 | 40 | 2442.00 | 60 | 2462.00 |
| 1 | 2403.00 | 21 | 2423.00 | 41 | 2443.00 | 61 | 2463.00 |
| 2 | 2404.00 | 22 | 2424.00 | 42 | 2444.00 | 62 | 2464.00 |
| 3 | 2405.00 | 23 | 2425.00 | 43 | 2445.00 | 63 | 2465.00 |
| 4 | 2406.00 | 24 | 2426.00 | 44 | 2446.00 | 64 | 2466.00 |
| 5 | 2407.00 | 25 | 2427.00 | 45 | 2447.00 | 65 | 2467.00 |
| 6 | 2408.00 | 26 | 2428.00 | 46 | 2448.00 | 66 | 2468.00 |
| 7 | 2409.00 | 27 | 2429.00 | 47 | 2449.00 | 67 | 2469.00 |
| 8 | 2410.00 | 28 | 2430.00 | 48 | 2450.00 | 68 | 2470.00 |
| 9 | 2411.00 | 29 | 2431.00 | 49 | 2451.00 | 69 | 2471.00 |
| 10 | 2412.00 | 30 | 2432.00 | 50 | 2452.00 | 70 | 2472.00 |
| 11 | 2413.00 | 31 | 2433.00 | 51 | 2453.00 | 71 | 2473.00 |
| 12 | 2414.00 | 32 | 2434.00 | 52 | 2454.00 | 72 | 2474.00 |
| 13 | 2415.00 | 33 | 2435.00 | 53 | 2455.00 | 73 | 2475.00 |
| 14 | 2416.00 | 34 | 2436.00 | 54 | 2456.00 | 74 | 2476.00 |
| 15 | 2417.00 | 35 | 2437.00 | 55 | 2457.00 | 75 | 2477.00 |
| 16 | 2418.00 | 36 | 2438.00 | 56 | 2458.00 | 76 | 2478.00 |
| 17 | 2419.00 | 37 | 2439.00 | 57 | 2459.00 | 77 | 2479.00 |
| 18 | 2420.00 | 38 | 2440.00 | 58 | 2460.00 | 78 | 2480.00 |
| 19 | 2421.00 | 39 | 2441.00 | 59 | 2461.00 | | |

Test frequencies are lowest channel: 2402 MHz, middle channel: 2441 MHz and highest channel: 2480 MHz for Bluetooth BR/EDR

Table 4: RF Channel and Frequency of Bluetooth LE

| RF Channel | Frequency (MHz) | RF Channel | Frequency (MHz) | RF Channel | Frequency (MHz) | RF Channel | Frequency (MHz) |
|------------|-----------------|------------|-----------------|------------|-----------------|------------|-----------------|
| 0 | 2402 | 10 | 2422 | 20 | 2442 | 30 | 2462 |
| 1 | 2404 | 11 | 2424 | 21 | 2444 | 31 | 2464 |
| 2 | 2406 | 12 | 2426 | 22 | 2446 | 32 | 2466 |
| 3 | 2408 | 13 | 2428 | 23 | 2448 | 33 | 2468 |
| 4 | 2410 | 14 | 2430 | 24 | 2450 | 34 | 2470 |
| 5 | 2412 | 15 | 2432 | 25 | 2452 | 35 | 2472 |
| 6 | 2414 | 16 | 2434 | 26 | 2454 | 36 | 2474 |
| 7 | 2416 | 17 | 2436 | 27 | 2456 | 37 | 2476 |
| 8 | 2418 | 18 | 2438 | 28 | 2458 | 38 | 2478 |
| 9 | 2420 | 19 | 2440 | 29 | 2460 | 39 | 2480 |

Test frequencies are lowest channel: 2402 MHz, middle channel: 2440 MHz and highest channel: 2480 MHz for Bluetooth LE

3.3 Independent Operation Modes

The basic operation modes are:

- A. On, Bluetooth transmitting mode (BR & EDR mode)
 - 1) Low Channel
 - 2) Middle Channel
 - 3) High Channel
- B. On, Bluetooth transmitting mode (Bluetooth LE mode)
 - 1) Low Channel
 - 2) Middle Channel
 - 3) High Channel
- C. On, Transmitting on Hopping channel
- D. Off

3.4 Noise Generating and Noise Suppressing Parts

Refer to Circuit Diagram for further details.

3.5 Submitted Documents

- Application Form
- Operation Description
- Schematics
- PCB Layout
- User Manual
- Block Diagram
- Rating Label
- Parts List

4 Test Set-up and Operation Modes

4.1 Principle of Configuration Selection

Radio Spectrum: The equipment under test (EUT) was configured at its highest power output in order to measure its highest possible radiation and conducted level. The test modes were adapted accordingly in reference to the instructions for use.

Emission: The equipment under test (EUT) was configured to measure its highest possible radiation level. The test modes were adapted accordingly in reference to the instructions for use.

4.2 Test Operation and Test Software

Test operation refers to test setup in chapter 5. All tests were performed according to the procedures in ANSI C63.10: 2013.

According to clause 3.1, all tests were performed on model EE6011GRNPRIFOB in this report.

4.3 Special Accessories and Auxiliary Equipment

Table 5: Auxiliary Equipment Used during Test

| Description | Manufacturer | Model | S/N | Remark |
|---------------|--------------|---------------|-----------|--------------------|
| Laptop | Lenovo | T480 | PF-16A6N8 | Provided by Lab |
| Laptop | Lenovo | ThinkPad T480 | 10Q67059 | Provided by Lab |
| Mobile Phone | HUAWEI | STK-AL00 | N/A | Provided by Lab |
| Charging base | N/A | N/A | N/A | Provided by client |

4.4 Countermeasures to Achieve EMC Compliance

The test sample which has been tested contained the noise suppression parts as described in the Technical Construction File (TCF).

No additional measures were employed to achieve compliance.

4.5 Test Setup Diagram

Diagram of Measurement Configuration for Radiation Test (Below 1GHz)




Diagram of Measurement Configuration for Radiation Test (Above 1GHz)




Diagram of Measurement Configuration for Mains Conduction Measurement





Diagram of Measurement Configuration for Conducted Transmitter Measurement



5 Test Results

5.1 Transmitter Requirement & Test Suites

5.1.1 Antenna Requirement

RESULT:

Pass

Test Specification

Test standard : FCC Part 15.247(b)(4) and Part 15.203

According to the manufacturer declared, the EUT has an Integral antenna, the directional gain of antenna is -0.58 dBi, and the antenna connector is designed with permanent attachment and no consideration of replacement.

Therefore the EUT is considered sufficient to comply with the provision.

Refer to EUT Photo for further details.

5.1.2 Maximum Peak Conducted Output Power

RESULT:
Pass
Test Specification

| | |
|-------------------|--|
| Test standard | : FCC Part 15.247(b)(1)&(3) |
| Basic standard | : ANSI C63.10: 2013 |
| Limits | : FHSS < 0.125 Watts, DSSS < 1.0 Watts |
| Kind of test site | : Shielded Room |

Test Setup

| | |
|----------------------|-----------------------------|
| Date of testing | : 2022-04-20 |
| Input voltage | : Internal battery operated |
| Operation mode | : A, B |
| Test channel | : Low / Middle / High |
| Ambient temperature | : 24.8 °C |
| Relative humidity | : 55 % |
| Atmospheric pressure | : 101 kPa |

Table 6: Test Result of Maximum Peak Conducted Output Power, Bluetooth BR & EDR

| Test Mode | Test Channel (MHz) | Measured Peak Power | | Limit (W) |
|-------------------------------|--------------------|---------------------|--------|-----------|
| | | (dBm) | (W) | |
| GFSK (BR) | 2402.0 | -3.10 | 0.0005 | < 0.125 |
| | 2441.0 | -1.23 | 0.0008 | |
| | 2480.0 | -0.33 | 0.0009 | |
| Maximum Measured Value | | -0.33 | 0.0009 | |

| Test Mode | Test Channel (MHz) | Measured Peak Power | | Limit (W) |
|-------------------------------|--------------------|---------------------|--------|-----------|
| | | (dBm) | (W) | |
| 8DPSK (EDR) | 2402.0 | -2.14 | 0.0006 | < 0.125 |
| | 2441.0 | -0.36 | 0.0009 | |
| | 2480.0 | 0.37 | 0.0011 | |
| Maximum Measured Value | | 0.37 | 0.0011 | |

Table 7: Test Result of Maximum Peak Conducted Output Power, Bluetooth LE

| Test Mode | Test Channel (MHz) | Measured Peak Power | | Limit (W) |
|----------------------------|--------------------|---------------------|--------|-----------|
| | | (dBm) | (W) | |
| BLE (1 Mbps) | 2402 | -3.03 | 0.0005 | < 1.0 |
| | 2440 | -1.17 | 0.0008 | |
| | 2480 | -0.15 | 0.0010 | |
| Max. Measured Value | | -0.15 | 0.0010 | |

| Test Mode | Test Channel (MHz) | Measured Peak Power | | Limit (W) |
|----------------------------|--------------------|---------------------|--------|-----------|
| | | (dBm) | (W) | |
| BLE (2 Mbps) | 2402 | -2.85 | 0.0005 | < 1.0 |
| | 2440 | -0.91 | 0.0008 | |
| | 2480 | 0.02 | 0.0010 | |
| Max. Measured Value | | 0.02 | 0.0010 | |

Table 8: Test Result of Average Conducted Output Power, Bluetooth BR & EDR

| Test Mode | Test Channel (MHz) | Measured Average Power | | Remark |
|-------------------------------|--------------------|------------------------|--------|---------------|
| | | (dBm) | (W) | |
| GFSK (BR) | 2402.0 | -3.23 | 0.0005 | For reference |
| | 2441.0 | -1.82 | 0.0007 | |
| | 2480.0 | -0.62 | 0.0009 | |
| Maximum Measured Value | | -0.62 | 0.0009 | |

| Test Mode | Test Channel (MHz) | Measured Average Power | | Remark |
|-------------------------------|--------------------|------------------------|--------|---------------|
| | | (dBm) | (W) | |
| 8DPSK (EDR) | 2402.0 | -4.61 | 0.0003 | For reference |
| | 2441.0 | -2.56 | 0.0006 | |
| | 2480.0 | -1.68 | 0.0007 | |
| Maximum Measured Value | | -1.68 | 0.0007 | |

Table 9: Test Result of Average Conducted Output Power, Bluetooth LE

| Test Mode | Test Channel (MHz) | Measured Average Power | | Remark |
|----------------------------|--------------------|------------------------|--------|---------------|
| | | (dBm) | (W) | |
| BLE (1 Mbps) | 2402 | -3.23 | 0.0005 | For reference |
| | 2440 | -1.75 | 0.0007 | |
| | 2480 | -0.46 | 0.0009 | |
| Max. Measured Value | | -0.46 | 0.0009 | |

| Test Mode | Test Channel (MHz) | Measured Peak Power | | Limit (W) |
|----------------------------|--------------------|---------------------|--------|---------------|
| | | (dBm) | (W) | |
| BLE (2 Mbps) | 2402 | -3.75 | 0.0004 | For reference |
| | 2440 | -2.33 | 0.0006 | |
| | 2480 | -0.69 | 0.0009 | |
| Max. Measured Value | | -0.69 | 0.0009 | |

Note:

- 1) The cable loss is taken into account in results.
- 2) Antenna gain(G): -0.58 dBi

Prüfbericht - Nr.: CN22OG63 002
Test Report No.:Seite 16 von 25
Page 16 of 25

5.1.3 Conducted Power Spectral Density

RESULT:

Pass

Test Specification

Test standard : FCC Part 15.247(e)
Basic standard : ANSI C63.10: 2013
Limits : < 8 dBm / 3kHz
Kind of test site : Shielded Room

Test Setup

Date of testing : 2022-04-20
Input voltage : Internal battery operated
Operation mode : B
Test channel : Low / Middle / High
Ambient temperature : 24.8 °C
Relative humidity : 55 %
Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix C.

5.1.4 6dB Bandwidth

RESULT:**Pass****Test Specification**

| | | |
|-------------------|---|-----------------------|
| Test standard | : | FCC Part 15.247(a)(2) |
| Basic standard | : | ANSI C63.10: 2013 |
| Limits | : | > 500 kHz |
| Kind of test site | : | Shielded Room |

Test Setup

| | | |
|----------------------|---|---------------------------|
| Date of testing | : | 2022-04-20 |
| Input voltage | : | Internal battery operated |
| Operation mode | : | B |
| Test channel | : | Low / Middle / High |
| Ambient temperature | : | 24.8 °C |
| Relative humidity | : | 55 % |
| Atmospheric pressure | : | 101 kPa |

For the measurement records, refer to the appendix C.

5.1.5 99% Bandwidth

RESULT:**Reference only****Test Specification**

| | |
|-------------------|----------------------|
| Test standard | : FCC Part 15.247(a) |
| Basic standard | : ANSI C63.10: 2013 |
| Kind of test site | : Shielded Room |

Test Setup

| | |
|----------------------|-----------------------------|
| Date of testing | : 2022-04-20 |
| Input voltage | : Internal battery operated |
| Operation mode | : A, B |
| Test channel | : Low / Middle / High |
| Ambient temperature | : 24.8 °C |
| Relative humidity | : 55 % |
| Atmospheric pressure | : 101 kPa |

For the measurement records, refer to the appendix B & C.

5.1.6 20dB Bandwidth

RESULT:**Pass****Test Specification**

Test standard : FCC Part 15.247(a)(1)
Basic standard : ANSI C63.10: 2013
Kind of test site : Shielded Room

Test Setup

Date of testing : 2022-04-20
Input voltage : Internal battery operated
Operation mode : A
Test channel : Low / Middle / High
Ambient temperature : 24.8 °C
Relative humidity : 55 %
Atmospheric pressure : 101 kPa

For the measurement records, refer to the appendix B.

5.1.7 Carrier Frequency Separation

RESULT:**Pass****Test Specification**

| | |
|-------------------|--|
| Test standard | : FCC Part 15.247(a)(1) |
| Basic standard | : ANSI C63.10: 2013 |
| Limits | : $\geq 25\text{kHz}$ or 2/3 of 20dB bandwidth, whichever is greater |
| Kind of test site | : Shielded Room |

Test Setup

| | |
|----------------------|-----------------------------|
| Date of testing | : 2022-04-20 |
| Input voltage | : Internal battery operated |
| Operation mode | : C |
| Test channel | : Low / Middle / High |
| Ambient temperature | : 24.8 °C |
| Relative humidity | : 55 % |
| Atmospheric pressure | : 101 kPa |

For the measurement records, refer to the appendix B.

5.1.8 Number of Hopping Frequency

RESULT:**Pass****Test Specification**

| | | |
|-------------------|---|-------------------------------|
| Test standard | : | FCC part 15.247(a)(1)(iii) |
| Basic standard | : | ANSI C63.10: 2013 |
| Limits | : | ≥ 15 non-overlapping channels |
| Kind of test site | : | Shielded Room |

Test Setup

| | | |
|----------------------|---|---------------------------|
| Date of testing | : | 2022-04-20 |
| Input voltage | : | Internal battery operated |
| Operation mode | : | C |
| Ambient temperature | : | 24.8 °C |
| Relative humidity | : | 55 % |
| Atmospheric pressure | : | 101 kPa |

For the measurement records, refer to the appendix B.

5.1.9 Time of Occupancy

RESULT:**Pass****Test Specification**

| | | |
|-------------------|---|----------------------------|
| Test standard | : | FCC part 15.247(a)(1)(iii) |
| Basic standard | : | ANSI C63.10: 2013 |
| Limits | : | < 0.4s |
| Kind of test site | : | Shielded Room |

Test Setup

| | | |
|----------------------|---|---------------------------|
| Date of testing | : | 2022-01-21 |
| Input voltage | : | Internal battery operated |
| Operation mode | : | C |
| Test channel | : | Low / Middle / High |
| Ambient temperature | : | 24.8 °C |
| Relative humidity | : | 55 % |
| Atmospheric pressure | : | 101 kPa |

For the measurement records, refer to the appendix B.

5.1.10 Conducted Spurious Emissions Measured in 100 kHz Bandwidth

RESULT:**Pass****Test Specification**

| | |
|-------------------|---|
| Test standard | : FCC Part 15.247(d) |
| Basic standard | : ANSI C63.10: 2013 |
| Limits | : 20dB (below that in the 100kHz bandwidth within the band that contains the highest level of the desired power) In addition, radiated emissions which fall in the restricted bands, must also comply with the radiated emission limits specified in 15.209(a) |
| Kind of test site | : Shielded Room |

Test Setup

| | |
|----------------------|-----------------------------|
| Date of testing | : 2022-04-20 |
| Input voltage | : Internal battery operated |
| Operation mode | : A, B |
| Test channel | : Low / Middle / High |
| Ambient temperature | : 24.8 °C |
| Relative humidity | : 55 % |
| Atmospheric pressure | : 101 kPa |

For the measurement records, refer to the appendix B & C.

5.1.11 Radiated Spurious Emission

RESULT:

Pass

Test Specification

| | |
|-------------------|--|
| Test standard | : FCC Part 15.247(d) & FCC Part 15.205 |
| Basic standard | : ANSI C63.10: 2013 |
| Limits | : Refer to 15.209(a) of FCC part 15.247(d) |
| Kind of test site | : 3m Semi-anechoic Chamber |

Test Setup

| | |
|----------------------|-----------------------------|
| Date of testing | : 2022-04-19 to 2022-04-22 |
| Input voltage | : Internal battery operated |
| Operation mode | : A, B |
| Test channel | : Low / Middle / High |
| Ambient temperature | : Refer to test result |
| Relative humidity | : Refer to test result |
| Atmospheric pressure | : 101 kPa |

Remark: Testing was carried out within frequency range 9kHz to the tenth harmonics. Only the worst case spurious emissions configuration of the each mode were reported.

For the measurement records, refer to the appendix B & C.

6 Photographs of the Test Set-Up

For photographs of the test set-up, refer to the appendix A.

7 List of Tables

| | |
|---|----|
| Table 1: List of Test and Measurement Equipment..... | 5 |
| Table 2: Technical Specification of EUT..... | 7 |
| Table 3: RF Channel and Frequency of Bluetooth BR/EDR | 8 |
| Table 4: RF Channel and Frequency of Bluetooth LE..... | 8 |
| Table 5: Auxiliary Equipment Used during Test | 10 |
| Table 6: Test Result of Maximum Peak Conducted Output Power, Bluetooth BR & EDR | 14 |
| Table 7: Test Result of Maximum Peak Conducted Output Power, Bluetooth LE | 14 |
| Table 8: Test Result of Average Conducted Output Power, Bluetooth BR & EDR..... | 15 |
| Table 9: Test Result of Average Conducted Output Power, Bluetooth LE..... | 15 |