# RF EXPOSURE REPORT



Report No.: Q191022S003-FCC-H

Supersede Report No.: N/A

Applicant	Medtrum Technologies Inc	
Product Name	Transmitter	
Model No.	MD1027	
Serial No.	N/A	
Test Standard	FCC 2.1093CHUJIAN	
Test Date	Nov. 20 to Dec. 26, 2019	
Issue Date	Feb. 18, 2020	
Test Result	Pass Fail	
Equipment complied with the specification		
Equipment did not comply with the specification		
Jamen Lioney		David Huang
Aaron Liang		David Huang Checked By
Test Engineer Checked By		

This test report may be reproduced in full only

Test result presented in this test report is applicable to the tested sample only

#### Issued by:

#### BUREAU VERITAS (SHENZHEN) CONSUMER PRODUCTS SERVICE CO., LTD

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn



Test Report	Q191022S003-FCC-H
Page	2 of 8

#### **Laboratories Introduction**

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

#### **Accreditations for Conformity Assessment**

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety



Test Report	Q191022S003-FCC-H
Page	3 of 8

This page has been left blank intentionally.



Test Report	Q191022S003-FCC-H
Page	4 of 8

## **CONTENTS**

1.	REPORT REVISION HISTORY	. 5
2.	CUSTOMER INFORMATION	. 5
3.	TEST SITE INFORMATION	. 5
	FOUNDATION TO THE TEST (FUT) INFORMATION	_
4.	EQUIPMENT UNDER TEST (EUT) INFORMATION	. 6
5.	FCC §2.1093 - RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: PORTABLE DEVICES	.7
5.1	RF EXPOSURE	.7
52	TEST RESULT	Q



Test Report	Q191022S003-FCC-H
Page	5 of 8

## 1. Report Revision History

Report No.	Report Version	Description	Issue Date
Q191022S003-FCC-H	NONE	Original	Feb. 18, 2020

## 2. Customer information

Applicant Name	Medtrum Technologies Inc	
Applicant Add	7F,Building 8, No.200 Niudun Road, Shanghai 201203, China	
Manufacturer	Medtrum Technologies Inc	
Manufacturer Add	7F,Building 8, No.200 Niudun Road, Shanghai 201203, China	

## 3. Test site information

Lab performing tests	BUREAU VERITAS (SHENZHEN) CONSUMER PRODUCTS SERVICE CO.,
	LTD
	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park
Lab Address	South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China
	518108
FCC Test Site No.	535293
IC Test Site No.	4842E-1
Test Software	EZ-EMC(ver.lcp-03A1)



Test Report	Q191022S003-FCC-H
Page	6 of 8

## 4. Equipment under Test (EUT) Information

Description of EUT:	Transmitter

Main Model: MD1027

Serial Model: N/A

Date EUT received: Nov. 19, 2019

Test Date(s): Nov. 20 to Dec. 26, 2019

Antenna Gain: BLE: 1.6dBi

Antenna Type: Ceramic antenna

Type of Modulation: BLE: GFSK

RF Operating Frequency (ies): BLE: 2402-2480 MHz

Number of Channels: BLE: 40CH

Port: Please refer to user's manual

Input Power: Battery: DC 3.7V

Trade Name : Medtrum

FCC ID: 2AARU-MD1027

Mark: The Product is a BLE device, that can connect via BLE to either a smartphone or a HUB to transfer the button clicks upon pushed.



Test Report	Q191022S003-FCC-H
Page	7 of 8

## 5. FCC §2.1093 - Radiofrequency radiation exposure evaluation: portable devices.

#### 5.1 RF Exposure

#### Standard Requirement:

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances ≤ 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)]  $\cdot [\sqrt{f_{(GHz)}}] \le 3.0$  for 1-g SAR and  $\le 7.5$  for 10-g extremity SAR,  $^{16}$  where

- f<sub>(GHz)</sub> is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $\leq 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

result =  $P\sqrt{F}/D$ 

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm



Test Report	Q191022S003-FCC-H	
Page	8 of 8	

#### 5.2 Test Result

#### BLE Mode:

Modulation	СН	Freq (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	-6.70	-6±1	-5	0.316	0.10	3
	Mid	2440	-6.45	-6±1	-5	0.316	0.10	3
	High	2480	-6.65	-6±1	-5	0.316	0.10	3

Result: Compliance

No SAR measurement is required.