

Maximum Permissible Exposure

Applicable Standard

According to §1.1307(b), systems operating under the provisions of this section shall be operated in a manner that ensure that the public is not exposed to radio frequency energy level in excess of the Commission’s guideline.

Remark: 1) For BT: The maximum output power for antenna is -0.68dBm (0.86mW) at 2402MHz, 2.5dBi antenna gain(with 1.78 numeric antenna gain.)

For BLE: The maximum output power for antenna is 8.27dBm (6.71mW) at 2480MHz, 2.5dBi antenna gain(with 1.78 numeric antenna gain.)

For WIFI: The maximum output power for antenna is 16.97dBm (49.77mW) at 2462MHz, 2.5dBi antenna gain(with 1.78 numeric antenna gain.)

For LoRa-DTS: The maximum output power for antenna is 15.91dBm (38.99mW) at 927.5MHz, 0.61dBi antenna gain(with 1.15 numeric antenna gain.)

For LoRa-DSS: The maximum output power for antenna is 19.62dBm (91.62mW) at 908.5MHz, 0.61dBi antenna gain(with 1.15 numeric antenna gain.)

2) For mobile or fixed location transmitters, no SAR consideration applied. The minimum separation generally be used is at least 20cm, even if the calculation indicate that the MPE distance would be lesser.

Calculation

Given $E = \frac{\sqrt{30 \times P \times G}}{d}$ & $S = \frac{E^2}{3770}$

Where $E =$ Field Strength in Volts / meter

$P =$ Power in Watts

$G =$ Numeric antenna gain

$d =$ Distance in meters

$S =$ Power Density in milliwatts / square centimeter

Substituting the MPE safe distance using d=20cm into above equation.

Yields: $S = 0.000199 * P * G$

Mode	Power(mW)	numeric antenna gain	Power density (mW/cm ²)	Limit (mW/cm ²)	Result
BT	0.86	1.78	0.000305	1.0	PASS
BLE	6.71	1.78	0.002377		
WIFI	49.77	1.78	0.017630		
LoRa-DTS	38.99	1.15	0.008923		
LoRa-DSS	91.62	1.15	0.020967		