

# TEST REPORT

<b>Product Name</b>	:	WIFI Module
<b>Brand Mark</b>	:	N/A
<b>Model No.</b>	:	6189S-SF
<b>FCC ID</b>	:	2AATL-6189S-SF
<b>Report Number</b>	:	BLA-EMC-202101-A4802
<b>Date of Sample Receipt</b>	:	2021/1/20
<b>Date of Test</b>	:	2021/1/20 to 2021/2/7
<b>Date of Issue</b>	:	2021/2/7
<b>Test Standard</b>	:	47 CFR Part 15, Subpart C 15.247
<b>Test Result</b>	:	Pass

Prepared for:

**HUNAN FN-LINK TECHNOLOGY LIMITED**  
**No. 8, Litong Road, Liuyang Economic Development Zone,**  
**Liuyang China**

Prepared by:

**BlueAsia of Technical Services(Shenzhen) Co.,Ltd.**  
**Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District,**  
**Shenzhen, Guangdong Province, China**  
**TEL: +86-755-23059481**

Compiled by: *Jozu*

Review by: *Sweet.Liang*

Approved by: *Tmen Li*

Date:

2021/2/7



**REPORT REVISE RECORD**

Version No.	Date	Description
00	2021/2/7	Original

cblueASIA

## TABLE OF CONTENTS

<b>1 TEST SUMMARY .....</b>	<b>6</b>
<b>2 GENERAL INFORMATION .....</b>	<b>7</b>
<b>3 GENERAL DESCRIPTION OF E.U.T.....</b>	<b>7</b>
<b>4 TEST ENVIRONMENT .....</b>	<b>8</b>
<b>5 TEST MODE .....</b>	<b>8</b>
<b>6 MEASUREMENT UNCERTAINTY .....</b>	<b>8</b>
<b>7 DESCRIPTION OF SUPPORT UNIT.....</b>	<b>9</b>
<b>8 LABORATORY LOCATION.....</b>	<b>9</b>
<b>9 TEST INSTRUMENTS LIST.....</b>	<b>10</b>
<b>1 CONDUCTED SPURIOUS EMISSIONS .....</b>	<b>14</b>
1.1 LIMITS .....	14
1.2 BLOCK DIAGRAM OF TEST SETUP .....	14
1.3 TEST DATA .....	15
<b>2 CONDUCTED BAND EDGES MEASUREMENT .....</b>	<b>16</b>
2.1 LIMITS .....	16
2.2 BLOCK DIAGRAM OF TEST SETUP .....	16
2.3 TEST DATA .....	17
<b>3 MINIMUM 6DB BANDWIDTH .....</b>	<b>18</b>
3.1 LIMITS .....	18
3.2 BLOCK DIAGRAM OF TEST SETUP .....	18
3.3 TEST DATA .....	18
<b>4 POWER SPECTRUM DENSITY.....</b>	<b>19</b>
4.1 LIMITS .....	19
4.2 BLOCK DIAGRAM OF TEST SETUP .....	19
4.3 TEST DATA .....	19
<b>5 CONDUCTED PEAK OUTPUT POWER .....</b>	<b>20</b>
5.1 LIMITS .....	20
5.2 BLOCK DIAGRAM OF TEST SETUP .....	20
5.3 EST DATA .....	20

<b>6 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ).....</b>	<b>21</b>
6.1 LIMITS .....	21
6.2 BLOCK DIAGRAM OF TEST SETUP .....	21
6.3 PROCEDURE .....	21
6.4 TEST DATA .....	23
<b>7 ANTENNA REQUIREMENT .....</b>	<b>25</b>
7.1 CONCLUSION .....	25
<b>8 RADIATED SPURIOUS EMISSIONS.....</b>	<b>26</b>
8.1 LIMITS .....	26
8.2 BLOCK DIAGRAM OF TEST SETUP .....	27
8.3 PROCEDURE .....	27
8.4 TEST DATA .....	29
<b>9 RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS.....</b>	<b>37</b>
9.1 LIMITS .....	37
9.2 BLOCK DIAGRAM OF TEST SETUP .....	38
9.3 PROCEDURE .....	38
9.4 TEST DATA .....	40
<b>10 APPENDIX .....</b>	<b>56</b>
10.1 APPENDIX : DTS BANDWIDTH .....	56
<i>Test Result.....</i>	56
<i>Test Graphs.....</i>	57
10.2 APPENDIX : OCCUPIED CHANNEL BANDWIDTH.....	61
<i>Test Result.....</i>	61
<i>Test Graphs.....</i>	62
10.3 APPENDIX : MAXIMUM CONDUCTED OUTPUT POWER .....	66
<i>Test Result.....</i>	66
<i>Test Graphs.....</i>	67
10.4 APPENDIX : MAXIMUM POWER SPECTRAL DENSITY .....	71
<i>Test Result.....</i>	71
<i>Test Graphs.....</i>	72
10.5 APPENDIX : BAND EDGE MEASUREMENTS .....	76
<i>Test Result.....</i>	76
<i>Test Graphs.....</i>	77
10.6 APPENDIX : CONDUCTED SPURIOUS EMISSION.....	80

<i>Test Result</i> .....	80
<i>Test Graphs</i> .....	81
10.7 APPENDIX G: DUTY CYCLE .....	93
<i>Test Result</i> .....	93
<i>Test Graphs</i> .....	94
<b>APPENDIX A: PHOTOGRAPHS OF TEST SETUP .....</b>	<b>98</b>
<b>APPENDIX B: PHOTOGRAPHS OF EUT .....</b>	<b>100</b>

cblueASIA

## 1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5 & Section 11.9.1	47 CFR Part 15, Subpart C 15.247(b)(1) & 15.247(b)(3)	Pass
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass

## 2 GENERAL INFORMATION

<b>Applicant</b>	HUNAN FN-LINK TECHNOLOGY LIMITED
<b>Address</b>	No. 8, Litong Road, Liuyang Economic Development Zone, Liuyang China
<b>Manufacturer</b>	HUNAN FN-LINK TECHNOLOGY LIMITED
<b>Address</b>	No. 8, Litong Road, Liuyang Economic Development Zone, Liuyang China
<b>Factory</b>	HUNAN FN-LINK TECHNOLOGY LIMITED
<b>Address</b>	No. 8, Litong Road, Liuyang Economic Development Zone, Liuyang China
<b>Product Name</b>	WIFI Module
<b>Test Model No.</b>	6189S-SF

## 3 GENERAL DESCRIPTION OF E.U.T.

<b>Hardware Version</b>	N/A
<b>Software Version</b>	N/A
<b>Operation Frequency:</b>	802.11b/g/n(HT20): 2412MHz to 2462MHz 802.11n(HT40): 2422MHz to 2452MHz
<b>Modulation Type:</b>	802.11b: DSSS (CCK, DQPSK, DBPSK) 802.11g/n: OFDM (64QAM, 16QAM, QPSK, BPSK)
<b>Channel Spacing:</b>	5MHz
<b>Number of Channels:</b>	802.11b/g/n(HT20):11 802.11n(HT40):7
<b>Antenna Type:</b>	PCB Antenna
<b>Antenna Gain:</b>	2dBi

#### 4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	+25°C	3.3Vdc

#### 5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
TX mode with modulation	Keep the EUT in continuously transmitting with modulation mode.
Remark: Only the data of the worst mode would be recorded in this report.	

#### 6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission(9kHz-30MHz)	±4.34dB
Radiated Emission(30Mz-1000MHz)	±4.24dB
Radiated Emission(1GHz-18GHz)	±4.68dB
AC Power Line Conducted Emission(150kHz-30MHz)	±3.45dB

Parameter	Expanded Uncertainty (Confidence of 95%)
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±1.5 dB
Power Spectral Density, conducted	±3.0 dB
Unwanted Emissions, conducted	±3.0 dB
Temperature	±3 °C
Supply voltages	±3 %
Time	±5 %
Radiated Emission (30MHz ~ 1000MHz)	±4.35 dB
Radiated Emission (1GHz ~ 18GHz)	±4.44 dB

## 7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
PC	HASEE	K610D	N/A	N/A

## 8 LABORATORY LOCATION

All tests were performed at:

BlueAsia of Technical Services(Shenzhen) Co., Ltd.

Building C, No. 107, Shihuan Road, Shiyan Sub-District, Baoan District, Shenzhen, Guangdong Province, China

Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673

No tests were sub-contracted.

## 9 TEST INSTRUMENTS LIST

Test Equipment Of Conducted Spurious Emissions					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Conducted Band Edges Measurement					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Minimum 6dB Bandwidth					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

Test Equipment Of Power Spectrum Density					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due

Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

**Test Equipment Of Conducted Peak Output Power**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Spectrum	Agilent	N9020A	MY49100060	2020/10/12	2021/10/11
Signal Generator	Agilent	N5182A	MY49060650	2020/10/12	2021/10/11
Signal Generator	Agilent	E8257D	MY44320250	2020/10/12	2021/10/11

**Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Shield room	SKET	833	N/A	2020/11/25	2023/11/24
Receiver	R&S	ESPI3	101082	2020/10/12	2021/10/11
LISN	R&S	ENV216	3560.6550.15	2020/10/12	2021/10/11
LISN	安泰信	AT166-2	AKK1806000003	2020/10/12	2021/10/11
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A

**Test Equipment Of Radiated Spurious Emissions**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	2020/11/10	2023/11/9
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11

Receiver	R&S	ESR7	101199	2020/10/12	2021/10/11
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2020/9/26	2022/9/25
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	2020/9/26	2022/9/25
Amplifier	SKET	PA-000318G-45	N/A	2020/10/16	2021/10/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2020/9/26	2022/9/25
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

**Test Equipment Of Radiated Emissions which fall in the restricted bands**

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	2020/11/10	2023/11/9
Spectrum	R&S	FSP40	100817	2020/10/12	2021/10/11
Receiver	R&S	ESR7	101199	2020/10/12	2021/10/11
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	2020/9/26	2022/9/25
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	2020/9/26	2022/9/25
Amplifier	SKET	PA-000318G-45	N/A	2020/10/16	2021/10/15
EMI software	EZ	EZ-EMC	EEMC-3A1	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2020/9/26	2022/9/25
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A

Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

cblueASIA


## 1 CONDUCTED SPURIOUS EMISSIONS

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX
<b>Tester</b>	Jozu
<b>Temperature</b>	25 °C
<b>Humidity</b>	60%

### 1.1 LIMITS

<b>Limit:</b>	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### 1.2 BLOCK DIAGRAM OF TEST SETUP



### 1.3 TEST DATA

**Pass: Please Refer To Appendix: Appendix1 For Details**

cblueASIA


## 2 CONDUCTED BAND EDGES MEASUREMENT

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX
<b>Tester</b>	Jozu
<b>Temperature</b>	25 °C
<b>Humidity</b>	60%

### 2.1 LIMITS

<b>Limit:</b>	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

### 2.2 BLOCK DIAGRAM OF TEST SETUP



### 2.3 TEST DATA

<b>Pass: Please Refer To Appendix: Appendix1 For Details</b>
--------------------------------------------------------------

cblueAsia


### 3 MINIMUM 6DB BANDWIDTH

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 11.8.1
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX
<b>Tester</b>	Jozu
<b>Temperature</b>	25 °C
<b>Humidity</b>	60%

#### 3.1 LIMITS

**Limit:**  $\geq 500$  kHz

#### 3.2 BLOCK DIAGRAM OF TEST SETUP



#### 3.3 TEST DATA

**Pass: Please Refer To Appendix: Appendix1 For Details**


## 4 POWER SPECTRUM DENSITY

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 11.10.2
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX
<b>Tester</b>	Jozu
<b>Temperature</b>	25 °C
<b>Humidity</b>	60%

### 4.1 LIMITS

**Limit:** ≤8dBm in any 3 kHz band during any time interval of continuous transmission

### 4.2 BLOCK DIAGRAM OF TEST SETUP



### 4.3 TEST DATA

**Pass: Please Refer To Appendix: Appendix1 For Details**


## 5 CONDUCTED OUTPUT POWER

<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 7.8.5 & Section 11.9.1
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX
<b>Tester</b>	Jozu
<b>Temperature</b>	25 °C
<b>Humidity</b>	60%

### 5.1 LIMITS

<b>Frequency range(MHz)</b>	<b>Output power of the intentional radiator(watt)</b>
902-928	1 for $\geq 50$ hopping channels
	0.25 for $25 \leq$ hopping channels $< 50$
	1 for digital modulation
2400-2483.5	1 for $\geq 75$ non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

### 5.2 BLOCK DIAGRAM OF TEST SETUP



### 5.3 EST DATA

**Pass: Please Refer To Appendix: Appendix1 For Details**

## 6 CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)


<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 6.2
<b>Test Mode (Pre-Scan)</b>	TX
<b>Test Mode (Final Test)</b>	TX
<b>Tester</b>	Jozu
<b>Temperature</b>	25 °C
<b>Humidity</b>	60%

### 6.1 LIMITS

Frequency of emission(MHz)	Conducted limit(dB $\mu$ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

\*Decreases with the logarithm of the frequency.

### 6.2 BLOCK DIAGRAM OF TEST SETUP



Remark  
E.U.T: Equipment Under Test  
LISN: Line Impedance Stabilization Network  
Test table height=0.8m

### 6.3 PROCEDURE

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50?H + 50hm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

- 3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,
- 4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.
- 5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor


cblueASIA

## 6.4 TEST DATA

[Test Mode: TX]; [Line: Neutral]

Power: AC120V60Hz

### Conducted Emission Measurement



Site

Limit: FCC Class B Conduction(QP)

Phase:

N

Temperature:

Humidity: %

EUT: WIFI Module

M/N: 6189S-SF

Mode: 2.4G WIFI mode

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over		
		MHz	dBuV/m	dB	dBuV/m	dBuV/m	dB	Detector	Comment
1		0.2100	32.87	9.75	42.62	63.21	-20.59	QP	
2		0.2100	25.23	9.75	34.98	53.21	-18.23	AVG	
3		0.6300	27.21	9.80	37.01	56.00	-18.99	QP	
4		0.6300	24.00	9.80	33.80	46.00	-12.20	AVG	
5		1.3619	27.05	9.85	36.90	56.00	-19.10	QP	
6		1.3619	23.67	9.85	33.52	46.00	-12.48	AVG	
7		3.2540	29.47	9.90	39.37	56.00	-16.63	QP	
8	*	3.2540	26.97	9.90	36.87	46.00	-9.13	AVG	
9		9.8660	29.12	10.15	39.27	60.00	-20.73	QP	
10		9.8660	26.49	10.15	36.64	50.00	-13.36	AVG	
11		19.5180	25.27	10.42	35.69	60.00	-24.31	QP	
12		19.5180	13.30	10.42	23.72	50.00	-26.28	AVG	

\*:Maximum data    x:Over limit    !:over margin


⟨Reference Only⟩

**Test Result: Pass**

[Test Mode: TX]; [Line: Line]

Power: AC120V60Hz

### Conducted Emission Measurement



Site

Phase:

**L1**

Temperature:

Limit: FCC Class B Conduction(QP)

Humidity: %

EUT: WIFI Module

M/N: 6189S-SF

Mode: 2.4G WIFI mode

Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measure-ment	Limit	Over	
		MHz	dBuV/m	dB	dBuV/m	dB	Detector	Comment
1		0.2100	33.46	9.83	43.29	63.21	-19.92	QP
2		0.2100	26.03	9.83	35.86	53.21	-17.35	AVG
3		0.5260	27.93	9.87	37.80	56.00	-18.20	QP
4		0.5260	24.72	9.87	34.59	46.00	-11.41	AVG
5		0.9460	29.31	9.91	39.22	56.00	-16.78	QP
6	*	0.9460	26.13	9.91	36.04	46.00	-9.96	AVG
7		2.4140	28.75	9.95	38.70	56.00	-17.30	QP
8		2.4140	25.89	9.95	35.84	46.00	-10.16	AVG
9		9.5540	30.12	10.19	40.31	60.00	-19.69	QP
10		9.5540	27.14	10.19	37.33	50.00	-12.67	AVG
11		19.2139	28.77	10.42	39.19	60.00	-20.81	QP
12		19.2139	18.41	10.42	28.83	50.00	-21.17	AVG

\*:Maximum data x:Over limit !:over margin

⟨Reference Only⟩

**Test Result: Pass**

## 7 ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A


### 7.1 CONCLUSION

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is 2dBi.



## 8 RADIATED SPURIOUS EMISSIONS


<b>Test Standard</b>	47 CFR Part 15, Subpart C 15.247
<b>Test Method</b>	ANSI C63.10 (2013) Section 6.4,6.5,6.6
<b>Test Mode (Pre-Scan)</b>	TX mode (SE) below 1G;TX mode (SE) Above 1G
<b>Test Mode (Final Test)</b>	TX mode (SE) below 1G;TX mode (SE) Above 1G
<b>Tester</b>	Jozu
<b>Temperature</b>	25 °C
<b>Humidity</b>	60%

### 8.1 LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

## 8.2 BLOCK DIAGRAM OF TEST SETUP



## 8.3 PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:  
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor "C Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 12.75GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported. Fundamental frequency is blocked by filter, and only spurious emission is shown.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.


## 8.4 TEST DATA

[TestMode: TX mode (SE) below 1G]; [Polarity: Horizontal]

### Radiated Emission Measurement

File :RE Data #:46 Date: 2021/2/2 星期 Time: 下午 5:30:14

72.0 dBuV/m



Site

Limit: FCC Part15 Class B

EUT: WIFI Module

M/N: 6189S-SF

Mode: TX mode

Note:

Polarization: **Horizontal**

Power:

Temperature:

Humidity: %

Distance: 3m


No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector	Antenna Height cm	Table Degree	Comment
1		48.6719	0.89	23.81	24.70	40.00	-15.30	peak			
2		127.2176	2.69	22.86	25.55	43.50	-17.95	peak			
3		211.5264	0.25	21.38	21.63	43.50	-21.87	peak			
4		435.5898	-0.06	27.94	27.88	46.00	-18.12	peak			
5		638.3686	0.94	32.00	32.94	46.00	-13.06	peak			
6	*	768.7481	0.49	33.90	34.39	46.00	-11.61	peak			

\*:Maximum data    x:Over limit    !:over margin

(Reference Only)

**Test Result: Pass**

[TestMode: TX mode (SE) below 1G]; [Polarity: Vertical]  
**Radiated Emission Measurement**



Site	Polarization: <b>Vertical</b>	Temperature:
Limit: FCC Part15 Class B	Power:	Humidity: %
EUT: WIFI Module	Distance: 3m	
M/N: 6189S-SF		
Mode: TX mode		
Note:		

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Antenna Height cm	Table Degree degree	Comment
1		41.4215	-0.27	24.01	23.74	40.00	-16.26	peak		
2		58.4074	-0.19	23.50	23.31	40.00	-16.69	peak		
3	*	126.7723	8.11	22.84	30.95	43.50	-12.55	peak		
4		224.5192	0.30	22.13	22.43	46.00	-23.57	peak		
5		403.2500	-0.32	27.62	27.30	46.00	-18.70	peak		
6		658.8360	1.04	32.18	33.22	46.00	-12.78	peak		

\*:Maximum data    x:Over limit    !:over margin

(Reference Only)

**Test Result: Pass**