

## RF EXPOSURE EVALUATION

### EUT Specification

<b>EUT</b>	WIFI Module
<b>Frequency band (Operating)</b>	<input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input type="checkbox"/> WLAN: 5.18GHz ~ 5.32GHz / 5.50GHz ~ 5.70GHz <input type="checkbox"/> WLAN: 5.745GHz ~ 5.825GHz <input type="checkbox"/> Others(Bluetooth: 2.402GHz ~ 2.480GHz)
<b>Device category</b>	<input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others ____
<b>Antenna diversity</b>	<input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity
<b>Max. output power</b>	16.28dBm(42.46mW)
<b>Antenna gain</b>	2.99dBi
<b>Evaluation applied</b>	<input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm <sup>2</sup> )	Average Time
<b>(A) Limits for Occupational/Control Exposures</b>				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
<b>(B) Limits for General Population/Uncontrol Exposures</b>				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

## Friis transmission formula: $P_d = \frac{P_{out} * G}{4 * \pi * R^2}$

Where

$P_d$  = Power density in  $mW/cm^2$

$P_{out}$  = output power to antenna in Mw

G = gain of antenna in linear scale

$\pi = 3.1416$

R = distance between observation point and center of the radiator in cm

$P_d$  the limit of MPE,  $1mW/cm^2$ . If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

Channel	Channel Frequency (MHz)	Max Output power (dBm)	Tolerance	Max Tune-UP power (mW)	Power density at 20cm ( $mW/cm^2$ )	Power density Limits ( $mW/cm^2$ )
<b>Test Mode: 802.11b</b>						
Low	2412	15.16	$\pm 0.5$	36.81	0.0146	1
Middle	2437	16.28	$\pm 0.5$	47.64	0.0189	1
High	2462	15.39	$\pm 0.5$	38.82	0.0154	1
<b>Test Mode: 802.11g</b>						
Low	2412	14.04	$\pm 0.5$	28.44	0.0113	1
Middle	2437	14.66	$\pm 0.5$	32.81	0.0130	1
High	2462	15.53	$\pm 0.5$	40.09	0.0159	1
<b>Test Mode: 802.11n(HT20)</b>						
Low	2412	13.29	$\pm 0.5$	23.93	0.0095	1
Middle	2437	14.94	$\pm 0.5$	34.99	0.0139	1
High	2462	14.82	$\pm 0.5$	34.04	0.0135	1
<b>Test Mode: 802.11n(HT40)</b>						
Low	2422	13.76	$\pm 0.5$	26.67	0.0106	1
Middle	2437	14.45	$\pm 0.5$	31.26	0.0124	1
High	2452	13.81	$\pm 0.5$	26.98	0.0107	1