## **RF Exposure Evaluation**

# Limit

The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) radiation as specified in 1.1310 & 2.1091

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)				
(A) Limits for Occupational/Controlled Exposures								
0.3–3.0	614	1.63	*(100)	6				
3.0–30	1842/f	4.89/f	*(900/f <sup>2</sup> )	6				
30–300	61.4	0.163	1.0	6				
300-1500	-	-	f/300	6				
1500-100,000	-	-	5	6				
(B) Limits for General Population/Uncontrolled Exposure								
0.3–1.34	614 1.63		*(100)	30				
1.34–30	824/f	2.19/f	*(180/f <sup>2</sup> )	30				
30–300	27.5	0.073	0.2	30				
300-1500	-	-	f/1500	30				
1500-100,000	-	-	1.0	30				

Note: f = frequency in MHz

## **Evaluation Method**

Transmission formula:  $P_d = (Pout*G)/(4*pi*R^2)$ Where

Pd = power density in mW/cm2, Pout = output power to antenna in mW, G = gain of antenna in linear scale; Pi = 3.1416, R = distance between observation point and center of the radiator in cm

#### **Conducted Power Results & Manufacturing tolerance**

Specification	Operating Mode	Conducted Output Power (dBm)	Target (dBm)	Tolerance ±(dB)	
2.4GWIFI	802.11b	15.58	16	1	
	802.11g	15.18	16	1	
	802.11n(HT20)	15.78	16	1	
	802.11n(HT40)	12.84	13	1	

### **Evaluation Results**

Spec.	Operating Mode	Antenna Distance (cm)	Conducted Output Power		Gain of antenna in linear	Power Density (mW	Limit (mW	Result
			dBm	mW	scale	<b>/cm</b> <sup>2</sup> )	<b>/cm</b> <sup>2</sup> )	
2.4GWIFI	802.11b	20	17	50.12	1.58	0.0158	1	PASS
	802.11g	20	17	50.12	1.58	0.0158	1	PASS
	802.11n(HT20)	20	17	50.12	1.58	0.0158	1	PASS
	802.11n(HT40)	20	14	25.12	1.58	0.0079	1	PASS

Remark:

1. Output power including tune up tolerance;

2. The maximum 2.4G antenna gain is 2dBi

3. The exposure safety distance is 20cm.

EUT can only work in 2.4GWIFI mode

The formula of calculated the Simulation Transmission MPE is:

CPD1/LPD1+CPD2/LPD2+.....etc.<1

CPD=Calculation Maximum Power Denisty

### Conclusion

The measurement results comply with the FCC Limit per 47 CFR 1.1310 & 2.1091 for the uncontrolled RF Exposure and MPE complicance per KDB 447498 v06.