

Bluetooth Thermometer

Model No. TP-25H2

Congratulations on your purchase of a Smart, Wireless Bluetooth-connected Cooking Thermometer. You will now be able to remotely monitor the temperature of food and how much time is left for the food to be done from your smartphone.

- 1. Temperature range of probe: 15.8°F to 572°F (-10°C to 300°C).
- 2. Temperature tolerance of internal food reading: +/-1.8°F (+/-1.0°C).
- 3. Power source 18650 battery
- 4. Display the temperature of 4 probes
- 5. 2.4GHZ wireless Bluetooth function, Connect to mobile app via Bluetooth module
- 6. Touch Backlight: Touch the "LIGHT" button to ON/OFF backlight
- 7. CF/ON/OFF: Press once to ON/OFF the unit, press and hold for 3 seconds to select the temperature unit
- 8、* Button: press and hold for 3 seconds to ON/OFF the Bluetooth function. If the mobile app is not connected within 10 minutes, the Bluetooth function will be turned off automatically and the Bluetooth symbol will disappear.
- 9-. Wire Stand Allows you to stand the unit on tabletop or it can be reversed and used as a hanger.

Quick Start

Follow the simple steps below to set up your ThermoPro Bluetooth Cooking Thermometer and help you cook like a pro!

- Step 1: Download and install the "ThermoPro BBQ"App.

 Search for "ThermoPro BBQ"on the Apple Store for IOS devices or on the Google Play

 Store for Android devices. Download the App and install it on your smartphone.
- Step 2: Enable Bluetooth on your smartphone under the smartphone Settings section. If your smartphone has Bluetooth enabled, you can skip this step.
- Step 3: Fully charge the ThermoPro Bluetooth Cooking Thermometer by connecting the USB charging cable provided to any USB charger.
- Step 4: Insert temperature probes provided into the thermometer transmitter. Insert the 4 colored probes into the matching colored sockets. For example, dark blue probe connector into dark blue socket.

Step 5: Turn on the thermometer transmitter by pressing the button once on the back of the transmitter unit. The Bluetooth icon will be flashing at the top of the transmitter display.

Step 6: Launch ThermoPro BBQ APP and press Click Here. Wait a moment while the thermometer pairs to your smartphone. Once pairing is complete, the Bluetooth icon 3 on the thermometer transmitter display will stop flashing and the APP will jump to the Cooking page which shows the temperatures measured by the probes.

Done! Your ThermoPro Bluetooth Cooking Thermometer is ready for use!

FCC Warning

This device complies with part 15 of the FCC rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

Changes or modifications not expressly approved by the party responsible for compliance could void the user's authority to operate the equipment.

NOTE: This equipment has been tested and found to comply with the limits for a Class B digital device, pursuant to part 15 of the FCC Rules. These limits are designed to provide reasonable protection against harmful interference in a residential installation. This equipment generates uses and can radiate radio frequency energy and, if not installed and used in accordance with the instructions, may cause harmful interference to radio communications. However, there is no guarantee that interference will not occur in a particular installation. If this equipment does cause harmful interference to radio or television reception, which can be determined by turning the equipment off and on, the user is encouraged to try to correct the interference by one or more of the following measures:

- Reorient or relocate the receiving antenna.
- Increase the separation between the equipment and receiver.
- Connect the equipment into an outlet on a circuit different from that to which the receiver is connected.
- Consult the dealer or an experienced radio/TV technician for help.

Radiation Exposure Statement

The device has been evaluated to meet general RF exposure requirement. The device can be used in portable exposure condition without restriction.