

RF Exposure evaluation

FCC ID: 2AAUI-MONDOELITE

1. Reference

According to §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to §1.1310 and §2.1091 RF exposure is calculated.

KDB 662911 D01: Mobile and Portable Devices RF Exposure Procedures and Equipment Authorization Policies

2. Limit

Limits for Maximum Permissible Exposure (MPE)/Controlled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	6
3.0 – 30	1842/f	4.89/f	(900/f ²)*	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	/	/	f/300	6
1500 – 100,000	/	/	5	6

Limits for Maximum Permissible Exposure (MPE)/Uncontrolled Exposure

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density (mW/cm ²)	Averaging Time (minute)
Limits for Occupational/Controlled Exposure				
0.3 – 3.0	614	1.63	(100) *	30
3.0 – 30	824/f	2.19/f	(180/f ²)*	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	/	/	f/1500	30
1500 – 100,000	/	/	1.0	30

F=frequency in MHz

*=Plane-wave equivalent power density

3. MPE Calculation Method

Predication of MPE limit at a given distance

Equation from page 18 of OET Bulletin 65, Edition 97-01

$$S=PG/4\pi R^2$$

Where: S=power density

P=power input to antenna

G=power gain of the antenna in the direction of interest relative to an isotropic radiator

R=distance to the center of radiation of the antenna

4. Result

As declared by the Applicant, the EUT is a wireless device used in a fix application, at least 20 cm from any body part of the user or nearby persons; from the maximum EUT RF output power, the minimum separation distance, $r = 20\text{cm}$.

For BLE (Antenna gain: Antenna 1: 1.6 dBi, Antenna 2: 2.0dBi)

Antenna 1

Frequency (MHz)	Max. Output Power (dBm)	Max. Output Power (mW)	Antenna Gain (Numeric)	Power Density At 20 cm (mW/cm ²)	Power Density Limit FCC (mW/cm ²)	Test Results
2402	4.96	3.1333	1.4454	0.0009	1.0000	PASS
2440	4.72	2.9648	1.4454	0.0009	1.0000	PASS
2480	4.26	2.6669	1.4454	0.0008	1.0000	PASS

Antenna 2

Frequency (MHz)	Max. Output Power (dBm)	Max. Output Power (mW)	Antenna Gain (Numeric)	Power Density At 20 cm (mW/cm ²)	Power Density Limit FCC (mW/cm ²)	Test Results
2402	4.97	3.1405	1.5849	0.0010	1.0000	PASS
2440	4.74	2.9785	1.5849	0.0009	1.0000	PASS
2480	4.27	2.6730	1.5849	0.0008	1.0000	PASS

For BR/EDR (Antenna gain: Antenna 1: 1.5 dBi, Antenna 2: 1.8 dBi)

Antenna 1

Frequency (MHz)	Max. Output Power (dBm)	Max. Output Power (mW)	Antenna Gain (Numeric)	Power Density At 20 cm (mW/cm ²)	Power Density Limit FCC (mW/cm ²)	Test Results
GFSK	4.49	2.8119	1.4454	0.0008	1.0000	PASS
Pi/4DQPSK	4.86	3.0620	1.4454	0.0009	1.0000	PASS
8DPSK	5.21	3.3189	1.4454	0.0010	1.0000	PASS

Antenna 2

Frequency (MHz)	Max. Output Power (dBm)	Max. Output Power (mW)	Antenna Gain (Numeric)	Power Density At 20 cm (mW/cm ²)	Power Density Limit FCC (mW/cm ²)	Test Results
GFSK	4.40	2.7542	1.5849	0.0009	1.0000	PASS
Pi/4DQPSK	4.82	3.0339	1.5849	0.0010	1.0000	PASS
8DPSK	5.12	3.2509	1.5849	0.0010	1.0000	PASS

For 2.4GHz wifi (Antenna gain: Antenna 1: 1.6 dBi, Antenna 2: 2.0dBi)

Antenna 1

	Frequency (MHz)	Max. Output Power (dBm)	Max. Output Power (mW)	Antenna Gain (Numeric)	Power Density At 20 cm (mW/cm ²)	Power Density Limit FCC (mW/cm ²)	Test Results
802.11b	2462	19.26	84.3335	1.4454	0.0243	1.0000	PASS
802.11g	2462	20.94	124.1652	1.4454	0.0357	1.0000	PASS
802.11n (HT20)	2437	21.12	129.4196	1.4454	0.0372	1.0000	PASS
802.11n (HT40)	2437	21.16	130.6171	1.4454	0.0376	1.0000	PASS

Antenna 2

	Frequency (MHz)	Max. Output Power (dBm)	Max. Output Power (mW)	Antenna Gain (Numeric)	Power Density At 20 cm (mW/cm ²)	Power Density Limit FCC (mW/cm ²)	Test Results
802.11b	2437	19.39	86.8960	1.5849	0.0274	1.0000	PASS
802.11g	2437	21.12	129.4196	1.5849	0.0408	1.0000	PASS
802.11n (HT20)	2437	21.26	133.6596	1.5849	0.0421	1.0000	PASS
802.11n (HT40)	2437	21.26	133.6596	1.5849	0.0421	1.0000	PASS

For 5.1G WIFI (Antenna gain: Antenna 1: 2.8 dBi, Antenna 2: 3.3dBi)

Antenna 1

	Frequency (MHz)	Max. Output Power (dBm)	Max. Output Power (mW)	Antenna Gain (Numeric)	Power Density At 20 cm (mW/cm ²)	Power Density Limit FCC (mW/cm ²)	Test Results
802.11a	5180	13.03	20.0909	1.9055	0.0076	1.0000	PASS
802.11n (HT20)	5180	12.70	18.6209	1.9055	0.0071	1.0000	PASS
802.11n (HT40)	5190	14.90	30.9030	1.9055	0.0117	1.0000	PASS
802.11ac (VHT20)	5180	12.71	18.6638	1.9055	0.0071	1.0000	PASS
802.11ac (VHT40)	5190	12.73	18.7499	1.9055	0.0071	1.0000	PASS
802.11ac (VHT80)	5210	13.29	21.3304	1.9055	0.0081	1.0000	PASS

Antenna 2

	Frequency (MHz)	Max. Output Power (dBm)	Max. Output Power (mW)	Antenna Gain (Numeric)	Power Density At 20 cm (mW/cm ²)	Power Density Limit FCC (mW/cm ²)	Test Results
802.11a	5180	12.89	19.4536	2.1380	0.0083	1.0000	PASS
802.11n (HT20)	5180	12.05	16.0325	2.1380	0.0068	1.0000	PASS
802.11n (HT40)	5230	14.51	28.2488	2.1380	0.0120	1.0000	PASS
802.11ac (VHT20)	5240	13.32	21.4783	2.1380	0.0091	1.0000	PASS
802.11ac (VHT40)	5230	13.30	21.3796	2.1380	0.0091	1.0000	PASS
802.11ac (VHT80)	5210	13.27	21.2324	2.1380	0.0090	1.0000	PASS

For 5.8G WIFI (Antenna gain: Antenna 1: 2.8 dBi, Antenna 2: 3.3dBi)

Antenna 1

	Frequency (MHz)	Max. Output Power (dBm)	Max. Output Power (mW)	Antenna Gain (Numeric)	Power Density At 20 cm (mW/cm ²)	Power Density Limit FCC (mW/cm ²)	Test Results
802.11a	5745	12.65	18.4077	1.9055	0.0070	1.0000	PASS
802.11n (HT20)	5745	12.69	18.5780	1.9055	0.0070	1.0000	PASS
802.11n (HT40)	5755	12.17	16.4816	1.9055	0.0062	1.0000	PASS
802.11ac (VHT20)	5745	11.56	14.3219	1.9055	0.0054	1.0000	PASS
802.11ac (VHT40)	5755	11.38	13.7404	1.9055	0.0052	1.0000	PASS
802.11ac (VHT80)	5775	11.70	14.7911	1.9055	0.0056	1.0000	PASS

Antenna 2

	Frequency (MHz)	Max. Output Power (dBm)	Max. Output Power (mW)	Antenna Gain (Numeric)	Power Density At 20 cm (mW/cm ²)	Power Density Limit FCC (mW/cm ²)	Test Results
802.11a	5745	12.50	17.7828	2.1380	0.0076	1.0000	PASS
802.11n (HT20)	5745	12.40	17.3780	2.1380	0.0074	1.0000	PASS
802.11n (HT40)	5755	12.07	16.1065	2.1380	0.0069	1.0000	PASS
802.11ac (VHT20)	5745	11.26	13.3660	2.1380	0.0057	1.0000	PASS
802.11ac (VHT40)	5755	11.03	12.6765	2.1380	0.0054	1.0000	PASS
802.11ac (VHT80)	5775	11.44	13.9316	2.1380	0.0059	1.0000	PASS

Simultaneous transmission MPE

Max.Power Density 2.4G WIFI (mW/cm ²)	Max.Power Density 5G WIFI (mW/cm ²)	Max.Power Density BT (mW/cm ²)	Max.Power Density BLE (mW/cm ²)	Max.sum of the MPE ratios	Limit	Test Results
0.0421	0.0120	0.0010	0.0010	0.0561	1	PASS

5. Conclusion

The SAR evaluation is not required.