

CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China Tel: +86-755-27521059 Fax: +86-755-27521011 http://www.sz-ctc.com.cn

RF Exposure Evaluation

FCC ID: 2AAVD-G1018E6

According to KDB447498 D01 General RF Exposure Guidance v06, Clause 4.3.1(a)

EUT Specification

EUT	Wireless Mouse		
Model/Type reference:	G1018E6		
Listed Model(s):	G1123E6		
Frequency band (Operating)	□BT: 2.402GHz ~ 2.480GHz □BLE: 2.402GHz ~ 2.480GHz □WLAN: 2.412GHz ~ 2.462GHz ⊠Others <u>2.4GHz ISM Band: 2.402GHz ~ 2.480GHz</u>		
Device category	 Portable (<5mm separation) Mobile (>20cm separation) fixed (>20cm separation) Others 		
Antenna diversity	Single antenna Multiple antennas Tx diversity Rx diversity Tx/Rx diversity		
Antenna gain (Max)	0.61dBi		

Limit

[(max. power of channel, including tune-up tolerance, mW) / (min. test separation distance, mm)] . $[\sqrt{f_{(GHz)}}] \le 3.0$

Where

-f_(GHz) is the RF channel transmit frequency in GHz

-Power and distance are rounded to the nearest mW and mm before calculation

-The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm, and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm according to 4.1 f) is applied to determine SAR test exclusion.

CTC Laboratories, Inc.





Measurement Result

Mode	Frequency (MHz)	Max. Measured Power (dBm)	Max. Tune up Power (dBm)	Result	Limit
тх	2402-2480	-10.177	-9.500	0.035	3.0

Note:

- 1. Calculate by Worst-case mode.
- 2. Max. Tune Up Power by Manufacturer's Declaration, and Max. Tune Up Power is used to calculate.
- 3. For a more detailed features description, please refer to the RF Test Report.