

# **FCC Test Report**

Report No.: AGC00917180601FE03

FCC ID : 2AAWE-SP14

**APPLICATION PURPOSE**: Original Equipment

**PRODUCT DESIGNATION**: Prime Wireless - High Performance Earphones with

Bluetooth

BRAND NAME : SOUL

**MODEL NAME** : PRIME WIRELESS, SP14

**CLIENT** : Soul Electronics Limited

**DATE OF ISSUE** : Jun. 12, 2018

STANDARD(S)

**TEST PROCEDURE(S)** 

: FCC Part 15 Subpart C Section 15.249

**REPORT VERSION**: V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

#### **CAUTION:**

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



The results spower this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true and the authenticity of the authenticity of

Attestation of Global Compliance

Tel: +86-755 2908 1955 Fax: +86-755 2600 8484 E-mail: agc@agc-cert.com @ 400 089 2118 Add: 2/F., Building 2, No.1-4,Chaxi Sanwei Technical Industrial Park,Gushu, Xixiang, Baoan District, Shenzhen, Guangdong China



Page 2 of 61

## **Report Revise Record**

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0		Jun. 12, 2018	Valid	Initial release

The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by KGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.agc.gett.com.



## TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	4
2. GENERAL INFORMATION	5
2.2. TABLE OF CARRIER FREQUENCYS	5
3. MEASUREMENT UNCERTAINTY	
4. DESCRIPTION OF TEST MODES	
5. SYSTEM TEST CONFIGURATION	8
5.1. CONFIGURATION OF EUT SYSTEM5.2. EQUIPMENT USED IN EUT SYSTEM5.3. SUMMARY OF TEST RESULTS	8
6. TEST FACILITY	10
7. TEST METHOD	11
8. TEST EQUIPMENT LIST	
9. RADIATED EMISSION	12
9.1. TEST LIMIT 9.2. MEASUREMENT PROCEDURE 9.3. TEST SETUP 9.4. TEST RESULT	12 13 15
10. BAND EDGE EMISSION	38
10.1. MEASUREMENT PROCEDURE 10.2 TEST SETUP 10.3 RADIATED TEST RESULT	38 39
11. 20DB BANDWIDTH	43
11.1. MEASUREMENT PROCEDURE	43
12. FCC LINE CONDUCTED EMISSION TEST	50
12.1. LIMITS OF LINE CONDUCTED EMISSION TEST	50 51 51
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	52
ADDENIDIY D. DUOTOCDADUS OF FUT	5.4



age 4 of 61

## 1. VERIFICATION OF CONFORMITY

Applicant	Soul Electronics Limited		
Address	6/F, Enterprise Square Three, 39 Wang Chiu Road, Kowloon Bay, HongKong		
Manufacturer	Soul Electronics Limited		
Address	6/F, Enterprise Square Three, 39 Wang Chui Road, Kowloon Bay, HongKong		
Product Designation	Prime Wireless - High Performance Earphones with Bluetooth		
Brand Name	SOUL		
Test Model	PRIME WIRELESS		
Series Model	SP14		
Difference Description	All the same except for the model name		
Date of test	Jun. 06, 2018 to Jun. 11, 2018		
Deviation	None None		
Condition of Test Sample	Normal		
Report Template	AGCRT-US-BR/RF		

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, the energy emitted by the sample tested as described in this report is in compliance with the requirements of FCC Rules Part 15.249. The test results of this report relate only to the tested sample identified in this report.

Tested By	Jorden Wand	
Cooked Completions 8	Jonhen Wang(Wang Yonghuan)	Jun. 11, 2018
Reviewed By	cul chang	
(S) The state of Global Complian	Cool Cheng(Cheng Mengguo)	Jun. 12, 2018
Approved By	Forest cen	
Marce © Marcelland	Forrest Lei(Lei Yonggang)  Authorized Officer	Jun. 12, 2018



#### 2. GENERAL INFORMATION

#### 2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz
RF Output Power	-2.35dBm(Max EIRP Power=Max radiation field-95.2)
Bluetooth Version	V4.1 • 4 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
Modulation	BR ⊠GFSK, EDR ⊠π /4-DQPSK, ⊠8DPSK BLE □GFSK
Number of channels	79
Hardware Version	V1.0
Software Version	V2.0
Antenna Designation	PCB Antenna
Antenna Gain	2.3dBi
Power Supply	DC 3.7V by battery
Note:	

The USB port only used for charging and can't be used to transfer data with PC.

The BT function of EUT isn't work when charging.

#### 2.2. TABLE OF CARRIER FREQUENCYS

**BR/EDR Channel List** 

Frequency Band	Channel Number	Frequency	
超過	0 0	2402MHz	
		2403MHz	
		The state of the s	
	38	2440 MHz	
2400~2483.5MHz	39	2441 MHz	
	40	2442 MHz	
		A Barrier C Marine	
	T. 177	2479 MHz	
	78	2480 MHz	



Page 6 of 61

#### 3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.


- Uncertainty of Conducted Emission, Uc = ±3.2 dB
- Uncertainty of Radiated Emission below 1GHz, Uc = ±3.9 dB
- Uncertainty of Radiated Emission above 1GHz, Uc = ±4.8 dB

#### 4. DESCRIPTION OF TEST MODES


NO.	TEST MODE DESCRIPTION
1 K to companie	Low channel GFSK
© 2 2 · · · · · · · · · · · · · · · · ·	Middle channel GFSK
3	High channel GFSK
4	Low channel π /4-DQPSK
5 K 1000000	Middle channel π /4-DQPSK
6	High channel π /4-DQPSK
7	Low channel 8DPSK
8	Middle channel 8DPSK
The state of the s	High channel 8DPSK
10	BT Link

#### Note:

- 1. All the test modes can be supply by battery, only the result of the worst case was recorded in the report, if no other cases.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. The EUT used fully-charged battery when tested.







The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 8 of 61


## 5. SYSTEM TEST CONFIGURATION

## 5.1. CONFIGURATION OF EUT SYSTEM

Configure 1: (Normal hopping)

EUT

Configure 2: (Control continuous TX)



## **5.2. EQUIPMENT USED IN EUT SYSTEM**

Item	Equipment	Mfr/Brand	Model/Type No.	Remark
O C	Prime Wireless - High Performance Earphones with Bluetooth	SOUL	PRIME WIRELESS	) ÉUT
2	Battery	VDL	351030	Accessory
3	PC	APPLE	A1465	A.E
4	Control box	AIROHA	N/A	A.E
5	USB Cable	N/A	1m unshielded	A.E
6	USB Cable	N/A	0.3m unshielded	Accessory
7	IPOD	APPLE	A1367	A.E

The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.



Page 9 of 61

#### **5.3. SUMMARY OF TEST RESULTS**

FCC RULES	DESCRIPTION OF TEST	RESULT
§15.249(a) §15.209	Radiated Emission	Compliant
§15.249(d)	Band Edges	Compliant
§15.207	Conduction Emission	N/A
§15.215	Bandwidth	Compliant

Note: N/A means it's not applicable to this item.



Page 10 of 61

## 6. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd		
Location	1-2F., Bldg.2, No.1-4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District B112-B113, Bldg.12, Baoan Bldg Materials Center, No.1 of Xixiang Inner Ring Road, Baoan District, Shenzhen 518012		
NVLAP Lab Code	600153-0		
Designation Number	CN5028		
Test Firm Registration Number	682566		
Description	Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by National Voluntary Laboratory Accreditation program, NVLAP Code 600153-0		



age 11 of 61

#### 7. TEST METHOD

All measurements contained in this report were conducted with ANSI C63.10-2013

#### 8. TEST EQUIPMENT LIST

#### **TEST EQUIPMENT OF RADIATED EMISSION TEST**

		100	20151	700	(0) 202
Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
TEST RECEIVER	R&S	ESCI	10096	Jun.20, 2017	Jun.19, 2018
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Dec.08, 2017	Dec.07, 2018
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Sep.20, 2017	Sep.19, 2018
preamplifier	ChengYi	EMC184045SE	980508	Sep.15, 2017	Sep.14, 2018
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	May 18, 2017	May 17, 2019
Broadband Preamplifier	SCHWARZBECK	BBV 9718	9718-205	Jun.20, 2017	Jun.19, 2018
ANTENNA	SCHWARZBECK	VULB9168	D69250	Sep.28, 2017	Sep.27, 2018
Radiation Cable 1	MXT	RS1	R005	June 6, 2018	June 5, 2019
Radiation Cable 2	MXT	RS1	R006	June 6, 2018	June 5, 2019
Loop Antenna	A.H.Systems,Inc	SAS-562B	station of Country	Mar. 01, 2018	Feb. 28, 2019
Filter (2.4-2.483GHz)	Micro-tronics	087		Jun.20, 2017	Jun.19, 2018



Page 12 of 61

#### 9. RADIATED EMISSION

#### 9.1. TEST LIMIT

#### Standard FCC15.249

Fundamental	Field Strength of Fundamental	Field Strength of Harmonics
Frequency	(millivolts/meter)	(microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

#### Standard FCC 15.209

Frequency	Distance	Field Strengths Limit				
(MHz)	Meters	μ V/m	dB(μV)/m			
0.009 ~ 0.490	300	2400/F(kHz)	2			
0.490 ~ 1.705	30	24000/F(kHz)	电测 乐意			
1.705 ~ 30	30	30	See The second of the second o			
30 ~ 88	3	100	40.0			
88 ~ 216	3	150	43.5			
216 ~ 960	3	200	46.0			
960 ~ 1000	3	500	54.0			
Above 1000	3 Maria Commission	Other:74.0 dB(µV)/m (Average)	(Peak) 54.0 dB(μV)/m			

Remark:

- (1) Emission level dB $\mu$  V = 20 log Emission level  $\mu$  V/m
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.



Page 13 of 61

#### 9.2. MEASUREMENT PROCEDURE

- 1. The measuring distance of 3m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Below 1GHz)
- 2. The measuring distance of 3m shall used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Above 1GHz)
- The height of the test antenna shall vary between 1m to 4m.Both horizontal and vertical polarization Of the antenna are set to make the measurement.
- 4. The initial step in collecting radiated emission data is a receive peak detector mode. Pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- 5. All readings are peak unless otherwise stated QP in column of Note. Peak denoted that the Peak reading compliance with the QP limits and then QP Mode measurement didn't perform(Below 1GHz)
- 6. All readings are Peak mode value unless otherwise stated AVG in column of Note. If the Peak mode measured value compliance with the Peak limits and lower than AVG Limits, the EUT shall be deemed to meet Peak & AVG limits and then only Peak mode was measured, but AVG mode didn't perform.(Above 1GHz)

The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 14 of 61


The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	Fundamental: 2.4~2.483GHz RBW 2MHz/ VBW 6MHz for Peak, RBW 2MHz/ VBW 10Hz for Average Harmonics: 1GHz~25GHz RBW 1MHz/ VBW 3MHz for Peak, RBW 1MHz/ VBW 10Hz for Average
Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP





#### 9.3. TEST SETUP

#### RADIATED EMISSION TEST-SETUP FREQUENCY BELOW 30MHz




#### RADIATED EMISSION TEST SETUP 30MHz-1000MHz







## RADIATED EMISSION TEST SETUP ABOVE 1000MHz



The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by 100°C, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at although the confirmed at although the confirmed at although the confirmed at all the confirme



Page 17 of 61

#### 9.4. TEST RESULT


(Worst modulation: GFSK)

#### **RADIATED EMISSION BELOW 30MHz**

No emission found between lowest internal used/generated frequencies to 30MHz.

#### **RADIATED EMISSION BELOW 1GHz**


RADIATED EMISSION TEST- (30MHz-1GHz)-LOW CHANNEL-HORIZONTAL



#### A. Suspected List:


20	Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(u√/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
	41.155	H	6.0	17.4	23.4	40.0	16.6	Pass	150.0	181.0
	94.990	Н	6.9	12.7	19.6	43.5	23.9	Pass	200.0	229.5
	159.980	H	5.5	16.6	22.1	43.5	21.4	Pass	100.0	286.2
	230.305	Н	4.7	15.7	20.4	46.0	25.6	Pass	200.0	300.0
	481.050	Н	5.4	22.6	28.0	46.0	18.0	Pass	100.0	143.5
	986.420	Н	5.4	31.0	36.4	54.0	17.6	Pass	200.0	192.9

**RESULT: PASS** 





## RADIATED EMISSION TEST- (30MHz-1GHz)-LOW CHANNEL -VERTICAL



#### A. Suspected List:

Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(u√/m) PK	Limit dB(u∀/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
35.335	v	7.0	16.3	23.3	40.0	16.7	Pass	100.0	235.5
60.555	v	6.7	16.1	22.8	40.0	17.2	Pass	100.0	344.0
128.455	v	6.5	16.1	22.6	43.5	20.9	Pass	200.0	107.8
274.440	v	5.2	17.4	22.6	46.0	23.4	Pass	150.0	178.8
478.625	v	6.1	22.5	28.6	46.0	17.4	Pass	100.0	271.8
986.420	V	6.2	31.0	37.2	54.0	16.8	Pass	150.0	324.7


#### **RESULT: PASS**

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.



#### RADIATED EMISSION TEST- (30MHz-1GHz)-MIDDLE CHANNEL-HORIZONTAL




#### A. Suspected List:

Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(uV/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
46.975	H	6.2	17.2	23.4	40.0	16.6	Pass	200.0	267.3
142.035	Н	6.4	16.6	23.0	43.5	20.5	Pass	100.0	354.8
221.575	Н	17.7	14.9	32.6	46.0	13.4	Pass	150.0	72.2
272.985	Н	5.3	17.2	22.5	46.0	23.5	Pass	100.0	71.1
515.485	Н	6.7	23.2	29.9	46.0	16.1	Pass	200.0	86.6
956.350	Н	6.4	30.7	37.1	46.0	8.9	Pass	200.0	122.7

**RESULT: PASS** 



#### RADIATED EMISSION TEST- (30MHz-1GHz)-MIDDLE CHANNEL -VERTICAL



#### A. Suspected List:

Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(uV/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
41.155	V	6.4	17.4	23.8	40.0	16.2	Pass	200.0	47.6
59.100	V	6.3	16.3	22.6	40.0	17.4	Pass	200.0	20.2
133.790	V	6.5	16.5	23.0	43.5	20.5	Pass	150.0	331.8
218.665	V	12.3	14.6	26.9	46.0	19.1	Pass	100.0	120.3
420.425	v	6.8	21.4	28.2	46.0	17.8	Pass	100.0	291.1
833.160	V	6.7	29.3	36.0	46.0	10.0	Pass	2000.0	301.4


#### **RESULT: PASS**

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.



## RADIATED EMISSION TEST- (30MHz-1GHz)-HIGH CHANNEL-HORIZONTAL



#### A. Suspected List:


	equency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(uV/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
3	39.215	H	6.7	17.4	24.1	40.0	15.9	Pass	200.0	87.1
:	52.795	Н	6.5	16.9	23.4	40.0	16.6	Pass	150.0	163.5
1	142.520	Н	5.9	16.6	22.5	43.5	21.0	Pass	200.0	229.0
2	218.665	Н	22.8	14.6	37.4	46.0	8.6	Pass	150.0	345.7
4	109.755	Н	10.4	21.1	31.5	46.0	14.5	Pass	100.0	63.8
6	533.340	Н	9.3	25.4	34.7	46.0	11.3	Pass	150.0	202.9

**RESULT: PASS** 



#### Page 22 of 61

#### RADIATED EMISSION TEST- (30MHz-1GHz)-HIGH CHANNEL -VERTICAL



#### A. Suspected List:

Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(uV/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
35.820	V	7.8	16.5	24.3	40.0	15.7	Pass	100.0	219.0
79.470	V	8.6	12.3	20.9	40.0	19.1	Pass	100.0	356.6
131.850	V	6.2	16.3	22.5	43.5	21.0	Pass	100.0	174.6
218.665	V	9.5	14.6	24.1	46.0	21.9	Pass	200.0	122.3
284.140	V	6.1	17.7	23.8	46.0	22.2	Pass	150.0	212.6
688.630	V	6.6	26.2	32.8	46.0	13.2	Pass	200.0	153.2

#### **RESULT: PASS**

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.




Page 23 of 61

#### **RADIATED EMISSION ABOVE 1GHz**

(Worst modulation: GFSK)

#### For Fundamental

#### RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL-HORIZONTAL




**RESULT: PASS** 



Page 24 of 61

## RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL- VERTICAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
§		MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2402.000	82.07	10.32	92.39	114.00	-21.61	peak			
2	*	2402.000	74.04	10.32	84.36	94.00	-9.64	AVG	100	291	

**RESULT: PASS** 



Page 25 of 61

## RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL-HORIZONTAL




**RESULT: PASS** 

The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true www.agc.gett.com.



Page 26 of 61

## RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL- VERTICAL



1	lo.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
-2		-	MHz	dBu∀	dB/m	dBu\//m	dBu∀/m	dB		cm	degree	
sti	1		2441.000	81.43	10.36	91.79	114.00	-22.21	peak			
	2	*	2441.000	73.38	10.36	83.74	94.00	-10.26	AVG	100	279	


**RESULT: PASS** 

The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 27 of 61

## RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL-HORIZONTAL




**RESULT: PASS** 

The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 28 of 61

## RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL- VERTICAL



#### **RESULT: PASS**

Note: Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system

94.00

AVG

100

The results spown this test report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.agc-cent.com.



Page 29 of 61

## Field strength of the fundamental signal

#### 1Mbps Result:

#### Peak value

Frequency	Reading Factor		Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	82.53	10.32	92.85	114	-21.15	Horizontal
2402	87.07	10.32	92.39	114	-21.61	Vertical
2441	81.85	10.36	92.21	114	-21.79	Horizontal
2441	81.43	10.36	91.79	114	-22.21	Vertical
2480	81.23	10.41	91.64	114	-22.36	Horizontal
2480	80.81	10.41	91.22	114	-22.78	Vertical

#### Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	74.56	10.32	84.88	94	-9.12	Horizontal
2402	74.04	10.32	84.36	94	-9.64	Vertical
2441	73.91	10.36	84.27	94	-9.73	Horizontal
2441	73.38	10.36	83.74	94	-10.26	Vertical
2480	73.27	10.41	83.68	94	-10.32	Horizontal
2480	72.77	10.41	83.18	94	-10.82	Vertical



Page 30 of 61

#### 2Mbps Result:

#### Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna Polarization	
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)		
2402	82.19	10.32	92.51	114	-21.49	Horizontal	
2402	81.61	10.32	91.93	114	-22.07	Vertical	
2441	81.48	10.36	91.84	114	-22.16	Horizontal	
2441	80.98	10.36	91.34	114	-22.66	Vertical	
2480	80.77	10.41	91.18	114	-22.82	Horizontal	
2480	80.49	10.41	90.90	114	-23.10	Vertical	

#### Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna	
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization	
2402	74.18	10.32	84.50	94	-9.50	Horizontal	
2402	73.62	10.32	83.94	94	-10.06	Vertical	
2441	73.38	10.36	83.74	94	-10.26	Horizontal	
2441	73.17	10.36	83.53	94	-10.47	Vertical	
2480	72.78	10.41	83.19	94	-10.81	Horizontal	
2480	72.39	10.41	82.80	94	-11.20	Vertical	



Page 31 of 61

#### 3Mbps Result:

#### Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna Polarization Horizontal	
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)		
2402	81.88	10.32	92.20	114	-21.80		
2402	81.13	10.32	91.45	114	-22.55	Vertical	
2441	81.04	10.36	91.40	114	-22.60	Horizontal	
2441	80.63	10.36	90.99	114	-23.01	Vertical	
2480	80.35	10.41	90.76	114	-23.24	Horizontal	
2480	80.01	10.41	90.42	114	-23.58	Vertical	

#### Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna	
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization	
2402	73.87	10.32	84.19	94	-9.81	Horizontal	
2402	73.31	10.32	83.63	94	-10.37	Vertical	
2441	72.96	10.36	83.32	94	-10.68	Horizontal	
2441	72.80	10.36	83.16	94	-10.84	Vertical	
2480	72.40	10.41	82.81	94	-11.19	Horizontal	
2480	72.06	10.41	82.47	94	-11.53	Vertical	




Page 32 of 61

## (Worst modulation: GFSK)

#### **For Harmonics**

#### RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL-HORIZONTAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		1975.000	36.83	9.62	46.45	74.00	-27.55	peak			
2		2808.333	36.10	11.18	47.28	74.00	-26.72	peak			
3	*	4804.000	43.71	7.69	51.40	74.00	-22.60	peak			

**RESULT: PASS** 



Page 33 of 61

## RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL- VERTICAL




**RESULT: PASS** 



Page 34 of 61

## RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL-HORIZONTAL




**RESULT: PASS** 

The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 35 of 61

#### RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL- VERTICAL



74.00

peak

**RESULT: PASS** 

4882.000


43.89

The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true www.ago.gent.com.



Page 36 of 61

#### RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL-HORIZONTAL



74.00

-22.31

peak

**RESULT: PASS** 

4960.000

43.60

8.09


51.69

The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by (GC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a titp://www.agc.gatt.com.



Page 37 of 61

# RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL- VERTICAL



	No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
3		-	· MHz	dBu∀	dB/m	dBu\//m	dBu∀/m	dB		cm	degree	
(3)	1		1833.333	37.66	8.13	45.79	74.00	-28.21	peak			
ſ	2		3883.333	33.06	14.47	47.53	74.00	-26.47	peak			
	3	*	4960.000	43.91	8.09	52.00	74.00	-22.00	peak			

# **RESULT: PASS**

Note: 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true www.ago.gent.com.



Page 38 of 61

## 10. BAND EDGE EMISSION


## 10.1. MEASUREMENT PROCEDURE

- 1. The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
- 2. Max hold the trace of the setup 1, and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.
- 3. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission.

	Start frequenc	y(MHz)		Stop frequency(MHz)				
	2200	Kimplence	The Committee	® A station of G	2405	100		
(S) ### (1)	2478	3lobal C	Autostation of Glob	-,0 "	2500			

#### **10.2 TEST SETUP**

## RADIATED EMISSION TEST SETUP



The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gent.com.




Page 39 of 61

# **10.3 RADIATED TEST RESULT**

(Worst modulation: GFSK)

## TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal



	No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
10.		-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
	1		2349.992	31.76	10.26	42.02	74.00	-31.98	peak			
	2		2390.000	32.50	10.31	42.81	74.00	-31.19	peak			
	3		2400.000	41.47	10.32	51.79	74.00	-22.21	peak			
	4	*	2402.000	82.72	10.32	93.04	74.00	19.04	peak			
	5	Х	2402.000	74.65	10.32	84.97	74.00	10.97	AVG	100	51	

The results showing this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gent.com.



Page 40 of 61

## TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Vertical




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
ê		MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2340.425	30.84	10.25	41.09	74.00	-32.91	peak			
2		2390.000	32.21	10.31	42.52	74.00	-31.48	peak			
3		2400.000	38.06	10.32	48.38	74.00	-25.62	peak			
4	*	2402.000	82.59	10.32	92.91	74.00	18.91	peak			
5	Х	2402.000	74.30	10.32	84.62	74.00	10.62	AVG	100		

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.



Page 41 of 61

## TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal




	No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1	1	*	2480.000	81.55	10.41	91.96	74.00	17.96	peak			
3	2	Х	2480.000	73.38	10.41	83.79	74.00	9.79	AVG	100	56	
Γ	3		2483.500	34.19	10.41	44.60	74.00	-29.40	peak			
	4		2487.863	33.40	10.42	43.82	74.00	-30.18	peak			

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by (c), this document to cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc-cert.com.



Page 42 of 61

## TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



No	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1	*	2480.000	81.32	10.41	91.73	74.00	17.73	peak			
2	Х	2480.000	73.00	10.41	83.41	74.00	9.41	AVG	100	283	
3		2483.500	34.26	10.41	44.67	74.00	-29.33	peak			
4		2487.753	34.95	10.42	45.37	74.00	-28.63	peak			

### **RESULT: PASS**

**Note**: Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Hopping on mode and Hopping off mode have been tested, but only worst case reported.

The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.




Page 43 of 61

## 11. 20DB BANDWIDTH

## 11.1. MEASUREMENT PROCEDURE

- 1. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 2. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hoping channel RBW ≥ 1% of the 20 dB bandwidth, VBW ≥ 3RBW; Sweep = auto; Detector function = peak
- 3. Set SPA Trace 1 Max hold, then View.

## 11.2. TEST SET-UP



## 11.3. LIMITS AND MEASUREMENT RESULTS

BLUETOOTH 1MBPS LIMITS AND MEASUREMENT RESULT								
		Measure	ement Result					
Applicable Limits		Test Data (MHz)						
		99%OBW (MHz)	-20dB BW(MHz)	Result				
The stands	Low Channel	0.918	1.090	PASS				
N/A	Middle Channel	0.922	1.080	PASS				
100	High Channel	0.919	1.082	PASS				


The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gent.com.




### TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



#### TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.






#### TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.





BLUETOOTH 2MBPS LIMITS AND MEASUREMENT RESULT								
		Measure	ement Result					
Applicable Limits		D K						
		99%OBW (MHz)	-20dB BW(MHz)	Result				
TO THE	Low Channel	1.218	1.379	PASS				
N/A	Middle Channel	1.216	1.359	PASS				
COC	High Channel	1.201	1.345	PASS				


## TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.




#### TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



#### TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.





**BLUETOOTH 3MBPS LIMITS AND MEASUREMENT RESULT** Measurement Result **Applicable Limits** Test Data (MHz) Result 99%OBW (MHz) -20dB BW(MHz) Low Channel 1.210 **PASS** 1.349 1.204 **PASS** N/A Middle Channel 1.345 **PASS High Channel** 1.216 1.359


#### TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




The results spowfil this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by 40°C, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



#### TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



#### TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



age 50 of 61

## 12. FCC LINE CONDUCTED EMISSION TEST


## 12.1. LIMITS OF LINE CONDUCTED EMISSION TEST

F	Maximum RF Line Voltage								
Frequency	Q.P.( dBuV)	Average( dBuV)							
150kHz~500kHz	66-56	56-46							
500kHz~5MHz	8 gg 200 56 gg 100 00 00 00 00 00 00 00 00 00 00 00 00	46 / W							
5MHz~30MHz	60	50							

### Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

## 12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 51 of 61

## 12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipments received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC charging voltage by adapter or PC which received 120V/60Hzpower by a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

## 12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST


- EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- The test data of the worst case condition(s) was reported on the Summary Data page.

### 12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

N/A

**Note:** The BT function of EUT isn't work when charging.

The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a trp://www.ago.go.tt.com.






# APPENDIX A: PHOTOGRAPHS OF TEST SETUP

FCC RADIATED EMISSION TEST SETUP





The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.goalt.com.









The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.



## **APPENDIX B: PHOTOGRAPHS OF EUT**

TOTAL VIEW OF EUT



TOP VIEW OF EUT




The results showing this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by ACC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gent.com.

Attestation of Global Compliance

Tel: +86-755 2908 1955 Fax: +86-755 2600 8484 E-mail: agc@agc-cert.com @ 400 089 2118 Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Baoan District, Shenzhen, Guangdong China



## **BOTTOM VIEW OF EUT**



FRONT VIEW OF EUT



The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by KGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.



## **BACK VIEW OF EUT**



**LEFT VIEW OF EUT** 



The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true www.agc. gent.com.

Attestation of Global Compliance

Tel: +86-755 2908 1955 Fax: +86-755 2600 8484 E-mail: agc@agc-cert.com @ 400 089 2118 Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Baoan District, Shenzhen, Guangdong China



# RIGHT VIEW OF EUT



VIEW OF EUT (PORT)



The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.

Attestation of Global Compliance

Tel: +86-755 2908 1955 Fax: +86-755 2600 8484 E-mail: agc@agc-cert.com @ 400 089 2118 Add: 2/F., Building 2, No.1-4,Chaxi Sanwei Technical Industrial Park,Gushu, Xixiang, Baoan District, Shenzhen, Guangdong China



## **OPEN VIEW OF EUT**



VIEW OF BATTERY




The results spowfor this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attr://www.agc.gett.com.

Attestation of Global Compliance


Tel: +86-755 2908 1955 Fax: +86-755 2600 8484 E-mail: agc@agc-cert.com @ 400 089 2118 Add: 2/F. , Building 2, No.1-4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Baoan District, Shenzhen, Guangdong China



# **INTERNAL VIEW OF EUT-1**



**INTERNAL VIEW OF EUT-2** 




The results showing this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a state of the sample (s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a state of the sample (s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a state of the sample (s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission.

Attestation of Global Compliance


Tel: +86-755 2908 1955 Fax: +86-755 2600 8484 E-mail: agc@agc-cert.com @ 400 089 2118 Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Baoan District, Shenzhen, Guangdong China



# **INTERNAL VIEW OF EUT-3**



**INTERNAL VIEW OF EUT-4** 




The results showing this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true; //www.agc.goalt.com.





Report No.: AGC00917180601FE03 Page 61 of 61

# **INTERNAL VIEW OF EUT-5**



---END OF REPORT----

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc-gett.com. AGC ?