

# RF EXPOSURE REPORT



Report No.: 17070182-FCC-H2

Supersede Report No.: N/A

Applicant	Jethro Trading LTD.	
Product Name	Jethro 3G Senior Cell Phone	
Model No.	SC318	
Serial No.	N/A	
Test Standard	FCC 2.1093:2015	
Test Date	March 15 to March 21, 2017	
Issue Date	March 22, 2017	
Test Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail	
Equipment complied with the specification <input checked="" type="checkbox"/>		
Equipment did not comply with the specification <input type="checkbox"/>		
Loren Luo	David Huang	
Loren Luo Test Engineer	David Huang Checked By	
This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: [China@siemic.com.cn](mailto:China@siemic.com.cn)

## Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

### Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	17070182-FCC-H2
Page	3 of 9

This page has been left blank intentionally.

## CONTENTS

1. REPORT REVISION HISTORY.....	5
2. CUSTOMER INFORMATION.....	5
3. TEST SITE INFORMATION .....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION .....	6
5. FCC §2.1093 - RADIOFREQUENCY RADIATION EXPOSURE EVALUATION: PORTABLE DEVICES.8	
5.1 RF EXPOSURE.....	8
5.2 TEST RESULT .....	9

## 1. Report Revision History

Report No.	Report Version	Description	Issue Date
17070182-FCC-H2	NONE	Original	March 22, 2017

## 2. Customer information

Applicant Name	Jethro Trading LTD.
Applicant Add	505 - 8840 210TH STREET, #231 Langley, Canada V1M2Y2
Manufacturer	Shenzhen Bayuda Technologies,co.,ltd
Manufacturer Add	Room A433 A Block,Shenzhen Industrial products exibition procurement center the baoyuan road baoan distric

## 3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1

#### **4. Equipment under Test (EUT) Information**

Description of EUT: Jethro 3G Senior Cell Phone

Main Model: SC318

Serial Model: N/A

Date EUT received: March 14, 2017

Test Date(s): March 15 to March 21, 2017

GSM850: 0.5dBi

PCS1900: 1.0dBi

Antenna Gain: UMTS-FDD Band V: 1.0dBi

UMTS-FDD Band II: 1.0dBi

Bluetooth: 0.5dBi

Antenna Type: GSM/PCS/UMTS-FDD :PIFA antenna  
BT : Monopole antenna

GSM / GPRS: GMSK

EGPRS: GMSK

UMTS-FDD: QPSK

Bluetooth: GFSK, π /4DQPSK, 8DPSK

GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz

PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz

UMTS-FDD Band V TX: 826.4 ~ 846.6 MHz; RX: 871.4 ~ 891.6 MHz

RF Operating Frequency (ies): UMTS-FDD Band II TX:1852.4 ~ 1907.6 MHz;  
RX: 1932.4 ~ 1987.6 MHz

Bluetooth: 2402-2480 MHz

GSM 850: 124CH

PCS1900: 299CH

Number of Channels: UMTS-FDD Band V: 102CH  
UMTS-FDD Band II: 277CH  
Bluetooth: 79CH

Test Report	17070182-FCC-H2
Page	7 of 9

Port: USB Port, Earphone Port

Adapter:

Model: HJ-050050-US

Input: AC100-240V~50/60Hz,0.1A

Output: DC 5.0V,500mA

Input Power: Battery:

Model:SC318

Spec: 3.7V,800mAh,2.96Wh

Voltage: 4.2V

Trade Name : Jethro

GPRS/EGPRS Multi-slot class 8/10/12

FCC ID: 2AAWJSC318

## 5. FCC §2.1093 - Radiofrequency radiation exposure evaluation: portable devices.

### 5.1 RF Exposure

#### **Standard Requirement:**

According to §15.247 (i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at *test separation distances*  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f_{(\text{GHz})}}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR,}^{16}$  where

- $f_{(\text{GHz})}$  is the RF channel transmit frequency in GHz
- Power and distance are rounded to the nearest mW and mm before calculation<sup>17</sup>
- The result is rounded to one decimal place for comparison

The test exclusions are applicable only when the minimum *test separation distance* is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum *test separation distance* is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

Routine SAR evaluation refers to that specifically required by § 2.1093, using measurements or computer simulation. When routine SAR evaluation is not required, portable transmitters with output power greater than the applicable low threshold require SAR evaluation to qualify for TCB approval.

$$\text{result} = P\sqrt{F} / D$$

P= Maximum turn-up power in mW

F= Channel frequency in GHz

D= Minimum test separation distance in mm

## 5.2 Test Result

### Bluetooth Mode:

Modulation	CH	Frequency (MHz)	Conducted Power (dBm)	Tune Up Power (dBm)	Max Tune Up Power (dBm)	Max Tune Up Power (mW)	Result	Limit
GFSK	Low	2402	1.606	2±1	3	1.995	0.62	3
	Mid	2441	2.120	2±1	3	1.995	0.62	3
	High	2480	2.376	2±1	3	1.995	0.63	3
$\pi/4$ DQPSK	Low	2402	1.226	2±1	3	1.995	0.62	3
	Mid	2441	1.904	2±1	3	1.995	0.62	3
	High	2480	2.042	2±1	3	1.995	0.63	3
8-DPSK	Low	2402	1.372	2±1	3	1.995	0.62	3
	Mid	2441	1.915	2±1	3	1.995	0.62	3
	High	2480	2.219	2±1	3	1.995	0.63	3

**Result:** Compliance

No SAR measurement is required.