

# FCC ID: 2AAXO-SMK250

## Portable device

According to §15.247(e)(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances  $\leq 50$  mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})]^*$   
 $[\sqrt{f(\text{GHz})}] \leq 3.0$  for 1-g SAR and  $\leq 7.5$  for 10-g extremity SAR, where  
 $f(\text{GHz})$  is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is  $\leq 50$  mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is  $< 5$  mm, a distance of 5 mm is applied to determine SAR test exclusion.

We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

BT DSS:

Transmit Frequency (GHz)	Mode	Max Conducted Power (dBm)	tune up maximum power	Result calculation	1-g SAR
2.402	GFSK	-1.653	-1 $\pm$ 1dBm	0.3100	3.0
2.441	GFSK	-0.798	-1 $\pm$ 1dBm	0.3125	3.0
2.480	GFSK	-0.506	-1 $\pm$ 1dBm	0.3150	3.0
2.402	$\pi/4$ -DQPSK	-0.775	0 $\pm$ 1dBm	0.3902	3.0
2.441	$\pi/4$ -DQPSK	0.049	0 $\pm$ 1dBm	0.3934	3.0
2.480	$\pi/4$ -DQPSK	0.317	0 $\pm$ 1dBm	0.3965	3.0

Conclusion:

For the max result :  $0.3965 \leq 3.0$  for 1-g SAR extremity SAR, No SAR is required.

Signature:



Date: 2017-04-21

**NAME AND TITLE (Please print or type):** Lisa Wang/Manager

**COMPANY (Please print or type):** EMTEK (Shenzhen) Co., Ltd./Building 69, Majialong Industry Zone, Nanshan District, Shenzhen, Guangdong, China