

RF EXPOSURE EVALUATION

1. PRODUCT INFORMATION

Product Description	DUET KARAOKE MICROPHONE
Model Name	SMM498
FCC ID	2AAXO-SMM498

2. EVALUATION METHOD

According to 447498 D01 General RF Exposure Guidance v05

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

$[(\text{max. power of channel, including tune-up tolerance, mW}) / (\text{min. test separation distance, mm})] \cdot [\sqrt{f(\text{GHz})}] \leq 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR.}$

Where $f(\text{GHz})$ is the RF channel transmit frequency in GHz

Power and distance are rounded to the nearest mW and mm before calculation

3. CALCULATION

$$P_t = 3.617 \text{ dBm} = 2.30 \text{ mW}$$

The value of the Maximum output power P_t is referred to the test report of the **CFR47 §15.247**.

The result for RF exposure evaluation $\text{SAR} = (2.30 \text{ mW} / 5 \text{ mm}) \cdot [\sqrt{2.441 \text{ GHz}}] = 0.72 < 3.0 \text{ for 1-g SAR and } \leq 7.5 \text{ for 10-g extremity SAR.}$

4. CONCLUSION

The SAR evaluation is not required.