

Modular Approval Request FCC (KDB 996369 D01 & Part 15.212)

FCC ID: 2AA YI-MFAD4-C02

<i>Items to be covered by Single modular transmitters.</i>	<i>Answer from applicant</i>
1. The radio elements must have the radio frequency circuitry shielded. Physical components and tuning capacitor(s) may be located external to the shield, but must be on the module assembly.	Yes
2. The module must have buffered modulation/data inputs to ensure that the device will comply with Part 15 requirements with any type of input signal.	Module chipset design incorporates integrated buffer circuitry
3. The module must contain power supply regulation on the module	Module chipset incorporates voltage regulation to transceiver circuitry
4. The module must contain a permanently attached antenna, or contain a unique antenna connector, and be marketed and operated only with specific antenna(s), per §§ 15.203, 15.204(b), 15.204(c), 15.212(a), 2.929(b).	Yes, the antenna employ a "unique" antenna coupler
5. The module must demonstrate compliance in a stand-alone configuration.	EUT conformance testing was performance in a standalone configuration
6. The module must be labeled with its permanently affixed FCC ID label, or use an electronic display (see KDB Publication 784748).	Please refer to FCC ID label format. Labeling instruction has been provided in the user manual
7. The module must comply with all specific rules applicable to the transmitter, including all the conditions provided in the integration instructions by the grantee.	This module is compliant with all applicable FCC rules. Compliance requirements are stated in the user manual.
8. The module must comply with RF exposure requirements.	Compliance with RF exposure requirements is address in report

<i>Items to be covered by Split modular transmitters.</i>	<i>Answer from applicant</i>
1. The modular transmitter must comply with all requirements of a single modular transmitter except for items (1) & (5) of the above single modular approval requirements.	
2. Only the radio front end must be shielded. The physical crystal and tuning capacitors may be located external to the shielded radio elements. The interface between the split sections of the modular system must be digital with a minimum signalling amplitude of 150 mV peak-to-peak.	
3. Control information and other data may be exchanged between the transmitter control elements and radio front end.	
4. The sections of a split modular transmitter must be tested installed in a host device(s) similar to that which is representative of the platform(s) intended for use.	
5. Manufacturers must ensure that only transmitter control elements and radio front end components that have been approved together are capable of operating together. The transmitter module must not operate unless it has verified that the installed transmitter control elements and radio front end have been authorized together. Manufacturers may use means including, but not limited to, coding in hardware and electronic signatures in software to meet these requirements, and must describe the methods in their application for equipment authorization.	



RF_734_03
26 March 2020

Note: A limited modular approval (LMA) may be granted for *single* or *split* modular transmitters that comply partially with the requirements above.

Name and surname of applicant (or authorized representative): Liya Lee / Special Assistant to G.M.

Date: Apr. 14, 2022

Signature:

A handwritten signature in blue ink that reads "Liya Lee".