




# FCC RADIO TEST REPORT

Applicant : Protop International Inc.  
Address : 10F-8, No.237, Sec.,1, Datong Rd., Xizhi Dist., 22161New Taipei  
City, Taiwan  
Equipment : Charging Stand with MagSafe  
Model No. : OBFTC-0108-A,78-80872,78-80873  
Trademark : OTTERBOX  
FCC ID : 2AAYX0108A

## I HEREBY CERTIFY THAT :

The sample was received on May 31, 2022 and the testing was carried out on Jul. 11, 2022 at CerpPASS Technology Corp. The test result refers exclusively to the test presented test model / sample. Without written approval of CerpPASS Technology Corp., the test report shall not be reproduced except in full.

Approved by:

  
\_\_\_\_\_  
Leevin Li / Supervisor



## Contents

<b>1. Report of Measurements and Examinations.....</b>	<b>4</b>
1.1 List of Measurements and Examinations .....	4
<b>2. Test Configuration of Equipment under Test.....</b>	<b>5</b>
2.1 Feature of Equipment under Test.....	5
2.2 Description of the test mode .....	6
2.3 Description of Test System.....	7
2.4 General Information of Test.....	8
2.5 Measurement Uncertainty .....	8
<b>3. Test Equipment and Ancillaries Used for Tests.....</b>	<b>9</b>
<b>4. Antenna Requirements.....</b>	<b>10</b>
4.1 Standard Applicable .....	10
4.2 Antenna Construction.....	10
4.3 Result .....	10
<b>5. Test of Conducted Emission.....</b>	<b>11</b>
5.1 Test Limit .....	11
5.2 Test Procedures .....	11
5.3 Typical Test Setup .....	12
5.4 Test Result and Data.....	13
<b>6. Test of Radiated Emission .....</b>	<b>15</b>
6.1 Test Limit .....	15
6.2 Test Procedures.....	16
6.3 Typical Test Setup .....	17
6.4 Test Result and Data .....	18
<b>7. 20dB Bandwidth .....</b>	<b>28</b>
7.1 Test Limit .....	28
7.2 Test Procedures.....	28
7.3 Typical Test Setup .....	28
7.4 Test Result and Data .....	29



### History of this test report

Original.

Additional attachment as following record:

Attachment No.	Issue Date	Description
DEFC2205044	Jul. 11, 2022	Initial Issue



# 1. Report of Measurements and Examinations

## 1.1 List of Measurements and Examinations

FCC CFR Title 47 Part 15 Subpart C Section 15.209

FCC Rule	Description of Test	Result
§ 15.203	. Antenna Requirement	Pass
§ 15.207(a)	. Conducted Emission	Pass
§ 15.209(a)	. Radiated Emission	Pass
§ 15.215	20dB Bandwidth	Pass

Note: Deviations Yes  No   
\*The lab has reduced the uncertainty risk factor from test equipment, environment and staff technicians which according to the standard on contract. Therefore, the test result will only be determined by standard requirement.



## 2. Test Configuration of Equipment under Test

### 2.1 Feature of Equipment under Test

Product	Charging Stand with MagSafe
Test Model	OBFTC-0108-A,78-80872,78-80873
Model Discrepancy	All models are identical to each other except the model name and appearance color. The tested model: OBFTC-0108-A
Frequency Range	iPhone Wireless Charging:127.7KHz and 360KHz
Antenna Type	Coil antenna
EUT Power Rating:	Input: 9.0V $\overline{\sim}$ 2.22A/12V $\overline{\sim}$ 1.67A, 20.0W MAX Output Wireless Magsafe:15W Max
Temperature	Operating Temp:0°C~+35°C Storage Temp: -20°C~+40°C

Note: The above EUT information is declared by manufacturer and for more detailed features description, please refer to the manufacturer's specifications or user's manual.



## 2.2 Description of the test mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned above was evaluated respectively.

The EUT was tested under the following modes, the worst mode was recorded in this report.

For Conducted Emission	
Pre-tested Mode:	Description
Mode 1	Wireless Charging for Wireless 1(Standby mode) for 120V
Mode 2	Wireless Charging for Wireless 1(15W for iPhone 13, Operating @360KHz) for 120V
Mode 3	Wireless Charging for Wireless 1(15W for iPhone 12, Operating @127.7KHz) for 120V
Mode 4	Wireless Charging for Wireless 1(15W for iPhone 13, Operating @360KHz) for 240V
Final test Mode	Description
Mode 2	Wireless Charging for Wireless 1(15W for iPhone 13, Operating @360KHz) for 120V
For Radiated Emission	
Pre-tested Mode:	Description
Mode 1	Wireless Charging for Wireless 1(Standby mode)
Mode 2	Wireless Charging for Wireless 1(15W for iPhone 13, Operating @360KHz)
Mode 3	Wireless Charging for Wireless 1(15W for iPhone 12, Operating @127.7KHz)
Final test Mode	For Radiated Emission ( 9KHz-30MHz ) : Description
Mode 2	Wireless Charging for Wireless 1(15W for iPhone 13, Operating @360KHz)
Mode 3	Wireless Charging for Wireless 1(15W for iPhone 12, Operating @127.7KHz)
Final test Mode	For Radiated Emission ( 30MHz-1GHz ) : Description
Mode 2	Wireless Charging for Wireless 1(15W for iPhone 13, Operating @360KHz)


Note:

- a: While charging, client devices were between 20% to 50% state of charging.
- b: The EUT Have one coils.



### 2.3 Description of Test System

Product	Manufacturer	Model No.	Power Cord
1 Adapter	OTTERBOX	OBFTC-0069-B	N/A
2 iPhone	Apple	iPhone 12	N/A
3 iPhone	Apple	iPhone X	N/A





## 2.4 General Information of Test

Test Site	<b>CerpPASS Technology Corporation(CerpPASS Laboratory)</b> Address: Room 102, No. 5, Xing'an Road, Chang'an Town, Dongguan City, Guangdong Province Tel: +86-769-8547-1212 Fax: +86-769-8547-1912
FCC Designation No.:	CN1288
Frequency Range Investigated:	Conducted: from 150kHz to 30 MHz Radiation: from 30 MHz to 40,000MHz
Test Distance:	9KHz~30MHz: radiated emission from antenna to EUT is 3 M. 30MHz~1GHz: radiated emission from antenna to EUT is 3 M.

Test Item	Test Site	Test period	Environmental Conditions	Tested By
Radiated Emissions	3M01-DG	2022/06/20~2022/07/11	24°C~26°C/ 52%~58%	Amos Zhang
AC Power Line Conducted Emission	CON01-DG	2022/06/20	26°C/ 55%	Amos Zhang

## 2.5 Measurement Uncertainty

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2)).

Measurement Item	Uncertainty
AC Power Line Conduction(150K~30MHz)	±3.17dB
Radiated Spurious Emission(9KHz~30MHz)	±4.99dB
Radiated Spurious Emission(30MHz~1GHz)	±4.39dB
6dB Bandwidth&20dB Bandwidth	±4.4%
Occupied Bandwidth	±4.4%





### 3. Test Equipment and Ancillaries Used for Tests

AC Power Line Conducted Emission					
Instrument/Ancillary	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date.
Test Receiver	R&S	ESCI	100564	2022.01.08	2023.01.07
LISN	SCHWARZBECK	NSLK 8127	8127748	2022.01.08	2023.01.07
LISN	R&S	ENV216	100024	2022.01.08	2023.01.07
ISN	TESEQ	ISN T800	42809	2022.05.07	2023.05.06
Pulse Limiter with 10dB Attenuation	SCHWARZBECK	VTSD 9561-F	9561-F106	2022.01.08	2023.01.07
Temperature/ Humidity Meter	GEMLEAD	STH200A	N/A	2021.08.17	2022.08.16

Radiated Emissions					
Instrument	Manufacturer	Model No.	Serial No.	Calibration Date	Valid Date
EMI Test Receiver	R&S	ESCI	100563	2022.05.07	2023.05.06
H64 Preamplifier	HP	8447F	3113A05582	2022.01.08	2023.01.07
Loop Antenna	R&S	HFH2-Z2	100150	2022.05.11	2024.05.10
Bilog Antenna	Sunol Science	JB1	A072414-1	2020.06.08	2022.06.07
Temperature/ Humidity Meter	GEMLEAD	STH200A	N/A	2021.08.17	2022.08.16



## 4. Antenna Requirements

### 4.1 Standard Applicable

For intentional device, according to FCC 47 CFR Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### 4.2 Antenna Construction

The antenna is Coil Antenna, and the antenna connector is de-signed with permanent attachment and on consideration of replacement. Please see the EUT photo for details.

### 4.3 Result

The EUT antenna is Loop Antenna. It complies with the standard requirement.



## 5. Test of Conducted Emission

### 5.1 Test Limit

According to §15.207: For all the consumer devices which is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed 250 microvolts (The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz). The limits at specific frequency range are listed as follows:

Frequency (MHz)	Quasi Peak (dB $\mu$ V)	Average (dB $\mu$ V)
0.15 – 0.5	66-56*	56-46*
0.5 – 5.0	56	46
5.0 – 30.0	60	50

Remark: (1)\*Decreases with the logarithm of the frequency.


(2)The lower limit shall apply at the transition frequency.

### 5.2 Test Procedures

- The EUT was placed 0.4 meter from the conducting wall of the shielding room was kept at least 80 centimeters from any other grounded conducting surface.
- Connect EUT to the power mains through a line impedance stabilization network (LISN).
- All the support units are connecting to the other LISN.
- The LISN provides 50 ohm coupling impedance for the measuring instrument.
- The FCC states that a 50 ohm, 50 micro-Henry LISN should be used.
- Both sides of AC line were checked for maximum conducted interference.
- The frequency range from 150 kHz to 30 MHz was searched.
- Set the test-receiver system to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.




### 5.3 Typical Test Setup





5.4 Test Result and Data

Test Mode :	Mode 2	Phase :	Line
Power :	AC 120V/60Hz		




No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.4740	9.71	41.63	51.34	56.44	-5.10	QP
2	0.4740	9.71	27.55	37.26	46.44	-9.18	AVG
3	0.4941	9.72	39.40	49.12	56.10	-6.98	QP
4	0.4941	9.72	24.13	33.85	46.10	-12.25	AVG
5	0.5140	9.72	38.70	48.42	56.00	-7.58	QP
6	0.5140	9.72	25.88	35.60	46.00	-10.40	AVG
7	0.9580	9.77	31.24	41.01	56.00	-14.99	QP
8	0.9580	9.77	15.96	25.73	46.00	-20.27	AVG
9	1.2940	9.78	31.07	40.85	56.00	-15.15	QP
10	1.2940	9.78	16.90	26.68	46.00	-19.32	AVG
11	26.9340	10.31	31.14	41.45	60.00	-18.55	QP
12	26.9340	10.31	20.96	31.27	50.00	-18.73	AVG

Note: Measurement Level = Reading Level + Correct Factor+ Attenuator



Test Mode :	Mode 2	Phase :	Neutral
Power :	AC 120V/60Hz		



No.	Frequency (MHz)	Factor (dB)	Reading (dBuV)	Level (dBuV)	Limit (dBuV)	Margin (dB)	Detector
1	0.4740	9.72	39.85	49.57	56.44	-6.87	QP
2	0.4740	9.72	29.43	39.15	46.44	-7.29	AVG
3	0.4940	9.71	39.23	48.94	56.10	-7.16	QP
4	0.4940	9.71	30.36	40.07	46.10	-6.03	AVG
5	0.5101	9.71	38.67	48.38	56.00	-7.62	QP
6	0.5101	9.71	28.86	38.57	46.00	-7.43	AVG
7	1.3020	9.80	30.06	39.86	56.00	-16.14	QP
8	1.3020	9.80	21.29	31.09	46.00	-14.91	AVG
9	27.2140	10.39	36.89	47.28	60.00	-12.72	QP
10	27.2140	10.39	22.30	32.69	50.00	-17.31	AVG
11	0.5660	9.73	27.48	37.21	56.00	-18.79	QP
12	0.5660	9.73	18.06	27.79	46.00	-18.21	AVG

Note: Measurement Level = Reading Level + Correct Factor+ Attenuator



## 6. Test of Radiated Emission

### 6.1 Test Limit

In any 100kHz bandwidth outside the frequency band, the radio frequency power produced by According to §15.209(a), for a intentional device, the general requirement of field strength of radiated emissions from intentional radiators at a distance of 3 meters shall not exceed the following values:

#### Radiated Emission Limit (9KHz~1000MHz)

FREQUENCIES(MHz)	FIELD STRENGTH(microvolts/meter)	MEASUREMENT DISTANCE(meters)
0.009~0.490	2400/F(kHz)	300
0.490~1.705	24000/F(kHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

Note:

- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dBuV/m)=20log Emission Level(uV/m)



## 6.2 Test Procedures


- a. The EUT was placed on a rotatable table top 0.8 meter above ground.
- b. The EUT was set 1/3 meters from the interference receiving antenna which was mounted on the top of a variable height antenna tower.
- c. The table was rotated 360 degrees to determine the position of the highest radiation.
- d. The antenna is a broadband antenna and its height is varied between one meter and four meters above ground to find the maximum value of the field strength both horizontal polarization and vertical polarization of the antenna are set to make the measurement.
- e. For each suspected emission the EUT was arranged to its worst case and then tune the antenna tower (from 1 M to 4 M) and turn table (from 0 degree to 360 degrees) to find the maximum reading.
- f. Set the test-receiver system to Peak or CISPR quasi-peak Detect Function and specified bandwidth with Maximum Hold Mode.
- g. If the emission level of the EUT in peak mode was 3 dB lower than the limit specified, then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions which do not have 3 dB margin will be repeated one by one using the quasi-peak method and reported.
- h. For testing above 1GHz, the emission level of the EUT in peak mode was 20dB lower than average limit (that means the emission level in peak mode also complies with the limit in average mode), then testing will be stopped and peak values of EUT will be reported, otherwise, the emissions will be measured in average mode again and reported.






### 6.3 Typical Test Setup

Below 30MHz Test Setup



30M - 1GHz Test Setup






### 6.4 Test Result and Data

For 9KHz~30MHz

Test Mode	: Mode 2	Polarization	: X
Power	: AC 120V/60Hz	Frequency range	9KHz-150KHz




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	0.0307	20.63	55.91	76.54	117.86	-41.32	AVG
2	0.0643	20.73	37.71	58.44	111.44	-53.00	AVG

Note: Level = Reading + Factor  
 Margin = Level – Limit  
 Factor= Antenna Factor + Cable Loss - Amplifier Factor



Test Mode	: Mode 2	Polarization	: X
Power	: AC 120V/60Hz	Frequency range	: 150KHz-30MHz




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	0.3596	20.58	42.00	62.58	96.49	-33.91	AVG
2	0.5378	20.88	49.04	69.92	72.99	-3.07	QP
3	1.4256	20.68	37.92	58.60	64.52	-5.92	QP

Note: Level = Reading + Factor  
Margin = Level – Limit  
Factor= Antenna Factor + Cable Loss - Amplifier Factor



Test Mode	: Mode 2	Polarization	: Y
Power	: AC 120V/60Hz	Frequency range	: 9KHz-150KHz




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	0.0308	20.63	56.79	77.42	117.83	-40.41	AVG
2	0.0350	20.78	37.97	58.75	116.72	-57.97	AVG

Note: Level = Reading + Factor  
 Margin = Level – Limit  
 Factor= Antenna Factor + Cable Loss - Amplifier Factor



Test Mode	: Mode 2	Polarization	: Y
Power	: AC 120V/60Hz	Frequency range	: 150KHz-30MHz




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	0.3596	20.58	41.46	62.04	96.49	-34.45	AVG
2	0.5350	20.89	49.92	70.81	73.04	-2.23	QP

Note: Level = Reading + Factor  
 Margin = Level – Limit  
 Factor= Antenna Factor + Cable Loss - Amplifier Factor



Test Mode	: Mode 3	Polarization	: X
Power	: AC 120V/60Hz	Frequency range	: 9KHz-150KHz




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	0.0305	20.62	59.12	79.74	117.92	-38.18	AVG
2	0.1276	20.34	55.26	75.60	105.49	-29.89	AVG

Note: Level = Reading + Factor  
Margin = Level – Limit  
Factor= Antenna Factor + Cable Loss - Amplifier Factor



Test Mode	: Mode 3	Polarization	: X
Power	: AC 120V/60Hz	Frequency range	: 150KHz-30MHz




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	0.3830	20.63	40.01	60.64	95.94	-35.30	AVG
2	0.5376	20.88	50.64	68.92	73.00	-4.08	QP

Note: Level = Reading + Factor  
Margin = Level – Limit  
Factor= Antenna Factor + Cable Loss - Amplifier Factor



Test Mode	: Mode 3	Polarization	: Y
Power	: AC 120V/60Hz	Frequency range	9KHz-150KHz




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	0.0307	20.63	56.70	77.33	117.86	-40.53	AVG
2	0.1278	20.33	53.40	73.73	105.47	-31.74	AVG

Note: Level = Reading + Factor  
Margin = Level – Limit  
Factor= Antenna Factor + Cable Loss - Amplifier Factor





Test Mode	: Mode 3	Polarization	: Y
Power	: AC 120V/60Hz	Frequency range	: 150KHz-30MHz




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.
1	0.3831	20.63	33.66	54.29	95.94	-41.65	AVG
2	0.5378	20.88	49.36	70.24	72.99	-2.75	QP

Note: Level = Reading + Factor  
 Margin = Level – Limit  
 Factor= Antenna Factor + Cable Loss - Amplifier Factor



For 30MHz~1GHz

Test Mode	: Mode 2	Pol/Phase	: VERTICAL
Power	: AC 120V/60Hz		




No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	33.8800	-6.56	40.70	34.14	40.00	-5.86	QP	100	168
2	40.6699	-10.95	41.16	30.21	40.00	-9.79	peak	200	127
3	54.2500	-16.77	46.88	30.11	40.00	-9.89	peak	100	309
4	108.5700	-13.29	38.16	24.87	43.50	-18.63	peak	200	241
5	139.6100	-10.24	32.61	22.37	43.50	-21.13	peak	200	296
6	154.1600	-11.98	33.37	21.39	43.50	-22.11	peak	100	342

Note: Level = Reading + Factor  
 Margin = Level – Limit  
 Factor= Antenna Factor + Cable Loss - Amplifier Factor



Test Mode	: Mode 2	Pol/Phase	: Horizontal
Power	: AC 120V/60Hz		



No.	Frequency (MHz)	Factor (dB/m)	Reading (dBuV)	Level (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Det.	Height (cm)	Azimuth (deg)
1	33.8800	-6.56	31.81	25.25	40.00	-14.75	peak	200	167
2	109.5400	-13.09	36.14	23.05	43.50	-20.45	peak	200	298
3	118.2700	-11.11	33.70	22.59	43.50	-20.91	peak	100	223
4	143.4900	-10.75	33.65	22.90	43.50	-20.60	peak	200	104
5	185.2000	-12.14	33.20	21.06	43.50	-22.44	peak	100	316
6	255.0400	-11.31	35.16	23.85	46.00	-22.15	peak	200	348

Note: Level = Reading + Factor  
 Margin = Level – Limit  
 Factor= Antenna Factor + Cable Loss - Amplifier Factor



## 7. 20dB Bandwidth


### 7.1 Test Limit

None: for reporting purposed only.

### 7.2 Test Procedures

Intentional radiators operating under the alternative provisions to the general emission limits, as contained in §15.215, must be designed to ensure that 20dB bandwidth of the emission, or whatever bandwidth may otherwise be specified in the specific rule section under which the equipment operates is contained within the frequency band designated in the rule section under which the equipment is operated.


### 7.3 Typical Test Setup






### 7.4 Test Result and Data

Frequency (kHz)	20 dB bandwidth (kHz)
360KHz	0.049



Frequency (kHz)	20 dB bandwidth (kHz)
127.7KHz	0.049



----- End of the report -----