

RF TEST REPORT



Report No.: 15070823-FCC-R2

Supersede Report No.: N/A

Applicant	NEG TECHNOLOGY CO., LIMITED	
Product Name	Mobile Phone	
Model No.	F1009D	
Serial No.	N/A	
Test Standard	FCC Part 15.247: 2014, ANSI C63.10: 2013	
Test Date	September 10 to September 24, 2015	
Issue Date	September 29, 2015	
Test Result	<input checked="" type="checkbox"/> Pass	<input type="checkbox"/> Fail
Equipment complied with the specification	<input checked="" type="checkbox"/>	
Equipment did not comply with the specification	<input type="checkbox"/>	
Winnie.Zhang	David Huang	
Winnie Zhang Test Engineer	Checked By	
<p>This test report may be reproduced in full only Test result presented in this test report is applicable to the tested sample only</p>		

Issued by:

SIEMIC (SHENZHEN-CHINA) LABORATORIES

Zone A, Floor 1, Building 2 Wan Ye Long Technology Park

South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108

Phone: +86 0755 2601 4629801 Email: China@siemic.com.cn

Laboratories Introduction

SIEMIC, headquartered in the heart of Silicon Valley, with superior facilities in US and Asia, is one of the leading independent testing and certification facilities providing customers with one-stop shop services for Compliance Testing and Global Certifications.



In addition to testing and certification, SIEMIC provides initial design reviews and compliance management throughout a project. Our extensive experience with China, Asia Pacific, North America, European, and International compliance requirements, assures the fastest, most cost effective way to attain regulatory compliance for the global markets.

Accreditations for Conformity Assessment

Country/Region	Scope
USA	EMC, RF/Wireless, SAR, Telecom
Canada	EMC, RF/Wireless, SAR, Telecom
Taiwan	EMC, RF, Telecom, SAR, Safety
Hong Kong	RF/Wireless, SAR, Telecom
Australia	EMC, RF, Telecom, SAR, Safety
Korea	EMI, EMS, RF, SAR, Telecom, Safety
Japan	EMI, RF/Wireless, SAR, Telecom
Singapore	EMC, RF, SAR, Telecom
Europe	EMC, RF, SAR, Telecom, Safety

Test Report	15070823-FCC-R2
Page	3 of 58

This page has been left blank intentionally.

CONTENTS

1. REPORT REVISION HISTORY	5
2. CUSTOMER INFORMATION	5
3. TEST SITE INFORMATION.....	5
4. EQUIPMENT UNDER TEST (EUT) INFORMATION	6
5. TEST SUMMARY	8
6. MEASUREMENTS, EXAMINATION AND DERIVED RESULTS	9
6.1 ANTENNA REQUIREMENT.....	9
6.2 CHANNEL SEPARATION	10
6.3 20DB BANDWIDTH.....	14
6.4 PEAK OUTPUT POWER.....	18
6.5 NUMBER OF HOPPING CHANNEL.....	22
6.6 TIME OF OCCUPANCY (DWELL TIME)	24
6.7 BAND EDGE.....	28
6.8 AC POWER LINE CONDUCTED EMISSIONS.....	36
6.9 RADIATED SPURIOUS EMISSIONS	42
ANNEX A. TEST INSTRUMENT.....	47
ANNEX B. EUT AND TEST SETUP PHOTOGRAPHS.....	48
ANNEX C. TEST SETUP AND SUPPORTING EQUIPMENT.....	53
ANNEX D. USER MANUAL / BLOCK DIAGRAM / SCHEMATICS / PARTLIST	57
ANNEX E. DECLARATION OF SIMILARITY	58

1. Report Revision History

Report No.	Report Version	Description	Issue Date
15070823-FCC-R2	NONE	Original	September 29, 2015

2. Customer information

Applicant Name	NEG TECHNOLOGY CO., LIMITED
Applicant Add	Rm 1406, Block B, Jinsejiali, Jingtian south road, Futian district, Shenzhen, China
Manufacturer	NEG TECHNOLOGY CO., LIMITED
Manufacturer Add	Rm 1406, Block B, Jinsejiali, Jingtian south road, Futian district, Shenzhen, China

3. Test site information

Lab performing tests	SIEMIC (Shenzhen-China) LABORATORIES
Lab Address	Zone A, Floor 1, Building 2 Wan Ye Long Technology Park South Side of Zhoushi Road, Bao'an District, Shenzhen, Guangdong China 518108
FCC Test Site No.	718246
IC Test Site No.	4842E-1
Test Software	Radiated Emission Program-To Shenzhen v2.0

4. Equipment under Test (EUT) Information

Description of EUT:	Mobile Phone
Main Model:	F1009D
Serial Model:	N/A
Date EUT received:	September 09, 2015
Test Date(s):	September 10 to September 24, 2015
Equipment Category :	DSS
Antenna Gain:	GSM850:0.3dBi PCS1900:0.35dBi Bluetooth:0.1dBi
Type of Modulation:	GSM / GPRS: GMSK Bluetooth: GFSK, π /4DQPSK, 8DPSK
RF Operating Frequency (ies):	GSM850 TX: 824.2 ~ 848.8 MHz; RX: 869.2 ~ 893.8 MHz PCS1900 TX: 1850.2 ~ 1909.8 MHz; RX: 1930.2 ~ 1989.8 MHz Bluetooth: 2402-2480 MHz
Max. Output Power:	-0.982dBm
Number of Channels:	GSM 850: 124CH PCS1900: 299CH Bluetooth: 79CH

AC Adapter:

Model:F1009D

Input: AC 100-240V; 50/60Hz;150mA

Output: DC5.0V; 500mA

Input Power:

Battery:

Model:F1009D

Bateria Li-on:2.59Wh

Voltaje de carga limite:4.2V

Capacidad de bateria:700mAh

Trade Name : OWN

Port: Power Port, Earphone Port, USB Port

GPRS Multi-slot class 8/10/12

FCC ID: 2AAZ8-F1009D

5. Test Summary

The product was tested in accordance with the following specifications.

All testing has been performed according to below product classification:

FCC Rules	Description of Test	Result
§15.203	Antenna Requirement	Compliance
§15.247(a)(1)	Channel Separation	Compliance
§15.247(a)(1)	20 dB Bandwidth	Compliance
§15.247(b)(1)	Peak Output Power	Compliance
§15.247(a)(1)(iii)	Number of Hopping Channel	Compliance
§15.247(a)(1)(iii)	Time of Occupancy (Dwell Time)	Compliance
§15.247(d)	Band Edge	Compliance
§15.207(a)	AC Line Conducted Emissions	Compliance
§15.205, §15.209, §15.247(d)	Radiated Emissions	Compliance

Measurement Uncertainty

Emissions		
Test Item	Description	Uncertainty
Band Edge and Radiated Spurious Emissions	Confidence level of approximately 95% (in the case where distributions are normal), with a coverage factor of 2 (for EUTs < 0.5m X 0.5m X 0.5m)	+5.6dB/-4.5dB
-	-	-

6. Measurements, Examination And Derived Results

6.1 Antenna Requirement

Applicable Standard

According to § 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the user of a standard antenna jack or electrical connector is prohibited. The structure and application of the EUT were analyzed to determine compliance with section §15.203 of the rules. §15.203 state that the subject device must meet the following criteria:

- a. Antenna must be permanently attached to the unit.
- b. Antenna must use a unique type of connector to attach to the EUT.

Unit must be professionally installed, and installer shall be responsible for verifying that the correct antenna is employed with the unit.

And according to FCC 47 CFR section 15.247 (b), if the transmitting antennas of directional gain greater than 6dBi are used, the power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Antenna Connector Construction

The EUT has 2 antennas:

A permanently attached Monopole antenna for Bluetooth, the gain is 0.1dBi for Bluetooth.

A permanently attached PIFA antenna for GSM and UMTS, the gain is 0.3dBi for GSM850, 0.35dBi for PCS1900.


The antenna meets up with the ANTENNA REQUIREMENT.

Result: Compliance.

6.2 Channel Separation

Temperature	22°C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	September 21, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§ 15.247(a)(1)	a)	Channel Separation < 20dB BW and 20dB BW < 25KHz ; Channel Separation Limit=25KHz Chanel Separation < 20dB BW and 20dB BW > 25kHz ; Channel Separation Limit=2/3 20dB BW	<input checked="" type="checkbox"/>
Test Setup	 <p style="text-align: center;">Spectrum Analyzer EUT</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.</p> <p><u>Use the following spectrum analyzer settings:</u></p> <ul style="list-style-type: none"> - The EUT must have its hopping function enabled - Span = wide enough to capture the peaks of two adjacent channels - Resolution (or IF) Bandwidth (RBW) \geq 1% of the span - Video (or Average) Bandwidth (VBW) \geq RBW - Sweep = auto - Detector function = peak - Trace = max hold - Allow the trace to stabilize. Use the marker-delta function to determine the separation between the peaks of the adjacent channels. The limit is specified in one of the subparagraphs of this Section. Submit this plot. 		

Remark		
Result	<input checked="" type="checkbox"/> Pass	<input type="checkbox"/> Fail


Test Data Yes N/A
 Test Plot Yes (See below) N/A


Channel Separation measurement result

Type/ Modulation	CH	CH Freq (MHz)	CH Separation (MHz)	Limit (MHz)	Result
CH Separation GFSK	Low Channel	2402	1.002	0.681	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.978	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.941	Pass
	Adjacency Channel	2479			
CH Separation $\pi/4$ DQPSK	Low Channel	2402	1.002	0.885	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.002	0.896	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.890	Pass
	Adjacency Channel	2479			
CH Separation 8DPSK	Low Channel	2402	1.002	0.869	Pass
	Adjacency Channel	2403			
	Mid Channel	2440	1.005	0.887	Pass
	Adjacency Channel	2441			
	High Channel	2480	1.002	0.862	Pass
	Adjacency Channel	2479			

Test Plots

Channel Separation measurement result






6.3 20dB Bandwidth

Temperature	22°C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	September 21, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)	a)	Frequency hopping systems shall have hopping channel carrier frequencies separated by a minimum of 25 kHz or the 20 dB bandwidth of the hopping channel, whichever is greater.	<input checked="" type="checkbox"/>
Test Setup			
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.</p> <p><u>Use the following spectrum analyzer settings:</u></p> <ul style="list-style-type: none"> - Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hopping channel - RBW \geq 1% of the 20 dB bandwidth - VBW \geq RBW - Sweep = auto - Detector function = peak - Trace = max hold. - The EUT should be transmitting at its maximum data rate. Allow the trace to stabilize. Use the marker-to-peak function to set the marker to the peak of the emission. Use the marker-delta function to measure 20 dB down one side of the emission. Reset the marker-delta function, and move the marker to the other side of the emission, until it is (as close as possible to) even with the reference 		

	marker level. The marker-delta reading at this point is the 20 dB bandwidth of the emission. If this value varies with different modes of operation (e.g., data rate, modulation format, etc.), repeat this test for each variation. The limit is specified in one of the subparagraphs of this Section. Submit this plot(s).
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A


Test Plot Yes (See below) N/A


Measurement result

Modulation	CH	CH Freq (MHz)	20dB Bandwidth (MHz)	99% Occupied Bandwidth (MHz)
GFSK	Low	2402	1.022	0.8876
	Mid	2441	0.978	0.8892
	High	2480	0.941	0.8764
$\pi/4$ DQPSK	Low	2402	1.328	1.1785
	Mid	2441	1.344	1.1921
	High	2480	1.335	1.1914
8-DPSK	Low	2402	1.304	1.1888
	Mid	2441	1.331	1.1957
	High	2480	1.293	1.1791

Test Plots

20dB Bandwidth measurement result






6.4 Peak Output Power

Temperature	22°C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	September 21, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(b) (2)	a)	FHSS in 2400-2483.5MHz with \geq 75 channels: \leq 1 Watt	<input checked="" type="checkbox"/>
	b)	FHSS in 5725-5850MHz: \leq 1 Watt	<input type="checkbox"/>
	c)	For all other FHSS in the 2400-2483.5MHz band: \leq 0.125 Watt.	<input checked="" type="checkbox"/>
	d)	FHSS in 902-928MHz with \geq 50 channels: \leq 1 Watt	<input type="checkbox"/>
	e)	FHSS in 902-928MHz with \geq 25 & $<$ 50 channels: \leq 0.25 Watt	<input type="checkbox"/>
	f)	DSSS in 902-928MHz, 2400-2483.5MHz, 5725-5850MHz: \leq 1 Watt	<input type="checkbox"/>
Test Setup		 Spectrum Analyzer EUT	
Test Procedure		<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.</p> <p><u>Use the following spectrum analyzer settings:</u></p> <ul style="list-style-type: none"> - Span = approximately 5 times the 20 dB bandwidth, centered on a hopping channel - RBW > the 20 dB bandwidth of the emission being measured - VBW \geq RBW - Sweep = auto - Detector function = peak - Trace = max hold 	

	<ul style="list-style-type: none"> - Allow the trace to stabilize. - Use the marker-to-peak function to set the marker to the peak of the emission. The indicated level is the peak output power (see the note above regarding external attenuation and cable loss). The limit is specified in one of the subparagraphs of this Section. Submit this plot. A peak responding power meter may be used instead of a spectrum analyzer.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A


Test Plot Yes (See below) N/A


Peak Output Power measurement result

Type	Modulation	CH	Freq (MHz)	Conducted Power (dBm)	Limit (mW)	Result
Output power	GFSK	Low	2402	-2.819	125	Pass
		Mid	2441	-3.945	1000	Pass
		High	2480	-4.280	1000	Pass
	$\pi/4$ DQPSK	Low	2402	-1.267	125	Pass
		Mid	2441	-2.053	125	Pass
		High	2480	-3.531	125	Pass
	8-DPSK	Low	2402	-0.982	125	Pass
		Mid	2441	-1.642	125	Pass
		High	2480	-3.049	125	Pass

Test Plots

Output Power measurement result





6.5 Number of Hopping Channel

Temperature	22°C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	September 21, 2015
Tested By :	Winnie Zhang

Requirement(s):

Test Data Yes

Yes (See below) N/A

Test Plot  Yes (See below)  N/A

Number of Hopping Channel measurement result

Type	Modulation	Frequency Range	Number of Hopping Channel	Limit
Number of Hopping Channel	GFSK	2400-2483.5	79	15
	$\pi/4$ DQPSK	2400-2483.5	79	15
	8-DPSK	2400-2483.5	79	15

Test Plots


Number of Hopping Channels measurement result



6.6 Time of Occupancy (Dwell Time)

Temperature	22°C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	September 21, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable	
§15.247(a) (1)(iii)	a)	Dwell Time < 0.4s	<input checked="" type="checkbox"/>	
Test Setup				
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines.</p> <p><u>Use the following spectrum analyzer</u></p> <ul style="list-style-type: none"> - Span = zero span, centered on a hopping channel - RBW = 1 MHz - VBW \geq RBW - Sweep = as necessary to capture the entire dwell time per hopping channel - Detector function = peak - Trace = max hold - use the marker-delta function to determine the dwell time 			
Remark				
Result	<input checked="" type="checkbox"/>	Pass	<input type="checkbox"/>	Fail

Test Data Yes N/A

Test Plot Yes (See below) N/A


Dwell Time measurement result


Type	Modulation	CH	Pulse Width (ms)	Dwell Time (ms)	Limit (ms)	Result
Dwell Time	GFSK	Low	2.87	306.133	400	Pass
		Mid	2.88	307.200	400	Pass
		High	2.89	308.267	400	Pass
	$\pi/4$ DQPSK	Low	2.86	305.067	400	Pass
		Mid	2.88	307.200	400	Pass
		High	2.87	306.133	400	Pass
	8-DPSK	Low	2.87	306.133	400	Pass
		Mid	2.87	306.133	400	Pass
		High	2.87	306.133	400	Pass

 Note: Dwell time=Pulse Time (ms) \times (1600 \div 6 \div 79) \times 31.6

Test Plots

Dwell Time measurement result






6.7 Band Edge

Temperature	22°C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	September 21, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable
§15.247(a) (1)(iii)	a)	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits.	<input checked="" type="checkbox"/>
Test Setup	 <p>The diagram illustrates the test setup. An Ant. Tower is positioned 3m away from the EUT & Support Units, which are placed on a Turn Table. The Turn Table is mounted on a Ground Plane. A Test Receiver is connected to the system, with a 1-4m Variable cable connecting the Test Receiver to the Ant. Tower. The height of the EUT & Support Units is specified as 0.8/1.5m.</p>		
Test Procedure	<p>The test follows FCC Public Notice DA 00-705 Measurement Guidelines. Radiated Method Only</p> <ul style="list-style-type: none"> - 1. Check the calibration of the measuring instrument using either an internal calibrator or a known signal from an external generator. - 2. Position the EUT without connection to measurement instrument. Put it on the Rotated table and turn on the EUT and make it operate in transmitting mode. Then set it to Low Channel and High Channel within its operating range, 		





	<p>and make sure the instrument is operated in its linear range.</p> <ul style="list-style-type: none"> - 3. First, set both RBW and VBW of spectrum analyzer to 100 kHz with a convenient frequency span including 100kHz bandwidth from band edge, check the emission of EUT, if pass then set Spectrum Analyzer as below: <ul style="list-style-type: none"> a. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz. b. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz. c. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz. - 4. Measure the highest amplitude appearing on spectral display and set it as a reference level. Plot the graph with marking the highest point and edge frequency. - 5. Repeat above procedures until all measured frequencies were complete.
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail


Test Data Yes N/A



Test Plot Yes (See below) N/A


Test Plots

GFSK Mode:




 <p>Test Report: 15070823-FCC-R2 Page: 30 of 58</p> <p>Plot 1: GFSK Mode Left Side-PK. Test parameters: * Att 5 dB, * RBW 1 MHz, * VBW 3 MHz, Ref 102.0 dBμV, SWT 2.5ms. Frequency range: Start 2.31 GHz, Stop 2.44 GHz. Span: 40.0 MHz. Peak power: 53.53 dBμV at 2.40000000 GHz. Line limit: 74 dBμV. M1: 47.34 dBμV at 2.38019000 GHz. M2: 53.53 dBμV at 2.40000000 GHz. F1: 47.34 dBμV at 2.40000000 GHz. Tdf: 10 dBμV to 90 dBμV. 1Pk Max: 90 dBμV. Date: 24.SEP.2015 09:25:22.</p>	 <p>Test Report: 15070823-FCC-R2 Page: 30 of 58</p> <p>Plot 2: GFSK Mode Right Side-PK. Test parameters: * Att 5 dB, * RBW 1 MHz, * VBW 3 MHz, Ref 102.0 dBμV, SWT 2.5ms. Frequency range: Start 2.44 GHz, Stop 2.5 GHz. Span: 40.0 MHz. Peak power: 47.39 dBμV at 2.49174000 GHz. Line limit: 74 dBμV. M1: 47.39 dBμV at 2.49174000 GHz. M2: 47.39 dBμV at 2.49174000 GHz. F1: 47.39 dBμV at 2.49174000 GHz. Tdf: 10 dBμV to 90 dBμV. 1Pk Max: 90 dBμV. Date: 24.SEP.2015 09:23:38.</p>
<p>GFSK-Hopping Left Side-PK</p> <p>Note: F1 is frequency 2400MHz</p>	<p>GFSK-Hopping Right Side-PK</p> <p>Note: F1 is frequency 2483.5MHz</p>
<p>Note: (no need if PK value less than the AV limit)</p>	<p>Note: (no need if PK value less than the AV limit)</p>
<p>GFSK-Hopping Left Side-AV</p>	<p>GFSK-Hopping Right Side-AV</p>
 <p>Test Report: 15070823-FCC-R2 Page: 30 of 58</p> <p>Plot 3: GFSK Mode Left Side-AV. Test parameters: * Att 5 dB, * RBW 1 MHz, * VBW 3 MHz, Ref 102.0 dBμV, SWT 2.5ms. Frequency range: CF 2.39 GHz, Stop 2.44 GHz. Span: 40.0 MHz. Peak power: 57.29 dBμV at 2.40000000 GHz. Line limit: 74 dBμV. M1: 48.72 dBμV at 2.38928100 GHz. M2: 57.29 dBμV at 2.40000000 GHz. F1: 48.72 dBμV at 2.40000000 GHz. Tdf: 10 dBμV to 90 dBμV. 1Pk Max: 90 dBμV. Date: 24.SEP.2015 09:08:35.</p>	 <p>Test Report: 15070823-FCC-R2 Page: 30 of 58</p> <p>Plot 4: GFSK Mode Right Side-AV. Test parameters: * Att 5 dB, * RBW 1 MHz, * VBW 3 MHz, Ref 102.0 dBμV, SWT 2.5ms. Frequency range: CF 2.4835 GHz, Stop 2.5 GHz. Span: 40.0 MHz. Peak power: 47.56 dBμV at 2.486614000 GHz. Line limit: 74 dBμV. M1: 47.56 dBμV at 2.486614000 GHz. M2: 47.56 dBμV at 2.486614000 GHz. F1: 47.56 dBμV at 2.486614000 GHz. Tdf: 10 dBμV to 90 dBμV. 1Pk Max: 90 dBμV. Date: 24.SEP.2015 09:20:39.</p>
<p>GFSK-Left Side-PK</p> <p>Note: F1 is frequency 2400MHz</p>	<p>GFSK-Right Side-PK</p> <p>Note: F1 is frequency 2483.5MHz</p>




π/4 DQPSK Mode:

π/4 DQPSK-Hopping Left Side-PK
Note: F1 is frequency 2400MHz
π/4 DQPSK-Hopping Right Side-PK
Note: F1 is frequency 2483.5MHz




8-DPSK Mode:


 <p>RBW 1 MHz VBW 3 MHz Att 5 dB Ref 102.0 dBμV SWT 2.5ms</p> <p>M2[1] 61.30 dBμV 2.40000000 GHz</p> <p>1Pk Max</p> <p>Limit Check: Line Limit-L 74 Limit-L 74</p> <p>90 dBμV 80 dBμV 70 dBμV 60 dBμV 50 dBμV 40 dBμV 30 dBμV 20 dBμV 10 dBμV</p> <p>Tdf</p> <p>Start 2.31 GHz Stop 2.44 GHz</p> <p>Date: 24.SEP.2015 09:36:32</p>	 <p>RBW 1 MHz VBW 3 MHz Att 5 dB Ref 102.0 dBμV SWT 2.5ms</p> <p>M1[1] 46.87 dBμV 2.49228000 GHz</p> <p>1Pk Max</p> <p>Limit Check: Line Limit-R 74 Limit-R 74</p> <p>90 dBμV 80 dBμV 70 dBμV 60 dBμV 50 dBμV 40 dBμV 30 dBμV 20 dBμV 10 dBμV</p> <p>Tdf</p> <p>Start 2.44 GHz Stop 2.5 GHz</p> <p>Date: 24.SEP.2015 09:35:05</p>
<p>8DPSK-Hopping Left Side-PK</p> <p>Note: F1 is frequency 2400MHz</p>	<p>8DPSK-Hopping Right Side-PK</p> <p>Note: F1 is frequency 2483.5MHz</p>
 <p>RBW 1 MHz VBW 3 MHz Att 5 dB Ref 102.0 dBμV SWT 2.5ms</p> <p>M2[1] 51.59 dBμV 2.40000000 GHz</p> <p>1Av Max</p> <p>Limit Check: Line Limit-L 54 Limit-L 54</p> <p>90 dBμV 80 dBμV 70 dBμV 60 dBμV 50 dBμV 40 dBμV 30 dBμV 20 dBμV 10 dBμV</p> <p>Tdf</p> <p>Start 2.31 GHz Stop 2.44 GHz</p> <p>Date: 24.SEP.2015 09:38:00</p>	<p>Note: (no need if PK value less than the AV limit)</p>
<p>8DPSK-Hopping Left-AV</p>	<p>8DPSK-Hopping Right-AV</p>



6.8 AC Power Line Conducted Emissions

Temperature	22°C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	September 21, 2015
Tested By :	Winnie Zhang

Requirement(s):


Spec	Item	Requirement	Applicable														
47CFR§15.207, RSS210 (A8.1)	a)	<p>For Low-power radio-frequency devices that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 [mu]H/50 ohms line impedance stabilization network (LISN). The lower limit applies at the boundary between the frequencies ranges.</p> <table border="1"> <thead> <tr> <th rowspan="2">Frequency ranges (MHz)</th> <th colspan="2">Limit (dBμV)</th> </tr> <tr> <th>QP</th> <th>Average</th> </tr> </thead> <tbody> <tr> <td>0.15 ~ 0.5</td> <td>66 – 56</td> <td>56 – 46</td> </tr> <tr> <td>0.5 ~ 5</td> <td>56</td> <td>46</td> </tr> <tr> <td>5 ~ 30</td> <td>60</td> <td>50</td> </tr> </tbody> </table>	Frequency ranges (MHz)	Limit (dB μ V)		QP	Average	0.15 ~ 0.5	66 – 56	56 – 46	0.5 ~ 5	56	46	5 ~ 30	60	50	<input checked="" type="checkbox"/>
Frequency ranges (MHz)	Limit (dB μ V)																
	QP	Average															
0.15 ~ 0.5	66 – 56	56 – 46															
0.5 ~ 5	56	46															
5 ~ 30	60	50															
Test Setup	 <p>Note: 1. Support units were connected to second LISN. 2. Both of LISNs (AMN) are 80cm from EUT and at least 80cm from other units and other metal planes support units.</p>																
Procedure	<ol style="list-style-type: none"> The EUT and supporting equipment were set up in accordance with the requirements of the standard on top of a 1.5m x 1m x 0.8m high, non-metallic table. The power supply for the EUT was fed through a 50W/50mH EUT LISN, connected to filtered mains. The RF OUT of the EUT LISN was connected to the EMI test receiver via a low-loss 																

	coaxial cable. 4. All other supporting equipment were powered separately from another main supply. 5. The EUT was switched on and allowed to warm up to its normal operating condition. 6. A scan was made on the NEUTRAL line (for AC mains) or Earth line (for DC power) over the required frequency range using an EMI test receiver. 7. High peaks, relative to the limit line, The EMI test receiver was then tuned to the selected frequencies and the necessary measurements made with a receiver bandwidth setting of 10 kHz. 8. Step 7 was then repeated for the LIVE line (for AC mains) or DC line (for DC power).
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A

Test Plot Yes (See below) N/A

Test Mode: Bluetooth Mode




Test Data

Phase Line Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBuV)	Detector	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)
1	L1	0.2397	23.90	QP	10.03	33.93	62.11	-28.18
2	L1	0.2397	11.79	AVG	10.03	21.82	52.11	-30.29
3	L1	0.3957	32.11	QP	10.03	42.14	57.94	-15.80
4	L1	0.3957	19.12	AVG	10.03	29.15	47.94	-18.79
5	L1	0.4386	33.73	QP	10.03	43.76	57.09	-13.33
6	L1	0.4386	23.25	AVG	10.03	33.28	47.09	-13.81
7	L1	0.5283	39.53	QP	10.03	49.56	56.00	-6.44
8	L1	0.5283	30.76	AVG	10.03	40.79	46.00	-5.21
9	L1	0.5712	36.11	QP	10.03	46.14	56.00	-9.86
10	L1	0.5712	26.65	AVG	10.03	36.68	46.00	-9.32
11	L1	0.8793	28.08	QP	10.03	38.11	56.00	-17.89
12	L1	0.8793	15.22	AVG	10.03	25.25	46.00	-20.75

Test Mode: Bluetooth Mode




Test Data

Phase Neutral Plot at 120Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBuV)	Detector	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)
1	N	0.1900	16.96	QP	10.02	26.98	64.04	-37.06
2	N	0.1900	8.08	AVG	10.02	18.10	54.04	-35.94
3	N	0.4300	22.57	QP	10.02	32.59	57.25	-24.66
4	N	0.4300	7.65	AVG	10.02	17.67	47.25	-29.58
5	N	0.5300	32.20	QP	10.02	42.22	56.00	-13.78
6	N	0.5300	26.66	AVG	10.02	36.68	46.00	-9.32
7	N	0.5800	19.65	QP	10.02	29.67	56.00	-26.33
8	N	0.5800	15.21	AVG	10.02	25.23	46.00	-20.77
9	N	1.0600	23.27	QP	10.03	33.30	56.00	-22.70
10	N	1.0600	15.24	AVG	10.03	25.27	46.00	-20.73
11	N	1.4400	14.63	QP	10.03	24.66	56.00	-31.34
12	N	1.4400	6.53	AVG	10.03	16.56	46.00	-29.44


Test Mode: Bluetooth Mode



Test Data

Phase Line Plot at 240Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBuV)	Detector	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)
1	L1	0.2241	33.45	QP	10.03	43.48	62.67	-19.19
2	L1	0.2241	24.53	AVG	10.03	34.56	52.67	-18.11
3	L1	0.3645	32.26	QP	10.03	42.29	58.63	-16.34
4	L1	0.3645	23.87	AVG	10.03	33.90	48.63	-14.73
5	L1	0.5439	35.17	QP	10.03	45.20	56.00	-10.80
6	L1	0.5439	28.32	AVG	10.03	38.35	46.00	-7.65
7	L1	0.7272	30.48	QP	10.03	40.51	56.00	-15.49
8	L1	0.7272	21.64	AVG	10.03	31.67	46.00	-14.33
9	L1	1.1796	30.40	QP	10.03	40.43	56.00	-15.57
10	L1	1.1796	23.33	AVG	10.03	33.36	46.00	-12.64
11	L1	3.7293	25.57	QP	10.06	35.63	56.00	-20.37
12	L1	3.7293	12.85	AVG	10.06	22.91	46.00	-23.09


Test Mode: Bluetooth Mode

Test Data
Phase Neutral Plot at 240Vac, 60Hz

No.	P/L	Frequency (MHz)	Reading (dBuV)	Detector	Corrected (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)
1	N	0.3762	32.32	QP	10.02	42.34	58.36	-16.02
2	N	0.3762	19.50	AVG	10.02	29.52	48.36	-18.84
3	N	0.5517	39.24	QP	10.02	49.26	56.00	-6.74
4	N	0.5517	29.51	AVG	10.02	39.53	46.00	-6.47
5	N	0.7350	37.68	QP	10.02	47.70	56.00	-8.30
6	N	0.7350	27.16	AVG	10.02	37.18	46.00	-8.82
7	N	1.1952	29.29	QP	10.03	39.32	56.00	-16.68
8	N	1.1952	18.84	AVG	10.03	28.87	46.00	-17.13
9	N	2.0220	31.97	QP	10.04	42.01	56.00	-13.99
10	N	2.0220	20.11	AVG	10.04	30.15	46.00	-15.85
11	N	4.5912	26.97	QP	10.07	37.04	56.00	-18.96
12	N	4.5912	13.65	AVG	10.07	23.72	46.00	-22.28

6.9 Radiated Spurious Emissions

Temperature	22°C
Relative Humidity	54%
Atmospheric Pressure	1021mbar
Test date :	September 21, 2015
Tested By :	Winnie Zhang

Requirement(s):

Spec	Item	Requirement	Applicable										
47CFR§15.205, §15.209, §15.247(d)	a)	<p>Except higher limit as specified elsewhere in other section, the emissions from the low-power radio-frequency devices shall not exceed the field strength levels specified in the following table and the level of any unwanted emissions shall not exceed the level of the fundamental emission. The tighter limit applies at the band edges</p> <table border="1"> <thead> <tr> <th>Frequency range (MHz)</th> <th>Field Strength (μV/m)</th> </tr> </thead> <tbody> <tr> <td>30 – 88</td> <td>100</td> </tr> <tr> <td>88 – 216</td> <td>150</td> </tr> <tr> <td>216 – 960</td> <td>200</td> </tr> <tr> <td>Above 960</td> <td>500</td> </tr> </tbody> </table>	Frequency range (MHz)	Field Strength (μ V/m)	30 – 88	100	88 – 216	150	216 – 960	200	Above 960	500	<input checked="" type="checkbox"/>
Frequency range (MHz)	Field Strength (μ V/m)												
30 – 88	100												
88 – 216	150												
216 – 960	200												
Above 960	500												
Test Setup		 <p>The diagram illustrates the test setup for radiated spurious emissions. A 'Turn Table' is positioned on a 'Ground Plane'. A 'EUT & Support Units' is mounted on the turn table. A 'Test Receiver' is connected to the EUT. An 'Ant. Tower' is mounted on the turn table, with a '1-4m Variable' height adjustment. The distance between the EUT and the Ant. Tower is 3m.</p>											
Procedure		<ol style="list-style-type: none"> The EUT was switched on and allowed to warm up to its normal operating condition. The test was carried out at the selected frequency points obtained from the EUT characterization. Maximization of the emissions, was carried out by rotating the EUT, changing the antenna polarization, and adjusting the antenna height in the following manner: <ol style="list-style-type: none"> Vertical or horizontal polarization (whichever gave the higher emission level over a full rotation of the EUT) was chosen. 											


	<p>b. The EUT was then rotated to the direction that gave the maximum emission.</p> <p>c. Finally, the antenna height was adjusted to the height that gave the maximum emission.</p> <p>3. The resolution bandwidth and video bandwidth of test receiver/spectrum analyzer is 120 kHz for Quasiy Peak detection at frequency below 1GHz.</p> <p>4. The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and video bandwidth is 3MHz with Peak detection for Peak measurement at frequency above 1GHz.</p> <p>The resolution bandwidth of test receiver/spectrum analyzer is 1MHz and the video bandwidth is 10Hz with Peak detection for Average Measurement as below at frequency above 1GHz.</p> <p>5. Steps 2 and 3 were repeated for the next frequency point, until all selected frequency points were measured.</p>
Remark	
Result	<input checked="" type="checkbox"/> Pass <input type="checkbox"/> Fail

Test Data Yes N/A

Test Plot Yes (See below) N/A

Test Mode: Bluetooth Mode

Below 1GHz




Test Data

Horizontal Polarity Plot @3m

No.	P/L	Frequency	Reading	Detector	Corrected	Result	Limit	Margin	Height	Degree
		(MHz)	(dBuV/m)		(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	()
1	H	30.4238	26.17	peak	-0.58	25.59	40.00	-14.41	100	81
2	H	35.8747	28.59	peak	-4.58	24.01	40.00	-15.99	100	212
3	H	110.1816	25.85	peak	-8.99	16.86	43.50	-26.64	100	227
4	H	125.4457	25.88	peak	-7.64	18.24	43.50	-25.26	100	66
5	H	168.4138	28.73	peak	-8.97	19.76	43.50	-23.74	100	40
6	H	432.5457	27.55	peak	-3.50	24.05	46.00	-21.95	100	3

Below 1GHz



Test Data

Vertical Polarity Plot @3m

No.	P/L	Frequency (MHz)	Readin g (dBuV/ m)	Detector	Corrected (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree
1	V	37.5479	37.37	peak	-5.80	31.57	40.00	-8.43	100	184
2	V	55.2207	41.18	peak	-13.79	27.39	40.00	-12.61	100	229
3	V	99.8777	36.23	peak	-10.83	25.40	43.50	-18.10	100	203
4	V	169.0054	31.56	peak	-9.02	22.54	43.50	-20.96	100	199
5	V	259.2338	29.65	peak	-8.76	20.89	46.00	-25.11	100	203
6	V	570.6100	28.41	peak	-0.48	27.93	46.00	-18.07	100	203

Test Mode:	Transmitting Mode
------------	-------------------

Mode: GFSK (Worst Case)

Low Channel (2402 MHz)

Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4804	37.93	AV	V	33.83	6.86	31.72	46.9	54	-7.1
4804	37.27	AV	H	33.83	6.86	31.72	46.24	54	-7.76
4804	46.84	PK	V	33.83	6.86	31.72	55.81	74	-18.19
4804	45.71	PK	H	33.83	6.86	31.72	54.68	74	-19.32

Middle Channel (2441 MHz)

Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4882	37.86	AV	V	33.86	6.82	31.82	46.72	54	-7.28
4882	37.32	AV	H	33.86	6.82	31.82	46.18	54	-7.82
4882	46.69	PK	V	33.86	6.82	31.82	55.55	74	-18.45
4882	46.08	PK	H	33.86	6.82	31.82	54.94	74	-19.06

High Channel (2480 MHz)

Frequency (MHz)	S.A. Reading (dB μ V)	Detector (PK/AV)	Polarity (H/V)	Ant. Factor (dB/m)	Cable Loss (dB)	Pre-Amp. Gain (dB)	Cord. Amp. (dB μ V/m)	Limit (dB μ V/m)	Margin (dB)
4960	37.93	AV	V	33.9	6.76	31.92	46.67	54	-7.33
4960	37.45	AV	H	33.9	6.76	31.92	46.19	54	-7.81
4960	46.81	PK	V	33.9	6.76	31.92	55.55	74	-18.45
4960	46.36	PK	H	33.9	6.76	31.92	55.1	74	-18.9

Annex A. TEST INSTRUMENT

Instrument	Model	Serial #	Cal Date	Cal Due	In use
AC Line Conducted					
EMI test receiver	ESCS30	8471241027	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191106	09/26/2014	09/25/2015	<input checked="" type="checkbox"/>
Line Impedance	LI-125A	191107	09/26/2014	09/25/2015	<input checked="" type="checkbox"/>
LISN	ISN T800	34373	09/26/2014	09/25/2015	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/25/2014	09/24/2015	<input checked="" type="checkbox"/>
Transient Limiter	LIT-153	531118	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
RF conducted test					
Agilent ESA-E SERIES	E4407B	MY45108319	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Power Splitter	1#	1#	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
DC Power Supply	E3640A	MY40004013	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Radiated Emissions					
EMI test receiver	ESL6	100262	09/17/2015	09/16/2016	<input checked="" type="checkbox"/>
Positioning Controller	UC3000	MF780208282	11/20/2014	11/19/2015	<input checked="" type="checkbox"/>
OPT 010 AMPLIFIER (0.1-1300MHz)	8447E	2727A02430	09/01/2015	08/31/2016	<input checked="" type="checkbox"/>
Microwave Preamplifier (1 ~ 26.5GHz)	8449B	3008A02402	03/25/2015	03/24/2016	<input checked="" type="checkbox"/>
Bilog Antenna (30MHz~6GHz)	JB6	A110712	09/22/2014	09/21/2015	<input checked="" type="checkbox"/>
Double Ridge Horn Antenna (1 ~18GHz)	AH-118	71283	09/25/2014	09/24/2015	<input checked="" type="checkbox"/>
Universal Radio Communication Tester	CMU200	121393	09/26/2014	09/25/2015	<input checked="" type="checkbox"/>

Annex B. EUT And Test Setup Photographs

Annex B.i. Photograph: EUT External Photo





EUT - Top View



EUT - Bottom View





EUT - Left View




EUT - Right View

Annex B.ii. Photograph: EUT Internal Photo






Mainborad Without Shielding - Front View




LCD – Front View



LCD – Rear View



GSM/PCS Antenna View



BT - Antenna View

Annex B.iii. Photograph: Test Setup Photo



Conducted Emissions Test Setup Front View



Conducted Emissions Test Setup Side View



Radiated Spurious Emissions Test Setup Below 1GHz




Radiated Spurious Emissions Test Setup Above 1GHz


Annex C. TEST SETUP AND SUPPORTING EQUIPMENT

Annex C.ii. TEST SET UP BLOCK


Block Configuration Diagram for AC Line Conducted Emissions



Block Configuration Diagram for Radiated Emissions (Below 1GHz) .



Block Configuration Diagram for Radiated Emissions (Above 1GHz) .



Annex C. ii. SUPPORTING EQUIPMENT DESCRIPTION

The following is a description of supporting equipment and details of cables used with the EUT.

Manufacturer	Equipment Description	Model	Calibration Date	Calibration Due Date
N/A	N/A	N/A	N/A	N/A

Test Report	15070823-FCC-R2
Page	57 of 58

Annex D. User Manual / Block Diagram / Schematics / Partlist

Please see attachment

Annex E. DECLARATION OF SIMILARITY

N/A