

EMC Test Report**Application for FCC Grant of Equipment Authorization
Canada Certification****FCC Part 15 Subpart C****Model: ACCRX02**IC CERTIFICATION #: 11508A-ACCRX02
FCC ID: 2AAZF-ACCRX02APPLICANT: Intuitive Surgical Inc.
1266 Kifer Road Building 101
Sunnyvale, CA 94086TEST SITE(S): National Technical Systems
41039 Boyce Road.
Fremont, CA. 94538-2435

IC SITE REGISTRATION #: 2845B-3

PROJECT NUMBER: PR117602

REPORT DATE: July 17, 2020

FINAL TEST DATES: June 18, 22 and 23, 2020


TOTAL NUMBER OF PAGES: 40



This report and the information contained herein represent the results of testing of only those articles / products identified in this document and selected by the client. The tests were performed to specifications and/or procedures selected by the client. National Technical Systems (NTS) makes no representations expressed or implied that such testing fully demonstrates efficiency, performance, reliability, or any other characteristic of the articles being tested, or similar products. This report should not be relied upon as an endorsement or certification by NTS of the equipment tested, nor does it present any statement whatsoever as to its merchantability or fitness of the test article or similar products, for a particular purpose. This report shall not be reproduced except in full without written approval from NTS.


VALIDATING SIGNATORIES

PROGRAM MGR



David W. Bare
Chief Engineer

TECHNICAL REVIEWER:




David W. Bare
Chief Engineer

FINAL REPORT PREPARER:



David Guidotti
Senior Technical Writer

QUALITY ASSURANCE DELEGATE



Gary Izard
Quality Assurance Representative



REVISION HISTORY

Rev#	Date	Comments	Modified By
-	July 17, 2020	First release	

TABLE OF CONTENTS

COVER PAGE.....1

VALIDATING SIGNATORIES2

REVISION HISTORY3

TABLE OF CONTENTS4

SCOPE.....5

OBJECTIVE6

STATEMENT OF COMPLIANCE.....6

DEVIATIONS FROM THE STANDARDS.....6

TEST RESULTS SUMMARY7

 MEASUREMENT UNCERTAINTIES.....7

EQUIPMENT UNDER TEST (EUT) DETAILS.....8

 GENERAL.....8

 ANTENNA SYSTEM8

 ENCLOSURE.....8

 MODIFICATIONS.....8

 SUPPORT EQUIPMENT.....8

 EUT INTERFACE PORTS9

 EUT OPERATION.....9

TEST SITE.....10

 GENERAL INFORMATION.....10

 CONDUCTED EMISSIONS CONSIDERATIONS10

 RADIATED EMISSIONS CONSIDERATIONS10

MEASUREMENT INSTRUMENTATION11

 RECEIVER SYSTEM.....11

 INSTRUMENT CONTROL COMPUTER.....11

 LINE IMPEDANCE STABILIZATION NETWORK (LISN).....11

 FILTERS/ATTENUATORS.....12

 ANTENNAS.....12

 ANTENNA MAST AND EQUIPMENT TURNTABLE.....12

 INSTRUMENT CALIBRATION.....12

TEST PROCEDURES13

 EUT AND CABLE PLACEMENT.....13

 CONDUCTED EMISSIONS.....13

 RADIATED EMISSIONS.....13

 BANDWIDTH MEASUREMENTS.....17

 SPECIFICATION LIMITS AND SAMPLE CALCULATIONS.....18

 CONDUCTED EMISSIONS SPECIFICATION LIMITS: FCC 15.207; RSS GEN.....18

 GENERAL TRANSMITTER RADIATED EMISSIONS SPECIFICATION LIMITS.....18

 SAMPLE CALCULATIONS - CONDUCTED EMISSIONS.....19

 SAMPLE CALCULATIONS - RADIATED EMISSIONS.....19

 SAMPLE CALCULATIONS - FIELD STRENGTH TO EIRP CONVERSION.....20

APPENDIX A TEST EQUIPMENT CALIBRATION DATA21

APPENDIX B TEST DATA22

END OF REPORT40

SCOPE

An electromagnetic emissions test has been performed on the Intuitive Surgical Inc. model ACCRX02, pursuant to the following rules:

RSS-GEN Issue 5 “General Requirements for Compliance of Radio Apparatus”
RSS 210 Issue 8 “Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment”
FCC Part 15 Subpart C

Conducted and radiated emissions data has been collected, reduced, and analyzed within this report in accordance with measurement guidelines set forth in the following reference standards and as outlined in National Technical Systems test procedures:

ANSI C63.10-2013

The intentional radiator above has been tested in a simulated typical installation to demonstrate compliance with the relevant Industry Canada performance and procedural standards.

Final system data was gathered in a mode that tended to maximize emissions by varying orientation of EUT, orientation of power and I/O cabling, antenna search height, and antenna polarization.

Every practical effort was made to perform an impartial test using appropriate test equipment of known calibration. All pertinent factors have been applied to reach the determination of compliance.

National Technical Systems is accredited by the A2LA, certificate number 0214.26, to perform the test(s) listed in this report, except where noted otherwise.

OBJECTIVE

The primary objective of the manufacturer is compliance with the regulations outlined in the previous section.

Prior to marketing in the USA, all unlicensed transmitters and transceivers require certification. Receive-only devices operating between 30 MHz and 960 MHz are subject to either certification or a manufacturer's declaration of conformity, with all other receive-only devices exempt from the technical requirements.

Prior to marketing in Canada, Class I transmitters, receivers and transceivers require certification. Class II devices are required to meet the appropriate technical requirements but are exempt from certification requirements.

Certification is a procedure where the manufacturer submits test data and technical information to a certification body and receives a certificate or grant of equipment authorization upon successful completion of the certification body's review of the submitted documents. Once the equipment authorization has been obtained, the label indicating compliance must be attached to all identical units, which are subsequently manufactured.

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product which may result in increased emissions should be checked to ensure compliance has been maintained (i.e., printed circuit board layout changes, different line filter, different power supply, harnessing or I/O cable changes, etc.).

STATEMENT OF COMPLIANCE

The tested sample of Intuitive Surgical Inc. model ACCRX02 complied with the requirements of the following regulations:

- RSS-GEN Issue 5 "General Requirements for Compliance of Radio Apparatus"
- RSS 210 Issue 8 "Low-power Licence-exempt Radiocommunication Devices (All Frequency Bands): Category I Equipment"
- FCC Part 15 Subpart C

Maintenance of compliance is the responsibility of the manufacturer. Any modifications to the product should be assessed to determine their potential impact on the compliance status of the device with respect to the standards detailed in this test report.

The test results recorded herein are based on a single type test of Intuitive Surgical Inc. model ACCRX02 and therefore apply only to the tested sample. The sample was selected and prepared by Tony Permsombut of Intuitive Surgical Inc..

DEVIATIONS FROM THE STANDARDS

No deviations were made from the published requirements listed in the scope of this report.

TEST RESULTS SUMMARY

FCC Rule Part	RSS Rule Part	Description	Measured Value / Comments	Limit / Requirement	Result
15.225	RSS 210 B.6	Transmitter Fundamental Signal Emissions, 13.56 MHz	8.80 dB μ V/m @ 13.563 MHz (-75.2 dB)	Refer to table in limits section	Complies
15.209	RSS-GEN Table 5 and 6	Transmitter Radiated Spurious Emissions, 10 - 150 MHz	33.5 dB μ V/m @ 47.38 MHz (-6.5 dB)	Refer to table in limits section	Complies
15.225	RSS 210 B.6	Frequency Stability	13 ppm	Less than 100 ppm	Complies

GENERAL REQUIREMENTS APPLICABLE TO ALL BANDS

FCC Rule Part	RSS Rule part	Description	Measured Value / Comments	Limit / Requirement	Result (margin)
15.203	-	RF Connector	Integral Antenna	Unique or integral antenna required	Complies
15.407 (b) (6)	RSS-Gen Table 4	AC Conducted Emissions	46.8 dB μ V @ 0.848 MHz (-9.2 dB)	Refer to page 18	Complies
	RSS 102	RF Exposure Requirements	Refer to RSS 102 exemption declaration.	Refer to RSS 102	Complies
-	RSS-Gen 8.4	User Manual		Statement for all products	Complies
-	RSP-100 RSS-Gen 6.7	Occupied Bandwidth	11 Hz	Information only	N/A

MEASUREMENT UNCERTAINTIES

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level and were calculated in accordance with UKAS document LAB 34.

Measurement Type	Measurement Unit	Frequency Range	Expanded Uncertainty
Radiated emission (field strength)	dB μ V/m	25 to 1000 MHz	\pm 3.6 dB
		1000 to 40000 MHz	\pm 6.0 dB
Conducted Emissions (AC Power)	dB μ V	0.15 to 30 MHz	\pm 2.4 dB

EQUIPMENT UNDER TEST (EUT) DETAILS

GENERAL

The Intuitive Surgical Inc. model ACCRX02 is a RFID 13.56MHz transceiver module for use in an Endoscopic Instrument Control System, intended to assist in the control of endoscopic instruments. Since the EUT would be installed in an Endoscopic system cart during operation, the EUT was treated as tabletop equipment during testing to simulate the end-user environment. The electrical rating of the EUT is 3.3 Volts. The electrical rating of the Endoscopic system cart is 100-230V, 50/60Hz, 12A.

The sample was received on June 5, 2020 and tested on June 18, 22 and 23, 2020. The EUT consisted of the following component(s):

Company	Model	Description	Serial Number	FCC ID
Intuitive Surgical, Inc.	ACCRX02	RFID Module	CT20162141	2AAZF-ACCRX02

ANTENNA SYSTEM

The antenna system consists of an integral loop.

ENCLOSURE

The EUT does not have an enclosure. It is intended to be installed in an Endoscopic system cart.

MODIFICATIONS

No modifications were made to the EUT during the time the product was at NTS Silicon Valley.

SUPPORT EQUIPMENT

The following equipment was used as support equipment for testing:

Company	Model	Description	Serial Number	FCC ID
Dell	Precision5530	Laptop	CGRY5Y2	-
Intuitive Surgical	RPUSBUART-02	USB-UART Adapter	P115310346	-

No remote support equipment was used during testing.

EUT INTERFACE PORTS

The I/O cabling configuration during testing was as follows:

EUT

Port	Connected To	Cable(s)		
		Description	Shielded or Unshielded	Length(m)
Power/Serial	USB-UR Adapter	Flat cable	Unshielded	0.1

Additional on Support Equipment

Port	Connected To	Cable(s)		
		Description	Shielded or Unshielded	Length(m)
USB-UR	Laptop	Multiwire	Shielded	1.8

EUT OPERATION

During emissions testing the EUT was commanded to transmit continuously at rated power.

TEST SITE

GENERAL INFORMATION

Final test measurements were taken at the test sites listed below. Pursuant to section 2.948 of the FCC's Rules and section 6.2 of RSS-GEN, NTS has been recognized as an accredited test laboratory by the Commission and Innovation, Science and Economic Development Canada. A description of the facilities employed for testing is maintained by NTS.

Site	Company / Registration Numbers		Location
	FCC	Canada	
Chamber 3	US1031	2845B (Wireless Test Lab #US0027)	41039 Boyce Road Fremont, CA 94538-2435

ANSI C63.4 recommends that ambient noise at the test site be at least 6 dB below the allowable limits. Ambient levels are below this requirement. The test site(s) contain separate areas for radiated and conducted emissions testing. Results from testing performed in this chamber have been correlated with results from an open area test site. Considerable engineering effort has been expended to ensure that the facilities conform to all pertinent requirements of ANSI C63.4.

CONDUCTED EMISSIONS CONSIDERATIONS

Conducted emissions testing is performed in conformance with ANSI C63.10. Measurements are made with the EUT connected to the public power network through a nominal, standardized RF impedance, which is provided by a line impedance stabilization network, known as a LISN. A LISN is inserted in series with each current-carrying conductor in the EUT power cord.

RADIATED EMISSIONS CONSIDERATIONS

The FCC has determined that radiation measurements made in a shielded enclosure are not suitable for determining levels of radiated emissions. Radiated measurements are performed in an open field environment or in a semi-anechoic chamber. The test sites are maintained free of conductive objects within the CISPR defined elliptical area incorporated in ANSI C63.4 guidelines and meet the Normalized Site Attenuation (NSA) requirements of ANSI C63.4.

MEASUREMENT INSTRUMENTATION

RECEIVER SYSTEM

An EMI receiver as specified in CISPR 16-1-1 is used for emissions measurements. The receivers used can measure over the frequency range of 9 kHz up to 2000 MHz. These receivers allow both ease of measurement and high accuracy to be achieved. The receivers have Peak, Average, and CISPR (Quasi-peak) detectors built into their design so no external adapters are necessary. The receiver automatically sets the required bandwidth for the CISPR detector used during measurements. If the repetition frequency of the signal being measured is below 20Hz, peak measurements are made in lieu of Quasi-Peak measurements.

For measurements above the frequency range of the receivers, a spectrum analyzer is utilized because it provides visibility of the entire spectrum along with the precision and versatility required to support engineering analysis. Average measurements above 1000MHz are performed on the spectrum analyzer using the linear-average method with a resolution bandwidth of 1 MHz and a video bandwidth of 10 Hz, unless the signal is pulsed in which case the average (or video) bandwidth of the measuring instrument is reduced to onset of pulse desensitization and then increased.

INSTRUMENT CONTROL COMPUTER

Software is used to view and convert receiver measurements to the field strength at an antenna or voltage developed at the LISN measurement port, which is then compared directly with the appropriate specification limit. This provides faster, more accurate readings by performing the conversions described under Sample Calculations within the Test Procedures section of this report. Results are printed in a graphic and/or tabular format, as appropriate. A personal computer is used to record all measurements made with the receivers. The software used for radiated and conducted emissions measurements is NTS EMI Test Software (rev 2.10)

LINE IMPEDANCE STABILIZATION NETWORK (LISN)

Line conducted measurements utilize a fifty microhenry Line Impedance Stabilization Network as the monitoring point. The LISN used also contains a 250 uH CISPR adapter. This network provides for calibrated radio frequency noise measurements by the design of the internal low pass and high pass filters on the EUT and measurement ports, respectively.

FILTERS/ATTENUATORS

External filters and precision attenuators are often connected between the receiving antenna or LISN and the receiver. This eliminates saturation effects and non-linear operation due to high amplitude transient events.

ANTENNAS

A loop antenna is used below 30 MHz. For the measurement range 30 MHz to 1000 MHz either a combination of a biconical antenna and a log periodic or a bi-log antenna is used. Above 1000 MHz, horn antennas are used. The antenna calibration factors to convert the received voltage to an electric field strength are included with appropriate cable loss and amplifier gain factors to determine an overall site factor, which is then programmed into the test receivers or incorporated into the test software.

ANTENNA MAST AND EQUIPMENT TURNTABLE

The antennas used to measure the radiated electric field strength are mounted on a non-conductive antenna mast equipped with a motor-drive to vary the antenna height. Measurements below 30 MHz are made with the loop antenna at a fixed height of 1m above the ground plane.

ANSI C63.10 specifies that the test height above ground for table mounted devices shall be 80 centimeters for testing below 1 GHz and 1.5m for testing above 1 GHz. Floor mounted equipment shall be placed on the ground plane if the device is normally used on a conductive floor or separated from the ground plane by insulating material from 3 to 12 mm if the device is normally used on a non-conductive floor as specified in ANSI C63.4. During radiated measurements, the EUT is positioned on a motorized turntable in conformance with this requirement.

INSTRUMENT CALIBRATION

All test equipment is regularly checked to ensure that performance is maintained in accordance with the manufacturer's specifications. All antennas are calibrated at regular intervals with respect to tuned half-wave dipoles. An exhibit of this report contains the list of test equipment used and calibration information.

TEST PROCEDURES

EUT AND CABLE PLACEMENT

The regulations require that interconnecting cables be connected to the available ports of the unit and that the placement of the unit and the attached cables simulate the worst case orientation that can be expected from a typical installation, so far as practicable. To this end, the position of the unit and associated cabling is varied within the guidelines of ANSI C63.10, and the worst-case orientation is used for final measurements.

CONDUCTED EMISSIONS

Conducted emissions are measured at the plug end of the power cord supplied with the EUT. Excess power cord length is wrapped in a bundle between 30 and 40 centimeters in length near the center of the cord. Preliminary measurements are made to determine the highest amplitude emission relative to the specification limit for all the modes of operation. Placement of system components and varying of cable positions are performed in each mode. A final peak mode scan is then performed in the position and mode for which the highest emission was noted on all current carrying conductors of the power cord.




Figure 1 Typical Conducted Emissions Test Configuration


RADIATED EMISSIONS

A preliminary scan of the radiated emissions is performed in which all significant EUT frequencies are identified with the system in a nominal configuration. At least two scans are performed, one scan for each antenna polarization (horizontal and vertical; loop parallel and perpendicular to the EUT). During the preliminary scans, the EUT is rotated through 360°, the antenna height is varied (for measurements above 30 MHz) and cable positions are varied to determine the highest emission relative to the limit. Preliminary scans may be performed in a fully anechoic chamber for the purposes of identifying the frequencies of the highest emissions from the EUT.


A speaker is provided in the receiver to aid in discriminating between EUT and ambient emissions. Other methods used during the preliminary scan for EUT emissions involve scanning with near field magnetic loops, monitoring I/O cables with RF current clamps, and cycling power to the EUT.

Final maximization is a phase in which the highest amplitude emissions identified in the spectral search are viewed while the EUT azimuth angle is varied from 0 to 360 degrees relative to the receiving antenna. The azimuth, which results in the highest emission is then maintained while varying the antenna height from one to four meters (for measurements above 30 MHz, measurements below 30 MHz are made with the loop antenna at a fixed height of 1m). The result is the identification of the highest amplitude for each of the highest peaks. Each recorded level is corrected in the receiver using appropriate factors for cables, connectors, antennas, and preamplifier gain.


When testing above 18 GHz, the receive antenna is located at 1 meter from the EUT and the antenna height is restricted to a maximum of 2.5 meters.




Typical Test Configuration for Radiated Field Strength Measurements



The ground plane extends beyond the ellipse defined in CISPR 16 / CISPR 22 / ANSI C63.4 and is large enough to accommodate test distances (d) of 3m and 10m. Refer to the test data tables for the actual measurement distance.




Test Configuration for Radiated Field Strength Measurements
OATS- Plan and Side Views



The anechoic materials on the walls and ceiling ensure compliance with the normalized site attenuation requirements of CISPR 16 / CISPR 22 / ANSI C63.4 for an alternate test site at the measurement distances used.

Floor-standing equipment is placed on the floor with insulating supports between the unit and the ground plane.



Test Configuration for Radiated Field Strength Measurements
Semi-Anechoic Chamber, Plan and Side Views

BANDWIDTH MEASUREMENTS

The 6dB, 20dB, 26dB and/or 99% signal bandwidth are measured using the bandwidths recommended by ANSI C63.10 and RSS GEN.

SPECIFICATION LIMITS AND SAMPLE CALCULATIONS

The limits for conducted emissions are given in units of microvolts, and the limits for radiated emissions are given in units of microvolts per meter at a specified test distance. Data is measured in the logarithmic form of decibels relative to one microvolt, or dB microvolts (dBuV). For radiated emissions, the measured data is converted to the field strength at the antenna in dB microvolts per meter (dBuV/m). The results are then converted to the linear forms of uV and uV/m for comparison to published specifications.

For reference, converting the specification limits from linear to decibel form is accomplished by taking the base ten logarithm, then multiplying by 20. These limits in both linear and logarithmic form are as follows:

CONDUCTED EMISSIONS SPECIFICATION LIMITS: FCC 15.207; RSS GEN

The table below shows the limits for the emissions on the AC power line from an intentional radiator and a receiver.

Frequency (MHz)	Average Limit (dBuV)	Quasi Peak Limit (dBuV)
0.150 to 0.500	Linear decrease on logarithmic frequency axis between 56.0 and 46.0	Linear decrease on logarithmic frequency axis between 66.0 and 56.0
0.500 to 5.000	46.0	56.0
5.000 to 30.000	50.0	60.0

GENERAL TRANSMITTER RADIATED EMISSIONS SPECIFICATION LIMITS

The table below shows the limits for the spurious emissions from transmitters that fall in restricted bands¹.

Frequency Range (MHz)	Limit (uV/m)	Limit (dBuV/m @ 3m)
0.009-0.490	$2400/F_{\text{KHz}} @ 300\text{m}$	$67.6-20*\log_{10}(F_{\text{KHz}}) @ 300\text{m}$
0.490-1.705	$24000/F_{\text{KHz}} @ 30\text{m}$	$87.6-20*\log_{10}(F_{\text{KHz}}) @ 30\text{m}$
1.705 to 30	30 @ 30m	29.5 @ 30m
30 to 88	100 @ 3m	40 @ 3m
88 to 216	150 @ 3m	43.5 @ 3m
216 to 960	200 @ 3m	46.0 @ 3m
Above 960	500 @ 3m	54.0 @ 3m

¹ The restricted bands are detailed in FCC 15.205 and RSS-Gen Table 7

SAMPLE CALCULATIONS - CONDUCTED EMISSIONS

Receiver readings are compared directly to the conducted emissions specification limit (decibel form) as follows:

$$R_r - S = M$$

where:

R_r = Receiver Reading in dBuV

S = Specification Limit in dBuV

M = Margin to Specification in +/- dB

SAMPLE CALCULATIONS - RADIATED EMISSIONS

Receiver readings are compared directly to the specification limit (decibel form). The receiver internally corrects for cable loss, preamplifier gain, and antenna factor. The calculations are in the reverse direction of the actual signal flow, thus cable loss is added and the amplifier gain is subtracted. The Antenna Factor converts the voltage at the antenna coaxial connector to the field strength at the antenna elements.

A distance factor, when used for electric field measurements above 30MHz, is calculated by using the following formula:

$$F_d = 20 * \text{LOG}_{10} (D_m/D_s)$$

where:

F_d = Distance Factor in dB

D_m = Measurement Distance in meters

D_s = Specification Distance in meters

For electric field measurements below 30MHz the extrapolation factor is either determined by making measurements at multiple distances or a theoretical value is calculated using the formula:

$$F_d = 40 * \text{LOG}_{10} (D_m/D_s)$$

Measurement Distance is the distance at which the measurements were taken and Specification Distance is the distance at which the specification limits are based. The antenna factor converts the voltage at the antenna coaxial connector to the field strength at the antenna elements.

The margin of a given emission peak relative to the limit is calculated as follows:

$$R_c = R_r + F_d$$

and

$$M = R_c - L_s$$

where:

R_r = Receiver Reading in dBuV/m

F_d = Distance Factor in dB

R_c = Corrected Reading in dBuV/m

L_s = Specification Limit in dBuV/m

M = Margin in dB Relative to Spec

SAMPLE CALCULATIONS - FIELD STRENGTH TO EIRP CONVERSION

Where the radiated electric field strength is expressed in terms of the equivalent isotropic radiated power (eirp), or where a field strength measurement of output power is made in lieu of a direct measurement, the following formula is used to convert between eirp and field strength at a distance of d (meters) from the equipment under test:

$$E = \frac{1000000 \sqrt{30 P}}{d} \text{ microvolts per meter}$$

where P is the eirp (Watts)

For a measurement at 3m the conversion from a logarithmic value for field strength (dBuV/m) to an eirp power (dBm) is -95.3dB.

Appendix A Test Equipment Calibration Data

<u>Manufacturer</u>	<u>Description</u>	<u>Model</u>	<u>Asset #</u>	<u>Calibrated</u>	<u>Cal Due</u>
Conducted Emissions - AC Power Ports, 18-Jun-20					
EMCO	LISN, 10 kHz-100 MHz	3825/2	WC064399	7/24/2019	7/24/2020
Rohde & Schwarz	Pulse Limiter	ESH3 Z2	WC064445	12/2/2019	12/2/2020
Rohde & Schwarz	EMI Test Receiver, 20 Hz-7 GHz	ESIB7	WC064455	2/11/2020	2/11/2021
Radiated Emissions, 10 - 30 MHz, 18-Jun-20					
Rhode & Schwarz	Loop Antenna	HFH2-Z2	WC062457	1/23/2020	1/23/2022
Rohde & Schwarz	EMI Test Receiver, 20 Hz-7 GHz	ESIB7	WC064455	2/11/2020	2/11/2021
Radiated Emissions, 30 - 150 MHz, 18-Jun-20					
Rohde & Schwarz	EMI Test Receiver, 20 Hz-7 GHz	ESIB7	WC064455	2/11/2020	2/11/2021
Sunol Sciences	Biconilog, 30-3000 MHz	JB3	WC064536	10/24/2018	1/9/2021
Com-Power	RF Preampfier	PAM-103	WC072429	10/25/2019	10/25/2020
Bandwidth, 22-Jun-20					
National Technical Systems	NTS Capture Analyzer Software (rev 4.0)	N/A	WC022706	N/A	
Rhode & Schwarz	Loop Antenna	HFH2-Z2	WC062457	1/23/2020	1/23/2022
Rohde & Schwarz	EMI Test Receiver, 20 Hz-7 GHz	ESIB7	WC064455	2/11/2020	2/11/2021
Radio Antenna Port (Power and Spurious Emissions), 23-Jun-20					
Agilent Technologies	PSA Spectrum Analyzer	E4446A	WC055650	7/18/2019	7/18/2020
Watlow	Environmental Chamber Controller	F4DH-CCCC-21RG	WC066185	5/8/2019	6/24/2020
Watlow	Limit Controller	Limit 97	WC071533	N/A	
Fluke	Digital Multimeter	87v	WC072501	3/5/2020	3/5/2021
Frequency Stability, 23-Jun-20					
Agilent Technologies	PSA Spectrum Analyzer	E4446A	WC055650	7/18/2019	7/18/2020
Watlow	Environmental Chamber Controller	F4DH-CCCC-21RG	WC066185	5/8/2019	6/24/2020
Watlow	Limit Controller	Limit 97	WC071533	N/A	

Appendix B Test Data

TL117602-RANA Pages 23 – 39



EMC Test Data

Client:	Intuitive Surgical, Inc.	PR Number:	PR117602
Product:	ACCRX02	T-Log Number:	TL117602-RANA
System Configuration:	IS4000	Project Manager:	Deepa Shetty
Contact:	Tony Permsonbut	Project Engineer:	David Bare
Emissions Standard(s):	FCC Part 15.225, RSS-210 B.6	Class:	-
Immunity Standard(s):	-	Environment:	Radio

EMC Test Data

For The

Intuitive Surgical, Inc.

Product

ACCRX02

Date of Last Test: 6/23/2020



EMC Test Data

Client:	Intuitive Surgical, Inc.	PR Number:	PR117602
Model:	ACCRX02	T-Log Number:	TL117602-RANA
Contact:	Tony Permsonbut	Project Manager:	Deepa Shetty
Standard:	FCC Part 15.225, RSS-210 B.6	Project Engineer:	David Bare
		Class:	-

Conducted Emissions

(NTS Silicon Valley, Fremont Facility, Semi-Anechoic Chamber)

Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

Date of Test: 6/18/2020	Config. Used: 1
Test Engineer: Rafael Varelas	Config Change: None
Test Location: Fremont Chamber #3	Host Voltage: 120V/60Hz

General Test Configuration

For tabletop equipment, the EUT was located on a wooden table inside the semi-anechoic chamber, 40 cm from a vertical coupling plane and 80cm from the LISN. A second LISN was used for all local support equipment. Remote support equipment was located outside of the semi-anechoic chamber. Any cables running to remote support equipment where routed through metal conduit and when possible passed through a ferrite clamp upon exiting the chamber.

Ambient Conditions:	Temperature:	23.8 °C
	Rel. Humidity:	37 %

Summary of Results

Run #	Test Performed	Limit	Result	Margin
1	CE, AC Power, 120V/60Hz	15.207	Pass	46.8 dBµV @ 0.848 MHz (-9.2 dB)

Modifications Made During Testing

No modifications were made to the EUT during testing

Deviations From The Standard



No deviations were made from the requirements of the standard.



EMC Test Data

Client: Intuitive Surgical, Inc.	PR Number: PR117602
Model: ACCRX02	T-Log Number: TL117602-RANA
Contact: Tony Permsonbut	Project Manager: Deepa Shetty
Standard: FCC Part 15.225, RSS-210 B.6	Project Engineer: David Bare
	Class: -

Run #1: AC Power Port Conducted Emissions, 0.15 - 30MHz, 120V/60Hz
RFID in Transmit mode





EMC Test Data

Client:	Intuitive Surgical, Inc.	PR Number:	PR117602
Model:	ACCRX02	T-Log Number:	TL117602-RANA
Contact:	Tony Permsonbut	Project Manager:	Deepa Shetty
Standard:	FCC Part 15.225, RSS-210 B.6	Project Engineer:	David Bare
		Class:	-

Preliminary peak readings captured during pre-scan (peak readings vs. average limit)

Frequency MHz	Level dB μ V	AC Line	FCC 15.207		Detector QP/Ave	Comments
			Limit	Margin		
0.163	50.4	Line	55.3	-4.9	Peak	
0.244	50.6	Line	52.0	-1.4	Peak	
0.372	44.5	Line	48.5	-4.0	Peak	
0.620	47.0	Line	46.0	1.0	Peak	
0.867	47.6	Line	46.0	1.6	Peak	
1.107	47.6	Line	46.0	1.6	Peak	
1.330	47.5	Line	46.0	1.5	Peak	
2.102	47.0	Line	46.0	1.0	Peak	
13.560	46.4	Line	50.0	-3.6	Peak	RFID
27.121	41.9	Line	50.0	-8.1	Peak	RFID
0.217	50.6	Neutral	53.0	-2.4	Peak	
0.336	48.1	Neutral	49.3	-1.2	Peak	
0.605	47.9	Neutral	46.0	1.9	Peak	
0.848	47.5	Neutral	46.0	1.5	Peak	
1.024	49.3	Neutral	46.0	3.3	Peak	
1.342	48.8	Neutral	46.0	2.8	Peak	
13.560	44.2	Neutral	50.0	-5.8	Peak	RFID
27.121	40.3	Neutral	50.0	-9.7	Peak	RFID



EMC Test Data

Client:	Intuitive Surgical, Inc.	PR Number:	PR117602
Model:	ACCRX02	T-Log Number:	TL117602-RANA
Contact:	Tony Permsonbut	Project Manager:	Deepa Shetty
Standard:	FCC Part 15.225, RSS-210 B.6	Project Engineer:	David Bare
		Class:	-

Final quasi-peak and average readings

Frequency MHz	Level dB μ V	AC Line	FCC 15.207		Detector QP/Ave	Comments
			Limit	Margin		
0.848	46.8	Neutral	56.0	-9.2	QP	QP (1.00s)
1.107	46.5	Line	56.0	-9.5	QP	QP (1.00s)
0.605	46.4	Neutral	56.0	-9.6	QP	QP (1.00s)
0.867	46.3	Line	56.0	-9.7	QP	QP (1.00s)
1.024	46.0	Neutral	56.0	-10.0	QP	QP (1.00s)
1.342	45.8	Neutral	56.0	-10.2	QP	QP (1.00s)
0.620	45.5	Line	56.0	-10.5	QP	QP (1.00s)
0.605	35.4	Neutral	46.0	-10.6	AVG	AVG (0.10s)
1.330	45.2	Line	56.0	-10.8	QP	QP (1.00s)
2.102	45.0	Line	56.0	-11.0	QP	QP (1.00s)
0.848	34.6	Neutral	46.0	-11.4	AVG	AVG (0.10s)
2.102	32.0	Line	46.0	-14.0	AVG	AVG (0.10s)
1.107	31.4	Line	46.0	-14.6	AVG	AVG (0.10s)
1.024	31.3	Neutral	46.0	-14.7	AVG	AVG (0.10s)
0.336	44.6	Neutral	59.3	-14.7	QP	QP (1.00s)
0.867	30.6	Line	46.0	-15.4	AVG	AVG (0.10s)
0.620	29.9	Line	46.0	-16.1	AVG	AVG (0.10s)
0.336	32.8	Neutral	49.3	-16.5	AVG	AVG (0.10s)
1.342	27.3	Neutral	46.0	-18.7	AVG	AVG (0.10s)
1.330	27.0	Line	46.0	-19.0	AVG	AVG (0.10s)
0.244	42.5	Line	61.9	-19.4	QP	QP (1.00s)
0.244	29.4	Line	51.9	-22.5	AVG	AVG (0.10s)



EMC Test Data

Client:	Intuitive Surgical, Inc.	PR Number:	PR117602
Model:	ACCRX02	T-Log Number:	TL117602-RANA
Contact:	Tony Permsonbut	Project Manager:	Deepa Shetty
Standard:	FCC Part 15.225, RSS-210 B.6	Project Engineer:	David Bare
		Class:	-

Radiated Emissions

Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

General Test Configuration

The EUT and any local support equipment were located on the turntable for radiated emissions testing. Remote support equipment was located outside the chamber.

The test distance and extrapolation factor (if used) are detailed under each run description.

Note, preliminary testing indicates that the emissions were maximized by orientation of the EUT and elevation of the measurement antenna. Maximized testing indicated that the emissions were maximized by orientation of the EUT, elevation of the measurement antenna, and manipulation of the EUT's interface cables.

Ambient Conditions: Temperature: 23.8 °C
Rel. Humidity: 37 %

Summary of Results

Run #	Test Performed	Limit	Result	Margin
1	Fundamental Signal Field Strength / Spectral Mask	FCC 15.255 & RSS 210 B.6	Pass	8.80 dBµV/m @ 13.563 MHz (-75.2 dB)
2	10 - 30 MHz	FCC 15.209/RSS-GEN	Pass	20.2 dBµV/m @ 30.00 MHz (-9.3 dB)
3	Transmitter Radiated Spurious Emissions, 30 - 150 MHz	FCC 15.209/RSS GEN	Pass	33.5 dBµV/m @ 47.38 MHz (-6.5 dB)

Modifications Made During Testing

No modifications were made to the EUT during testing

Deviations From The Standard

No deviations were made from the requirements of the standard.



EMC Test Data

Client:	Intuitive Surgical, Inc.	PR Number:	PR117602
Model:	ACCRX02	T-Log Number:	TL117602-RANA
Contact:	Tony Permsonbut	Project Manager:	Deepa Shetty
Standard:	FCC Part 15.225, RSS-210 B.6	Project Engineer:	David Bare
		Class:	-

Run #1: Fundamental Signal Field Strength / Spectral Mask

Date of Test: 6/18/2020
 Test Engineer: Rafael Varelas
 Test Location: Fremont Chamber #3

Config. Used: 1
 Config Change: None
 Host Unit Voltage 120V/60Hz

Frequency Range	Test Distance	Limit Distance	Extrapolation Factor
13.06 - 14.06 MHz	3	30	-40.0

Fundamental Field Strength


Frequency	Level	Pol	FCC 15.255/RSS-210		Detector	Azimuth	Height	Comments
MHz	dB μ V/m	v/h	Limit	Margin	Pk/QP/Avg	degrees	meters	
13.563	8.2	O	84.0	-75.8	Peak	254	1.25	EUT upright
13.566	5.3	C	84.0	-78.7	Peak	165	1.25	EUT upright
13.563	2.8	O	84.0	-81.2	Peak	29	1.25	EUT flat
13.566	2.3	C	84.0	-81.7	Peak	93	1.25	EUT flat
13.563	8.8	O	84.0	-75.2	Peak	255	1.25	EUT side
13.566	5.4	C	84.0	-78.6	Peak	179	1.25	EUT side




EMC Test Data

Client: Intuitive Surgical, Inc.	PR Number: PR117602
Model: ACCRX02	T-Log Number: TL117602-RANA
Contact: Tony Permsonbut	Project Manager: Deepa Shetty
Standard: FCC Part 15.225, RSS-210 B.6	Project Engineer: David Bare
	Class: -

EUT Upright, Antenna Open



EUT Upright, Antenna Closed







EMC Test Data

Client: Intuitive Surgical, Inc.	PR Number: PR117602
Model: ACCRX02	T-Log Number: TL117602-RANA
Contact: Tony Permsonbut	Project Manager: Deepa Shetty
Standard: FCC Part 15.225, RSS-210 B.6	Project Engineer: David Bare
	Class: -

EUT Flat, Antenna Open



EUT Flat, Antenna Closed







EMC Test Data

Client: Intuitive Surgical, Inc.	PR Number: PR117602
Model: ACCRX02	T-Log Number: TL117602-RANA
Contact: Tony Permsonbut	Project Manager: Deepa Shetty
Standard: FCC Part 15.225, RSS-210 B.6	Project Engineer: David Bare
	Class: -

EUT Side, Antenna Open



EUT Side, Antenna Closed





EMC Test Data

Client:	Intuitive Surgical, Inc.	PR Number:	PR117602
Model:	ACCRX02	T-Log Number:	TL117602-RANA
Contact:	Tony Permsonbut	Project Manager:	Deepa Shetty
Standard:	FCC Part 15.225, RSS-210 B.6	Project Engineer:	David Bare
		Class:	-

Limits for Fundamental

Freq (MHz)		RBW (kHz)	Limit (dBuV/m) @ 30m
< 13.110		9	29.5
13.110	13.410	9	40.5
13.410	13.553	9	50.5
13.553	13.567	9	84.0
13.567	13.710	9	50.5
13.710	14.010	9	40.5
> 14.010		9	29.5

Note 1: As all emisison from the radio were less than the spurious emisison limits, the EUT met the mask limits.



EMC Test Data

Client: Intuitive Surgical, Inc.	PR Number: PR117602
Model: ACCRX02	T-Log Number: TL117602-RANA
Contact: Tony Permsonbut	Project Manager: Deepa Shetty
Standard: FCC Part 15.225, RSS-210 B.6	Project Engineer: David Bare
	Class: -

Run #2: Radiated Spurious Emissions, 10 - 30 MHz


Date of Test: 6/18/2020
 Test Engineer: Rafael Varelas
 Test Location: Fremont Chamber #3

Config. Used: 1
 Config Change: None
 Host Unit Voltage 120V/60Hz


Frequency Range	Test Distance	Limit Distance	Extrapolation Factor
10 - 30.0 MHz	3	30	-40.0

Note - the extrapolation factor is based on $40 \cdot \log(\text{test distance/limit distance})$ as permitted by FCC 15.31

EUT Side, Antenna Open



EUT Side, Antenna Closed





EMC Test Data

Client:	Intuitive Surgical, Inc.	PR Number:	PR117602
Model:	ACCRX02	T-Log Number:	TL117602-RANA
Contact:	Tony Permsonbut	Project Manager:	Deepa Shetty
Standard:	FCC Part 15.225, RSS-210 B.6	Project Engineer:	David Bare
		Class:	-

Preliminary readings

Frequency	Level	Pol	FCC 15.209/RSS-GEN		Detector	Azimuth	Height	Comments
MHz	dB μ V/m	v/h	Limit	Margin	Pk/QP/Avg	degrees	meters	
13.561	8.5	O	29.5	-21.0	Peak	261	1.25	RFID Fundamental
27.120	-4.7	O	29.5	-34.2	Peak	347	1.25	RFID 2nd harmonic
13.561	4.1	C	29.5	-25.4	Peak	186	1.25	RFID Fundamental
27.121	1.3	C	29.5	-28.2	Peak	193	1.25	RFID 2nd harmonic

Note 1: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, with a peak limit 20dB above the average limit.

Maximized readings (includes manipulation of EUT interface cables)

Frequency	Level	Pol	FCC 15.209/RSS-GEN		Detector	Azimuth	Height	Comments
MHz	dB μ V/m	v/h	Limit	Margin	Pk/QP/Avg	degrees	meters	
27.121	-0.8	C	29.5	-30.3	QP	188	1.25	QP (1.00s)

Note 1: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, with a peak limit 20dB above the average limit.




EMC Test Data

Client: Intuitive Surgical, Inc.	PR Number: PR117602
Model: ACCRX02	T-Log Number: TL117602-RANA
Contact: Tony Permsonbut	Project Manager: Deepa Shetty
Standard: FCC Part 15.225, RSS-210 B.6	Project Engineer: David Bare
	Class: -

Run #3: Radiated Spurious Emissions, 30 - 150 MHz

Frequency Range	Test Distance	Limit Distance	Extrapolation Factor
30 - 150 MHz	3	3	0.0



Preliminary Readings

Frequency	Level	Pol	FCC 15.209/RSS-GEN		Detector	Azimuth	Height	Comments
MHz	dB μ V/m	v/h	Limit	Margin	Pk/QP/Avg	degrees	meters	
47.384	37.1	V	40.0	-2.9	Peak	275	1.0	
62.771	33.7	V	40.0	-6.3	Peak	300	1.5	
120.007	32.6	V	43.5	-10.9	Peak	266	1.0	
126.512	31.5	H	43.5	-12.0	Peak	156	2.5	
135.608	32.2	V	43.5	-11.3	Peak	255	1.0	

Maximized readings (includes manipulation of EUT interface cables)

Frequency	Level	Pol	FCC 15.209/RSS-GEN		Detector	Azimuth	Height	Comments
MHz	dB μ V/m	v/h	Limit	Margin	Pk/QP/Avg	degrees	meters	
47.384	33.5	V	40.0	-6.5	QP	268	1.0	QP (1.00s)
62.771	28.0	V	40.0	-12.0	QP	304	1.0	QP (1.00s)
120.007	31.2	V	43.5	-12.3	QP	266	1.0	QP (1.00s)
126.512	13.1	H	43.5	-30.4	QP	151	1.0	QP (1.00s)
135.608	31.0	V	43.5	-12.5	QP	261	1.0	QP (1.00s)

Note 1: Harmonic of the RFID radio observed 135.6 MHz is only higher than the fundamental due to different extrapolation factor.



EMC Test Data

Client:	Intuitive Surgical, Inc.	PR Number:	PR117602
Model:	ACCRX02	T-Log Number:	TL117602-RANA
Contact:	Tony Permsonbut	Project Manager:	Deepa Shetty
Standard:	FCC Part 15.225, RSS-210 B.6	Project Engineer:	David Bare
		Class:	N/A

RSS-GEN and FCC Part 15.255 Occupied Bandwidth and Frequency Stability

Test Specific Details

Objective: The objective of this test session is to perform final qualification testing of the EUT with respect to the specification listed above.

General Test Configuration

With the exception of the radiated spurious emissions tests, all measurements are made with the EUT's rf port connected to the measurement instrument via an attenuator or dc-block if necessary. All amplitude measurements are adjusted to account for the attenuation between EUT and measuring instrument. For frequency stability measurements the EUT was placed inside an environmental chamber.

Radiated measurements are made with the EUT located on a non-conductive table, 3m from the measurement antenna.

Ambient Conditions: Temperature: 20 °C
 Rel. Humidity: 41 %

Summary of Results

Run #	Test Performed	Limit	Pass / Fail	Result / Margin
1	99% or Occupied Bandwidth	-	Pass	11 Hz
2	Frequency Stability	100 ppm	Pass	12.7ppm

Modifications Made During Testing

No modifications were made to the EUT during testing

Deviations From The Standard

No deviations were made from the requirements of the standard.



EMC Test Data

Client: Intuitive Surgical, Inc.	PR Number: PR117602
Model: ACCRX02	T-Log Number: TL117602-RANA
Contact: Tony Permsonbut	Project Manager: Deepa Shetty
Standard: FCC Part 15.225, RSS-210 B.6	Project Engineer: David Bare
	Class: N/A


Run #1: Signal Bandwidth

Date of Test: 6/22/2020
 Test Engineer: David Bare
 Test Location: Fremont Chamber #3

Config. Used: 1
 Config Change: None
 EUT Voltage: 3.3VDC

Frequency (MHz)	Resolution Bandwidth	Bandwidth	
			99%
13.56	3 Hz		0.011

Note 1: 99% bandwidth measured in accordance with ANSI C63.10, with RB between 1% and 5% of the measured bandwidth and VB $\geq 3 \cdot RB$ and Span $\geq 1.5\%$ and $\leq 5\%$ of measured bandwidth.



Analyzer Settings

Rohde&Schwarz, ESI
 CF: 13.560 MHz
 SPAN: 30 Hz
 RB: 1 Hz
 VB: 100 Hz
 Detector: POS
 Attn: 10 DB
 RL Offset: 15.0 DB
 Sweep Time: 50.0s
 Ref Lvl: -7.0 DBM

Comments

99% power BW: 11 Hz

Cursor 13.560155 -13.3

Cursor 13.560166 -39.3

Delta Freq. 11 Hz

Delta Amplitude 26.0





EMC Test Data

Client:	Intuitive Surgical, Inc.	PR Number:	PR117602
Model:	ACCRX02	T-Log Number:	TL117602-RANA
Contact:	Tony Permsonbut	Project Manager:	Deepa Shetty
Standard:	FCC Part 15.225, RSS-210 B.6	Project Engineer:	David Bare
		Class:	N/A

Run #2: Frequency Stability

Date of Test: 6/23/2020

Test Engineer: M. Birgani / R. Varelas

Test Location: FT Lab #4B

Config. Used: -

Config Change: -

EUT Voltage: 3.3VDC

Nominal Frequency: 13.56 MHz

Frequency Stability Over Temperature

The EUT was soaked at each temperature for a minimum of 30 minutes prior to making the measurements to ensure the EUT and chamber had stabilized at that temperature.

Temperature (Celsius)	Frequency Measured (MHz)	Drift	
		(Hz)	(ppm)
-20	13.560114	114	8.4
-10	13.560155	155	11.4
0	13.560172	172	12.7
10	13.560170	170	12.5
20	13.560150	150	11.1
30	13.560142	142	10.5
40	13.560130	130	9.6
50	13.560132	132	9.7
Worst case:		172	12.7

Frequency Stability Over Input Voltage

Nominal Voltage of host unit is 120V

Voltage (AC)	Frequency Measured (MHz)	Drift	
		(Hz)	(ppm)
85%	13.560150	150	11.1
115%	13.560149	149	11.0
Worst case:		150	12.7

End of Report

This page is intentionally blank and marks the last page of this test report.