

APPLICATION CERTIFICATION
On Behalf of
Carewell Electric Technology (Zhongshan) Co., Ltd.

REMOTE CONTROL
Model No.: FAN-57T

FCC ID: 2AAZPFAN57T

Prepared for : Carewell Electric Technology (Zhongshan) Co., Ltd.
Address : Torch Development Zone, No.2, Ouya Road, Zhongshan,
Guangdong, China

Prepared by : ACCURATE TECHNOLOGY CO., LTD
Address : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.
Science & Industry Park, Nanshan, Shenzhen, Guangdong
P.R. China

Tel: (0755) 26503290
Fax: (0755) 26503396

Report Number : ATE20162173
Date of Test : October 22, 2016
Date of Report : October 26, 2016

TABLE OF CONTENTS

Description
Page

Test Report Certification

1. GENERAL INFORMATION	4
1.1. Description of Device (EUT).....	4
1.2. Description of Test Facility	5
1.3. Measurement Uncertainty	5
2. MEASURING DEVICE AND TEST EQUIPMENT	6
3. SUMMARY OF TEST RESULTS.....	7
4. THE FIELD STRENGTH OF RADIATION EMISSION	8
4.1. Block Diagram of Test Setup.....	8
4.2. The Field Strength of Radiation Emission Measurement Limits.....	9
4.3. Configuration of EUT on Measurement	9
4.4. Operating Condition of EUT	9
4.5. Test Procedure	10
4.6. The Field Strength of Radiation Emission Measurement Results	11
5. 20DB OCCUPIED BANDWIDTH	13
5.1. Block Diagram of Test Setup.....	13
5.2. The Bandwidth of Emission Limit According To FCC Part 15 Section 15.231(c).....	13
5.3. EUT Configuration on Measurement	14
5.4. Operating Condition of EUT	14
5.5. Test Procedure	14
5.6. Measurement Result	14
6. RELEASE TIME MEASUREMENT.....	15
6.1. Block Diagram of Test Setup.....	15
6.2. Release Time Measurement According To FCC Part 15 Section 15.231(a)	15
6.3. EUT Configuration on Measurement	16
6.4. Operating Condition of EUT	16
6.5. Test Procedure	16
6.6. Measurement Result	16
7. AVERAGE FACTOR MEASUREMENT.....	17
7.1. Block Diagram of Test Setup.....	17
7.2. Average factor Measurement according to ANSI C63.10-2013.....	17
7.3. EUT Configuration on Measurement	18
7.4. Operating Condition of EUT	18
7.5. Test Procedure	18
7.6. Measurement Result	18
8. ANTENNA REQUIREMENT.....	19
8.1. The Requirement	19
8.2. Antenna Construction	19

Test Report Certification

Applicant : Carewell Electric Technology (Zhongshan) Co., Ltd.
Manufacturer : Carewell Electric Technology (Zhongshan) Co., Ltd.
EUT Description : REMOTE CONTROL
(A) MODEL NO.: FAN-57T
(B) SERIAL NO.: N/A
(C) POWER SUPPLY: DC 3V (Battery)


Measurement Procedure Used:


FCC Rules and Regulations Part 15 Subpart C Section 15.231a ANSI C63.10-2013

The device described above is tested by ACCURATE TECHNOLOGY CO., LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.231a. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO., LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO., LTD.

Date of Test : October 22, 2016
Date of Report : October 26, 2016

Prepared by : 
(Bob Wang, Engineer)

Approved & Authorized Signer : 
(Sean Liu, Manager)

1. GENERAL INFORMATION

1.1. Description of Device (EUT)

EUT	:	REMOTE CONTROL
Model Number	:	FAN-57T
Power Supply	:	DC 3V (powered by battery)
Modulation:	:	ASK
Operation Frequency	:	315MHz
Applicant	:	Carewell Electric Technology (Zhongshan) Co., Ltd.
Address	:	Torch Development Zone, No.2, Ouya Road, Zhongshan, Guangdong, China
Manufacturer	:	Carewell Electric Technology (Zhongshan) Co., Ltd.
Address	:	Torch Development Zone, No.2, Ouya Road, Zhongshan, Guangdong, China
Date of sample received	:	October 12, 2016
Date of Test	:	October 22, 2016

1.2. Description of Test Facility

EMC Lab : Accredited by TUV Rheinland Shenzhen

Listed by FCC
The Registration Number is 752051

Listed by Industry Canada
The Registration Number is 5077A-2

Accredited by China National Accreditation Committee
for Laboratories
The Certificate Registration Number is L3193

Name of Firm : ACCURATE TECHNOLOGY CO., LTD
Site Location : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.
Science & Industry Park, Nanshan, Shenzhen, Guangdong
P.R. China

1.3. Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2

Radiated emission expanded uncertainty = 3.08dB, k=2
(9kHz-30MHz)

Radiated emission expanded uncertainty = 4.42dB, k=2
(30MHz-1000MHz)

Radiated emission expanded uncertainty = 4.06dB, k=2
(Above 1GHz)

2. MEASURING DEVICE AND TEST EQUIPMENT

Table 1: List of Test and Measurement Equipment

Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Cal. Interval
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 09, 2016	One Year
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 09, 2016	One Year
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 09, 2016	One Year
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 09, 2016	One Year
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 14, 2016	One Year
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 14, 2016	One Year
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 14, 2016	One Year
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1067	Jan. 14, 2016	One Year
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 09, 2016	One Year
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 09, 2016	One Year
Highpass Filter	Wainwright Instruments	WHKX3.6/18 G-10SS	N/A	Jan. 09, 2016	One Year
Band Reject Filter	Wainwright Instruments	WRCG2400/2 485-2375/2510 -60/11SS	N/A	Jan. 09, 2016	One Year

3. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
Section 15.207	Conducted Emission	N/A
Section 15.231(b)	Radiated Emission	Compliant
Section 15.231(c)	20dB Bandwidth	Compliant
Section 15.231(a)(1)	Release Time Measurement	Compliant
Section 15.203	Antenna Requirement	Compliant

The product is a manually operated transmitter.
Section 15.231 (a) (2), (3), (4) and (5) are not applicable.

All normal using modes of the normal function were tested but only the worst test data of the worst mode is recorded by this report.

Note: The power supply mode of the EUT is DC 3V, According to the FCC standard requirements, conducted emission is not applicable

4. THE FIELD STRENGTH OF RADIATION EMISSION


4.1. Block Diagram of Test Setup

4.1.1. Block diagram of connection between the EUT and simulators



(EUT: REMOTE CONTROL)

4.1.2. Semi-Anechoic Chamber Test Setup Diagram



(EUT: REMOTE CONTROL)

4.2. The Field Strength of Radiation Emission Measurement Limits

4.2.1. Radiation Emission Measurement Limits According to FCC Part 15 Section 15.231(b)

Frequency Range of Fundamental [MHz]	Field Strength of Fundamental Emission [Average] [$\mu\text{V/m}$]	Field Strength of Spurious Emission [Average] [$\mu\text{V/m}$]
40.66-40.70	2250	225
70-130	1250	125
130-174	1250-3750	125-375
174-260	3750	375
260-470	3750-12500	375-1250
Above 470	12500	1250

Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz, $\mu\text{V/m}$ at 3 meters = $56.81818(F) - 6136.3636$; for the band 260-470 MHz, $\mu\text{V/m}$ at 3 meters = $41.6667(F) - 7083.3333$. The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.

4.2.2. Restricted Band Radiation Emission Measurement Limits According to FCC part 15 Section 15.205 and Section 15.209.

4.3. Configuration of EUT on Measurement

The following equipment is installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

4.3.1. REMOTE CONTROL (EUT)

Model Number : FAN-57T
Serial Number : N/A
Manufacturer : Carewell Electric Technology (Zhongshan) Co., Ltd.

4.4. Operating Condition of EUT

4.4.1. Setup the EUT and simulator as shown as Section 4.1.

4.4.2. Turn on the power of all equipment.

4.4.3. Let the EUT work in TX mode measure it.

4.5. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground (Below 1GHz). The EUT and its simulators are placed on a turntable, which is 1.5 meter high above ground (Above 1GHz). The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the EUT location must be manipulated according to ANSI C63.10:2013 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

The bandwidth of test receiver is set at 120 kHz in 30-1000 MHz, and 1 MHz in 1000-4000 MHz.

The frequency range from 30 MHz to 4000 MHz is checked.

4.6. The Field Strength of Radiation Emission Measurement Results

PASS.

The frequency range 30MHz to 4000MHz is investigated.

EUT:	REMOTE CONTROL	
Model No.:	FAN-57T	Power Supply: DC 3V
Test Mode:	TX	Test Engineer: Frank

Frequency (MHz)	Reading (dBμV/m)	Factor Corr.	Average Factor	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	PEAK	(dB)	(dB)	AV	PEAK	AV	PEAK	AV	PEAK	
315	83.64	-16.72	-5.07	61.85	66.92	75.62	95.62	-13.77	-28.70	Horizontal
630	66.96	-9.82	-5.07	52.07	57.14	55.62	75.62	-3.55	-18.48	
945	54.54	-3.67	-5.07	45.8	50.87	55.62	75.62	-9.82	-24.75	
38.6355	36.17	-18.21	---	---	17.96	---	40.00	---	-22.04 (QP)	
103.3353	38.70	-23.69	---	---	15.01	---	43.50	---	-28.49 (QP)	
357.1923	41.18	-15.15	---	---	26.03	---	46.00	---	-19.97 (QP)	
1260	61.64	-9.08	-5.07	47.49	52.56	55.62	75.62	-8.13	-23.06	
1575	61.22	-8.36	-5.07	47.79	52.86	55.62	75.62	-7.83	-22.76	
1890	51.53	-7.21	-5.07	39.25	44.32	55.62	75.62	-16.37	-31.30	
2205	49.72	-6.21	-5.07	38.44	43.51	55.62	75.62	-17.18	-32.11	
2520	54.53	-5.32	-5.07	44.14	49.21	55.62	75.62	-11.48	-26.41	
3780	45.69	-1.14	-5.07	39.48	44.55	55.62	75.62	-16.14	-31.07	
315	80.60	-16.72	-5.07	58.81	63.88	75.62	95.62	-16.81	-31.74	
630	64.04	-9.82	-5.07	49.15	54.22	55.62	75.62	-6.47	-21.40	
945	50.20	-3.67	-5.07	41.46	46.53	55.62	75.62	-14.16	-29.09	
37.6970	33.69	-17.78	---	---	15.91	---	40.00	---	-24.09 (QP)	
103.3353	41.68	-23.69	---	---	17.99	---	43.50	---	-25.51 (QP)	
222.2806	37.92	-19.29	---	---	18.63	---	46.00	---	27.37(QP)	
1260	61.08	-9.08	-5.07	46.93	52.00	55.62	75.62	-8.69	-23.62	
1575	59.44	-8.36	-5.07	46.01	51.08	55.62	75.62	-9.61	-24.54	
2205	50.04	-6.21	-5.07	38.76	43.83	55.62	75.62	-16.86	-31.79	

2520	54.37	-5.32	-5.07	43.98	49.05	55.62	75.62	-11.64	-26.57	
3465	49.97	-2.06	-5.07	42.84	47.91	55.62	75.62	-12.78	-27.71	
3780	44.92	-1.14	-5.07	38.71	43.78	55.62	75.62	-16.91	-31.84	

Note:

1. Emissions attenuated more than 20 dB below the permissible value are not reported.
2. The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:
Result = Reading + Corrected Factor
Where Corrected Factor = Antenna Factor + Cable Loss + High Pass Filter Loss – Amplifier Gain
3. FCC Limit for Average Measurement = $41.6667(315)-7083.3333 = 6041.6772 \mu\text{V/m} = 75.62 \text{ dB}\mu\text{V/m}$
4. The spectral diagrams in appendix I display the measurement of peak values.
5. Average value= PK value + Average Factor (duty factor)
6. If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.
7. The EUT is tested radiation emission in three axes(X,Y,Z). The worst emissions are reported in three axes.

8. Pulse Desensitization Correction Factor

$$\text{Pulse Width (PW)} = 0.44\text{ms}$$

$$2/\text{PW} = 2/0.44\text{ms} = 4.5455 \text{ kHz}$$

$$\text{RBW (100 kHz)} > 2/\text{PW (4.5455 kHz)}$$

Therefore PDCF is not needed

5. 20DB OCCUPIED BANDWIDTH


5.1. Block Diagram of Test Setup

5.1.1. Block diagram of connection between the EUT and simulators



(EUT: REMOTE CONTROL)

5.1.2. Semi-Anechoic Chamber Test Setup Diagram



(EUT: REMOTE CONTROL)

5.2. The Bandwidth of Emission Limit According To FCC Part 15 Section

15.231(c)

The bandwidth of emission shall be no wider than 0.25% of the center frequency. Therefore, the bandwidth of the emission limit is $315 \text{ MHz} \times 0.25\% = 787.5 \text{ kHz}$. Bandwidth is determined at the two points 20 dB down from the top of modulated carrier.

5.3.EUT Configuration on Measurement

The following equipment are installed on the bandwidth of emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

5.3.1.REMOTE CONTROL (EUT)

Model Number : FAN-57T
Serial Number : N/A
Manufacturer : Carewell Electric Technology (Zhongshan) Co., Ltd.

5.4.Operating Condition of EUT

5.4.1.Setup the EUT and simulator as shown as Section 5.1.

5.4.2.Turn on the power of all equipment.

5.4.3.Let the EUT work in TX mode measure it.

5.5.Test Procedure

5.5.1.Set SPA Center Frequency = Fundamental frequency, RBW = 10 kHz, VBW = 30 kHz, Span = 1MHz.

5.5.2.Set SPA Max hold, Mark peak, -20 dB.

5.6.Measurement Result

The EUT does meet the FCC requirement.

-20 dB bandwidth =56 kHz <787.5 kHz.

The spectral diagrams in appendix I.

6. RELEASE TIME MEASUREMENT


6.1. Block Diagram of Test Setup

6.1.1. Block diagram of connection between the EUT and simulators



(EUT: REMOTE CONTROL)

6.1.2. Semi-Anechoic Chamber Test Setup Diagram



(EUT: REMOTE CONTROL)

6.2. Release Time Measurement According To FCC Part 15 Section 15.231(a)

Section 15.231(a) (1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

6.3.EUT Configuration on Measurement

The following equipment are installed on Release Time Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

6.3.1. REMOTE CONTROL (EUT)

Model Number : FAN-57T
Serial Number : N/A
Manufacturer : Carewell Electric Technology (Zhongshan) Co., Ltd.

6.4.Operating Condition of EUT

6.4.1.Setup the EUT and simulator as shown as Section 6.1.

6.4.2.Turn on the power of all equipment.

6.4.3.Let the EUT work in TX mode measure it.

6.5.Test Procedure

6.5.1.Set SPA Center Frequency = Fundamental frequency, RBW = 100 kHz, VBW = 300 kHz, Span = 0 Hz. Sweep time = 10 s.

6.5.2.Set EUT as normal operation and press Transmitter button.

6.5.3.Set SPA View. Delta Mark time.

6.6. Measurement Result

The release time less than 5 seconds.

Release Time = 2.83584s

The spectral diagrams in appendix I.

7. AVERAGE FACTOR MEASUREMENT


7.1. Block Diagram of Test Setup

7.1.1. Block diagram of connection between the EUT and simulators



(EUT: REMOTE CONTROL)

7.1.2. Semi-Anechoic Chamber Test Setup Diagram



7.2. Average factor Measurement according to ANSI C63.10-2013

ANSI C63.10-2013 Section 7.5 Unless otherwise specified, when the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 s (100 ms). In cases where the pulse train exceeds 0.1 s, the measured field strength shall be determined during a 0.1 s interval.⁶⁴ The following procedure is an example of how the average value may be determined. The average field strength may be found by measuring the peak pulse amplitude (in log equivalent units) and determining the duty cycle correction factor (in dB) associated with the pulse modulation as shown in Equation (10):

Average factor in dB = 20 log (duty cycle)

7.3.EUT Configuration on Measurement

The following equipment are installed on average factor Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

7.3.1. REMOTE CONTROL

Model Number : FAN-57T
Serial Number : N/A
Manufacturer : Carewell Electric Technology (Zhongshan) Co., Ltd.

7.4.Operating Condition of EUT

7.4.1.Setup the EUT and simulator as shown as Section 7.1.

7.4.2.Turn on the power of all equipment.

7.4.3.Let the EUT work in TX mode measure it.

7.5.Test Procedure

7.5.1.The time period over which the duty cycle is measured is 100 milliseconds, or the repetition cycle, whichever is a shorter time frame. The worst case (highest percentage on) duty cycle is used for the calculation.

7.5.2.Set SPA Center Frequency = Fundamental frequency, RBW = 100 kHz, VBW = 300 kHz, Span = 0 Hz.

7.5.3.Set EUT as normal operation.

7.5.4.Set SPA View. Delta Mark time.

7.6. Measurement Result

The duty cycle is simply the on time divided by the period:

The duration of one cycle = 35.0ms

Effective period of the cycle = $(0.44 \times 13) + (0.92 \times 15)$ ms =19.52 ms

DC = $19.52\text{ms}/35.0\text{ms}$ =0.558

Therefore, the average factor is found by $20\log 0.558 = -5.07\text{dB}$

The spectral diagrams in appendix I.


8. ANTENNA REQUIREMENT

8.1. The Requirement

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

8.2. Antenna Construction

Device is equipped with permanent attached antenna, which isn't displaced by other antenna. The Antenna gain of EUT is 0dBi. Therefore, the equipment complies with the antenna requirement of Section 15.203.



Antenna

APPENDIX I (Test Curves)




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Frank #3052	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 3V
Test item: Radiation Test	Date: 2016/10/22
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 11:27:17
EUT: REMOTE CONTROL	Engineer Signature: Frank
Mode: TX	Distance: 3m
Model: FAN-57T	
Manufacturer: Carewell	

Note: Report NO.:ATE20162173



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	37.6970	33.69	-17.78	15.91	40.00	-24.09	QP			"X"axes
2	103.3353	41.68	-23.69	17.99	43.50	-25.51	QP			"X"axes
3	222.2806	37.92	-19.29	18.63	46.00	-27.37	QP			"X"axes
4	315.000	80.60	-16.72	63.88	95.62	-31.74	peak			"X"axes
5	630.000	64.04	-9.82	54.22	75.62	-21.40	peak			"X"axes
6	945.000	50.20	-3.67	46.53	75.62	-29.09	peak			"X"axes




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Frank #3054	Polarization: Horizontal
Standard: FCC Class B 3M Radiated	Power Source: DC 3V
Test item: Radiation Test	Date: 2016/10/22
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 11:28:14
EUT: REMOTE CONTROL	Engineer Signature: Frank
Mode: TX	Distance: 3m
Model: FAN-57T	
Manufacturer: Carewell	

Note: Report NO.:ATE20162173



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	38.6355	36.17	-18.21	17.96	40.00	-22.04	QP			"X"axes
2	103.3353	38.70	-23.69	15.01	43.50	-28.49	QP			"X"axes
3	315.0000	83.64	-16.72	66.92	95.62	-28.70	peak			"X"axes
4	357.1923	41.18	-15.15	26.03	46.00	-19.97	QP			"X"axes
5	630.0000	66.96	-9.82	57.14	75.62	-18.48	peak			"X"axes
6	945.0000	54.54	-3.67	50.87	75.62	-24.75	peak			"X"axes



ACCURATE TECHNOLOGY CO., LTD.


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396

Job No.: Frank #3055
Standard: FCC PK
Test item: Radiation Test
Temp.(C)/Hum.(%) 25 C / 55 %
EUT: REMOTE CONTROL
Mode: TX
Model: FAN-57T
Manufacturer: Carewell

Polarization: Horizontal
Power Source: DC 3V
Date: 2016/10/22
Time: 11:31:10
Engineer Signature: Frank
Distance: 3m

Note: Report NO.:ATE20162173



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	1260.000	61.64	-9.08	52.56	75.62	-23.06	peak			"X"axes
2	1575.000	61.22	-8.36	52.86	75.62	-22.76	peak			"X"axes
3	1890.000	51.53	-7.21	44.32	75.62	-31.30	peak			"X"axes
4	2205.000	49.72	-6.21	43.51	75.62	-32.11	peak			"X"axes
5	2520.000	54.53	-5.32	49.21	75.62	-26.41	peak			"X"axes
6	3780.000	45.69	-1.14	44.55	75.62	-31.07	peak			"X"axes




ACCURATE TECHNOLOGY CO., LTD.

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,
Science & Industry Park,Nanshan Shenzhen,P.R.China


Site: 1# Chamber
Tel:+86-0755-26503290
Fax:+86-0755-26503396


Job No.: Frank #3056	Polarization: Vertical
Standard: FCC PK	Power Source: DC 3V
Test item: Radiation Test	Date: 2016/10/22
Temp.(C)/Hum.(%) 25 C / 55 %	Time: 11:33:01
EUT: REMOTE CONTROL	Engineer Signature: Frank
Mode: TX	Distance: 3m
Model: FAN-57T	
Manufacturer: Carewell	

Note: Report NO.:ATE20162173



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	1260.000	61.08	-9.08	52.00	75.62	-23.62	peak			"X"axes
2	1575.000	59.44	-8.36	51.08	75.62	-24.54	peak			"X"axes
3	2205.000	50.04	-6.21	43.83	75.62	-31.79	peak			"X"axes
4	2520.000	54.37	-5.32	49.05	75.62	-26.57	peak			"X"axes
5	3465.000	49.97	-2.06	47.91	75.62	-27.71	peak			"X"axes
6	3780.000	44.92	-1.14	43.78	75.62	-31.84	peak			"X"axes





Release Time = 2.83584s

The graph shows the pattern of coding during the signal transmission.
The duration of one cycle = 35.0 ms.

