

APPLICATION CERTIFICATION  
On Behalf of  
Carewell Electric Technology (Zhongshan) Co., Ltd.

REMOTE CONTROL  
Model No.: FAN61T-3SP

FCC ID: 2AAZPFAN61T3SP

Prepared for : Carewell Electric Technology (Zhongshan) Co., Ltd.  
Address : Torch Development Zone, No.2, Ouya Road, Zhongshan,  
Guangdong, China

Prepared by : ACCURATE TECHNOLOGY CO., LTD  
Address : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.  
Science & Industry Park, Nanshan, Shenzhen, Guangdong  
P.R. China

Tel: (0755) 26503290  
Fax: (0755) 26503396

Report Number : ATE20151900  
Date of Test : Aug 27, 2015-Sep 07, 2015  
Date of Report : Sep 08,2015

## TABLE OF CONTENTS

Description  
Page

### Test Report Certification

<b>1. GENERAL INFORMATION .....</b>	<b>4</b>
1.1. Description of Device (EUT).....	4
1.2. Description of Test Facility .....	5
1.3. Measurement Uncertainty .....	5
<b>2. MEASURING DEVICE AND TEST EQUIPMENT .....</b>	<b>6</b>
<b>3. SUMMARY OF TEST RESULTS.....</b>	<b>7</b>
<b>4. THE FIELD STRENGTH OF RADIATION EMISSION .....</b>	<b>8</b>
4.1. Block Diagram of Test Setup.....	8
4.2. The Field Strength of Radiation Emission Measurement Limits.....	9
4.3. Configuration of EUT on Measurement .....	9
4.4. Operating Condition of EUT .....	9
4.5. Test Procedure .....	10
4.6. The Field Strength of Radiation Emission Measurement Results .....	11
<b>5. 20DB OCCUPIED BANDWIDTH .....</b>	<b>13</b>
5.1. Block Diagram of Test Setup.....	13
5.2. The Bandwidth of Emission Limit According To FCC Part 15 Section 15.231(c).....	13
5.3. EUT Configuration on Measurement .....	14
5.4. Operating Condition of EUT .....	14
5.5. Test Procedure .....	14
5.6. Measurement Result .....	14
<b>6. RELEASE TIME MEASUREMENT.....</b>	<b>15</b>
6.1. Block Diagram of Test Setup.....	15
6.2. Release Time Measurement According To FCC Part 15 Section 15.231(a) .....	15
6.3. EUT Configuration on Measurement .....	16
6.4. Operating Condition of EUT .....	16
6.5. Test Procedure .....	16
6.6. Measurement Result .....	16
<b>7. AVERAGE FACTOR MEASUREMENT.....</b>	<b>17</b>
7.1. Block Diagram of Test Setup.....	17
7.2. Average factor Measurement according to ANSI C63.10-2013.....	17
7.3. EUT Configuration on Measurement .....	18
7.4. Operating Condition of EUT .....	18
7.5. Test Procedure .....	18
7.6. Measurement Result .....	18
<b>8. ANTENNA REQUIREMENT.....</b>	<b>19</b>
8.1. The Requirement .....	19
8.2. Antenna Construction .....	19

## Test Report Certification

Applicant : Carewell Electric Technology (Zhongshan) Co., Ltd.  
Manufacturer : Carewell Electric Technology (Zhongshan) Co., Ltd.  
EUT Description : REMOTE CONTROL  
(A) MODEL NO.: FAN61T-3SP  
(B) SERIAL NO.: N/A  
(C) POWER SUPPLY: DC 3V (Battery 2x AAA)

Measurement Procedure Used:

### FCC Rules and Regulations Part 15 Subpart C Section 15.231a ANSI C63.10-2013

The device described above is tested by ACCURATE TECHNOLOGY CO., LTD to determine the maximum emission levels emanating from the device. The maximum emission levels are compared to the FCC Part 15 Subpart C Section 15.231a. The measurement results are contained in this test report and ACCURATE TECHNOLOGY CO., LTD is assumed full responsibility for the accuracy and completeness of these measurements. Also, this report shows that the Equipment Under Test (EUT) is to be technically compliant with the FCC requirements.

This report applies to above tested sample only. This report shall not be reproduced in part without written approval of ACCURATE TECHNOLOGY CO., LTD.

Date of Test : Aug 27, 2015-Sep 07, 2015  
Date of Report : Sep 08, 2015

Prepared by : Tim Zhang  
(Tim.zhang, Engineer)

Approved & Authorized Signer : Sean Liu  
( Sean Liu, Manager)

## 1. GENERAL INFORMATION

### 1.1. Description of Device (EUT)

EUT : REMOTE CONTROL  
Model Number : FAN61T-3SP

Power Supply : DC 3V (battery 2x AAA)  
Modulation: : ASK

Operation Frequency : 315MHz

Applicant : Carewell Electric Technology (Zhongshan) Co., Ltd.  
Address : Torch Development Zone, No.2, Ouya Road, Zhongshan, Guangdong, China

Manufacturer : Carewell Electric Technology (Zhongshan) Co., Ltd.  
Address : Torch Development Zone, No.2, Ouya Road, Zhongshan, Guangdong, China

Date of sample received : Aug 27, 2015  
Date of Test : Aug 27, 2015-Sep 07, 2015

## 1.2. Description of Test Facility

EMC Lab : Accredited by TUV Rheinland Shenzhen

Listed by FCC  
The Registration Number is 752051

Listed by Industry Canada  
The Registration Number is 5077A-2

Accredited by China National Accreditation Committee  
for Laboratories  
The Certificate Registration Number is L3193

Name of Firm : ACCURATE TECHNOLOGY CO., LTD  
Site Location : F1, Bldg. A, Changyuan New Material Port, Keyuan Rd.  
Science & Industry Park, Nanshan, Shenzhen, Guangdong  
P.R. China

## 1.3. Measurement Uncertainty

Conducted Emission Expanded Uncertainty = 2.23dB, k=2

Radiated emission expanded uncertainty = 3.08dB, k=2  
(9kHz-30MHz)

Radiated emission expanded uncertainty = 4.42dB, k=2  
(30MHz-1000MHz)

Radiated emission expanded uncertainty = 4.06dB, k=2  
(Above 1GHz)

## 2. MEASURING DEVICE AND TEST EQUIPMENT

**Table 1: List of Test and Measurement Equipment**

Kind of equipment	Manufacturer	Type	S/N	Calibrated dates	Cal. Interval
EMI Test Receiver	Rohde&Schwarz	ESCS30	100307	Jan. 10, 2015	One Year
EMI Test Receiver	Rohde&Schwarz	ESPI3	101526/003	Jan. 10, 2015	One Year
Spectrum Analyzer	Agilent	E7405A	MY45115511	Jan. 10, 2015	One Year
Pre-Amplifier	Rohde&Schwarz	CBLU118354 0-01	3791	Jan. 10, 2015	One Year
Loop Antenna	Schwarzbeck	FMZB1516	1516131	Jan. 15, 2015	One Year
Bilog Antenna	Schwarzbeck	VULB9163	9163-323	Jan. 15, 2015	One Year
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-655	Jan. 15, 2015	One Year
Horn Antenna	Schwarzbeck	BBHA9120D	9120D-1067	Jan. 15, 2015	One Year
LISN	Rohde&Schwarz	ESH3-Z5	100305	Jan. 10, 2015	One Year
LISN	Schwarzbeck	NSLK8126	8126431	Jan. 10, 2015	One Year
Highpass Filter	Wainwright Instruments	WHKX3.6/18 G-10SS	N/A	Jan. 10, 2015	One Year
Band Reject Filter	Wainwright Instruments	WRCG2400/2 485-2375/2510 -60/11SS	N/A	Jan. 10, 2015	One Year

### 3. SUMMARY OF TEST RESULTS

FCC Rules	Description of Test	Result
Section 15.207	Conducted Emission	N/A
Section 15.231(b)	Radiated Emission	Compliant
Section 15.231(c)	20dB Bandwidth	Compliant
Section 15.231(a)(1)	Release Time Measurement	Compliant
Section 15.203	Antenna Requirement	Compliant

The product is a manually operated transmitter.  
Section 15.231 (a) (2), (3), (4) and (5) are not applicable.

All normal using modes of the normal function were tested but only the worst test data of the worst mode is recorded by this report.

## 4. THE FIELD STRENGTH OF RADIATION EMISSION


### 4.1. Block Diagram of Test Setup

#### 4.1.1. Block diagram of connection between the EUT and simulators



(EUT: REMOTE CONTROL)

#### 4.1.2. Semi-Anechoic Chamber Test Setup Diagram



(EUT: REMOTE CONTROL)



## 4.2. The Field Strength of Radiation Emission Measurement Limits

### 4.2.1. Radiation Emission Measurement Limits According to FCC Part 15 Section 15.231(b)

Frequency Range of Fundamental [MHz]	Field Strength of Fundamental Emission [Average] [ $\mu\text{V/m}$ ]	Field Strength of Spurious Emission [Average] [ $\mu\text{V/m}$ ]
40.66-40.70	2250	225
70-130	1250	125
130-174	1250-3750	125-375
174-260	3750	375
260-470	3750-12500	375-1250
Above 470	12500	1250

Where F is the frequency in MHz, the formulas for calculating the maximum permitted fundamental field strengths are as follows: for the band 130-174 MHz,  $\mu\text{V/m}$  at 3 meters =  $56.81818(F) - 6136.3636$ ; for the band 260-470 MHz,  $\mu\text{V/m}$  at 3 meters =  $41.6667(F) - 7083.3333$ . The maximum permitted unwanted emission level is 20 dB below the maximum permitted fundamental level.

### 4.2.2. Restricted Band Radiation Emission Measurement Limits According to FCC part 15 Section 15.205 and Section 15.209.

## 4.3. Configuration of EUT on Measurement

The following equipment is installed on Radiated Emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

### 4.3.1. REMOTE CONTROL (EUT)

Model Number : FAN61T-3SP  
Serial Number : N/A  
Manufacturer : Carewell Electric Technology (Zhongshan) Co., Ltd.

## 4.4. Operating Condition of EUT

4.4.1. Setup the EUT and simulator as shown as Section 4.1.

4.4.2. Turn on the power of all equipment.

4.4.3. Let the EUT work in TX mode measure it.

#### 4.5. Test Procedure

The EUT and its simulators are placed on a turntable, which is 0.8 meter high above ground (Below 1GHz). The EUT and its simulators are placed on a turntable, which is 1.5 meter high above ground (Above 1GHz). The turntable can rotate 360 degrees to determine the position of the maximum emission level. EUT is set 3.0 meters away from the receiving antenna, which is mounted on an antenna tower. The antenna can be moved up and down between 1.0 meter and 4 meters to find out the maximum emission level. Broadband antenna (calibrated bi-log antenna) is used as receiving antenna. Both horizontal and vertical polarizations of the antenna are set on measurement. In order to find the maximum emission levels, all of the EUT location must be manipulated according to ANSI C63.10:2013 on radiated emission measurement. The EUT was tested in 3 orthogonal planes.

The bandwidth of test receiver is set at 120 kHz in 30-1000 MHz, and 1 MHz in 1000-4000 MHz.

The frequency range from 30 MHz to 4000 MHz is checked.

### 4.6. The Field Strength of Radiation Emission Measurement Results **PASS.**

The frequency range 30MHz to 4000MHz is investigated.

EUT:	<u>REMOTE CONTROL</u>		
Model No.:	<u>FAN61T-3SP</u>	Power Supply:	<u>DC 3V</u>
Test Mode:	<u>TX</u>	Test Engineer:	<u>Star</u>

Frequency (MHz)	Reading (dBμV/m)	Factor Corr. (dB)	Average Factor (dB)	Result(dBμV/m)		Limit(dBμV/m)		Margin(dB)		Polarization
	PEAK			AV	PEAK	AV	AV	PEAK		
<b>315</b>	<b>96.10</b>	<b>-15.91</b>	<b>-5.97</b>	<b>74.22</b>	<b>80.19</b>	<b>75.62</b>	<b>95.62</b>	<b>-1.40</b>	<b>-15.43</b>	Horizontal
630	70.15	-9.28	-5.97	54.90	60.87	55.62	75.62	-0.72	-14.75	
945	60.81	-3.48	-5.97	51.36	57.33	55.62	75.62	-6.26	-18.29	
1260	64.98	-12.03	-5.97	46.98	52.95	55.62	75.62	-8.64	-22.67	
1575	59.43	-11.02	-5.97	42.44	48.41	55.62	75.62	-13.18	-27.21	
<b>315</b>	<b>88.94</b>	<b>-15.91</b>	<b>-5.97</b>	<b>67.06</b>	<b>73.03</b>	<b>75.62</b>	<b>95.62</b>	<b>-8.56</b>	<b>-22.59</b>	Vertical
630	67.29	-9.28	-5.97	52.04	58.01	55.62	75.62	-3.58	-17.61	
945	56.18	-3.48	-5.97	46.73	52.70	55.62	75.62	-8.89	-22.92	
1260	60.23	-12.03	-5.97	42.23	48.20	55.62	75.62	-13.39	-27.42	
1575	61.76	-11.02	-5.97	44.77	50.74	55.62	75.62	-10.85	-24.88	

Note:

- Emissions attenuated more than 20 dB below the permissible value are not reported.
- The field strength is calculated by adding the antenna factor, high pass filter loss(if used) and cable loss, and subtracting the amplifier gain(if any)from the measured reading. The basic equation calculation is as follows:  
Result = Reading + Corrected Factor  
Where Corrected Factor = Antenna Factor + Cable Loss + High Pass Filter Loss – Amplifier Gain
- FCC Limit for Average Measurement =  $41.6667(315)-7083.3333 = 6041.6772 \mu\text{V/m} = 75.62 \mu\text{V/m}$
- The spectral diagrams in appendix I display the measurement of peak values.
- Average value= PK value + Average Factor (duty factor)
- If the peak-detected amplitude can be shown to comply with the average limit, then it is not necessary to perform a separate average measurement.
- The EUT is tested radiation emission in three axes(X,Y,Z). The worst emissions are reported in three axes.

8. Pulse Desensitization Correction Factor

Pulse Width (PW) = 0.46377ms

$2/PW = 2/0.46377\text{ms} = 4.31\text{kHz}$

RBW (100 kHz) > 2/PW (4.31 kHz)

Therefore PDCF is not needed

## 5. 20DB OCCUPIED BANDWIDTH


### 5.1. Block Diagram of Test Setup

#### 5.1.1. Block diagram of connection between the EUT and simulators



(EUT: REMOTE CONTROL)

#### 5.1.2. Semi-Anechoic Chamber Test Setup Diagram



(EUT: REMOTE CONTROL)

### 5.2. The Bandwidth of Emission Limit According To FCC Part 15 Section

#### 15.231(c)

The bandwidth of emission shall be no wider than 0.25% of the center frequency. Therefore, the bandwidth of the emission limit is  $315 \text{ MHz} \times 0.25\% = 787.5 \text{ kHz}$ . Bandwidth is determined at the two points 20 dB down from the top of modulated carrier.

### 5.3.EUT Configuration on Measurement

The following equipment are installed on the bandwidth of emission Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

#### 5.3.1.REMOTE CONTROL (EUT)

Model Number : FAN61T-3SP  
Serial Number : N/A  
Manufacturer : Carewell Electric Technology (Zhongshan) Co., Ltd.

### 5.4.Operating Condition of EUT

5.4.1.Setup the EUT and simulator as shown as Section 5.1.

5.4.2.Turn on the power of all equipment.

5.4.3.Let the EUT work in TX mode measure it.

### 5.5.Test Procedure

5.5.1.Set SPA Center Frequency = Fundamental frequency, RBW = 10 kHz, VBW = 30 kHz, Span = 1MHz.

5.5.2.Set SPA Max hold, Mark peak, -20 dB.

### 5.6.Measurement Result

**The EUT does meet the FCC requirement.**

-20 dB bandwidth = 62.2 kHz <787.5 kHz.

The spectral diagrams in appendix I.

## 6. RELEASE TIME MEASUREMENT


### 6.1. Block Diagram of Test Setup

#### 6.1.1. Block diagram of connection between the EUT and simulators



(EUT: REMOTE CONTROL)

#### 6.1.2. Semi-Anechoic Chamber Test Setup Diagram



(EUT: REMOTE CONTROL)

### 6.2. Release Time Measurement According To FCC Part 15 Section 15.231(a)

Section 15.231(a) (1) A manually operated transmitter shall employ a switch that will automatically deactivate the transmitter within not more than 5 seconds of being released.

### 6.3.EUT Configuration on Measurement

The following equipment are installed on Release Time Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

#### 6.3.1. REMOTE CONTROL (EUT)

Model Number : FAN61T-3SP  
Serial Number : N/A  
Manufacturer : Carewell Electric Technology (Zhongshan) Co., Ltd.

### 6.4.Operating Condition of EUT

6.4.1.Setup the EUT and simulator as shown as Section 6.1.

6.4.2.Turn on the power of all equipment.

6.4.3.Let the EUT work in TX mode measure it.

### 6.5.Test Procedure

6.5.1.Set SPA Center Frequency = Fundamental frequency, RBW = 100 kHz, VBW = 300 kHz, Span = 0 Hz. Sweep time = 10 s.

6.5.2.Set EUT as normal operation and press Transmitter button.

6.5.3.Set SPA View. Delta Mark time.

### 6.6. Measurement Result

**The release time less than 5 seconds.**

Release Time = 2.7391s

The spectral diagrams in appendix I.



## 7. AVERAGE FACTOR MEASUREMENT


### 7.1. Block Diagram of Test Setup

#### 7.1.1. Block diagram of connection between the EUT and simulators



(EUT: REMOTE CONTROL)

#### 7.1.2. Semi-Anechoic Chamber Test Setup Diagram



### 7.2. Average factor Measurement according to ANSI C63.10-2013

**ANSI C63.10-2013 Section 7.5** Unless otherwise specified, when the radiated emission limits are expressed in terms of the average value of the emission, and pulsed operation is employed, the measurement field strength shall be determined by averaging over one complete pulse train, including blanking intervals, as long as the pulse train does not exceed 0.1 s (100 ms). In cases where the pulse train exceeds 0.1 s, the measured field strength shall be determined during a 0.1 s interval.<sup>64</sup> The following procedure is an example of how the average value may be determined. The average field strength may be found by measuring the peak pulse amplitude (in log equivalent units) and determining the duty cycle correction factor (in dB) associated with the pulse modulation as shown in Equation (10):

**Average factor in dB = 20 log (duty cycle)**

### 7.3.EUT Configuration on Measurement

The following equipment are installed on average factor Measurement to meet the commission requirements and operating regulations in a manner which tends to maximize its emission characteristics in normal application.

#### 7.3.1. REMOTE CONTROL

Model Number : FAN61T-3SP  
Serial Number : N/A  
Manufacturer : Carewell Electric Technology (Zhongshan) Co., Ltd.

### 7.4.Operating Condition of EUT

7.4.1.Setup the EUT and simulator as shown as Section 7.1.

7.4.2.Turn on the power of all equipment.

7.4.3.Let the EUT work in TX mode measure it.

### 7.5.Test Procedure

7.5.1.The time period over which the duty cycle is measured is 100 milliseconds, or the repetition cycle, whichever is a shorter time frame. The worst case (highest percentage on) duty cycle is used for the calculation.

7.5.2.Set SPA Center Frequency = Fundamental frequency, RBW = 100 kHz, VBW = 100 kHz, Span = 0 Hz.

7.5.3.Set EUT as normal operation.

7.5.4.Set SPA View. Delta Mark time.

### 7.6. Measurement Result

**The duty cycle is simply the on time divided by the period:**

The duration of one cycle = 34.638ms

Effective period of the cycle =  $(0.46377 \times 7) + (0.74638 \times 19)$ ms = 17.42761 ms

DC =  $17.42761$ ms/ $34.638$ ms = 0.503

**Therefore, the average factor is found by  $20\log 0.503 = -5.97$ dB**

The spectral diagrams in appendix I.


## 8. ANTENNA REQUIREMENT

### 8.1. The Requirement

According to Section 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device.

### 8.2. Antenna Construction

Device is equipped with permanent attached antenna, which isn't displaced by other antenna. The Antenna gain of EUT is 0dBi. Therefore, the equipment complies with the antenna requirement of RSS GEN 8.3.



Antenna

# APPENDIX I (Test Curves)



**ACCURATE TECHNOLOGY CO., LTD.**


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber  
Tel:+86-0755-26503290  
Fax:+86-0755-26503396

Job No.: star2015 #1138  
Standard: FCC Class B 3M Radiated  
Test item: Radiation Test  
Temp.( C)/Hum.(%) 25 C / 55 %  
EUT: REMOTE CONTROL  
Mode: TX  
Model: FAN61T-3SP  
Manufacturer: Carewell

Polarization: Horizontal  
Power Source: DC 3V  
Date: 15/09/04/  
Time: 8/57/23  
Engineer Signature:  
Distance: 3m

Note: Report No.:ATE20151900



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	315.2599	96.10	-15.91	80.19	95.62	15.43	peak			
2	630.4895	70.15	-9.28	60.87	75.62	14.75	peak			
3	945.6212	60.81	-3.48	57.33	75.62	18.29	peak			



**ACCURATE TECHNOLOGY CO., LTD.**


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber  
Tel:+86-0755-26503290  
Fax:+86-0755-26503396

Job No.: star2015 #1137  
Standard: FCC Class B 3M Radiated  
Test item: Radiation Test  
Temp.( C)/Hum.(%) 25 C / 55 %  
EUT: REMOTE CONTROL  
Mode: TX  
Model: FAN61T-3SP  
Manufacturer: Carewell

Polarization: Vertical  
Power Source: DC 3V  
Date: 15/09/04/  
Time: 8/56/40  
Engineer Signature:  
Distance: 3m

Note: Report No.:ATE20151900



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	315.2599	88.94	-15.91	73.03	95.62	22.59	peak			
2	630.4993	67.29	-9.28	58.01	75.62	17.61	peak			
3	945.6211	56.18	-3.48	52.70	75.62	22.92	peak			



**ACCURATE TECHNOLOGY CO., LTD.**


F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber  
Tel:+86-0755-26503290  
Fax:+86-0755-26503396

Job No.: star2015 #1140  
Standard: FCC Class B 3M Radiated  
Test item: Radiation Test  
Temp.( C)/Hum.(%) 25 C / 55 %  
EUT: REMOTE CONTROL  
Mode: TX  
Model: FAN61T-3SP  
Manufacturer: Carewell

Polarization: Horizontal  
Power Source: DC 3V  
Date: 15/09/04/  
Time: 9/01/02  
Engineer Signature:  
Distance: 3m

Note: Report No.:ATE20151900



No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	1260.747	64.98	-12.03	52.95	74.00	-21.05	peak			
2	1575.330	59.43	-11.02	48.41	74.00	-25.59	peak			






**ACCURATE TECHNOLOGY CO., LTD.**

F1,Bldg,A,Changyuan New Material Port Keyuan Rd,  
Science & Industry Park,Nanshan Shenzhen,P.R.China

Site: 1# Chamber  
Tel:+86-0755-26503290  
Fax:+86-0755-26503396


Job No.: star2015 #1139	Polarization: Vertical
Standard: FCC Class B 3M Radiated	Power Source: DC 3V
Test item: Radiation Test	Date: 15/09/04/
Temp.( C)/Hum.(%) 25 C / 55 %	Time: 8/59/45
EUT: REMOTE CONTROL	Engineer Signature:
Mode: TX	Distance: 3m
Model: FAN61T-3SP	
Manufacturer: Carewell	

Note: Report No.:ATE20151900




No.	Freq. (MHz)	Reading (dBuV/m)	Factor (dB)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Detector	Height (cm)	Degree (deg.)	Remark
1	1260.747	60.23	-12.03	48.20	74.00	-25.80	peak			
2	1575.330	61.76	-11.02	50.74	74.00	-23.26	peak			






Date: 6.SEP.2015 17:57:14




Date: 6.SEP.2015 18:06:56

Release Time = 2.7391s


The graph shows the pattern of coding during the signal transmission.  
The duration of one cycle = 34.638 ms.



Date: 6.SEP.2015 18:02:01



The graph shows the duration of 'on' signal. From marker 1 to marker 2, duration is 0.46377ms.



The graph shows the duration of 'on' signal. From marker 1 to marker 2, duration is 0.74638ms.