




# FCC Radio Test Report

## FCC ID: 2AAZR-HSD8033A-1

### Original Grant

**Report No.** : TB-FCC165700  
**Applicant** : SHENZHEN HIGHSTAR ELECTRICAL CO.,LTD  
**Equipment Under Test (EUT)**  
**EUT Name** : MINI BLUETOOTH SPEAKER WITH FAN  
**Model No.** : HSD8033A  
**Serial Model No.** : N/A  
**Brand Name** : ---  
**Receipt Date** : 2019-02-28  
**Test Date** : 2019-03-01 to 2019-05-05  
**Issue Date** : 2019-05-06  
**Standards** : FCC Part 15, Subpart C (15.247:2019)  
**Test Method** : ANSI C63.10: 2013  
**Conclusions** : **PASS**

In the configuration tested, the EUT complied with the standards specified above,

**Test/Witness Engineer** :  Jason Xu  
**Engineer Supervisor** :  Ivan Su  
**Engineer Manager** :  Ray Lai

This report details the results of the testing carried out on one sample. The results contained in this test report do not relate to other samples of the same product. The manufacturer should ensure that all products in series production are in conformity with the product sample detailed in the report.



---

---

## Contents

<b>CONTENTS.....</b>	<b>2</b>
<b>1. GENERAL INFORMATION ABOUT EUT .....</b>	<b>5</b>
1.1 Client Information.....	5
1.2 General Description of EUT (Equipment Under Test) .....	5
1.3 Block Diagram Showing the Configuration of System Tested.....	6
1.4 Description of Support Units .....	6
1.5 Description of Test Mode.....	7
1.6 Description of Test Software Setting .....	8
1.7 Measurement Uncertainty .....	8
1.8 Test Facility.....	9
<b>2. TEST SUMMARY .....</b>	<b>10</b>
<b>3. TEST EQUIPMENT.....</b>	<b>11</b>
<b>4. CONDUCTED EMISSION TEST .....</b>	<b>12</b>
4.1 Test Standard and Limit.....	12
4.2 Test Setup.....	12
4.3 Test Procedure.....	12
4.4 EUT Operating Mode .....	13
4.5 Test Data.....	13
<b>5. RADIATED EMISSION TEST .....</b>	<b>14</b>
5.1 Test Standard and Limit.....	14
5.2 Test Setup.....	15
5.3 Test Procedure.....	16
5.4 EUT Operating Condition .....	17
5.5 Test Data.....	17
<b>6. RESTRICTED BANDS AND BAND-EDGE TEST .....</b>	<b>18</b>
6.1 Test Standard and Limit.....	18
6.2 Test Setup.....	18
6.3 Test Procedure.....	18
6.4 EUT Operating Condition .....	19
6.5 Test Data.....	19
<b>7. BANDWIDTH TEST.....</b>	<b>20</b>
7.1 Test Standard and Limit.....	20
7.2 Test Setup.....	20
7.3 Test Procedure.....	20
7.4 EUT Operating Condition .....	20
7.5 Test Data.....	20
<b>8. PEAK OUTPUT POWER TEST.....</b>	<b>21</b>
8.1 Test Standard and Limit.....	21
8.2 Test Setup.....	21



8.3 Test Procedure.....	21
8.4 EUT Operating Condition .....	21
8.5 Test Data.....	21
<b>9. POWER SPECTRAL DENSITY TEST .....</b>	<b>22</b>
9.1 Test Standard and Limit.....	22
9.2 Test Setup.....	22
9.3 Test Procedure.....	22
9.4 EUT Operating Condition .....	22
9.5 Test Data.....	22
<b>10. ANTENNA REQUIREMENT.....</b>	<b>23</b>
10.1 Standard Requirement.....	23
10.2 Antenna Connected Construction.....	23
10.3 Result.....	23
<b>ATTACHMENT A-- CONDUCTED EMISSION TEST DATA .....</b>	<b>24</b>
<b>ATTACHMENT B-- RADIATED EMISSION TEST DATA .....</b>	<b>26</b>
<b>ATTACHMENT C-- RESTRICTED BANDS REQUIREMENT TEST DATA.....</b>	<b>34</b>
<b>ATTACHMENT D-- CONDUCTED RF SPURIOUS EMISSION TEST DATA.....</b>	<b>39</b>
<b>ATTACHMENT E-- BANDWIDTH TEST DATA.....</b>	<b>40</b>
<b>ATTACHMENT F-- PEAK OUTPUT POWER TEST DATA.....</b>	<b>42</b>
<b>ATTACHMENT G-- POWER SPECTRAL DENSITY TEST DATA.....</b>	<b>44</b>

---

---

### Revision History

Report No.	Version	Description	Issued Date
TB-FCC165700	Rev.01	Initial issue of report	2019-05-06



# 1. General Information about EUT

## 1.1 Client Information

<b>Applicant</b>	:	SHENZHEN HIGHSTAR ELECTRICAL CO.,LTD
<b>Address</b>	:	2F,4&5F,Building6,Ya Lian Highstar Industrial Zone, 5022 Wuhe Avenue,Bantian Street,Longgang District, Shenzhen, China
<b>Manufacturer</b>	:	SHENZHEN HIGHSTAR ELECTRICAL CO.,LTD
<b>Address</b>	:	2F,4&5F,Building6,Ya Lian Highstar Industrial Zone, 5022 Wuhe Avenue,Bantian Street,Longgang District, Shenzhen, China

## 1.2 General Description of EUT (Equipment Under Test)

<b>EUT Name</b>	:	MINI BLUETOOTH SPEAKER WITH FAN	
<b>Models No.</b>	:	HSD8033A	
<b>Model Difference</b>	:	N/A	
<b>Product Description</b>	:	Operation Frequency:	Bluetooth V4.2: 2402~2480 MHz
		Number of Channel:	Bluetooth: 40 Channels <small>See Note 2</small>
		Max Peak Output Power:	Bluetooth: -9.479dBm(GFSK)
		Antenna Gain:	-0.68dBi PCB Antenna
		Modulation Type:	GFSK (1 Mbps)
<b>Power Supply</b>	:	DC Voltage Supply from Adapter DC Voltage supplied by Li-ion battery.	
<b>Power Rating</b>	:	Iutput: DC 5.0V 1.5A by adapter DC 3.7V by 2200mAh Li-ion battery	
<b>Software Version</b>	:	N/A	
<b>Hardware Version</b>	:	N/A	
<b>Connecting I/O Port(S)</b>	:	Please refer to the User's Manual	

### Note:

This Test Report is FCC Part 15.247 for Bluetooth BLE, the test procedure follows the FCC KDB 558074 D01 v05r02.

- (1) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.
- (2) Antenna information provided by the applicant.

(3) Channel List:


Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
00	2402	14	2430	28	2458
01	2404	15	2432	29	2460
02	2406	16	2434	30	2462
03	2408	17	2436	31	2464
04	2410	18	2438	32	2466
05	2412	19	2440	33	2468
06	2414	20	2442	34	2470
07	2416	21	2444	35	2472
08	2418	22	2446	36	2474
09	2420	23	2448	37	2476
10	2422	24	2450	38	2478
11	2424	25	2452	39	2480
12	2426	26	2454		
13	2428	27	2456		

1.3 Block Diagram Showing the Configuration of System Tested

**Adapter + TX Mode**



**TX Mode**



1.4 Description of Support Units

**Equipment Information**



Name	Model	FCC ID/VOC	Manufacturer	Used “√”
----	----	----	----	----
Cable Information				
Number	Shielded Type	Ferrite Core	Length	Note
----	----	----	----	----

### 1.5 Description of Test Mode

To investigate the maximum EMI emission characteristics generates from EUT, the test system was pre-scanning tested base on the consideration of following EUT operation mode or test configuration mode which possible have effect on EMI emission level. Each of these EUT operation mode(s) or test configuration mode(s) mentioned follow was evaluated respectively.

For Conducted Test	
Final Test Mode	Description
Mode 1	Adapter + TX Mode

For Radiated Test	
Final Test Mode	Description
Mode 2	Adapter + TX Mode
Mode 3	Adapter + TX Mode (Channel 00/20/39)

**Note:**

- (1) For all test, we have verified the construction and function in typical operation. And all the test modes were carried out with the EUT in transmitting operation in maximum power with all kinds of data rate.  
According to ANSI C63.10 standards, the measurements are performed at the highest, middle, lowest available channels, and the worst case data rate as follows:  
BLE Mode: GFSK Modulation Transmitting mode.
- (2) During the testing procedure, the continuously transmitting with the maximum power mode was programmed by the customer.
- (3) The EUT is considered a portable unit; in normal use it was positioned on X-plane. The worst case was found positioned on X-plane. Therefore only the test data of this X-plane was used for radiated emission measurement test.

## 1.6 Description of Test Software Setting

During testing channel & Power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of RF setting.

Test Software Version			
Frequency	2402 MHz	2442MHz	2480 MHz
BLE GFSK	DEF	DEF	DEF

## 1.7 Measurement Uncertainty

The reported uncertainty of measurement  $y \pm U$ , where expanded uncertainty  $U$  is based on a standard uncertainty multiplied by a coverage factor of  $k=2$ , providing a level of confidence of approximately 95 %.

Test Item	Parameters	Expanded Uncertainty ( $U_{Lab}$ )
Conducted Emission	Level Accuracy: 9kHz~150kHz	$\pm 3.42$ dB
	150kHz to 30MHz	$\pm 3.42$ dB
Radiated Emission	Level Accuracy: 9kHz to 30 MHz	$\pm 4.60$ dB
Radiated Emission	Level Accuracy: 30MHz to 1000 MHz	$\pm 4.40$ dB
Radiated Emission	Level Accuracy: Above 1000MHz	$\pm 4.20$ dB



## 1.8 Test Facility

The testing was performed by the Shenzhen Toby Technology Co., Ltd., in their facilities located at:1A/F., Bldg.6, Yusheng Industrial Zone, The National Road No.107 Xixiang Section 467, Xixiang, Bao'an, Shenzhen, Guangdong, China.

At the time of testing, the following bodies accredited the Laboratory:

### **CNAS (L5813)**

The Laboratory has been accredited by CNAS to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the competence in the field of testing. And the Registration No.: CNAS L5813.

### **A2LA Certificate No.: 4750.01**

The laboratory has been accredited by American Association for Laboratory Accreditation(A2LA) to ISO/IEC 17025: 2005 General Requirements for the Competence of Testing and Calibration Laboratories for the technical competence in the field of Electrical Testing. And the A2LA Certificate No.: 4750.01.

FCC Accredited Test Site Number: 854351.

### **IC Registration No.: (11950A-1)**

The Laboratory has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing. The site registration: Site# 11950A-1.

## 2. Test Summary

FCC Part 15 Subpart C(15.247)/RSS 247 Issue 2				
Standard Section		Test Item	Judgment	Remark
FCC	IC			
15.203		Antenna Requirement	PASS	N/A
15.207(a)	RSS-GEN 7.2.4	Conducted Emission	PASS	N/A
15.205&15.247(d)	RSS-GEN 7.2.2	Band-Edge & Unwanted Emissions into Restricted Frequency	PASS	N/A
15.247(a)(2)	RSS 247 5.2 (1)	6dB Bandwidth	PASS	N/A
15.247(b)(3)	RSS 247 5.4 (4)	Conducted Max Output Power	PASS	N/A
15.247(e)	RSS 247 5.2 (2)	Power Spectral Density	PASS	N/A
15.205, 15.209&15.247(d)	RSS 247 5.5	Transmitter Radiated Spurious & Unwanted Emissions into Restricted Frequency	PASS	N/A

**Note:** N/A is an abbreviation for Not Applicable.



### 3. Test Equipment

Conducted Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
EMI Test Receiver	Rohde & Schwarz	ESCI	100321	Jul.18, 2018	Jul. 17, 2019
RF Switching Unit	Compliance Direction Systems Inc	RSU-A4	34403	Jul.18, 2018	Jul. 17, 2019
AMN	SCHWARZBECK	NNBL 8226-2	8226-2/164	Jul.18, 2018	Jul. 17, 2019
LISN	Rohde & Schwarz	ENV216	101131	Jul.18, 2018	Jul. 17, 2019
Radiation Emission Test					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul.18, 2018	Jul. 17, 2019
EMI Test Receiver	Rohde & Schwarz	ESPI	100010/007	Jul.18, 2018	Jul. 17, 2019
Bilog Antenna	ETS-LINDGREN	3142E	00117537	Jan. 27, 2019	Jan. 26, 2020
Bilog Antenna	ETS-LINDGREN	3142E	00117542	Jan. 27, 2019	Jan. 26, 2020
Horn Antenna	ETS-LINDGREN	3117	00143207	Mar.03, 2019	Mar. 02, 2020
Horn Antenna	ETS-LINDGREN	3117	00143209	Mar.03, 2019	Mar. 02, 2020
Loop Antenna	SCHWARZBECK	FMZB 1519 B	1519B-059	Jul. 14, 2018	Jul.13, 2019
Pre-amplifier	Sonoma	310N	185903	Mar.04, 2019	Mar. 03, 2020
Pre-amplifier	HP	8449B	3008A00849	Mar.03, 2019	Mar. 02, 2020
Cable	HUBER+SUHNER	100	SUCOFLEX	Mar.03, 2019	Mar. 02, 2020
Positioning Controller	ETS-LINDGREN	2090	N/A	N/A	N/A
Antenna Conducted Emission					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal. Due Date
Spectrum Analyzer	Agilent	E4407B	MY45106456	Jul.18, 2018	Jul. 17, 2019
Spectrum Analyzer	Rohde & Schwarz	ESCI	100010/007	Jul.18, 2018	Jul. 17, 2019
MXA Signal Analyzer	Agilent	N9020A	MY49100060	Oct. 15, 2018	Sep. 14, 2019
Vector Signal Generator	Agilent	N5182A	MY50141294	Oct. 15, 2018	Sep. 14, 2019
Analog Signal Generator	Agilent	N5181A	MY50141953	Oct. 15, 2018	Sep. 14, 2019
RF Power Sensor	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO26	Oct. 15, 2018	Sep. 14, 2019
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO29	Oct. 15, 2018	Sep. 14, 2019
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO31	Oct. 15, 2018	Sep. 14, 2019
	DARE!! Instruments	RadiPowerRPR3006W	17I00015SNO33	Oct. 15, 2018	Sep. 14, 2019

## 4. Conducted Emission Test

### 4.1 Test Standard and Limit

#### 4.1.1 Test Standard

FCC Part 15.207

#### 4.1.2 Test Limit

**Conducted Emission Test Limit**

Frequency	Maximum RF Line Voltage (dB $\mu$ V)	
	Quasi-peak Level	Average Level
150kHz~500kHz	66 ~ 56 *	56 ~ 46 *
500kHz~5MHz	56	46
5MHz~30MHz	60	50


Notes:

(1) \*Decreasing linearly with logarithm of the frequency.

(2) The lower limit shall apply at the transition frequencies.

(3) The limit decrease in line with the logarithm of the frequency in the range of 0.15 to 0.50MHz.

### 4.2 Test Setup



### 4.3 Test Procedure

The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipments powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.

Interconnecting cables that hang closer than 40 cm to the ground plane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.



I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.

LISN at least 80 cm from nearest part of EUT chassis.

The bandwidth of EMI test receiver is set at 9 kHz, and the test frequency band is from 0.15MHz to 30MHz.

#### 4.4 EUT Operating Mode

Please refer to the description of test mode.

#### 4.5 Test Data

Please refer to the Attachment A.

## 5. Radiated Emission Test

### 5.1 Test Standard and Limit

#### 5.1.1 Test Standard

FCC Part 15.247(d)

#### 5.1.2 Test Limit

#### Radiated Emission Limits (9kHz~1000MHz)

Frequency (MHz)	Field Strength (microvolt/meter)	Measurement Distance (meters)
0.009~0.490	2400/F(KHz)	300
0.490~1.705	24000/F(KHz)	30
1.705~30.0	30	30
30~88	100	3
88~216	150	3
216~960	200	3
Above 960	500	3

#### Radiated Emission Limit (Above 1000MHz)


Frequency (MHz)	Distance Meters(at 3m)	
	Peak (dBuV/m)	Average (dBuV/m)
Above 1000	74	54

**Note:**


- (1) The tighter limit applies at the band edges.
- (2) Emission Level (dBuV/m)=20log Emission Level (uV/m)




5.2 Test Setup



Below 30MHz Test Setup



Below 1000MHz Test Setup



Above 1GHz Test Setup

### 5.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.



## 5.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

## 5.5 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

Please refer to the Attachment B.

## 6. Restricted Bands and Band-edge test

### 6.1 Test Standard and Limit


#### 6.1.1 Test Standard

FCC Part 15.247(d) FCC Part 15.205

#### 6.1.2 Test Limit

Restricted Frequency Band (MHz)	Distance Meters(at 3m)	
	Peak (dBuV/m)	Average (dBuV/m)
2310 ~2390	74	54
2483.5 ~2500	74	54

### 6.2 Test Setup



### 6.3 Test Procedure

- (1) The measuring distance of 3m shall be used for measurements at frequency up to 1GHz and above 1 GHz. The EUT was placed on a rotating 0.8m high above ground, the table was rotated 360 degrees to determine the position of the highest radiation.
- (2) Measurements at frequency above 1GHz. The EUT was placed on a rotating 1.5m high above the ground. RF absorbers covered the ground plane with a minimum area of 3.0m by 3.0m between the EUT and measurement receiver antenna. The RF absorber shall not exceed 30cm in high above the conducting floor. The table was rotated 360 degrees to determine the position of the highest radiation.
- (3) The Test antenna shall vary between 1m and 4m, Both Horizontal and Vertical antenna are set to make measurement.
- (4) The initial step in collecting conducted emission data is a spectrum analyzer peak detector



mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.

- (5) If the Peak Mode measured value compliance with and lower than Quasi Peak Mode Limit Bellow 1 GHz, the EUT shall be deemed to meet QP Limits and then no additional QP Mode measurement performed. But the Peak Value and average value both need to comply with applicable limit above 1 GHz.
- (6) Testing frequency range below 1GHz the measuring instrument use VBW=120 kHz with Quasi-peak detection.
- (7) Testing frequency range above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.
- (8) For the actual test configuration, please see the test setup photo.

#### 6.4 EUT Operating Condition

The Equipment Under Test was set to Continual Transmitting in maximum power.

#### 6.5 Test Data

Remark: During testing above 1GHz the measuring instrument use RBW=1 MHz and VBW=3 MHz with Peak Detector for Peak Values, and use RBW=1 MHz and VBW=10 Hz with Peak Detector for Average Values.

Please refer to the Attachment C.



## 7. Bandwidth Test

### 7.1 Test Standard and Limit


#### 7.1.1 Test Standard

FCC Part 15.247 (a)(2)

#### 7.1.2 Test Limit

FCC Part 15 Subpart C(15.247)/RSS-247		
Test Item	Limit	Frequency Range(MHz)
Bandwidth	$\geq 500$ KHz (6dB bandwidth)	2400~2483.5

### 7.2 Test Setup



### 7.3 Test Procedure

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) The bandwidth is measured at an amplitude level reduced 6dB from the reference level. The reference level is the level of the highest amplitude signal observed from the transmitter at the fundamental frequency. Once the reference level is established, the equipment is conditioned with typical modulating signal to produce the worst -case (i.e the widest) bandwidth.
- (3) Measure the channel separation the spectrum analyzer was set to Resolution Bandwidth:100 kHz, and Video Bandwidth:300 kHz, Detector: Peak, Sweep Time set auto.

### 7.4 EUT Operating Condition

The EUT was set to continuously transmitting in each mode and low, middle and high channel for the test.

### 7.5 Test Data

Please refer to the Attachment D.



## 8. Peak Output Power Test

### 8.1 Test Standard and Limit


#### 8.1.1 Test Standard

FCC Part 15.247 (b)(3)

#### 8.1.2 Test Limit

FCC Part 15 Subpart C(15.247)/RSS-247		
Test Item	Limit	Frequency Range(MHz)
Peak Output Power	1 Watt or 30 dBm	2400~2483.5

### 8.2 Test Setup



### 8.3 Test Procedure

The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement is according to section 9.1.1 of KDB 558074 D01 DTS Meas Guidance v04.

- (1) Set the  $RBW \geq DTS$  Bandwidth
- (2) Set  $VBW \geq 3 * RBW$
- (3) Set  $Span \geq 3 * RBW$
- (4) Sweep time=auto
- (5) Detector= peak
- (6) Trace mode= maxhold.
- (7) Allow trace to fully stabilize, and then use peak marker function to determine the peak amplitude level.

### 8.4 EUT Operating Condition

The EUT was set to continuously transmitting in the max power during the test.

### 8.5 Test Data

Please refer to the Attachment E.

## 9. Power Spectral Density Test

### 9.1 Test Standard and Limit


#### 9.1.1 Test Standard

FCC Part 15.247 (e)

#### 9.1.2 Test Limit

FCC Part 15 Subpart C(15.247)		
Test Item	Limit	Frequency Range(MHz)
Power Spectral Density	8dBm(in any 3 kHz)	2400~2483.5

### 9.2 Test Setup



### 9.3 Test Procedure

The EUT was directly connected to the Spectrum Analyzer and antenna output port as show in the block diagram above. The measurement according to section 10.2 of KDB 558074 D01 DTS Meas Guidance v04.

- (1) The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram above.
- (2) Set analyser center frequency to DTS channel center frequency.
- (3) Set the span to 1.5 times the DTS bandwidth.
- (4) Set the RBW to: 3 kHz
- (5) Set the VBW to: 10 kHz
- (6) Detector: peak
- (7) Sweep time: auto
- (8) Allow trace to fully stabilize. Then use the peak marker function to determine the maximum amplitude level.

### 9.4 EUT Operating Condition

The EUT was set to continuously transmitting in each mode and low, Middle and high channel for the test.

### 9.5 Test Data

Please refer to the Attachment F.



## 10. Antenna Requirement

### 10.1 Standard Requirement

#### 10.1.1 Standard

FCC Part 15.203

#### 10.1.2 Requirement

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this Section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

### 10.2 Antenna Connected Construction

The gains of the antenna used for transmitting is -0.68dBi, and the antenna de-signed with permanent attachment and no consideration of replacement. Please see the EUT photo for details.


### 10.3 Result

The EUT antenna is PCB Antenna. It complies with the standard requirement.

Antenna Type
<input checked="" type="checkbox"/> Permanent attached antenna
<input type="checkbox"/> Unique connector antenna
<input type="checkbox"/> Professional installation antenna

## Attachment A-- Conducted Emission Test Data

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120V/ 60Hz		
Terminal:	Line		
Test Mode:	Charging + BLE Mode 2402Mhz		
Remark:	All channels have been tested and Shows only the worst channels.		




No. Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1	4.1860	13.44	9.69	23.13	56.00	-32.87	QP
2	4.1860	4.26	9.69	13.95	46.00	-32.05	AVG
3	4.8260	16.24	9.73	25.97	56.00	-30.03	QP
4	4.8260	6.06	9.73	15.79	46.00	-30.21	AVG
5	5.7860	15.85	9.79	25.64	60.00	-34.36	QP
6	5.7860	7.47	9.79	17.26	50.00	-32.74	AVG
7	7.4020	15.64	9.89	25.53	60.00	-34.47	QP
8	7.4020	5.89	9.89	15.78	50.00	-34.22	AVG
9 *	8.6700	20.52	9.97	30.49	60.00	-29.51	QP
10	8.6700	5.84	9.97	15.81	50.00	-34.19	AVG
11	9.3020	8.47	10.01	18.48	60.00	-41.52	QP
12	9.3020	0.52	10.01	10.53	50.00	-39.47	AVG

Emission Level= Read Level+ Correct Factor



<b>Temperature:</b>	25 °C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	AC 120V/ 60Hz		
<b>Terminal:</b>	Neutral		
<b>Test Mode:</b>	Charging + BLE Mode 2402Mhz		
<b>Remark:</b>	All channels have been tested and Shows only the worst channels.		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector
1		1.9100	16.22	9.61	25.83	56.00	-30.17	QP
2		1.9100	6.10	9.61	15.71	46.00	-30.29	AVG
3		3.4860	14.39	9.69	24.08	56.00	-31.92	QP
4		3.4860	4.51	9.69	14.20	46.00	-31.80	AVG
5		4.7540	13.62	9.86	23.48	56.00	-32.52	QP
6		4.7540	4.10	9.86	13.96	46.00	-32.04	AVG
7		6.3900	23.29	10.17	33.46	60.00	-26.54	QP
8		6.3900	11.23	10.17	21.40	50.00	-28.60	AVG
9		7.3500	26.58	10.28	36.86	60.00	-23.14	QP
10		7.3500	12.40	10.28	22.68	50.00	-27.32	AVG
11	*	8.6380	29.16	10.26	39.42	60.00	-20.58	QP
12		8.6380	13.15	10.26	23.41	50.00	-26.59	AVG

Emission Level= Read Level+ Correct Factor

## Attachment B-- Radiated Emission Test Data

### 9 KHz~30 MHz


From 9 KHz to 30 MHz: Conclusion: PASS

Note: The amplitude of spurious emissions which are attenuated by more than 20dB

Below the permissible value has no need to be reported.

### 30MHz~1GHz

<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V BY 2200MAH LI-ION BATTERY		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	BLE TX 2402 Mode		
<b>Remark:</b>	Only worse case is reported		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measurement dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	149.4857	53.47	-21.49	31.98	43.50	-11.52	QP
2		181.9202	47.72	-20.10	27.62	43.50	-15.88	QP
3		229.2931	45.36	-18.33	27.03	46.00	-18.97	QP
4		321.0608	47.33	-15.52	31.81	46.00	-14.19	QP
5		482.2156	43.20	-11.10	32.10	46.00	-13.90	QP
6		562.6624	43.31	-8.96	34.35	46.00	-11.65	QP

\*:Maximum data x:Over limit !:over margin



<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V BY 2200MAH LI-ION BATTERY		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	BLE TX 2402 Mode		
<b>Remark:</b>	Only worse case is reported		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		32.1795	47.36	-14.64	32.72	40.00	-7.28	QP
2	*	49.0145	57.35	-22.92	34.43	40.00	-5.57	QP
3		122.8340	56.98	-22.34	34.64	43.50	-8.86	QP
4		146.3735	55.87	-21.81	34.06	43.50	-9.44	QP
5		482.2156	48.52	-11.10	37.42	46.00	-8.58	QP
6		562.6624	46.98	-8.96	38.02	46.00	-7.98	QP

\*:Maximum data    x:Over limit    !:over margin

**Emission Level= Read Level+ Correct Factor**

**Above 1GHz**

<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 3.7V BY 2200MAH LI-ION BATTERY							
<b>Ant. Pol.</b>	Horizontal							
<b>Test Mode:</b>	BLE Mode TX 2402 MHz							
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.							
<hr/>								
No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4804.084	34.92	12.42	47.34	54.00	-6.66	AVG
2		4804.490	45.91	12.43	58.34	74.00	-15.66	peak
<hr/>								
<b>Emission Level= Read Level+ Correct Factor</b>								



<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 3.7V BY 2200MAH LI-ION BATTERY							
<b>Ant. Pol.</b>	Vertical							
<b>Test Mode:</b>	BLE Mode TX 2402 MHz							
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.							
<hr/>								
No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4803.886	37.14	12.42	49.56	54.00	-4.44	AVG
2		4804.258	47.03	12.42	59.45	74.00	-14.55	peak
<hr/>								
<b>Emission Level= Read Level+ Correct Factor</b>								

<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 3.7V BY 2200MAH LI-ION BATTERY							
<b>Ant. Pol.</b>	Horizontal							
<b>Test Mode:</b>	BLE Mode TX 2442 MHz							
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.							
<b>No. Mk.</b>	<b>Freq.</b>	<b>Reading Level</b>	<b>Correct Factor</b>	<b>Measurement</b>	<b>Limit</b>	<b>Over</b>		
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector	
1	*	4882.188	37.32	12.90	50.22	54.00	-3.78	AVG
2		4882.398	46.44	12.90	59.34	74.00	-14.66	peak
<b>Emission Level= Read Level+ Correct Factor</b>								



<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%					
<b>Test Voltage:</b>	DC 3.7V BY 2200MAH LI-ION BATTERY							
<b>Ant. Pol.</b>	Vertical							
<b>Test Mode:</b>	BLE Mode TX 2442 MHz							
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.							
<hr/>								
No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	*	4881.600	36.94	12.90	49.84	54.00	-4.16	AVG
2		4881.804	45.37	12.90	58.27	74.00	-15.73	peak
<hr/>								
<b>Emission Level= Read Level+ Correct Factor</b>								

<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.7V BY 2200MAH LI-ION BATTERY						
<b>Ant. Pol.</b>	Horizontal						
<b>Test Mode:</b>	BLE Mode TX 2480 MHz						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
<b>No. Mk.</b>	<b>Freq.</b>	<b>Reading Level</b>	<b>Correct Factor</b>	<b>Measurement</b>	<b>Limit</b>	<b>Over</b>	
	MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB	Detector
1	4960.070	45.32	13.37	58.69	74.00	-15.31	peak
2 *	4960.070	37.82	13.37	51.19	54.00	-2.81	AVG

**Emission Level= Read Level+ Correct Factor**



<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%				
<b>Test Voltage:</b>	DC 3.7V BY 2200MAH LI-ION BATTERY						
<b>Ant. Pol.</b>	Vertical						
<b>Test Mode:</b>	BLE Mode TX 2480 MHz						
<b>Remark:</b>	No report for the emission which more than 10 dB below the prescribed limit.						
<hr/>							
<b>No.</b>	<b>Mk.</b>	<b>Freq.</b>	<b>Reading Level</b>	<b>Correct Factor</b>	<b>Measurement</b>	<b>Limit</b>	<b>Over</b>
		MHz	dBuV	dB/m	dBuV/m	dBuV/m	dB Detector
1	*	4960.030	37.95	13.37	51.32	54.00	-2.68 AVG
2		4960.110	46.00	13.37	59.37	74.00	-14.63 peak
<hr/>							
<b>Emission Level= Read Level+ Correct Factor</b>							

## Attachment C-- Restricted Bands Requirement Test Data

### (1) Radiation Test

<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V BY 2200MAH LI-ION BATTERY		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	BLE Mode TX 2402 MHz		
<b>Remark:</b>	N/A		

100.0 dBuV/m


3	2390.000	47.83	1.51	49.34	74.00	-24.66	peak
4	2390.000	34.79	1.51	36.30	54.00	-17.70	AVG
5	X 2402.200	94.10	1.56	95.66	Fundamental Frequency		peak
6	* 2402.200	89.39	1.56	90.95	Fundamental Frequency		AVG

**Emission Level= Read Level+ Correct Factor**




<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V BY 2200MAH LI-ION BATTERY		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	BLE Mode TX 2402 MHz		
<b>Remark:</b>	N/A		



No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1		2390.000	44.76	1.51	46.27	74.00	-27.73	peak
2		2390.000	31.47	1.51	32.98	54.00	-21.02	AVG
3	*	2402.200	75.47	1.56	77.03	Fundamental Frequency		AVG
4	X	2402.400	88.71	1.56	90.27	Fundamental Frequency		peak

Emission Level= Read Level+ Correct Factor

<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V BY 2200MAH LI-ION BATTERY		
<b>Ant. Pol.</b>	Horizontal		
<b>Test Mode:</b>	BLE Mode TX 2480 MHz		
<b>Remark:</b>	N/A		




No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	X	2480.000	94.38	2.07	96.45	Fundamental Frequency		peak
2	*	2480.000	79.85	2.07	81.92	Fundamental Frequency		AVG
3		2483.500	57.28	2.10	59.38	74.00	-14.62	peak
4		2483.500	47.01	2.10	49.11	54.00	-4.89	AVG

Emission Level= Read Level+ Correct Factor



<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V BY 2200MAH LI-ION BATTERY		
<b>Ant. Pol.</b>	Vertical		
<b>Test Mode:</b>	BLE Mode TX 2480 MHz		
<b>Remark:</b>	N/A		





No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB/m	Measure- ment dBuV/m	Limit dBuV/m	Over dB	Detector
1	*	2480.000	77.98	2.07	80.05	Fundamental Frequency		AVG
2	X	2480.200	92.06	2.07	94.13	Fundamental Frequency		peak
3		2483.500	55.41	2.10	57.51	74.00	-16.49	peak
4		2483.500	45.19	2.10	47.29	54.00	-6.71	AVG

Emission Level= Read Level+ Correct Factor

**(2) Conducted Band Edge Test**

<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V BY 2200MAH LI-ION BATTERY		
<b>Test Mode:</b>	BLE Mode TX 2402MHz / BLE Mode TX 2480MHz		
<b>Remark:</b>	The EUT is programed in continuously transmitting mode		






## Attachment D-- Conducted RF Spurious Emission Test Data

Temperature:	25 °C	Relative Humidity:	55%
Test Voltage:	AC 120/60Hz		
Test Mode:	TX BLE Mode		
Remark:	This report only shall the worst case mode.		

2402 MHz

0.03GHz-26.5GHz




## Attachment E-- Bandwidth Test Data

Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 3.7V BY 2200MAH LI-ION BATTERY		
Test Mode:	BLE TX Mode		
Channel frequency (MHz)	6dB Bandwidth (kHz)	99% Bandwidth (kHz)	Limit (kHz)
2402	690.640	1065.4	>=500
2442	705.524	1060.8	
2480	714.134	1056.2	


BLE Mode

2402 MHz






**BLE Mode**  
**2442 MHz**



**BLE Mode**  
**2480 MHz**




### Attachment F-- Peak Output Power Test Data


<b>Temperature:</b>	25°C	<b>Relative Humidity:</b>	55%
<b>Test Voltage:</b>	DC 3.7V BY 2200MAH LI-ION BATTERY		
<b>Test Mode:</b>	BLE TX Mode		
<b>Channel frequency (MHz)</b>	<b>Test Result (dBm)</b>	<b>Limit (dBm)</b>	
2402	-9.479	<b>30</b>	
2442	-9.826		
2480	-9.739		
<b>BLE Mode</b>			
<b>2402 MHz</b>			



**BLE Mode**  
**2442 MHz**



**BLE Mode**  
**2480 MHz**




## Attachment G-- Power Spectral Density Test Data

Temperature:	25°C	Relative Humidity:	55%
Test Voltage:	DC 3.7V BY 2200MAH LI-ION BATTERY		
Test Mode:	BLE TX Mode		
Channel Frequency (MHz)	Power Density (dBm/3KHz)	Limit (dBm/3KHz)	Result
2402	-22.54	8	PASS
2442	-22.86		
2480	-22.80		
<b>BLE Mode</b>			
<b>2402 MHz</b>			




**BLE Mode**

**2442 MHz**



**BLE Mode**

**2480 MHz**



-----END OF REPORT-----