

# MPE REPORT

FCC ID: 2AB22-EWN-S12

Date of issue: Dec. 27, 2018

Report Number:	MTi181105E029
Sample Description:	White Noise Machine with Bluetooth Speaker
Model(s):	EWN-S12
Applicant:	Etekcitey Corporation
Address:	1202 N Miller St. Suite A, Anaheim, CA 92806, USA
Date of Test:	Nov. 01, 2018 to Dec. 27, 2018

Shenzhen Microtest Co., Ltd.

<http://www.mtitest.com>

<b>TEST RESULT CERTIFICATION</b>	
Applicant's name:	Etekc City Corporation
Address:	1202 N Miller St. Suite A, Anaheim, CA 92806, USA
Manufacture's Name:	Dongguan Excellent Speed Electronic Technology Co., Ltd.
Address:	2F, Building B, 1SO Technology Park, Baoshi Industrial Park, No.12 Baoshi Rd, Jiaoyitang Village, Tangxia Town, Dongguan, China.
Product name:	White Noise Machine with Bluetooth Speaker
Trademark:	ETEKCITY
Model and/or type reference:	EWN-S12
Serial Model:	N/A
RF Exposure Procedures:	KDB 447498 D01 v06

*This device described above has been tested by Shenzhen Microtest Co., Ltd and the test results show that the equipment under test (EUT) is in compliance with the FCC requirements. And it is applicable only to the tested sample identified in the report.*

Tested by:




---

Demi Mu

Dec. 27, 2018

Reviewed by:




---

Blue Zheng

Dec. 27, 2018

Approved by:




---

Smith Chen

Dec. 27, 2018

## RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency range (MHz)	Electric field strength (V/m)	Magnetic field strength (A/m)	Power density (mW/cm <sup>2</sup> )	Averaging time (minutes)
<b>(A) Limits for Occupational/Controlled Exposure</b>				
0.3-3.0	614	1.63	*100	6
3.0-30	1842/f	4.89/f	*900/f <sup>2</sup>	6
30-300	61.4	0.163	1.0	6
300-1,500			f/300	6
1,500-100,000			5	6
<b>(B) Limits for General Population/Uncontrolled Exposure</b>				
0.3-1.34	614	1.63	*100	30
1.34-30	824/f	2.19/f	*180/f <sup>2</sup>	30
30-300	27.5	0.073	0.2	30
300-1,500			f/1500	30
1,500-100,000			1.0	30

f = frequency in MHz \* = Plane-wave equivalent power density

### MPE Calculation Method

Friis transmission formula:  $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

$P_d$  = Power density in mW/cm<sup>2</sup>

$P_{out}$  = output power to antenna in mW

$G$  = Numeric gain of the antenna relative to isotropic antenna

$\pi$  = 3.1415926

$R$  = distance between observation point and center of the radiator in cm (20cm)

$P_d$  the limit of MPE, 1mW/cm<sup>2</sup>. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

## Measurement Result

### BT:

Operation Frequency: BT GFSK/ $\pi$ /4-DQPSK/8DPSK: 2402-2480MHz,

Power density limited: 1mW/ cm<sup>2</sup>

Antenna Type: BT Antenna: PCB Antenna;

BT antenna gain: -0.33dBi

R=20cm

$mW=10^{(dBm/10)}$

antenna gain Numeric= $10^{(dBi/10)}=10^{(-0.33/10)}=0.93$

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
				tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
2402	GFSK	-1.881	-1±1	0	1.000	-0.33	0.93	0.0002	1
2441		-1.090	-1±1	0	1.000	-0.33	0.93	0.0002	1
2480		-1.651	-1±1	0	1.000	-0.33	0.93	0.0002	1
2402	$\pi$ /4-DQPSK	-0.664	0±1	1	1.259	-0.33	0.93	0.0002	1
2441		0.846	0±1	1	1.259	-0.33	0.93	0.0002	1
2480		0.264	0±1	1	1.259	-0.33	0.93	0.0002	1
2402	8DPSK	-0.432	0±1	1	1.259	-0.33	0.93	0.0002	1
2441		1.019	0±1	1	1.259	-0.33	0.93	0.0002	1
2480		0.429	0±1	1	1.259	-0.33	0.93	0.0002	1

### Conclusion:

For the max result: 0.0002 ≤ 1.0 for 1g SAR, No SAR is required.

### BLE

Channel Freq. (MHz)	modulation	conducted power (dBm)	Tune-up power (dBm)	Max		Antenna		Evaluation result (mW/cm <sup>2</sup> )	Power density Limits (mW/cm <sup>2</sup> )
				tune-up power		Gain			
				(dBm)	(mW)	(dBi)	Numeric		
2402	GFSK	-2.051	-1±1	0	1.000	0.33	0.93	0.0002	1
2440		-0.528	-1±1	0	1.000	0.33	0.93	0.0002	1
2480		-1.123	-1±1	0	1.000	0.33	0.93	0.0002	1

### Conclusion:

For the max result: 0.0002 ≤ 1.0 for 1g SAR, No SAR is required.

----END OF REPORT----