

MPE Calculation

Applicant:	LEEDARSON LIGHTING CO., LTD
Address:	Xingda Road, Xingtai Industrial Zone, Changtai County, Zhangzhou, Fujian, China
Product:	Mini Gateway
FCC ID:	2AB2Q-7BGWBWAH0
Model No.:	7B-GW-BWA-H0-01
Reference RF report #	68.950.19.0529.01 for Wi-Fi report 68.950.19.0528.01 for BLE report

According to subpart 15.247(i) and subpart §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

Limits for Maximum Permissible Exposure (MPE) (§1.1310, §2.1091)

(B) Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (minutes)
0.3–1.34	614	1.63	*(100)	30
1.34–30	824/f	2.19/f	*(180/f ²)	30
30–300	27.5	0.073	0.2	30
300–1,500	/	/	f/1500	30
1,500–100,000	/	/	1.0	30

f = frequency in MHz; * = Plane-wave equivalent power density;

According to §1.1310 and §2.1091 RF exposure is calculated.

Calculated Formulary:

Predication of MPE limit at a given distance

$S = PG/4 \pi R^2$ = power density (in appropriate units, e.g. mW/cm²);

P = power input to the antenna (in appropriate units, e.g., mW);

G = power gain of the antenna in the direction of interest relative to an isotropic radiator, the power gain factor, is normally numeric gain;

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm);

Calculated Data:

For Wi-Fi

Maximum peak output power at antenna input terminal (dBm):	15.1
Maximum peak output power at antenna input terminal (mW):	32.359
Prediction distance (cm):	20
Antenna Gain, typical (dBi):	2
Maximum Antenna Gain (numeric):	1.58
The worst case is power density at predication frequency at 20 cm (mW/cm ²):	0.01
MPE limit for general population exposure at prediction frequency (mW/cm ²):	1.0
0.01 (mW/cm ²) < 1 (mW/cm ²)	

For BLE

Maximum peak output power at antenna input terminal (dBm):	4.86
Maximum peak output power at antenna input terminal (mW):	3.06
Prediction distance (cm):	20
Antenna Gain, typical (dBi):	2
Maximum Antenna Gain (numeric):	1.58
The worst case is power density at predication frequency at 20 cm (mW/cm ²):	0.0009
MPE limit for general population exposure at prediction frequency (mW/cm ²):	1.0
0.0009 (mW/cm ²) < 1 (mW/cm ²)	


For simultaneous transmission evaluation

The worst case is power density at predication frequency at 20 cm (mW/cm ²):	0.0109
MPE limit for general population exposure at prediction frequency (mW/cm ²):	1.0
0.0109 (mW/cm ²) < 1 (mW/cm ²)	

Result: Compliant

TUV SUD China, Shenzhen Branch

Reviewed by:



Laurent Yuan/ EMC Project Manager

Date: 2019-06-17

Prepared By:



Henry Chen/EMC Project Engineer

Date: 2019-06-17