



# FCC RF EXPOSURE REPORT

### **CERTIFICATION TEST REPORT**

For

Wi-Fi and Bluetooth Module

### MODEL NUMBER: LA66701, LDE42FX11A

### **REPORT NUMBER: 4790941398-1-RF-3**

ISSUE DATE: August 24, 2023

FCC ID: 2AB2Q-LA66701

Prepared for

LEEDARSON LIGHTING CO., LTD Xingda Road, Xingtai Industrial Zone, Changtai County,Zhangzhou, Fujian China

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

> Tel: +86 769 22038881 Fax: +86 769 33244054 Website: www.ul.com



### **Revision History**

Rev.	Issue Date	Revisions	Revised By
V0	August 24, 2023	Initial Issue	



# TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS	.4
2.	TEST METHODOLOGY	.5
3.	FACILITIES AND ACCREDITATION	.5
4.	DESCRIPTION OF EUT	.6
5.	REQUIREMENT	.7



## **1. ATTESTATION OF TEST RESULTS**

#### **Applicant Information**

Company Name:	LEEDARSON LIGHTING CO., LTD
Address:	Xingda Road, Xingtai Industrial Zone, Changtai
	County,Zhangzhou, Fujian China

#### Manufacturer Information

Company Name:	LEEDARSON LIGHTING CO., LTD
Address:	Xingda Road, Xingtai Industrial Zone, Changtai
	County, Zhangzhou, Fujian China

### **EUT Information**

EUT Name:	Wi-Fi and Bluetooth Module
Model:	LA66701
Series Model:	LDE42FX11A
Model Difference:	Please refer to section 4
Sample Received Date:	July 25, 2023
Sample Status:	Normal
Sample ID:	6298008
Date of Tested:	July 25, 2023 to August 24, 2023

APPLICABLE STANDARDS			
STANDARD	TEST RESULTS		
FCC 47CFR§2.1091	PASS		

Prepared By:

Jammy Huang

Fanny Huang **Engineer Project Associate**  Verry

Checked By:

**Denny Huang** Senior Project Engineer

Suny

Approved By:

olver

Stephen Guo **Operations Manager** 



# 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 and KDB447498D01v06.

# 3. FACILITIES AND ACCREDITATION

	A2LA (Certificate No.: 4102.01)
	<ul> <li>A2LA (Certificate No.: 4102.01)</li> <li>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</li> <li>FCC (FCC Designation No.: CN1187)</li> <li>UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject</li> </ul>
	to the Commission's Delcaration of Conformity (DoC) and Certification rules
	ISED (Company No.: 21320)
Accreditation Certificate	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.
	VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011)
	UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	has been assessed and proved to be in compliance with VCCI, the
	Membership No. is 3793.
	Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004
	Shielding Room B, the VCCI registration No. is C-20012 and T-20011

Note: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China.



# 4. DESCRIPTION OF EUT

EUT Name:		WIFI+BT Module		
Model:		DT3AR1501		
Product	Frequency Range:	2402 MHz to 2480 MHz		
Description (BLE)	Type of Modulation:	GFSK		
, , , , , , , , , , , , , , , , , , ,	Data Rate:	1Mbps/2Mbps		
	Frequency Range:	2412 MHz to 2462 MHz		
Product Description (2.4G WLAN)	Type of Modulation:	IEEE 802.11b: DSSS(CCK, DQPSK, DBPSK) IEEE 802.11g/n: OFDM(64-QAM, 16-QAM, QPSK, BPSK)		
(2.46 WLAN)	Radio Technology:	IEEE 802.11b/g/n HT20/11n HT40		
Normal Test Voltage:		DC 5 V		



## 5. REQUIREMENT

### LIMIT AND CALCULATION METHOD

Systems operating under the provisions of FCC 47 CFR section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as mobile device whereby a distance of 0.2m normally can be maintained between the user and the device, and below RF Permissible Exposure limit shall comply with.

Limits for General Population/Uncontrolled Exposure

### **RF EXPOSURE LIMIT**

Frequency Range (MHz)	E-field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (Minutes)
0.3 1.34	614	1.63	(100)*	30
1.34 30	824/f	2.19/f	(180/f <sup>2</sup> )*	30
30 300	27.5	0.073	0.2	30
300 1500			f/1500	30
1500 100,000			1.0	30

### **CALCULATION METHOD**

S=PG/4πR<sup>2</sup> Where: S=power density P=power input to antenna G=power gain of the antenna in the direction of interest relative to an isotropic radiator R=distance to the center of radiation of the antenna



## CALCULATED RESULTS

Worst Case						
Mode	Max Tune Up Power	Antenna Gain	Power Density	Power Density Limit	Test Result	
	dBm	dBi	mW/cm2	mW/cm2		
BLE	20	4	0.04997	1.0	Complies	

Worst Case							
Mode	Max Tune Up Power	Antenna Gain	Power Density	Power Density Limit	Test Result		
	dBm	dBi	mW/cm2	mW/cm2			
WIFI 2.4G	20	4	0.04997	1.0	Complies		

Note:

1. The Power comes from report operation description.

2. BLE and WIFI cannot support simultaneous emission (declared by client).

3. The minimum separation distance of the device is greater than 20 cm, and 20 cm separation distance was set for calculation.

4. Calculate by WORST-CASE mode.

# END OF REPORT