



## FCC RF EXPOSURE REPORT

For

Wi-Fi Smart Plug

## MODEL NUMBER: HPPA11SWB

## FCC ID: 2AB2QHPPA11SWB

### **REPORT NUMBER: 4789546352-3**

## ISSUE DATE: July 17, 2020

Prepared for

LEEDARSON LIGHTING CO.,Ltd. XINGDA RD, XINGTAI INDUSTRIAL ZONE, CHANGTAI COUNTY, ZHANGZHOU, FUJIAN, 363900, CHINA

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone, Dongguan, People's Republic of China Tel: +86 769-22038881 Fax: +86 769 33244054 Website: www.ul.com

The results reported herein have been performed in accordance with the laboratory's terms of accreditation. This report shall not be reproduced except in full without the written approval of the Laboratory. The results in this report apply to the test sample(s) mentioned above at the time of the testing period only and are not to be used to indicate applicability to other similar products. This report does not imply that the product(s) has met the criteria for certification.



## TABLE OF CONTENTS

1.	ATTESTATION OF TEST RESULTS	3
2.	TEST METHODOLOGY	4
3.	FACILITIES AND ACCREDITATION	4
4.	REQUIREMENT	5



## **1. ATTESTATION OF TEST RESULTS**

Applicant InformationCompany Name:LEEDARSON LIGHTING CO.,Ltd.Address:XINGDA RD, XINGTAI INDUSTRIAL ZONE, CHANGTAI<br/>COUNTY, ZHANGZHOU, FUJIAN, 363900, CHINA

#### Manufacturer Information

Company Name:	LEEDARSON LIGHTING CO., Ltd.
Address:	XINGDA RD, XINGTAI INDUSTRIAL ZONE, CHANGTAI
	COUNTY, ZHANGZHOU, FUJIAN, 363900, CHINA

#### **EUT Information**

EUT Name:	Wi-Fi Smart Plug
Model:	HPPA11SWB
Sample Received Date:	July 6, 2020
Sample Status:	Normal
Sample ID:	3172174

APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
FCC 47CFR§2.1091	PASS
KDB-447498 D01 V06	

Prepared By:

Kebo. zhong.

Checked By:

Shenny been

Shawn Wen Laboratory Leader

Kebo Zhang Project Engineer

Approved By:

ephentin

Stephen Guo Laboratory Manager



# 2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with KDB 447498 D01 General RF Exposure Guidance v06.

# 3. FACILITIES AND ACCREDITATION

	A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch.
	has been assessed and proved to be in compliance with A2LA. <b>FCC (FCC Designation No.: CN1187)</b> UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Delcaration of Conformity (DoC) and Certification rules
Accreditation Certificate	ISED(Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with Industry Canada. The Company Number is 21320. VCCI (Registration No.: G-20019, R-20004, C-20012 and T-20011) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20019 and R-20004 Shielding Room B, the VCCI registration No. is C-20012 and T-20011

Note 1: All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, Song Shan Lake Hi tech Development Zone, Dongguan, 523808, China

Note 2: The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3: For below 30MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30MHz had been correlated to measurements performed on an OFS.



# 4. REQUIREMENT

## LIMIT

Limits for General Population/Uncontrolled Exposure

Limits for General Population/Uncontrolled Exposure				
Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm²)	Averaging Time  E  <sup>2</sup> ,  H  <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f2)*	30
30-300	27.5	0.073	0.2	30
300-1500			f/150	30
1500-100,000			1.0	30
Note 1: f = frequency in MHz, * means Plane-wave equivalent power density				

Note 2: General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over

their exposure.

Note 3: The limit value 1.0mW/cm<sup>2</sup> is available for this EUT.

## **MPE CALCULATION METHOD**

 $S = PG/(4\pi R^2)$ 

where: S = power density (in appropriate units, e.g. mW/ cm2)

P = power input to the antenna (in appropriate units, e.g., mW)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = distance to the center of radiation of the antenna (appropriate units, e.g., cm)

Radio Frequency Radiation Exposure Evaluation

WIFI 2.4G (Worst case)						
Operating	Max. Power	Max. Antenna Gain		Power density	Limit	
Mode	(dBm)	(dBi)	(num)	(mW/ cm <sup>2</sup> )		
2.4 G Wifi	18	-3.9	0.407	0.00511	1	
BLE	12	-3.9	0.407	0.00128	1	

Note:

1. The calculated distance is 20cm.

2. The customer declared that BT&WLAN 2.4G WIFI cannot transmit simultaneously.

## **END OF REPORT**