

## FCC 47 CFR MPE REPORT

ION Audio, LLC

PORTABLE BLUETOOTH®-ENABLED SPEAKER WITH  
LIGHTS AND PREMIUM WIDE SOUND

Model Number: PARTY BOOM™ PLUS

Additional Model: iPA163, PARTY\*\*\*\*\*, iPA163\*\*\*\*

FCC ID: 2AB3E-IPA163

Applicant:	ION Audio, LLC
Address:	200 Scenic View Drive, Cumberland, RI 02864 U.S.A.
Prepared By:	EST Technology Co., Ltd.
	Chilingxiang, Qishantou, Santun, Houjie, Dongguan, Guangdong, China
Tel: 86-769-83081888-808	

Report Number:	ESTE-R2212304
Date of Test:	Dec. 10~24, 2022
Date of Report:	Dec. 28, 2022

## Maximum Permissible Exposure

### 1. Applicable Standards

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess limit for maximum permissible exposure. In accordance with 47 CFR FCC Part 2 Subpart J, section 2.1091 this device has been defined as a mobile device whereby a distance of 0.2m normally can be maintained between the user and the device.

#### 1.1. Limits for Maximum Permissible Exposure (MPE)

##### (a) Limits for Occupational/Controlled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-3.0	614	1.63	(100)*	6
3.0-30	1842/f	4.89/f	(900/f)*	6
30-300	61.4	0.163	1.0	6
300-1500			F/300	6
1500-10000			5	6

##### (b) Limits for General Population / Uncontrolled Exposure

Frequency Range (MHz)	Electric Field Strength (E) (V/m)	Magnetic Field Strength (H) (A/m)	Power Density (S) (mW/cm <sup>2</sup> )	Averaging Times   E   <sup>2</sup> ,   H   <sup>2</sup> or S (minutes)
0.3-1.34	614	1.63	(100)*	30
1.34-30	824/f	2.19/f	(180/f)*	30
30-300	27.5	0.073	0.2	30
300-1500			F/1500	30
1500-10000			1.0	30

Note: f=frequency in MHz; \*Plane-wave equivalent power density

## 1.2. MPE Calculation Method

$$E \text{ (V/m)} = \frac{\sqrt{30 \times P \times G}}{d} \quad \text{Power Density: Pd (W/m}^2\text{)} = \frac{E^2}{377}$$

E = Electric Field (V/m)

P = Peak RF output Power (W)

G = EUT Antenna numeric gain (numeric)

d = Separation distance between radiator and human body (m)

The formula can be changed to

$$Pd = \frac{30 \times P \times G}{377 \times d^2}$$

From the peak EUT RF output power, the minimum mobile separation distance,  $d=0.2\text{m}$ , as well as the gain of the used antenna, the RF power density can be obtained

## 2. Conducted Power Result

Mode	Frequency (MHz)	Peak output power (dBm)	Peak output power (mW)
GFSK	2402	3.43	2.2029
	2441	2.98	1.9861
	2480	2.93	1.9634
$\pi/4$ -DQPSK	2402	3.93	2.4717
	2441	3.42	2.1979
	2480	3.36	2.1677
8-DPSK	2402	4.38	2.7416
	2441	3.70	2.3442
	2480	3.48	2.2284
BLE 1M	2402	3.19	2.0845
	2440	2.78	1.8967
	2480	2.65	1.8408
BLE 2M	2412	3.31	2.1429
	2440	2.90	1.9498
	2480	2.75	1.8836

### 3. Calculated Result and Limit

Mode	Peak output power (dBm)	Target power (dBm)	MAX Target power (dBm)	Antenna gain		Power Density (S) (mW /cm <sup>2</sup> )	Limited of Power Density (S) (mW /cm <sup>2</sup> )	Test Result
				(dBi)	(Linear)			
2.4G Band								
GFSK	3.43	3±1	4	1.78	1.5066	0.0008	1	Complies
$\pi/4$ -DQPSK	3.93	3±1	4	1.78	1.5066	0.0008	1	Complies
8-DPSK	4.38	4±1	5	1.78	1.5066	0.0009	1	Complies
BLE	3.31	3±1	4	1.78	1.5066	0.0008	1	Complies

**End of Test Report**