

TEST REPORT

Reference No...... : WTS14S0312001E
FCC ID : 2AB3XIC6008
Applicant..... : Infocare Industries Corporation Limited
Address..... : 5-6 F, B-Block, Huali Industrial Building, 28 District, Baoan, Shenzhen,
Guangdong
Manufacturer : Infocare Industries Corporation Limited
Address..... : 5-6 F, B-Block, Huali Industrial Building, 28 District, Baoan, Shenzhen,
Guangdong
Product Name..... : Digital Cooking thermometer
Model No. : IC6008, 70006
Standards..... : FCC CFR47 Part 15 Section 15.231: 2012
Date of Receipt sample : Mar.12, 2014
Date of Test..... : Mar.15-20, 2014
Date of Issue..... : Mar.22, 2014
Test Result..... : **Pass ***

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of compiler and approver.

Prepared By:

Waltek Services (Shenzhen) Co., Ltd.

Address: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen,
Guangdong, China

Testing location: 1/F., Fukangtai Building, West Baima Road, Songgang Street, Baoan District, Shenzhen,
Guangdong, China

Tel :+86-755-83551033


Fax:+86-755-83552400

Compiled by:



Zero Zhou / Project Engineer

Approved by:



Philo Zhong / Manager

2 Test Summary

| Test Items | Test Requirement | Result |
|-----------------------------|----------------------------------|--------|
| Conducted Emissions | 15.207 | N/A |
| Radiated Spurious Emissions | 15.205(a) 15.209 15.231(e) | PASS |
| Periodic Operation | 15.231(e) | PASS |
| 20dB Bandwidth | 15.231(c) | PASS |
| Antenna Requirement | 15.203 | PASS |

3 Contents

| | Page |
|--|-----------|
| 1 COVER PAGE | 1 |
| 2 TEST SUMMARY | 2 |
| 3 CONTENTS | 3 |
| 4 GENERAL INFORMATION | 4 |
| 4.1 GENERAL DESCRIPTION OF E.U.T. | 4 |
| 4.2 DETAILS OF E.U.T..... | 4 |
| 4.3 TEST FACILITY..... | 4 |
| 4.4 TEST LOCATION..... | 4 |
| 5 EQUIPMENT USED DURING TEST | 5 |
| 5.1 EQUIPMENTS LIST | 5 |
| 5.2 MEASUREMENT UNCERTAINTY | 5 |
| 5.3 TEST EQUIPMENT CALIBRATION | 5 |
| 6 CONDUCTED EMISSION TEST | 6 |
| 7 RADIATION EMISSION TEST | 7 |
| 7.1 EUT OPERATION: | 7 |
| 7.2 TEST SETUP | 7 |
| 7.3 SPECTRUM ANALYZER SETUP | 9 |
| 7.4 TEST PROCEDURE | 9 |
| 7.5 CORRECTED AMPLITUDE & MARGIN CALCULATION | 9 |
| 7.6 SUMMARY OF TEST RESULTS | 10 |
| 8 PERIODIC OPERATION | 11 |
| 9 20DB BANDWIDTH | 13 |
| 9.1 TEST PROCEDURE | 13 |
| 9.2 TEST RESULT | 13 |
| 10 ANTENNA REQUIREMENT | 14 |
| 11 PHOTOGRAPHS OF TESTING | 15 |
| 11.1 RADIATION EMISSION TEST SETUP..... | 15 |
| 12 PHOTOGRAPHS - CONSTRUCTIONAL DETAILS | 17 |
| 12.1 EUT - APPEARANCE VIEW | 17 |
| 12.2 EUT- INTERNAL VIEW | 21 |

4 General Information

4.1 General Description of E.U.T.

| | |
|------------------------------|--|
| Product Name | : Digital Cooking thermometer |
| Model No. | : IC6008, 70006 |
| Model Difference | : Only the model name is different. IC6008 is the tested sample. |
| Type of Modulation | : ASK |
| Frequency Range | : 433.92 MHz |
| The Lowest Oscillator | : 32.678kHz |
| Antenna installation | : PCB Printed Antenna |

4.2 Details of E.U.T.

| | |
|-----------------------|----------------------|
| Technical Data | : DC 3.0V, Max. 20mA |
|-----------------------|----------------------|

4.3 Test Facility

The test facility has a test site registered with the following organizations:

- **IC – Registration No.: 7760A-1**

Waltek Services (Shenzhen) Co., Ltd. has been registered and fully described in a report filed with the Industry Canada. The acceptance letter from the Industry Canada is maintained in our files. Registration 7760A-1, July 12, 2012.

- **FCC – Registration No.: 880581**

Waltek Services (Shenzhen) Co., Ltd. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 880581, May 26, 2011.

4.4 Test Location

All Emissions tests were performed at:-

Waltek Services (Shenzhen) Co., Ltd. at 1/F, Fukangtai Building, West Baima Rd., Songgang Street, Baoan District, Shenzhen 518105, China.

5 Equipment Used during Test

5.1 Equipments List

| 3m Semi-anechoic Chamber for Radiation | | | | | | |
|--|----------------------------|----------------------|-------------|------------|-----------------------|----------------------|
| Item | Equipment | Manufacturer | Model No. | Serial No. | Last Calibration Date | Calibration Due Date |
| 1 | EMC Analyzer | Agilent | E7405A | MY45114943 | Sep.18,2013 | Sep.17,2014 |
| 2 | Active Loop Antenna | Beijing Dazhi | ZN30900A | - | Sep.18,2013 | Sep.17,2014 |
| 3 | Trilog Broadband Antenna | SCHWARZBECK | VULB9163 | 336 | Apr.20,2013 | Apr.19,2014 |
| 4 | Coaxial Cable (below 1GHz) | Top | TYPE16(13M) | - | Sep.18,2013 | Sep.17,2014 |
| 5 | Broad-band Horn Antenna | SCHWARZBECK | BBHA 9120 D | 667 | Apr.20,2013 | Apr.19,2014 |
| 6 | Broad-band Horn Antenna | SCHWARZBECK | BBHA 9170 | 335 | Apr.20,2013 | Apr.19,2014 |
| 7 | Broadband Preamplifier | COMPLIANCE DIRECTION | PAP-1G18 | 2004 | Apr.07,2013 | Apr.06,2014 |
| 8 | Coaxial Cable (above 1GHz) | Top | 1GHz-25GHz | EW02014-7 | Apr.20,2013 | Apr.19,2014 |

5.2 Measurement Uncertainty

| Test Item | Frequency Range | Uncertainty | Note |
|--------------------|-----------------|-------------|------|
| Radiation Emission | 30MHz~1000MHz | ±5.03dB | (1) |
| | 1000M~5000MHz | ± 5.47 dB | (1) |

(1)This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

5.3 Test Equipment Calibration

All the test equipments used are valid and calibrated by CEPREI Certification Body that address is No.110 Dongguan Zhuang RD. Guangzhou, P.R.China.

6 Conducted Emission Test

| | |
|-------------------|--|
| Test Requirement: | FCC CFR 47 Part 15 Section 15.207 |
| Test Method: | ANSI C63.4:2003 |
| Frequency Range: | 150kHz to 30MHz |
| Class: | Class B |
| Limit: | 66-56 dB μ V between 0.15MHz & 0.5MHz 56 dB μ V between 0.5MHz & 5MHz 60 dB μ V between 5MHz & 30MHz |
| Detector: | Peak for pre-scan (9kHz Resolution Bandwidth) Quasi-Peak & Average if maximised peak within 6dB of Average Limit |
| Test Result: | N/A |
| Remark: | The EUT is powered by DC 3V, It is no application. |

7 Radiation Emission Test

| | |
|-----------------------|-------------------------------------|
| Test Requirement: | FCC Part15 Paragraph 15.231 |
| Test Method: | Based on FCC Part15 Paragraph 15.33 |
| Frequency Range: | 32.678kHz to 5GHz |
| Measurement Distance: | 3m |
| Test Result: | PASS |

7.1 EUT Operation:

Operating Environment:


| | |
|-----------------------|-----------|
| Temperature: | 23.5 °C |
| Humidity: | 52.1 % RH |
| Atmospheric Pressure: | 101.0 kPa |

Operation Mode:


The EUT was tested in Transmitting mode, and the test data were shown as follow.

7.2 Test Setup


The radiated emission tests were performed in the 3m Semi- Anechoic Chamber test site, using the setup accordance with the ANSI C63.4: 2003.
The test setup for emission measurement below 30MHz.



The test setup for emission measurement from 30 MHz to 1 GHz.



The test setup for emission measurement above 1 GHz.



7.3 Spectrum Analyzer Setup

According to FCC Part15 Rules, the system was tested 32.678kHz to 5000MHz.

Below 30MHz

Sweep SpeedAuto
 IF Bandwidth10kHz
 Video Bandwidth.....10kHz
 Resolution Bandwidth.....10kHz

30MHz ~ 1GHz

Sweep SpeedAuto
 DetectorPK
 Resolution Bandwidth.....100kHz
 Video Bandwidth.....300kHz

Above 1GHz

Sweep SpeedAuto
 DetectorPK
 Resolution Bandwidth.....1MHz
 Video Bandwidth.....3MHz

7.4 Test Procedure

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is moved from 1m to 4m to find out the maximum emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Repeat above procedures until the measurements for all frequencies are complete.
7. The radiation measurements are tested under 3-axes(X, Y, Z) position(X denotes lying on the table, Y denotes side stand and Z denotes vertical stand). After pre-test, It was found that the worse radiation emission was get at the X position. So the data shown was the X position only.

7.5 Corrected Amplitude & Margin Calculation

The Corrected Amplitude is calculated by adding the Antenna Factor and Cable Factor, and subtracting the Amplifier Gain from the Amplitude reading. The basic equation is as follows:

Corr. Ampl. = Indicated Reading + Antenna Factor + Cable Factor - Amplifier Gain the "Margin" column of the following data tables indicates the degree of compliance with the applicable limit. For example, a margin of -7dB means the emission is 7dB below the maximum limit for Class B. The equation for margin calculation is as follows:

$$\text{Margin} = \text{Corr. Ampl.} - \text{Limit}$$

7.6 Summary of Test Results

Test Frequency :Below 30MHz

The measurements were more than 20 dB below the limit and not reported.

Test Frequency : 30MHz ~ 5GHz

| Frequency | Receiver Reading | Detector | Turn table Angle | RX Antenna | | Corrected Factor | Corrected Amplitude | FCC Part 15.231/15.209/205 | |
|-----------|------------------|-------------|------------------|------------|-------|------------------|---------------------|----------------------------|--------|
| | | | | Height | Polar | | | Limit | Margin |
| (MHz) | (dBμV) | (PK/QP/Ave) | Degree | (m) | (H/V) | (dB) | (dBμV/m) | (dBμV/m) | (dB) |
| 433.92 | 69.36 | PK | 285 | 1.1 | H | 19.68 | 89.04 | 92.87 | -3.83 |
| 433.92 | 63.47 | PK | 260 | 1.6 | V | 19.68 | 83.15 | 92.87 | -9.72 |
| 867.84 | 46.12 | PK | 299 | 1.5 | H | 23.56 | 69.68 | 72.87 | -3.19 |
| 867.84 | 40.82 | PK | 162 | 1.9 | V | 23.56 | 64.38 | 72.87 | -8.49 |
| 1301.76 | 40.68 | PK | 267 | 1.5 | H | -16.38 | 24.30 | 72.87 | -48.57 |
| 1301.76 | 36.85 | PK | 56 | 1.6 | V | -16.38 | 20.47 | 74.00 | -53.53 |
| 1563.85 | 45.63 | PK | 100 | 1.6 | H | -14.87 | 30.76 | 74.00 | -43.24 |
| 1563.85 | 40.27 | PK | 41 | 1.7 | V | -14.87 | 25.40 | 74.00 | -48.60 |

AV = Peak +20Log₁₀(duty cycle) =PK+(-9.3) [refer to section 8 for more detail]

| Frequency | PK | Turn table Angle | RX Antenna | | Duty cycle Factor | AV | FCC Part 15.231/209/205 | |
|-----------|----------|------------------|------------|-------|-------------------|----------|-------------------------|--------|
| | | | Height | Polar | | | Limit | Margin |
| (MHz) | (dBμV/m) | Degree | (m) | (H/V) | (dB) | (dBμV/m) | (dBμV/m) | (dB) |
| 433.92 | 69.36 | 335 | 1.5 | H | -9.3 | 60.06 | 72.87 | -12.81 |
| 433.92 | 63.47 | 18 | 1.9 | V | -9.3 | 54.17 | 72.87 | -18.70 |
| 867.84 | 46.12 | 110 | 1.2 | H | -9.3 | 36.82 | 52.87 | -16.05 |
| 867.84 | 40.82 | 227 | 1.4 | V | -9.3 | 31.52 | 52.87 | -21.35 |
| 1301.76 | 40.68 | 79 | 1.1 | H | -9.3 | 31.38 | 52.87 | -21.49 |
| 1301.76 | 36.85 | 187 | 1.5 | V | -9.3 | 27.55 | 52.87 | -25.32 |
| 1563.85 | 45.63 | 110 | 1.1 | H | -9.3 | 36.33 | 54.00 | -17.67 |
| 1563.85 | 40.27 | 78 | 1.4 | V | -9.3 | 30.97 | 54.00 | -23.03 |

8 Periodic Operation

The duty cycle was determined by the following equation:

To calculate the actual field intensity, The duty cycle correction factor in decibel is needed for later use and can be obtained from following conversion

$$\text{Duty Cycle(\%)} = \text{Total On interval in a complete pulse train} / \text{Length of a complete pulse train} * \%$$


$$\text{Duty Cycle Correction Factor(dB)} = 20 * \text{Log}_{10}(\text{Duty Cycle(\%)})$$

| | |
|--|-------|
| Total transmission time(ms) | 0.504 |
| Length of a complete transmission period(ms) | 1.47 |
| Duty Cycle(%) | 34.3 |
| Duty Cycle Correction Factor(dB) | -9.3 |

Refer to the duty cycle plot (as below), This device meets the FCC requirement.


Length of a complete pulse train:

Remark: FCC part 15.35(c) required that a complete pulse train is more than 0.1 seconds, the measured field strength shall be determined from the average absolute voltage during a 0.1 second interval during which the field strength is at its maximum value.



FCC Part15.231(e) In addition, devices operated under the provisions of this paragraph shall be provided with a means for automatically limiting operation so that the duration of each transmission shall not be greater than one second and the silent period between transmissions shall be at least 30 times the duration of the transmission but in no case less than 10 seconds.

Result:the duration of each transmission is 0.504ms,the silent period is 40s.



9 20dB Bandwidth

Test Requirement: FCC Part15 C
 Test Method: FCC Part15 Paragraph 15.231(c)
 Limit: The bandwidth of the emission shall be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz. For devices operating above 900 MHz, the emission shall be no wider than 0.5% of the center frequency.

9.1 Test Procedure


1. The transmitter output (antenna port) was connected to the spectrum analyzer.EUT and its simulators are placed on a table, let EUT working in test mode,then test it.
2. The bandwidth of the fundamental frequency was measure by spectrum analyser with 3kHz RBW and 10kHz VBW.The 20dB bandwidth is defined as the total spectrum the power of which is higher than peak power 20dB.

9.2 Test Result

| Frequency (MHz) | Bandwidth Emission (kHz) | Limit (kHz) | Result |
|-----------------|--------------------------|-------------|--------|
| 433.92 | 15.57 | 1084.80 | Pass |

Limit=Center Frequency*0.25%

Test Plot



10 Antenna Requirement

According to the FCC Part 15 Paragraph 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna to the intentional radiator shall be considered sufficient to comply with the provisions of this section. This product use a permanent PCB printed antenna, fulfill the requirement of this section


11 Photographs of Testing

11.1 Radiation Emission Test Setup


Below 30MHz



From 30MHz to 1GHz



Above 1GHz



12 Photographs - Constructional Details

12.1 EUT - Appearance View













12.2 EUT- Internal View







====End of Report====