FCC ID: 2AB4KMTYH3692 Portable device

According to §15.247(i) and §1.1307(b)(1), systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy level in excess of the Commission's guidelines.

According to KDB447498 D01 General RF Exposure Guidance V06

The 1-g and 10-g SAR test exclusion thresholds for 100 MHz to 6 GHz at test separation distances \leq 50 mm are determined by:

[(max. power of channel, including tune-up tolerance, mW)/(min. test separation distance, mm)] * [$\sqrt{f(GHz)}$] \leq 3.0 for 1-g SAR and \leq 7.5 for 10-g extremity SAR, where

f(GHz) is the RF channel transmit frequency in GHz;

Power and distance are rounded to the nearest mW and mm before calculation;

The result is rounded to one decimal place for comparison;

The test exclusions are applicable only when the minimum test separation distance is \leq 50 mm and for transmission frequencies between 100 MHz and 6 GHz. When the minimum test separation distance is < 5 mm, a distance of 5 mm is applied to determine SAR test exclusion. We use 5mm as separation distance to calculate.

Maximum measured transmitter power:

BT DSS:

Transmit Frequency (GHz)	Mode	Max Conducted Power (dBm)	tune up maximum power(dBm)	Result calculation	1-g SAR
2.402	GFSK	-13.89	-13	0.016	3
2.441	GFSK	-16.22	-17	0.006	3
2.480	GFSK	-18.77	-17	0.006	3
2.402	pi/4-DQPSK	-15.04	-17	0.006	3
2.441	pi/4-DQPSK	-17.28	-17	0.006	3
2.480	pi/4-DQPSK	-19.95	-19	0.004	3
2.402	8DPSK	-15.22	-17	0.006	3
2.441	8DPSK	-17.52	-17	0.006	3
2.480	8DPSK	-20.16	-19	0.004	3

Date: 2018.05.07

Conclusion:

Signature:

For the max result : $0.016 \le 3.0$ for 1-g SAR extremity SAR, No SAR is required.

NAME AND TITLE (Please print or type): David Lee/Manager

COMPANY (Please print or type): Shenzhen EMTEK Co., Ltd./Building 69, Majialong Industry

Zone, Nanshan District, Shenzhen, Guangdong, China