


### 6.3. Emission Bandwidth

#### 6.3.1. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.247 (a)(2)
<b>Test Method:</b>	ANSI C63.10:2013 and KDB558074
<b>Limit:</b>	>500kHz
<b>Test Setup:</b>	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>
<b>Test Mode:</b>	Transmitting mode with modulation
<b>Test Procedure:</b>	<ol style="list-style-type: none"> <li>1. The testing follows FCC KDB Publication No. 558074 DTS D01 Meas. Guidance v03r02.</li> <li>2. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>3. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW) = 100 kHz. Set the Video bandwidth (VBW) = 300 kHz. In order to make an accurate measurement. The 6dB bandwidth must be greater than 500 kHz.</li> <li>4. Measure and record the results in the test report.</li> </ol>
<b>Test Result:</b>	PASS

#### 6.3.2. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100060	Dec. 21, 2015
RF cable	TCT	RE-06	N/A	Nov.15 , 2015
Antenna Connector	TCT	RFC-01	N/A	Nov.15 , 2015

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

**6.3.3. Test data**

**Antenna 1:**

Test channel	6dB Emission Bandwidth (MHz)			
	802.11b	802.11g	802.11n(H20)	802.11n(H40)
Lowest	10.09	15.13	15.15	33.89
Middle	10.05	15.11	15.14	35.07
Highest	9.562	15.14	15.14	33.89
Limit:	>500k			
Test Result:	PASS			


**Antenna 2:**

Test channel	6dB Emission Bandwidth (MHz)			
	802.11b	802.11g	802.11n(H20)	802.11n(H40)
Lowest	10.04	15.08	15.03	33.81
Middle	10.03	15.12	15.10	33.81
Highest	9.60	15.12	15.09	33.78
Limit:	>500k			
Test Result:	PASS			


Test plots as follows:

Antenna 1:  
802.11b Modulation


Lowest channel



Middle channel




Highest channel




## 802.11g Modulation


### Lowest channel



### Middle channel




### Highest channel




## 802.11n (HT20) Modulation


### Lowest channel



### Middle channel




### Highest channel




## 802.11n (HT40) Modulation


### Lowest channel



### Middle channel




### Highest channel




Antenna 2:  
802.11b Modulation


Lowest channel



Middle channel




Highest channel




## 802.11g Modulation


### Lowest channel



### Middle channel




### Highest channel






## 802.11n (HT20) Modulation


### Lowest channel



### Middle channel




### Highest channel




## 802.11n (HT40) Modulation


### Lowest channel



### Middle channel




### Highest channel



## 6.4. Power Spectral Density

### 6.5. Test Specification

<b>Test Requirement:</b>	FCC Part15 C Section 15.247 (e)
<b>Test Method:</b>	ANSI C63.10:2013 and KDB558074, KDB662911
<b>Limit:</b>	The peak power spectral density shall not be greater than 8dBm in any 3kHz band at any time interval of continuous transmission.
<b>Test Setup:</b>	 <p style="text-align: center;">Spectrum Analyzer                      EUT</p>
<b>Test Mode:</b>	Transmitting mode with modulation
<b>Test Procedure:</b>	<ol style="list-style-type: none"> <li>1. The testing follows Measurement Procedure 10.3 Method AVGPSD of FCC KDB Publication No.558074 D01 DTS Meas. Guidance v03r02</li> <li>2. The RF output of EUT was connected to the spectrum analyzer by RF cable and attenuator. The path loss was compensated to the results for each measurement.</li> <li>3. Set to the maximum power setting and enable the EUT transmit continuously.</li> <li>4. Make the measurement with the spectrum analyzer's resolution bandwidth (RBW): <math>3 \text{ kHz} \leq \text{RBW} \leq 100 \text{ kHz}</math>. Video bandwidth VBW <math>\geq 3 \times \text{RBW}</math>. Set the span to at least 1.5 times the OBW.</li> <li>5. Detector = RMS, Sweep time = auto couple.</li> <li>6. Employ trace averaging (RMS) mode over a minimum of 100 traces. Use the peak marker function to determine the maximum power level.</li> <li>7. Measure and record the results in the test report.</li> <li>8. The calculation method follows FCC KDB662911 D01 Multiple Transmitter Output v02r01</li> </ol>
<b>Test Result:</b>	PASS

#### 6.5.1. Test Instruments

RF Test Room				
Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	N9020A	MY49100060	Dec. 21, 2015
RF cable	TCT	RE-06	N/A	Nov.15 , 2015

Antenna Connector	TCT	RFC-01	N/A	Nov.15 , 2015
-------------------	-----	--------	-----	---------------

**Note:** The calibration interval of the above test instruments is 12 months and the calibrations are traceable to international system unit (SI).

### 6.5.2. Test data


Configuration IEEE 802.11b/ Antenna 1, Antenna 2					
Test channel	AVG Power Spectral Density (dBm/3kHz)			Limit (dBm)	Result
	Antenna 1	Antenna 2	Total		
Lowest	-18.653	-19.201	-15.91	8dBm/3kHz	PASS
Middle	-19.124	-20.297	-16.66	8dBm/3kHz	PASS
Highest	-19.151	-19.772	-16.44	8dBm/3kHz	PASS

Configuration IEEE 802.11g/ Antenna 1, Antenna 2					
Test channel	AVG Power Spectral Density (dBm/3kHz)			Limit (dBm)	Result
	Antenna 1	Antenna 2	Total		
Lowest	-20.273	-20.077	-17.16	8dBm/3kHz	PASS
Middle	-20.268	-20.802	-17.52	8dBm/3kHz	PASS
Highest	-19.479	-20.466	-16.93	8dBm/3kHz	PASS

Configuration IEEE 802.11n (HT20)/ Antenna 1, Antenna 2					
Test channel	AVG Power Spectral Density (dBm/3kHz)			Limit (dBm)	Result
	Antenna 1	Antenna 2	Total		
Lowest	-20.078	-20.112	-17.08	8dBm/3kHz	PASS
Middle	-21.306	-21.228	-18.26	8dBm/3kHz	PASS
Highest	-19.193	-21.941	-17.34	8dBm/3kHz	PASS


Configuration IEEE 802.11n (HT40)/ Antenna 1, Antenna 2					
Test channel	AVG Power Spectral Density (dBm/3kHz)			Limit (dBm)	Result
	Antenna 1	Antenna 2	Total		
Lowest	-25.125	-24.899	-22.00	8dBm/3kHz	PASS
Middle	-25.810	-25.371	-22.57	8dBm/3kHz	PASS
Highest	-25.517	-25.270	-22.38	8dBm/3kHz	PASS

Test plots as follows:




Antenna 1:  
802.11b Modulation


Lowest channel



Middle channel




Highest channel




## 802.11g Modulation


Lowest channel



Middle channel




Highest channel




## 802.11n (HT20) Modulation


### Lowest channel



### Middle channel




### Highest channel






802.11n (HT40) Modulation


Lowest channel



Middle channel




Highest channel




Antenna 2:  
802.11b Modulation


Lowest channel



Middle channel




Highest channel




## 802.11g Modulation


Lowest channel



Middle channel




Highest channel




802.11n (HT20) Modulation


Lowest channel



Middle channel




Highest channel




802.11n (HT40) Modulation

Lowest channel



Middle channel



Highest channel

