



CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel: +86-755- 27521059 Fax: +86-755- 27521011 Http://www.sz-ctc.com.cn

Maximum Permissible Exposure Evaluation

FCC ID: 2AB75-BT581

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency (RF) Radiation as specified in §1.1307(b)

EUT Specification

| | |
|----------------------------|--|
| EUT | Bluetooth Earphone |
| Frequency band (Operating) | <input type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input checked="" type="checkbox"/> EDR: 2.402GHz ~ 2.480GHz <input type="checkbox"/> BL E: 2.402GHz ~ 2.480GHz <input type="checkbox"/> Others |
| Device category | <input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (<20cm separation) <input type="checkbox"/> fixed (>20cm separation) <input type="checkbox"/> Others |
| Exposure classification | <input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²) |
| Antenna diversity | <input checked="" type="checkbox"/> Single antenna <input type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity |
| Max. output power | EDR:1.28SdBm(8-DPSK) |
| Antenna gain (Max) | 2.5dBi |
| Evaluation applied | <input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation |

Limits for Maximum Permissible Exposure (MPE)

| Frequency Range(MHz) | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density(mW/cm ²) | Average Time |
|---|------------------------------|------------------------------|------------------------------------|--------------|
| (A) Limits for Occupational/Control Exposures | | | | |
| 300-1500 | -- | -- | F/300 | 6 |
| 1500-100000 | -- | -- | 5 | 6 |
| (B) Limits for General Population/Uncontrol Exposures | | | | |
| 300-1500 | -- | -- | F/1500 | 6 |
| 1500-100000 | -- | -- | 1 | 30 |

CTC Laboratories, Inc.

1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

Tel.: (86)755-27521059

Fax: (86)755-27521011

Http://www.sz-ctc.org.cn



中国国家认证认可监督管理委员会
Certification and Accreditation Administration of the People's Republic of China

For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : yz.cncaic.cn



Friis transmission formula: $P_d = (P_{out} * G) / (4 * \pi * R^2)$

Where

P_d = Power density in mW/cm^2

P_{out} = output power to antenna in Mw

G = gain of antenna in linear scale

π = 3.1416

R = distance between observation point and center of the radiator in cm

P_d the limit of MPE $1mW/cm^2$. If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

EDR:

| Support type | Operating Mode | Channel Frequency (MHz) | Max. Measured Power (dBm) | Tune up tolerance (dBm) | Max. Tune up Power (dBm) | Antenna Gain (dBi) | Power density at 0.5cm (mW/cm ²) | Power density Limits (mW/cm ²) |
|--------------|----------------|-------------------------|---------------------------|-------------------------|--------------------------|--------------------|--|--|
| EDR | GFSK | 2402 | -0.73 | -0.73 ± 1 | 0.27 | 2.5 | 0.60237 | 1 |
| EDR | GFSK | 2441 | -1.42 | -1.42 ± 1 | -0.42 | 2.5 | 0.51388 | 1 |
| EDR | GFSK | 2480 | -2.38 | -2.38 ± 1 | -1.38 | 2.5 | 0.41197 | 1 |
| EDR | $\pi/4$ -DQPSK | 2402 | 0.95 | 0.95 ± 1 | 1.95 | 2.5 | 0.88688 | 1 |
| EDR | $\pi/4$ -DQPSK | 2441 | 0.33 | 0.33 ± 1 | 1.33 | 2.5 | 0.76889 | 1 |
| EDR | $\pi/4$ -DQPSK | 2480 | -0.62 | -0.62 ± 1 | 0.38 | 2.5 | 0.61782 | 1 |
| EDR | 8-DPSK | 2402 | 1.28 | 1.28 ± 1 | 2.28 | 2.5 | 0.95689 | 1 |
| EDR | 8-DPSK | 2441 | 0.72 | 0.72 ± 1 | 1.72 | 2.5 | 0.84113 | 1 |
| EDR | 8-DPSK | 2480 | -0.18 | -0.18 ± 1 | 0.82 | 2.5 | 0.68370 | 1 |

Note

The transmitter signals are correlated:

For a more detailed features description, please refer to the RF Test Report.

*****THE END*****