

TEST REPORT

Product Name : Bluetooth Earphone
Brand Mark : N/A
Model No. : TWS-587, T7
FCC ID : 2AB75-TWS-587
Report Number : BLA-EMC-202005-A2902
Date of Sample Receipt : 2020/5/11
Date of Test : 2020/5/14 to 2020/5/19
Date of Issue : 2020/5/19
Test Standard : 47 CFR Part 15, Subpart C 15.247
Test Result : Pass

Prepared for:

Wintop Electronics Co., Limited

**Flat 2, 8/F Workingport Com'L Bldg, 3 Hau Fook ST, Tsim Sha Tsui, Kln
Hong Kong**

Prepared by:

BlueAsia of Technical Services(Shenzhen) Co.,Ltd.

IOT Test Centre of BlueAsia

No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen,China

TEL: +86-755-28682673

FAX: +86-755-28682673

Compiled by:

Jozu.

Review by:

Sweet. Liang

Approved by:

Jamen Li

Date: 2020/5/19



REPORT REVISE RECORD

Version No.	Date	Description
00	2020/5/19	Original

BlueAsia

TABLE OF CONTENTS

1	TEST SUMMARY	6
2	GENERAL INFORMATION	7
3	GENERAL DESCRIPTION OF E.U.T.	7
4	TEST ENVIRONMENT	8
5	TEST MODE	8
6	MEASUREMENT UNCERTAINTY	8
7	DESCRIPTION OF SUPPORT UNIT.....	9
8	LABORATORY LOCATION.....	9
9	TEST INSTRUMENTS LIST	10
	CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)	13
	LIMITS.....	13
	BLOCK DIAGRAM OF TEST SETUP.....	13
	PROCEDURE	13
	TEST DATA	15
	CONDUCTED BAND EDGES MEASUREMENT	17
	LIMITS.....	17
	BLOCK DIAGRAM OF TEST SETUP.....	17
	TEST DATA	18
	RADIATED SPURIOUS EMISSIONS	19
	LIMITS.....	19
	BLOCK DIAGRAM OF TEST SETUP.....	20
	PROCEDURE	20
	TEST DATA	22
	RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS	27
	LIMITS.....	27
	BLOCK DIAGRAM OF TEST SETUP.....	28
	PROCEDURE	28
	TEST DATA	30
	CONDUCTED SPURIOUS EMISSIONS.....	32
	LIMITS.....	32

BLOCK DIAGRAM OF TEST SETUP	32
TEST DATA	33
POWER SPECTRUM DENSITY	34
LIMITS.....	34
BLOCK DIAGRAM OF TEST SETUP	34
TEST DATA	34
CONDUCTED PEAK OUTPUT POWER	35
LIMITS.....	35
BLOCK DIAGRAM OF TEST SETUP	35
TEST DATA	36
MINIMUM 6DB BANDWIDTH	37
LIMITS.....	37
BLOCK DIAGRAM OF TEST SETUP	37
TEST DATA	37
ANTENNA REQUIREMENT.....	38
CONCLUSION.....	38
10 APPENDIX.....	39
10.1 APPENDIX: DTS BANDWIDTH	39
<i>Test Result</i>	39
<i>Test Graphs</i>	40
10.2 APPENDIX: OCCUPIED CHANNEL BANDWIDTH	42
<i>Test Result</i>	42
<i>Test Graphs</i>	43
10.3 APPENDIX: MAXIMUM CONDUCTED OUTPUT POWER	45
<i>Test Result</i>	45
<i>Test Graphs</i>	46
10.4 APPENDIX: MAXIMUM POWER SPECTRAL DENSITY	48
<i>Test Result</i>	48
<i>Test Graphs</i>	49
10.5 APPENDIX: BAND EDGE MEASUREMENTS.....	51
<i>Test Result</i>	51
<i>Test Graphs</i>	52
10.6 APPENDIX: CONDUCTED SPURIOUS EMISSION	53
<i>Test Result</i>	53

Test Graphs..... 54

APPENDIX A: PHOTOGRAPHS OF TEST SETUP 58

APPENDIX B: PHOTOGRAPHS OF EUT 60

BlueAsia

1 TEST SUMMARY

Test item	Test Requirement	Test Method	Class/Severity	Result
Conducted Emissions at AC Power Line (150kHz-30MHz)	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.2	47 CFR Part 15, Subpart C 15.207	Pass
Conducted Band Edges Measurement	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2	47 CFR Part 15, Subpart C 15.247(d)	Pass
Radiated Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.4,6.5,6.6	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Radiated Emissions which fall in the restricted bands	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 6.10.5	47 CFR Part 15, Subpart C 15.209 & 15.247(d)	Pass
Conducted Spurious Emissions	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11	47 CFR Part 15, Subpart C 15.247(d)	Pass
Power Spectrum Density	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.10.2	47 CFR Part 15, Subpart C 15.247(e)	Pass
Conducted Peak Output Power	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 7.8.5	47 CFR Part 15, Subpart C 15.247(b)(3)	Pass
Minimum 6dB Bandwidth	47 CFR Part 15, Subpart C 15.247	ANSI C63.10 (2013) Section 11.8.1	47 CFR Part 15, Subpart C 15.247a(2)	Pass
Antenna Requirement	47 CFR Part 15, Subpart C 15.247	N/A	47 CFR Part 15, Subpart C 15.203 & 15.247(c)	Pass

2 GENERAL INFORMATION

Applicant	Wintop Electronics Co., Limited
Address	Flat 2,8/F Workingport Com'L Bldg,3 Hau Fook ST,Tsim Sha Tsui,Kln Hong Kong
Manufacturer	ShenZhen Wintop Electronics Co.,Ltd
Address	Room 402 Building 1 No.34 XinHe Road, No 46 XinHe Road, Floor 4 No.50 XinHe Road ShangMuGu Community,PingHu Street,LongGang District,ShenZhen City,GuangDong Province,China
Factory	ShenZhen Wintop Electronics Co.,Ltd
Address	Room 402 Building 1 No.34 XinHe Road, No 46 XinHe Road, Floor 4 No.50 XinHe Road ShangMuGu Community,PingHu Street,LongGang District,ShenZhen City,GuangDong Province,China
Product Name	Bluetooth Earphone
Test Model No.	TWS-587

3 GENERAL DESCRIPTION OF E.U.T.

Hardware Version	TWS587_1V1
Software Version	V1
Operation Frequency:	2402MHz-2480MHz
Modulation Type:	GFSK
Channel Spacing:	2MHz
Number of Channels:	40
Antenna Type:	Chip Antenna
Antenna Gain:	-0.5dBi

4 TEST ENVIRONMENT

Environment	Temperature	Voltage
Normal	25°C	DC3.7V

5 TEST MODE

TEST MODE	TEST MODE DESCRIPTION
TX	Keep the EUT in transmitting mode with modulation
Remark: Only the data of the worst mode would be recorded in this report.	

6 MEASUREMENT UNCERTAINTY

Parameter	Expanded Uncertainty (Confidence of 95%)
Radiated Emission	±4.34dB
Radiated Emission	±4.24dB
Radiated Emission	±4.68dB
AC Power Line Conducted Emission	±3.45dB

Parameter	Expanded Uncertainty (Confidence of 95%)
Occupied Channel Bandwidth	±5 %
RF output power, conducted	±1.5 dB
Power Spectral Density, conducted	±3.0 dB
Unwanted Emissions, conducted	±3.0 dB
Temperature	±3 °C
Supply voltages	±3 %
Time	±5 %
Radiated Emission (30MHz ~ 1000MHz)	±4.35 dB
Radiated Emission (1GHz ~ 18GHz)	±4.44 dB

7 DESCRIPTION OF SUPPORT UNIT

Device Type	Manufacturer	Model Name	Serial No.	Remark
AC Adapter	UGREEN	CD112	N/A	N/A
PC	HASEE	K610D	N/A	N/A

8 LABORATORY LOCATION

All tests were performed at:
BlueAsia of Technical Services(Shenzhen) Co., Ltd.
IOT Test Centre of BlueAsia
No. 448 Bulong Road, Bantian Street, Longgang District, Shenzhen,China
Telephone: TEL: +86-755-28682673 FAX: +86-755-28682673
No tests were sub-contracted.

9 TEST INSTRUMENTS LIST

Test Equipment Of Conducted Emissions at AC Power Line (150kHz-30MHz)					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Shield room	SKET	833	N/A	6/10/2018	6/9/2021
Receiver	R&S	ESPI3	101082	4/20/2020	4/19/2021
LISN	R&S	ENV216	3560.6550.15	7/4/2019	7/3/2020
LISN	安泰信	AT166-2	AKK1806000003	12/17/2019	12/16/2020
EMI software	EZ	EZ-EMC	N/A	N/A	N/A

Test Equipment Of Conducted Band Edges Measurement					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/4/2019	7/3/2020
Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020
Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

Test Equipment Of Radiated Spurious Emissions					
Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	5/8/2018	5/7/2021
Spectrum	R&S	FSP40	100817	7/4/2019	7/3/2020
Receiver	R&S	ESR7	101199	4/20/2020	4/19/2021
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	7/14/2018	7/13/2020
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	7/14/2018	7/13/2020

Amplifier	SKET	LNPA-0118-45	N/A	7/4/2019	7/3/2020
EMI software	EZ	EZ-EMC	N/A	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2/14/2019	2/13/2022
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

Test Equipment Of Radiated Emissions which fall in the restricted bands

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Chamber	SKET	966	N/A	5/8/2018	5/7/2021
Spectrum	R&S	FSP40	100817	7/4/2019	7/3/2020
Receiver	R&S	ESR7	101199	4/20/2020	4/19/2021
broadband Antenna	Schwarzbeck	VULB9168	00836 P:00227	7/14/2018	7/13/2020
Horn Antenna	Schwarzbeck	9120D	01892 P:00331	7/14/2018	7/13/2020
Amplifier	SKET	LNPA-0118-45	N/A	7/4/2019	7/3/2020
EMI software	EZ	EZ-EMC	N/A	N/A	N/A
Loop antenna	SCHNARZBECK	FMZB1519B	00102	2/14/2019	2/13/2022
Controller	SKET	N/A	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-02	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-03	N/A	N/A	N/A
Coaxial Cable	BlueAsia	BLA-XC-01	N/A	N/A	N/A

Test Equipment Of Conducted Spurious Emissions

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/4/2019	7/3/2020

Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020
Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

Test Equipment Of Power Spectrum Density

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/4/2019	7/3/2020
Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020
Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

Test Equipment Of Conducted Peak Output Power

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/4/2019	7/3/2020
Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020
Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

Test Equipment Of Minimum 6dB Bandwidth

Equipment	Manufacturer	Model	S/N	Cal.Date	Cal.Due
Spectrum	R&S	FSP40	100817	7/4/2019	7/3/2020
Spectrum	Agilent	N9020A	MY49100060	12/17/2019	12/16/2020
Signal Generator	Agilent	N5182A	MY49060650	12/17/2019	12/16/2020
Signal Generator	Agilent	E8257D	MY44320250	4/20/2020	4/19/2021

CONDUCTED EMISSIONS AT AC POWER LINE (150KHZ-30MHZ)


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

LIMITS

Frequency of emission(MHz)	Conducted limit(dB μ V)	
	Quasi-peak	Average
0.15-0.5	66 to 56*	56 to 46*
0.5-5	56	46
5-30	60	50

*Decreases with the logarithm of the frequency.

BLOCK DIAGRAM OF TEST SETUP



Remark
 E.U.T: Equipment Under Test
 LISN: Line Impedance Stabilization Network
 Test table height=0.8m

PROCEDURE

- 1) The mains terminal disturbance voltage test was conducted in a shielded room.
- 2) The EUT was connected to AC power source through a LISN 1 (Line Impedance Stabilization Network) which provides a 50ohm/50 μ H + 5ohm linear impedance. The power cables of all other units of the EUT were connected to a second LISN 2, which was bonded to the ground reference plane in the same way as

the LISN 1 for the unit being measured. A multiple socket outlet strip was used to connect multiple power cables to a single LISN provided the rating of the LISN was not exceeded.

3) The tabletop EUT was placed upon a non-metallic table 0.8m above the ground reference plane. And for floor-standing arrangement, the EUT was placed on the horizontal ground reference plane,


4) The test was performed with a vertical ground reference plane. The rear of the EUT shall be 0.4 m from the vertical ground reference plane. The vertical ground reference plane was bonded to the horizontal ground reference plane. The LISN 1 was placed 0.8 m from the boundary of the unit under test and bonded to a ground reference plane for LISNs mounted on top of the ground reference plane. This distance was between the closest points of the LISN 1 and the EUT. All other units of the EUT and associated equipment was at least 0.8 m from the LISN 2.

5) In order to find the maximum emission, the relative positions of equipment and all of the interface cables must be changed according to ANSI C63.10 on conducted measurement.

Remark: LISN=Read Level+ Cable Loss+ LISN Factor

TEST DATA

[TestMode: TX]; [Line: Line]




Site: Phase: **L1** Temperature: 26
 Limit: FCC Class B Conduction(QP) Power: AC120V/60Hz Humidity: 60 %
 EUT: Bluetooth Earphone
 M/N: TWS-587
 Mode: LE mode
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.2220	20.62	9.91	30.53	62.74	-32.21	QP	
2		0.2220	15.76	9.91	25.67	52.74	-27.07	AVG	
3		0.4540	29.31	9.71	39.02	56.80	-17.78	QP	
4	*	0.4540	26.98	9.71	36.69	46.80	-10.11	AVG	
5		1.3099	19.61	9.82	29.43	56.00	-26.57	QP	
6		1.3099	14.66	9.82	24.48	46.00	-21.52	AVG	
7		2.2260	22.77	9.82	32.59	56.00	-23.41	QP	
8		2.2260	13.89	9.82	23.71	46.00	-22.29	AVG	
9		7.8420	30.98	9.87	40.85	60.00	-19.15	QP	
10		7.8420	18.88	9.87	28.75	50.00	-21.25	AVG	
11		14.5180	18.60	9.97	28.57	60.00	-31.43	QP	
12		14.5180	9.54	9.97	19.51	50.00	-30.49	AVG	

Test Result: Pass

[TestMode: TX]; [Line: Nutral]



Site: Phase: **N** Temperature: 26
 Limit: FCC Class B Conduction(QP) Power: AC120V/60Hz Humidity: 60 %
 EUT: Bluetooth Earphone
 M/N: TWS-587
 Mode: LE mode
 Note:

No.	Mk.	Freq. MHz	Reading Level dBuV	Correct Factor dB	Measure- ment dBuV	Limit dBuV	Over dB	Detector	Comment
1		0.2420	21.09	9.85	30.94	62.03	-31.09	QP	
2		0.2420	15.15	9.85	25.00	52.03	-27.03	AVG	
3		0.4460	27.53	9.70	37.23	56.95	-19.72	QP	
4	*	0.4460	17.80	9.70	27.50	46.95	-19.45	AVG	
5		1.2020	17.84	9.83	27.67	56.00	-28.33	QP	
6		1.2020	12.30	9.83	22.13	46.00	-23.87	AVG	
7		2.2220	24.23	9.86	34.09	56.00	-21.91	QP	
8		2.2220	12.78	9.86	22.64	46.00	-23.36	AVG	
9		7.6140	28.85	9.85	38.70	60.00	-21.30	QP	
10		7.6140	16.69	9.85	26.54	50.00	-23.46	AVG	
11		14.4060	17.75	10.01	27.76	60.00	-32.24	QP	
12		14.4060	8.52	10.01	18.53	50.00	-31.47	AVG	

Test Result: Pass


CONDUCTED BAND EDGES MEASUREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.8 & Section 11.13.3.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

BLOCK DIAGRAM OF TEST SETUP



TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia

RADIATED SPURIOUS EMISSIONS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.4,6.5,6.6
Test Mode (Pre-Scan)	TX mode (SE) below 1G;TX mode (SE) Above 1G
Test Mode (Final Test)	TX mode (SE) below 1G;TX mode (SE) Above 1G
Tester	Jozu
Temperature	25℃
Humidity	60%

LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

BLOCK DIAGRAM OF TEST SETUP



PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark:

- 1) For emission below 1GHz, through pre-scan found the worst case is the lowest channel. Only the worst case is recorded in the report.
- 2) The field strength is calculated by adding the Antenna Factor, Cable Factor & Preamplifier. The basic equation with a sample calculation is as follows:
Final Test Level = Receiver Reading + Antenna Factor + Cable Factor + Preamplifier Factor
- 3) Scan from 9kHz to 25GHz, the disturbance above 18GHz and below 30MHz was very low. The points marked on above plots are the highest emissions could be found when testing, so only above points had been displayed. The amplitude of spurious emissions from the radiator which are attenuated more than 20dB below the limit need not be reported.
- 4) For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

TEST DATA

[TestMode: TX mode (SE) Above 1G]						
Test channel:lowest						
Peak value:						
Frequency (MHz)	Read Level (dBuV)	Correct factor	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	51.85	2.38	54.23	74	-19.77	Vertical
7206.00	50.68	2.17	52.85	74	-21.15	Vertical
9608.00	51.72	2.06	53.78	74	-20.22	Vertical
12010.00	*			74		Vertical
14412.00	*			74		Vertical
4804.00	51.74	2.38	54.12	74	-19.88	Horizontal
7206.00	50.44	2.17	52.61	74	-21.39	Horizontal
9608.00	53.09	2.06	55.15	74	-18.85	Horizontal
12010.00	*			74		Horizontal
14412.00	*			74		Horizontal
Average value:						
Frequency (MHz)	Read Level (dBuV)	Correct factor	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4804.00	42.01	2.38	44.39	54	-9.61	Vertical
7206.00	40.28	2.17	42.45	54	-11.55	Vertical
9608.00	42.36	2.06	44.42	54	-9.58	Vertical
12010.00	*			54		Vertical
14412.00	*			54		Vertical
4804.00	42.25	2.38	44.63	54	-9.37	Horizontal
7206.00	43.41	2.17	45.58	54	-8.42	Horizontal
9608.00	44.09	2.06	46.15	54	-7.85	Horizontal
12010.00	*			54		Horizontal
14412.00	*			54		Horizontal
Test channel:Middle						
Peak value:						
Frequency (MHz)	Read Level (dBuV)	Correct factor	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	51.9	0.17	52.07	74	-21.93	Vertical
7323.00	55.83	1.43	57.26	74	-16.74	Vertical


9764.00	51.76	1.26	53.02	74	-20.98	Vertical
12205.00	*			74		Vertical
14646.00	*			74		Vertical
4882.00	52.83	0.17	53	74	-21	Horizontal
7323.00	52.08	1.43	53.51	74	-20.49	Horizontal
9764.00	51.99	1.26	53.25	74	-20.75	Horizontal
12205.00	*			74		Horizontal
14646.00	*			74		Horizontal
Average value:						
Frequency (MHz)	Read Level (dBuV)	Correct factor	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4882.00	42.02	0.17	42.19	54	-11.81	Vertical
7323.00	42.35	1.43	43.78	54	-10.22	Vertical
9764.00	40.16	1.26	41.42	54	-12.58	Vertical
12205.00	*			54		Vertical
14646.00	*			54		Vertical
4882.00	43.04	0.17	43.21	54	-10.79	Horizontal
7323.00	42.83	1.43	44.26	54	-9.74	Horizontal
9764.00	43.31	1.26	44.57	54	-9.43	Horizontal
12205.00	*			54		Horizontal
14646.00	*			54		Horizontal
Test channel: Highest						
Peak value:						
Frequency (MHz)	Read Level (dBuV)	Correct factor	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
4960.00	51.96	1.04	53	74	-21	Vertical
7440.00	50.89	2.59	53.48	74	-20.52	Vertical
9920.00	55.64	2.74	58.38	74	-15.62	Vertical
12400.00	*			74		Vertical
14880.00	*			74		Vertical
4960.00	57.97	1.04	59.01	74	-14.99	Horizontal
7440.00	56.72	2.59	59.31	74	-14.69	Horizontal
9920.00	57.89	2.74	60.63	74	-13.37	Horizontal
12400.00	*			74		Horizontal
14880.00	*			74		Horizontal
Average						

value:						
Frequency (MHz)	Read Level (dBUV)	Correct factor	Level (dBUV/m)	Limit Line (dBUV/m)	Over Limit (dB)	Polarization
4960.00	42.65	1.04	43.69	54	-10.31	Vertical
7440.00	43.41	2.59	46	54	-8	Vertical
9920.00	42.09	2.74	44.83	54	-9.17	Vertical
12400.00	*			54		Vertical
14880.00	*			54		Vertical
4960.00	48.46	1.04	49.5	54	-4.5	Horizontal
7440.00	45.23	2.59	47.82	54	-6.18	Horizontal
9920.00	44.08	2.74	46.82	54	-7.18	Horizontal
12400.00	*			54		Horizontal
14880.00	*			54		Horizontal
Test Result: Pass						

[TestMode: TX mode (SE) below 1G]; [Polarity: Horizontal]

Radiated Emission Measurement

File :FCC-RE Data :#9 Date: 2020/5/14 星期 Time: 上午 10:25:44
72.0 dBuV/m



Site: Polarization: **Horizontal** Temperature:
Limit: FCC Part15 Class B Power: DC3.7V Humidity: %
EUT: Bluetooth Earphone Distance:
M/N: TWS-587
Mode: LE BT mode
Note:

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		52.7600	-1.86	24.19	22.33	40.00	-17.67	QP		
2		70.5836	3.49	21.06	24.55	40.00	-15.45	QP		
3		103.8055	4.17	21.06	25.23	43.50	-18.27	QP		
4		195.1365	7.26	20.26	27.52	43.50	-15.98	QP		
5		396.2415	0.24	26.89	27.13	46.00	-18.87	QP		
6	*	597.2234	1.22	31.15	32.37	46.00	-13.63	QP		


*:Maximum data x:Over limit !:over margin

⟨Reference Only

Test Result: Pass

[TestMode: TX mode (SE) below 1G]; [Polarity: Vertical]

Radiated Emission Measurement



Site	Polarization: Vertical	Temperature:
Limit: FCC Part15 Class B	Power: DC3.7V	Humidity: %
EUT: Bluetooth Earphone	Distance:	
M/N: TWS-587		
Mode: LE BT mode		
Note:		

No.	Mk.	Freq.	Reading Level	Correct Factor	Measurement	Limit	Over	Antenna Height	Table Degree	
		MHz	dBuV	dB	dBuV/m	dBuV/m	dB	cm	degree	Comment
1		35.3750	7.46	23.27	30.73	40.00	-9.27	QP		
2	*	72.0843	12.40	20.74	33.14	40.00	-6.86	QP		
3		135.9822	7.00	23.18	30.18	43.50	-13.32	QP		
4		185.7882	9.78	20.74	30.52	43.50	-12.98	QP		
5		403.2500	0.22	27.07	27.29	46.00	-18.71	QP		
6		654.2318	1.53	32.02	33.55	46.00	-12.45	QP		

*:Maximum data x:Over limit !:over margin <Reference Only

Test Result: Pass

RADIATED EMISSIONS WHICH FALL IN THE RESTRICTED BANDS


Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 6.10.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

LIMITS

Frequency(MHz)	Field strength(microvolts/meter)	Measurement distance(meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90kHz, 110-490kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation.

BLOCK DIAGRAM OF TEST SETUP



PROCEDURE

- For below 1GHz, the EUT was placed on the top of a rotating table 0.8 meters above the ground at a 3 or 10 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- For above 1GHz, the EUT was placed on the top of a rotating table 1.5 meters above the ground at a 3 meter fully-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.
- The EUT was set 3 or 10 meters away from the interference-receiving antenna, which was mounted on the top of a variable-height antenna tower.
- The antenna height is varied from one meter to four meters above the ground to determine the maximum value of the field strength. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights from 1 meter to 4 meters (for the test frequency of below 30MHz, the antenna was tuned to heights 1 meter) and the rotatable table was turned from 0 degrees to 360 degrees to find the maximum reading.
- The test-receiver system was set to Peak Detect Function and Specified Bandwidth with Maximum Hold Mode.
- If the emission level of the EUT in peak mode was 10dB lower than the limit specified, then testing could be stopped and the peak values of the EUT would be reported. Otherwise the emissions that did not have 10dB margin would be re-tested one by one using peak, quasi-peak or average method as specified and then reported in a data sheet.

- h. Test the EUT in the lowest channel, the middle channel, the Highest channel.
- i. The radiation measurements are performed in X, Y, Z axis positioning for Transmitting mode, and found the X axis positioning which it is the worst case.
- j. Repeat above procedures until all frequencies measured was complete.

Remark 1: $Level = Read\ Level + Cable\ Loss + Antenna\ Factor - Preamp\ Factor$

Remark 2: For frequencies above 1GHz, the field strength limits are based on average limits. However, the peak field strength of any emission shall not exceed the maximum permitted average limits specified above by more than 20 dB under any condition of modulation. For the emissions whose peak level is lower than the average limit, only the peak measurement is shown in the report.

BlueAsia

TEST DATA

[TestMode: TX]; [Polarity: Horizontal]						
Test channel:lowest						
Peak value:						
Frequency (MHz)	Read Level (dBuV)	Correct factor	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310	44.89	-4.2	40.69	74	-33.31	Horizontal
2390	48.24	-3.88	44.36	74	-29.64	Horizontal
2310	46.36	-4.49	41.87	74	-32.13	Vertical
2390	50.23	-4.21	46.02	74	-27.98	Vertical
Average value:						
Frequency (MHz)	Read Level (dBuV)	Correct factor(dB/m)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310	34.47	-4.2	30.27	54	-23.73	Horizontal
2390	35.13	-3.88	31.25	54	-22.75	Horizontal
2310	36.05	-4.49	31.56	54	-22.44	Vertical
2390	38.29	-4.21	34.08	54	-19.92	Vertical
Test channel:Highest						
Peak value:						
Frequency (MHz)	Read Level (dBuV)	Correct factor	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	54.06	-3.38	50.68	74	-23.32	Horizontal
2500	51.66	-3.3	48.36	74	-25.64	Horizontal
2483.5	49.24	-3.77	45.47	74	-28.53	Vertical
2500	55.37	-3.7	51.67	74	-22.33	Vertical
Average value:						
Frequency	Read Level	Correct	Level	Limit Line	Over Limit	Polarization

(MHz)	(dBuV)	factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	n
2483.5	43.57	-3.88	39.69	54	-14.31	Horizontal
2500	42.2	-3.3	38.9	54	-15.1	Horizontal
2483.5	37.03	-3.77	33.26	54	-20.74	Vertical
2500	44.48	-3.7	40.78	54	-13.22	Vertical

Test Result: Pass

BlueAsia


CONDUCTED SPURIOUS EMISSIONS

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.6 & Section 11.11
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

LIMITS

Limit:	In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in §15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in §15.209(a) (see §15.205(c)).
---------------	--

BLOCK DIAGRAM OF TEST SETUP



TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia


POWER SPECTRUM DENSITY

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 11.10.2
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

LIMITS

Limit:	$\leq 8\text{dBm}$ in any 3 kHz band during any time interval of continuous transmission
---------------	--

BLOCK DIAGRAM OF TEST SETUP



TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details
--


CONDUCTED PEAK OUTPUT POWER

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 7.8.5
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

LIMITS

Frequency range(MHz)	Output power of the intentional radiator(watt)
902-928	1 for ≥ 50 hopping channels
	0.25 for $25 \leq$ hopping channels < 50
	1 for digital modulation
2400-2483.5	1 for ≥ 75 non-overlapping hopping channels
	0.125 for all other frequency hopping systems
	1 for digital modulation
5725-5850	1 for frequency hopping systems and digital modulation

BLOCK DIAGRAM OF TEST SETUP



TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

BlueAsia


MINIMUM 6DB BANDWIDTH

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	ANSI C63.10 (2013) Section 11.8.1
Test Mode (Pre-Scan)	TX
Test Mode (Final Test)	TX
Tester	Jozu
Temperature	25°C
Humidity	60%

LIMITS

Limit:	≥500 kHz
--------	----------

BLOCK DIAGRAM OF TEST SETUP



TEST DATA

Pass: Please Refer To Appendix: Appendix1 For Details

ANTENNA REQUIREMENT

Test Standard	47 CFR Part 15, Subpart C 15.247
Test Method	N/A


CONCLUSION

Standard Requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of an antenna that uses a unique coupling to the intentional radiator, the manufacturer may design the unit permanently attached antenna or of an so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:

The antenna is integrated on the main PCB and no consideration of replacement. The best case gain of the antenna is -0.5dBi.



10 APPENDIX


Appendix1


10.1 APPENDIX: DTS BANDWIDTH

Test Result

TestMode	Antenna	Channel	DTS BW [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE	Ant1	2402	0.680	2401.660	2402.340	≥ 0.5	PASS
		2442	0.672	2441.656	2442.328	≥ 0.5	PASS
		2480	0.676	2479.652	2480.328	≥ 0.5	PASS

Test Graphs







10.2 APPENDIX: OCCUPIED CHANNEL BANDWIDTH**Test Result**

TestMode	Antenna	Channel	OCB [MHz]	FL[MHz]	FH[MHz]	Limit[MHz]	Verdict
BLE BLE	Ant1	2402	1.0397	2401.491	2402.531	---	PASS
		2442	1.0396	2441.483	2442.523	---	PASS
		2480	1.0407	2479.483	2480.524	---	PASS

BlueAsia

Test Graphs





BlueAsia


10.3 APPENDIX: MAXIMUM CONDUCTED OUTPUT POWER


Test Result

TestMode	Antenna	Channel	Result[dBm]	Limit[dBm]	Verdict
BLE	Ant1	2402	5.35	<=30	PASS
		2442	6.15	<=30	PASS
		2480	6.46	<=30	PASS

BlueAsia

Test Graphs







10.4 APPENDIX: MAXIMUM POWER SPECTRAL DENSITY**Test Result**

TestMode	Antenna	Channel	Result[dBm/3-100kHz]	Limit[dBm/3kHz]	Verdict
BLE	Ant1	2402	-0.29	<=8	PASS
		2442	0.59	<=8	PASS
		2480	0.96	<=8	PASS

BlueAsia

Test Graphs





10.5 APPENDIX: BAND EDGE MEASUREMENTS**Test Result**

TestMode	Antenna	ChName	Channel	RefLevel[dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE	Ant1	Low	2402	4.92	-56.34	<=-15.08	PASS
		High	2480	6.24	-55.12	<=-13.77	PASS

BlueAsia

Test Graphs





10.6 APPENDIX: CONDUCTED SPURIOUS EMISSION

Test Result


TestMode	Antenna	Channel	FreqRange [MHz]	RefLevel [dBm]	Result[dBm]	Limit[dBm]	Verdict
BLE	Ant1	2402	Reference	4.23	4.23	---	PASS
			30~1000	30~1000	-68.026	<=-15.766	PASS
			1000~26500	1000~26500	-38.595	<=-15.766	PASS
		2442	Reference	5.82	5.82	---	PASS
			30~1000	30~1000	-67.793	<=-14.184	PASS
			1000~26500	1000~26500	-39.173	<=-14.184	PASS
		2480	Reference	6.10	6.10	---	PASS
			30~1000	30~1000	-67.714	<=-13.902	PASS
			1000~26500	1000~26500	-37.296	<=-13.902	PASS

Test Graphs








BLE_Ant1_2442_0-Reference



BLE_Ant1_2442_30~1000







APPENDIX A: PHOTOGRAPHS OF TEST SETUP

Conducted Emissions at AC Power Line (150kHz-30MHz)



Radiated Spurious Emissions





BlueAsia

APPENDIX B: PHOTOGRAPHS OF EUT

































----END OF REPORT----

The test report is effective only with both signature and specialized stamp, The result(s) shown in this report refer only to the sample(s) tested. Without written approval of BlueAsia, this report can't be reproduced except in full.

BlueAsia