

FCC ID:2AB7K-R5121

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

Limits for Maximum Permissible Exposure (MPE)

Frequency Range(MHz)	Electric Field Strength(V/m)	Magnetic Field Strength(A/m)	Power Density(mW/cm ²)	Average Time
(A) Limits for Occupational/Control Exposures				
300-1500	--	--	F/300	6
1500-100000	--	--	5	6
(B) Limits for General Population/Uncontrol Exposures				
300-1500	--	--	F/1500	6
1500-100000	--	--	1	30

$$11.1 \text{ Friis transmission formula: } P_d = (P_{out} * G) / (4 * \pi * R^2)$$

Where

Pd= Power density in mW/cm²

Pout=output power to antenna in mW

G= Numeric gain of the antenna relative to isotropic antenna

Pi=3.1416

R= distance between observation point and center of the radiator in cm(20cm)

Pd the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

mW=10^(dBm/10)

11.2 Measurement Result

Operation Frequency: 2402MHz~2480MHz

Power density limited: 1mW/ cm²

Antenna Type: FPCB Antenna

Antenna gain: 1.0dBi,

R=20cm

mW=10^(dBm/10)

Bluetooth DTS:

Channel Freq. (MHz)	modulation	conducted power (mW)	conducted power (dBm)	Tune-up power (dBm)	Max tune-up power (dBm)	Antenna Gain Numeric	Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
2402	GFSK	0.35	-4.52	-4.5±1	-3.5	1.26	0.000112	1
2440		0.37	-4.33	-4.5±1	-3.5	1.26	0.000112	1
2480		0.31	-5.09	-4.5±1	-3.5	1.26	0.000112	1

simultaneous emission

Power density Limits (mW/cm ²) BLE	Calculate Evaluation result (mW/cm ²)	Power density Limits (mW/cm ²)
0.000112	0.000112	1

Conclusion:

For the max result : 0.000112≤ 1.0, compliance with FCC's RF Exposure.

Signature:

Date: 2017-10-26

NAME AND TITLE (Please print or type): Jason Chen/Manager

COMPANY (Please print or type): Shenzhen NTEK Testing Technology Co., Ltd./ 1/F, Building E, Fenda Science Park, Sanwei Community, Xixiang Street Bao'an District, Shenzhen P.R. China.