


# FCC Radio Test Report


## FCC ID: 2AB7X-WISEPRO

This report concerns:Original Grant

**Project No.** : 1906H001  
**Equipment** : WisePOS Pro  
**Brand Name** : BBPOS  
**Test Model** : WSP71  
**Series Model** : WSP72, WSP73  
**Applicant** : BBPOS International Limited  
**Address** : Suite 1903-04, 19/F, Tower 2, Nina Tower, No. 8 Yeung Uk Road,  
Tsuen Wan, N.T. HK  
**Manufacturer** : BBPOS International Limited  
**Address** : Suite 1903-04, 19/F, Tower 2, Nina Tower, No. 8 Yeung Uk Road,  
Tsuen Wan, N.T. HK  
**Date of Receipt** : Jul. 12, 2019  
**Date of Test** : Jul. 12, 2019~Sep. 13, 2019  
**Issued Date** : Sep. 13, 2019  
**Report Version** : R00  
**Test Sample** : Engineering Sample No.: SH19070367  
**Standard(s)** : FCC Part15, Subpart C (15.247)  
ANSI C63.10-2013  
KDB 558074 D01 15.247 Meas Guidance V05r02

The above equipment has been tested and found compliance with the requirement of the relevant standards by BTL Inc.

  
Prepared by :Krain Wu

  
Approved by :Young Chai



Certificate # 5123.03

Add: No. 29, Jintang Road, Tangzhen Industry Park, Pudong New Area, Shanghai 201210, China  
TEL: +86-021-61765666  
Web: www.newbtl.com

**Declaration**

**BTL** represents to the client that testing is done in accordance with standard procedures as applicable and that test instruments used has been calibrated with standards traceable to international standard(s) and/or national standard(s).

**BTL's** reports apply only to the specific samples tested under conditions. It is manufacture's responsibility to ensure that additional production units of this model are manufactured with the identical electrical and mechanical components. **BTL** shall have no liability for any declarations, inferences or generalizations drawn by the client or others from **BTL** issued reports.

The report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, A2LA, or any agency of the U.S. Government.

This report is the confidential property of the client. As a mutual protection to the clients, the public and ourselves, the test report shall not be reproduced, except in full, without our written approval.

**BTL's** laboratory quality assurance procedures are in compliance with the **ISO/IEC17025** requirements, and accredited by the conformity assessment authorities listed in this test report.

**BTL** is not responsible for the sampling stage, so the results only apply to the sample as received.

The information, data and test plan are provided by manufacturer which may affect the validity of results, so it is manufacturer's responsibility to ensure that the apparatus meets the essential requirements of applied standards and in all the possible configurations as representative of its intended use.

**Limitation**

For the use of the authority's logo is limited unless the Test Standard(s)/Scope(s)/Item(s) mentioned in this test report is (are) included in the conformity assessment authorities acceptance respective.

Please note that the measurement uncertainty is provided for informational purpose only and are not use in determining the Pass/Fail results.

| <b>Table of Contents</b>                                    | <b>Page</b> |
|---|-------------|
| <b>REPORT ISSUED HISTORY</b>                                | <b>5</b>    |
| <b>1 . SUMMARY OF TEST RESULTS</b>                          | <b>6</b>    |
| 1.1 TEST FACILITY   | 7           |
| 1.2 MEASUREMENT UNCERTAINTY                                 | 7           |
| 1.3 TEST ENVIRONMENT CONDITIONS                             | 7           |
| <b>2 . GENERAL INFORMATION</b>                              | <b>8</b>    |
| 2.1 GENERAL DESCRIPTION OF EUT                              | 8           |
| 2.2DESCRIPTION OF TEST MODES                                | 10          |
| 2.3PARAMETERS OF TEST SOFTWARE                              | 10          |
| 2.4BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED | 11          |
| 2.5SUPPORT UNITS  | 11          |
| <b>3 . AC POWER LINE CONDUCTED EMISSIONS TEST</b>           | <b>12</b>   |
| 3.1 LIMIT   | 12          |
| 3.2TEST PROCEDURE   | 12          |
| 3.3DEVIATION FROM TEST STANDARD                             | 12          |
| 3.4TEST SETUP   | 13          |
| 3.5EUT OPERATING CONDITIONS                                 | 13          |
| 3.6 TEST RESULTS  | 13          |
| <b>4 . RADIATED EMISSION TEST</b>                           | <b>14</b>   |
| 4.1 LIMIT   | 14          |
| 4.2 TEST PROCEDURE  | 15          |
| 4.3 DEVIATION FROM TEST STANDARD                            | 15          |
| 4.4 TEST SETUP  | 16          |
| 4.5 EUT OPERATING CONDITIONS                                | 17          |
| 4.6 TEST RESULT - 9KHZ TO 30MHZ                             | 17          |
| 4.7 TEST RESULT - 30MHZ TO 1000 MHZ                         | 17          |
| 4.8 TEST RESULT - ABOVE 1000 MHZ                            | 17          |
| <b>5 . BANDWIDTH TEST</b>                                   | <b>18</b>   |
| 5.1 LIMIT   | 18          |
| 5.2 TEST PROCEDURE  | 18          |
| 5.3 DEVIATION FROM STANDARD                                 | 18          |
| 5.4 TEST SETUP  | 18          |
| 5.5 EUT OPERATION CONDITIONS                                | 18          |

| <b>Table of Contents</b>                                 | <b>Page</b> |
|--|-------------|
| <b>5.6 TESTRESULTS</b>                                   | <b>18</b>   |
| <b>6 . MAXIMUM OUTPUT POWER &amp; E.I.R.P. TEST</b>      | <b>19</b>   |
| 6.1 LIMIT  | 19          |
| 6.2 TEST PROCEDURE                                       | 19          |
| 6.3 DEVIATION FROM STANDARD                              | 19          |
| 6.4 TEST SETUP   | 19          |
| 6.5 EUT OPERATION CONDITIONS                             | 19          |
| 6.6 TEST RESULTS   | 19          |
| <b>7 . CONDUCTED SPURIOUS EMISSION</b>                   | <b>20</b>   |
| 7.1 LIMIT  | 20          |
| 7.2 TEST PROCEDURE                                       | 20          |
| 7.3 DEVIATION FROM STANDARD                              | 20          |
| 7.4 TEST SETUP   | 20          |
| 7.5 EUT OPERATION CONDITIONS                             | 20          |
| 7.6 TEST RESULTS   | 20          |
| <b>8 . POWER SPECTRAL DENSITY TEST</b>                   | <b>21</b>   |
| 8.1 LIMIT  | 21          |
| 8.2 TEST PROCEDURE                                       | 21          |
| 8.3 DEVIATION FROM STANDARD                              | 21          |
| 8.4 TEST SETUP   | 21          |
| 8.5 EUT OPERATION CONDITIONS                             | 21          |
| 8.6 TEST RESULTS   | 21          |
| <b>9 . MEASUREMENT INSTRUMENTS LIST</b>                  | <b>22</b>   |
| <b>APPENDIX A - AC POWER LINE CONDUCTED EMISSIONS</b>    | <b>24</b>   |
| <b>APPENDIX B - RADIATED EMISSION -9 KHZ TO 30 MHZ</b>   | <b>27</b>   |
| <b>APPENDIX C - RADIATED EMISSION-30 MHZ TO 1000 MHZ</b> | <b>32</b>   |
| <b>APPENDIX D - RADIATED EMISSION - ABOVE 1000 MHZ</b>   | <b>35</b>   |
| <b>APPENDIX E - BANDWIDTH</b>                            | <b>48</b>   |
| <b>APPENDIX F - MAXIMUM OUTPUT POWER &amp; E.I.R.P.</b>  | <b>50</b>   |
| <b>APPENDIX G - CONDUCTED SPURIOUS EMISSION</b>          | <b>52</b>   |
| <b>APPENDIX H - POWER SPECTRAL DENSITY</b>               | <b>54</b>   |

**REPORT ISSUED HISTORY**

| Report Version | Description     | Issued Date   |
|----------------|-----------------|---------------|
| R00            | Original Issue. | Sep. 13, 2019 |

### 1. SUMMARY OF TEST RESULTS

Test procedures according to the technical standard(s):

| FCC Part15, Subpart C (15.247)      |                                   |  |          |        |
|-------------------------------------|-----------------------------------|--|----------|--------|
| Standard(s) Section                 | Test Item                         | Test Result                            | Judgment | Remark |
| 15.207                              | AC Power Line Conducted Emissions | APPENDIX A                             | N/A      | -----  |
| 15.247(d)<br>15.205(a)<br>15.209(a) | Radiated Emissions                | APPENDIX B<br>APPENDIX C<br>APPENDIX D | PASS     | -----  |
| 15.247(a)(2)                        | Bandwidth                         | APPENDIX E                             | PASS     | -----  |
| 15.247(b)(3)                        | Maximum Output Power & e.i.r.p.   | APPENDIX F                             | PASS     | -----  |
| 15.247(d)                           | Conducted Spurious Emission       | APPENDIX G                             | PASS     | -----  |
| 15.247(e)                           | Power Spectral Density            | APPENDIX H                             | PASS     | -----  |
| 15.203                              | Antenna Requirement               | -----                                  | PASS     | -----  |

**NOTE:**

(1) "N/A" denotes test is not applicable to this device.

### 1.1 TEST FACILITY

The test facilities used to collect the test data in this report is at the location of No.29, Jintang Road, Tangzhen Industry Park, Pudong New Area, Shanghai 201210, China  
 BTL's Test Firm Registration Number for FCC: 476765  
 BTL's Designation Number for FCC: CN1241

### 1.2 MEASUREMENT UNCERTAINTY

ISO/IEC 17025 requires that an estimate of the measurement uncertainties associated with the emissions test results be included in the report. The measurement uncertainties given below are based on a 95% confidence level (based on a coverage factor (k=2))  
 The BTL measurement uncertainty as below table:

#### A. AC power line conducted emissions test:

| Test Site | Method | Measurement Frequency Range | U, (dB) |
|-----------|--------|-----------------------------|---------|
| SH-C01    | CISPR  | 150 kHz~30MHz               | ± 2.26  |

#### B. Radiated emissions test:

| Test Site     | Method | Measurement Frequency Range | Ant. H / V | U, (dB) |
|---------------|--------|-----------------------------|------------|---------|
| SH-CB01       | CISPR  | 9 KHz~30 MHz                | V          | 3.79    |
|               |        | 9 KHz~30 MHz                | H          | 3.57    |
|               |        | 30MHz~200MHz                | V          | 4.04    |
|               |        | 30MHz~200MHz                | H          | 3.76    |
|               |        | 200MHz~1,000MHz             | V          | 4.24    |
|               |        | 200MHz~1,000MHz             | H          | 3.84    |
|               |        | 1GHz~18GHz                  | V          | 4.46    |
|               |        | 1GHz~18GHz                  | H          | 4.40    |
|               |        | 18 GHz~40 GHz               | V          | 3.95    |
| 18 GHz~40 GHz | H      | 3.95                        |            |         |

Note: Unless specifically mentioned, the uncertainty of measurement has not been taken into account to declare the compliance or non-compliance to the specification.

### 1.3 TEST ENVIRONMENT CONDITIONS

| Test Item                         | Temperature | Humidity | Test Voltage | Tested By |
|-----------------------------------|-------------|----------|--------------|-----------|
| AC Power Line Conducted Emissions | 22°C        | 55%      | AC 120V      | Summer Xu |
| Radiated Emissions-9K-30MHz       | 22°C        | 59%      | AC 120V      | Summer Xu |
| Radiated Emissions-30 MHz to 1GHz | 22°C        | 59%      | AC 120V      | Summer Xu |
| Radiated Emissions-Above 1000 MHz | 22°C        | 59%      | AC 120V      | Summer Xu |
| Bandwidth                         | 22°C        | 55%      | AC 120V      | Summer Xu |
| Maximum Output Power& e.i.r.p.    | 22°C        | 55%      | AC 120V      | Summer Xu |
| Conducted Spurious Emission       | 22°C        | 55%      | AC 120V      | Summer Xu |
| Power Spectral Density            | 22°C        | 55%      | AC 120V      | Summer Xu |

## 2. GENERAL INFORMATION

### 2.1 GENERAL DESCRIPTION OF EUT

|                         |  |
|-------------------------|--|
| Equipment               | WisePOS Pro  |
| Brand Name              | BBPOS  |
| Test Model              | WSP71  |
| Series Model            | WSP72, WSP73   |
| Model Difference(s)     | WSP71: WisePOS Pro device only; WSP72: WisePOS Pro device with hand strap; WSP73: WisePOS Pro device with pistol grip. |
| Software Version        | 970ADGAAK2_BB_V009   |
| Hardware Version        | 7MD_V01  |
| PowerSource             | 1. DC Voltage supplied from AC/DC adapter<br>2. Supplied from Li-ion battery pack                                      |
| Power Rating            | 1. I/P: 100-240V ~ 50/60Hz 1.0A<br>O/P: 5V---3A/9V---3A<br>2. 6400mAH 3.8V   |
| Operation Frequency     | 2402 MHz ~ 2480 MHz  |
| Modulation Technology   | GFSK   |
| Bit Rate of Transmitter | 1Mbps  |
| Max. Output Power       | 5.50dBm (0.0035 W)   |
| Max. e.i.r.p.           | 8.70dBm (0.0074 W)   |

Note:

1. For a more detailed features description, please refer to the manufacturer's specifications or the user's manual.



## 2. Channel List:

| Channel | Frequency (MHz) | Channel | Frequency (MHz) |
|---------|-----------------|---------|-----------------|
| 00      | 2402            | 20      | 2442            |
| 01      | 2404            | 21      | 2444            |
| 02      | 2406            | 22      | 2446            |
| 03      | 2408            | 23      | 2448            |
| 04      | 2410            | 24      | 2450            |
| 05      | 2412            | 25      | 2452            |
| 06      | 2414            | 26      | 2454            |
| 07      | 2416            | 27      | 2456            |
| 08      | 2418            | 28      | 2458            |
| 09      | 2420            | 29      | 2460            |
| 10      | 2422            | 30      | 2462            |
| 11      | 2424            | 31      | 2464            |
| 12      | 2426            | 32      | 2466            |
| 13      | 2428            | 33      | 2468            |
| 14      | 2430            | 34      | 2470            |
| 15      | 2432            | 35      | 2472            |
| 16      | 2434            | 36      | 2474            |
| 17      | 2436            | 37      | 2476            |
| 18      | 2438            | 38      | 2478            |
| 19      | 2440            | 39      | 2480            |

## 3. Table for Filed Antenna:

| Ant. | Brand | Model Name | Antenna Type | Connector | Gain (dBi) |
|------|-------|------------|--------------|-----------|------------|
| 1    | N/A   | N/A        | PIFA         | N/A       | 3.2        |

## 2.2 DESCRIPTION OF TEST MODES

The test system was pre-tested based on the consideration of all possible combinations of EUT operation mode.

| Pretest Mode | Description               |
|--------------|---------------------------|
| Mode 1       | TX Mode <b>NOTE (1)</b>   |
| Mode 2       | TX Mode Channel 39 _1Mbps |

Following mode(s) as (were) found to be the worst case(s) and selected for the final test.

| <b>AC power line conducted emissions test</b> |                           |
|---|---------------------------|
| Final Test Mode                               | Description               |
| Mode 2  | TX Mode Channel 39 _1Mbps |

| <b>Radiated emissions test - Below 1GHz</b> |                           |
|---|---------------------------|
| Final Test Mode                             | Description               |
| Mode 2                                      | TX Mode Channel 39 _1Mbps |

| <b>Radiated emissions test - Above 1GHz</b> |                         |
|---|-------------------------|
| Final Test Mode                             | Description             |
| Mode 1                                      | TX Mode <b>NOTE (1)</b> |

| <b>Conducted test</b> |                         |
|-----------------------|-------------------------|
| Final Test Mode       | Description             |
| Mode 1                | TX Mode <b>NOTE (1)</b> |

Note:


- (1) The measurements are performed at the high, middle, low available channels.
- (2) For radiated emission above 1GHz test, 1GHz~26.5GHz have been pre-tested and in this report only recorded the worst case. The remaining spurious points are all below the limit value of 20dB.

## 2.3 PARAMETERS OF TEST SOFTWARE

During testing channel & power controlling software provided by the customer was used to control the operating channel as well as the output power level. The RF output power selection is for the setting of RF output power expected by the customer and is going to be fixed on the firmware of the final end product power parameters of BT LE

| Test Software   | N/A  |      |      |
|-----------------|------|------|------|
| Frequency (MHz) | 2402 | 2440 | 2480 |
| Parameters      | N/A  | N/A  | N/A  |

**2.4 BLOCK DIAGRAM SHOWING THE CONFIGURATION OF SYSTEM TESTED**



**2.5 SUPPORT UNITS**

| Item | Equipment | Brand | Model/Type No. | Series No. |
|------|-----------|-------|----------------|------------|
| -    | -         | -     | -              | -          |

| Item | Cable Type | Shielded Type | Ferrite Core | Length |
|------|------------|---------------|--------------|--------|
| 1    | DC Cable   | N/A           | N/A          | 1m     |

### 3.AC POWER LINE CONDUCTED EMISSIONS TEST

#### 3.1LIMIT

| Frequency of Emission (MHz) | Limit (dB $\mu$ V) |           |
|-----------------------------|--------------------|-----------|
|                             | Quasi-peak         | Average   |
| 0.15 -0.5                   | 66 to 56*          | 56 to 46* |
| 0.50 -5.0                   | 56                 | 46        |
| 5.0 -30.0                   | 60                 | 50        |

Note:

- (1) The tighter limit applies at the band edges.
- (2) The limit of " \* " marked band means the limitation decreases linearly with the logarithm of the frequency in the range.

The following table is the setting of the receiver

| Receiver Parameters | Setting  |
|---------------------|----------|
| Attenuation         | 10 dB    |
| Start Frequency     | 0.15 MHz |
| Stop Frequency      | 30 MHz   |
| IF Bandwidth        | 9 kHz    |


#### 3.2TEST PROCEDURE

- a. The EUT was placed 0.8 meters from the horizontal ground plane with EUT being connected to the power mains through a line impedance stabilization network (LISN). All other support equipment powered from additional LISN(s). The LISN provide 50 Ohm/ 50uH of coupling impedance for the measuring instrument.
- b. Interconnecting cables that hang closer than 40 cm to the groundplane shall be folded back and forth in the center forming a bundle 30 to 40 cm long.
- c. I/O cables that are not connected to a peripheral shall be bundled in the center. The end of the cable may be terminated, if required, using the correct terminating impedance. The overall length shall not exceed 1 m.
- d. LISN at least 80 cm from nearest part of EUT chassis.
- e. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 3.3DEVIATIONFROMTESTSTANDARD

No deviation

### 3.4 TEST SETUP



### 3.5 EUT OPERATING CONDITIONS

The EUT was configured for testing in a typical fashion (as a customer would normally use it). The EUT has been programmed to continuously transmit during test. This operating condition was tested and used to collect the included data.

### 3.6 TEST RESULTS

Please refer to the APPENDIX A.

Remark:

- (1) All readings are QP Mode value unless otherwise stated AVG in column of 『Note』. If the QP Mode Measured value compliance with the QP Limits and lower than AVG Limits, the EUT shall be deemed to meet both QP & AVG Limits and then only QP Mode was measured, but AVG Mode didn't perform. In this case, a "\*" marked in AVG Mode column of Interference Voltage Measured.
- (2) Measuring frequency range from 150 kHz to 30MHz.

## 4. RADIATED EMISSION TEST

### 4.1 LIMIT

In case the emission fall within the restricted band specified on 15.205(a), then the 15.209(a) limit in the table below has to be followed.

#### LIMITS OF RADIATED EMISSION MEASUREMENT (9 kHz-1000MHz)

| Frequency (MHz) | Field Strength (microvolts/meter) | Measurement Distance (meters) |
|-----------------|-----------------------------------|-------------------------------|
| 0.009-0.490     | 2400/F(kHz)                       | 300                           |
| 0.490-1.705     | 24000/F(kHz)                      | 30                            |
| 1.705-30.0      | 30                                | 30                            |
| 30-88           | 100                               | 3                             |
| 88-216          | 150                               | 3                             |
| 216-960         | 200                               | 3                             |
| Above 960       | 500                               | 3                             |

#### LIMITS OF RADIATED EMISSION MEASUREMENT (9 kHz-30 MHz)

| Frequency (MHz) | Magnetic field strength (H-Field) ( $\mu$ A/m) | Measurement Distance (meters) |
|-----------------|--|-------------------------------|
| 0.009-0.490     | 6.37/F(kHz)                                    | 300                           |
| 0.490-1.705     | 6.37/F(kHz)                                    | 30                            |
| 1.705-30.0      | 0.08   | 30                            |

#### LIMITS OF RADIATED EMISSION MEASUREMENT (30 MHz-1000MHz)

| Frequency (MHz) | Field Strength ( $\mu$ V/m at 3m) |
|-----------------|-----------------------------------|
| 30-88           | 100                               |
| 88-216          | 150                               |
| 216-960         | 200                               |
| Above 960       | 500                               |

#### LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1000MHz)

| Frequency (MHz) | (dBuV/m at 3 m) |         |
|-----------------|-----------------|---------|
|                 | Peak            | Average |
| Above 1000      | 74              | 54      |

**Note:**

- (1) The limit for radiated test was performed according to FCC PART 15C.
- (2) The tighter limit applies at the band edges.
- (3) Emission level (dBuV/m)=20log Emission level (uV/m).
- (4) The test result calculated as following:  
 Measurement Value = Reading Level + Correct Factor  
 Correct Factor = Antenna Factor + Cable Loss - Amplifier Gain(if use)  
 Margin Level = Measurement Value - Limit Value

| Spectrum Parameter                         | Setting   |
|--|---|
| Attenuation                                | Auto  |
| Start Frequency                            | 1000 MHz  |
| Stop Frequency                             | 10th carrier harmonic   |
| RBW / VBW<br>(Emission in restricted band) | RBW 1MHz VBW 3MHz peak detector for Pk value<br>RMS detector for AV value |



| Receiver Parameter     | Setting                           |
|------------------------|-----------------------------------|
| Attenuation            | Auto                              |
| Start ~ Stop Frequency | 9 kHz~90kHz for PK/AVG detector   |
| Start ~ Stop Frequency | 90kHz~110kHz for QP detector      |
| Start ~ Stop Frequency | 110kHz~490kHz for PK/AVG detector |
| Start ~ Stop Frequency | 490kHz~30MHz for QP detector      |
| Start ~ Stop Frequency | 30MHz~1000MHz for QP detector     |

#### 4.2 TEST PROCEDURE


- a. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(below 1GHz)
- b. The measuring distance of 3 m shall be used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation.(above 1GHz)
- c. The height of the equipment or of the substitution antenna shall be 0.8m or 1.5m; the height of the test antenna shall vary between 1 m to 4 m. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
- d. For each suspected emission, the EUT was arranged to its worst case and then the antenna was tuned to heights find the maximum reading (used Bore sight function).
- e. The receiver system was set to peak and average detect function and specified bandwidth with maximum hold mode when the test frequency is above 1GHz.
- f. The initial step in collecting radiated emission data is a receiver peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- g. All readings are Peak unless otherwise stated QP in column of Note. Peak denotes that the Peak reading compliance with the QP Limits and then QP Mode measurement didn't perform. (below 1GHz)
- h. All readings are Peak Mode value unless otherwise stated AVG in column of Note. If the Peak Mode Measured value compliance with the Peak Limits and lower than AVG Limits, the EUT shall be deemed to meet both Peak & AVG Limits and then only Peak Mode was measured, but AVG Mode didn't perform. (above 1GHz)
- i. For the actual test configuration, please refer to the related Item –EUT Test Photos.

#### 4.3 DEVIATION FROM TEST STANDARD

No deviation

**4.4 TEST SETUP****9 kHz-30 MHz****30 MHz to 1 GHz**





#### 4.5 EUT OPERATING CONDITIONS

The EUT was programmed to be in continuously transmitting mode.

#### 4.6 TEST RESULT- 9kHz TO 30MHz

Please refer to the APPENDIX B

Remark:

- (1) Distance extrapolation factor =  $40 \log (\text{specific distance} / \text{test distance})$  (dB).
- (2) Limit line = specific limits (dBuV) + distance extrapolation factor.

#### 4.7 TEST RESULT- 30MHz TO 1000MHz

Please refer to the APPENDIX C.

#### 4.8 TEST RESULT- ABOVE 1000MHz

Please refer to the APPENDIX D.

Remark:

- (1) No limit: This is fundamental signal, the judgment is not applicable.  
For fundamental signal judgment was referred to Peak output test.

**5.BANDWIDTH TEST****5.1LIMIT**

| FCC Part15, Subpart C (15.247) |           |                                   |
|--------------------------------|-----------|-----------------------------------|
| Section                        | Test Item | Limit                             |
| 15.247(a)(2)                   | Bandwidth | $\geq 500$ kHz<br>(6dB bandwidth) |

**5.2TEST PROCEDURE**

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- Spectrum Setting : RBW= 100 kHz, VBW=300 kHz, Sweep time = 2.5 ms.

**5.3DEVIATION FROM STANDARD**

No deviation.

**5.4TEST SETUP****5.5EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 4.5 unless otherwise a special operating condition is specified in the follows during the testing.

**5.6TESTRESULTS**

Please refer to the APPENDIXE.

**6. MAXIMUM OUTPUT POWER & E.I.R.P. TEST****6.1 LIMIT**

| FCC Part15, Subpart C (15.247) |                      |                 |
|--------------------------------|----------------------|-----------------|
| Section                        | Test Item            | Limit           |
| 15.247(b)(3)                   | Maximum Output Power | 1 watt or 30dBm |

**6.2 TEST PROCEDURE**

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- b. The maximum conducted output power was performed in accordance with method 11.9.1.1(for peak power) or 11.9.2.2(for AVG power) of ANSI C63.10-2013.

**6.3 DEVIATION FROM STANDARD**

No deviation.

**6.4 TEST SETUP****6.5 EUT OPERATION CONDITIONS**

The EUT tested system was configured as the statements of 4.5 unless otherwise a special operating condition is specified in the follows during the testing.

**6.6 TEST RESULTS**

Please refer to the APPENDIXF.

## 7.CONDUCTED SPURIOUS EMISSION

### 7.1LIMIT

In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak Output Power limits. If the transmitter complies with the Output Power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in Section 15.209(a) is not required. In addition, radiated emissions which fall in the restricted bands, as defined in Section 15.205(a), must also comply with the radiated emission limits specified in Section 15.209(a) (see Section 15.205(c)).

### 7.2TEST PROCEDURE

- a. The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- b. Spectrum Setting : RBW= 100 kHz, VBW=300 kHz, Sweep time = 10 ms.

### 7.3DEVIATION FROM STANDARD

No deviation.

### 7.4TEST SETUP



### 7.5EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.5unless otherwise a special operating condition is specified in the follows during the testing.

### 7.6 TEST RESULTS

Please refer to the APPENDIXG.

## 8. POWER SPECTRAL DENSITY TEST

### 8.1 LIMIT

| FCC Part15, Subpart C (15.247) |                        |                         |
|--------------------------------|------------------------|-------------------------|
| Section                        | Test Item              | Limit                   |
| 15.247(e)                      | Power Spectral Density | 8 dBm<br>(in any 3 kHz) |

### 8.2 TEST PROCEDURE

- The EUT was directly connected to the spectrum analyzer and antenna output port as show in the block diagram below.
- Spectrum Setting: RBW=3 kHz, VBW=10kHz, Sweep time = auto.

### 8.3 DEVIATION FROM STANDARD

No deviation.

### 8.4 TEST SETUP



### 8.5 EUT OPERATION CONDITIONS

The EUT tested system was configured as the statements of 4.5 unless otherwise a special operating condition is specified in the follows during the testing.

### 8.6 TEST RESULTS

Please refer to the APPENDIXH.

**9. MEASUREMENT INSTRUMENTS LIST**

| <b>AC Power Line Conducted Emissions</b> |                                      |              |                       |            |                  |
|--|--------------------------------------|--------------|-----------------------|------------|------------------|
| Item                                     | Kind of Equipment                    | Manufacturer | Type No.              | Serial No. | Calibrated until |
| 1  | Line Impedance Stabilisation Network | Schwarzbeck  | NNLK 8121             | 8121-822   | Mar. 29, 2020    |
| 2  | TWO-LINE V-NETWORK                   | R&S          | ENV216                | 101340     | Nov. 20, 2019    |
| 3  | Test Cable                           | emci         | EMCRG400-BM-NM-10000  | 170628     | Apr. 17, 2020    |
| 4  | EMI Test Receiver                    | R&S          | ESCI                  | 100082     | Mar. 29, 2020    |
| 5  | 50Ω Terminator                       | SHX          | TF2-1G-A              | 17051602   | Mar. 29, 2020    |
| 6  | 50Ω coaxial switch                   | Anritsu      | MP59B                 | 6201750902 | Mar. 29, 2020    |
| 7  | Measurement Software                 | Farad        | EZ-EMC Ver.NB-03A1-01 | N/A        | N/A              |

| <b>Radiated Emissions - 9 kHz to 30MHz</b> |                      |              |                       |            |                  |
|--|----------------------|--------------|-----------------------|------------|------------------|
| Item                                       | Kind of Equipment    | Manufacturer | Type No.              | Serial No. | Calibrated until |
| 1  | Loop Antenna         | EMCI         | EMCI LPA600           | 275        | Mar. 29, 2020    |
| 2  | EMI Test Receiver    | R&S          | ESCI                  | 100082     | Mar. 29, 2020    |
| 3  | Measurement Software | Farad        | EZ-EMC Ver.NB-03A1-01 | N/A        | N/A              |

| <b>Radiated Emissions - 30 MHz to 1 GHz</b> |                          |              |                       |            |                  |
|---|--------------------------|--------------|-----------------------|------------|------------------|
| Item  | Kind of Equipment        | Manufacturer | Type No.              | Serial No. | Calibrated until |
| 1   | TRILOG Broadband Antenna | Schwarzbeck  | VULB 9168             | 719        | Mar. 29, 2020    |
| 2   | Pre-Amplifier            | emci         | EMC9135               | 980400     | Mar. 29, 2020    |
| 3   | MXE EMI Receiver         | Keysight     | N9038A                | MY57150106 | Mar. 29, 2020    |
| 4   | Test Cable               | emci         | EMC104-SM-SM-7000     | 170330     | Apr. 17, 2020    |
| 5   | Test Cable               | emci         | EMC104-SM-SM-1000     | 170331     | Apr. 17, 2020    |
| 6   | Test Cable               | emci         | EMC104-SM-NM-3500     | 170621     | Apr. 17, 2020    |
| 7   | Measurement Software     | Farad        | EZ-EMC Ver.NB-03A1-01 | N/A        | N/A              |

| Radiated Emissions - Above 1GHz |                                      |              |                       |            |                  |
|---------------------------------|--------------------------------------|--------------|-----------------------|------------|------------------|
| Item                            | Kind of Equipment                    | Manufacturer | Type No.              | Serial No. | Calibrated until |
| 1                               | Double-Ridged Waveguide Horn Antenna | ETS-Lindgren | 9120D                 | 00206960   | Mar. 29, 2020    |
| 2                               | Pre-Amplifier                        | emci         | EMC012645SE           | 980421     | Mar. 29, 2020    |
| 3                               | EXA Spectrum Analyzer                | Keysight     | N9010A                | MY56480545 | Mar. 29, 2020    |
| 4                               | Test Cable                           | emci         | EMC104-SM-SM-7000     | 170330     | Apr. 17, 2020    |
| 5                               | Test Cable                           | emci         | EMC104-SM-SM-1000     | 170331     | Apr. 17, 2020    |
| 6                               | Test Cable                           | emci         | EMC104-SM-NM-3500     | 170621     | Apr. 17, 2020    |
| 7                               | Measurement Software                 | Farad        | EZ-EMC Ver.NB-03A1-01 | N/A        | N/A              |
| 8                               | MXE EMI Receiver                     | Keysight     | N9038A                | MY57150106 | Mar. 29, 2020    |

| Bandwidth |                   |              |          |            |                  |
|-----------|-------------------|--------------|----------|------------|------------------|
| Item      | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
| 1         | Spectrum Analyzer | R&S          | FSP40    | 100626     | Mar. 29, 2020    |

| Maximum Output Power |                    |              |          |            |                  |
|----------------------|--------------------|--------------|----------|------------|------------------|
| Item                 | Kind of Equipment  | Manufacturer | Type No. | Serial No. | Calibrated until |
| 1                    | Power Meter        | Keysight     | 8990B    | MY51000507 | Mar. 29, 2020    |
| 2                    | Pulse Power Sensor | Keysight     | N1923A   | MY58310003 | Mar. 29, 2020    |

| Antenna Conducted Spurious Emissions |                   |              |          |            |                  |
|--------------------------------------|-------------------|--------------|----------|------------|------------------|
| Item                                 | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
| 1                                    | Spectrum Analyzer | R&S          | FSP40    | 100626     | Mar. 29, 2020    |

| Power Spectral Density |                   |              |          |            |                  |
|------------------------|-------------------|--------------|----------|------------|------------------|
| Item                   | Kind of Equipment | Manufacturer | Type No. | Serial No. | Calibrated until |
| 1                      | Spectrum Analyzer | R&S          | FSP40    | 100626     | Mar. 29, 2020    |

Remark: "N/A" denotes no model name, serial no. or calibration specified.


All calibration period of equipment list is one year.

## **APPENDIX A - AC POWER LINE CONDUCTED EMISSIONS**



Test Mode: TX Mode

### Line



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Margin<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|--------------|----------|---------|
| 1   | *   | 0.1544       | 41.60                    | 9.76                    | 51.36                    | 65.76         | -14.40       | QP       |         |
| 2   |     | 0.1544       | 23.30                    | 9.76                    | 33.06                    | 55.76         | -22.70       | AVG      |         |
| 3   |     | 0.2220       | 33.50                    | 9.82                    | 43.32                    | 62.74         | -19.42       | QP       |         |
| 4   |     | 0.2220       | 9.80                     | 9.82                    | 19.62                    | 52.74         | -33.12       | AVG      |         |
| 5   |     | 0.2670       | 29.70                    | 9.82                    | 39.52                    | 61.21         | -21.69       | QP       |         |
| 6   |     | 0.2670       | 7.80                     | 9.82                    | 17.62                    | 51.21         | -33.59       | AVG      |         |
| 7   |     | 0.3075       | 26.50                    | 9.76                    | 36.26                    | 60.04         | -23.78       | QP       |         |
| 8   |     | 0.3075       | 14.00                    | 9.76                    | 23.76                    | 50.04         | -26.28       | AVG      |         |
| 9   |     | 0.3525       | 23.60                    | 9.83                    | 33.43                    | 58.90         | -25.47       | QP       |         |
| 10  |     | 0.3525       | 13.00                    | 9.83                    | 22.83                    | 48.90         | -26.07       | AVG      |         |
| 11  |     | 0.7620       | 12.00                    | 9.78                    | 21.78                    | 56.00         | -34.22       | QP       |         |
| 12  |     | 0.7620       | 4.60                     | 9.78                    | 14.38                    | 46.00         | -31.62       | AVG      |         |


**REMARKS:**

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode: TX Mode

### Neutral



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV | Limit<br>dBuV | Margin<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|--------------------------|---------------|--------------|----------|---------|
| 1   | *   | 0.1500       | 40.60                    | 9.62                    | 50.22                    | 66.00         | -15.78       | QP       |         |
| 2   |     | 0.1500       | 21.30                    | 9.62                    | 30.92                    | 56.00         | -25.08       | AVG      |         |
| 3   |     | 0.1725       | 38.50                    | 9.57                    | 48.07                    | 64.84         | -16.77       | QP       |         |
| 4   |     | 0.1725       | 21.30                    | 9.57                    | 30.87                    | 54.84         | -23.97       | AVG      |         |
| 5   |     | 0.2040       | 34.50                    | 9.64                    | 44.14                    | 63.45         | -19.31       | QP       |         |
| 6   |     | 0.2040       | 14.50                    | 9.64                    | 24.14                    | 53.45         | -29.31       | AVG      |         |
| 7   |     | 0.2625       | 28.20                    | 9.71                    | 37.91                    | 61.35         | -23.44       | QP       |         |
| 8   |     | 0.2625       | 11.80                    | 9.71                    | 21.51                    | 51.35         | -29.84       | AVG      |         |
| 9   |     | 0.3885       | 18.00                    | 9.72                    | 27.72                    | 58.10         | -30.38       | QP       |         |
| 10  |     | 0.3885       | 2.50                     | 9.72                    | 12.22                    | 48.10         | -35.88       | AVG      |         |
| 11  |     | 29.4180      | 18.60                    | 9.63                    | 28.23                    | 60.00         | -31.77       | QP       |         |
| 12  |     | 29.4180      | 7.50                     | 9.63                    | 17.13                    | 50.00         | -32.87       | AVG      |         |


**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

**APPENDIX B - RADIATED EMISSION -9 KHZ TO 30 MHZ**

Test Mode: TX Mode

Ant 0°




| No. | Mk. | Freq.  | Reading Level | Correct Factor | Measurement | Limit  | Margin | Detector | Comment |
|-----|-----|--------|---------------|----------------|-------------|--------|--------|----------|---------|
|     |     | MHz    | dBuV          | dB             | dBuV/m      | dBuV/m | dB     |          |         |
| 1   |     | 0.0108 | -12.70        | 77.91          | 65.21       | 126.94 | -61.73 | AVG      |         |
| 2   |     | 0.0370 | -16.67        | 67.60          | 50.93       | 116.24 | -65.31 | AVG      |         |
| 3   | *   | 0.1025 | -4.56         | 57.85          | 53.29       | 107.39 | -54.10 | QP       |         |

REMARKS:

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode: TX Mode

Ant 0°



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1   |     | 0.2850       | -3.90                    | 49.21                   | 45.31                      | 98.51           | -53.20       | AVG      |         |
| 2   | *   | 2.7015       | 8.23                     | 38.24                   | 46.47                      | 69.54           | -23.07       | QP       |         |
| 3   |     | 14.2980      | 7.35                     | 38.14                   | 45.49                      | 69.54           | -24.05       | QP       |         |


REMARKS:

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode: TX Mode

**Ant 90°**




| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1   |     | 0.0133       | -14.30                   | 76.39                   | 62.09                      | 125.13          | -63.04       | AVG      |         |
| 2   |     | 0.0357       | -16.40                   | 67.99                   | 51.59                      | 116.55          | -64.96       | AVG      |         |
| 3   | *   | 0.1025       | -4.90                    | 57.85                   | 52.95                      | 107.39          | -54.44       | QP       |         |

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode: TX Mode

**Ant 90°**



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1   |     | 0.3525       | -3.80                    | 47.55                   | 43.75                      | 96.66           | -52.91       | AVG      |         |
| 2   | *   | 1.7790       | 8.54                     | 39.33                   | 47.87                      | 69.54           | -21.67       | QP       |         |
| 3   |     | 14.7930      | 7.42                     | 38.06                   | 45.48                      | 69.54           | -24.06       | QP       |         |

**REMARKS:**


- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

## **APPENDIX C - RADIATED EMISSION-30 MHZ TO 1000 MHZ**



Test Mode: TX Mode

### Vertical



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1   | *   | 36.3050      | 48.47                    | -15.52                  | 32.95                      | 40.00           | -7.05        | peak     |         |
| 2   |     | 98.3850      | 45.70                    | -17.31                  | 28.39                      | 43.50           | -15.11       | peak     |         |
| 3   |     | 152.7050     | 44.25                    | -12.05                  | 32.20                      | 43.50           | -11.30       | peak     |         |
| 4   |     | 179.8650     | 46.88                    | -14.37                  | 32.51                      | 43.50           | -10.99       | peak     |         |
| 5   |     | 624.1250     | 37.17                    | -5.64                   | 31.53                      | 46.00           | -14.47       | peak     |         |
| 6   |     | 990.3000     | 33.91                    | -3.82                   | 30.09                      | 54.00           | -23.91       | peak     |         |


**REMARKS:**

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode: TX Mode

### Horizontal




| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Margin<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|--------------|----------|---------|
| 1   |     | 92.0800      | 45.01                    | -18.01                  | 27.00                      | 43.50           | -16.50       | peak     |         |
| 2   | *   | 155.6150     | 49.56                    | -12.19                  | 37.37                      | 43.50           | -6.13        | peak     |         |
| 3   |     | 197.8100     | 47.59                    | -16.10                  | 31.49                      | 43.50           | -12.01       | peak     |         |
| 4   |     | 261.3450     | 41.38                    | -14.52                  | 26.86                      | 46.00           | -19.14       | peak     |         |
| 5   |     | 391.3250     | 39.37                    | -11.32                  | 28.05                      | 46.00           | -17.95       | peak     |         |
| 6   |     | 624.1250     | 36.35                    | -5.64                   | 30.71                      | 46.00           | -15.29       | peak     |         |

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

**APPENDIX D - RADIATED EMISSION - ABOVE 1000 MHZ**

Test Mode : TX 2402 MHz\_CH00\_1Mbps




| No. Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment  |
|---------|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|----------|
| 1       | 2390.000     | 23.02                    | 33.24                   | 56.26                      | 74.00           | -17.74     | peak     |          |
| 2       | 2390.000     | 7.52                     | 33.24                   | 40.76                      | 54.00           | -13.24     | AVG      |          |
| 3 X     | 2401.700     | 52.89                    | 33.28                   | 86.17                      | 74.00           | 12.17      | peak     | No Limit |
| 4 *     | 2402.000     | 51.81                    | 33.28                   | 85.09                      | 54.00           | 31.09      | AVG      | No Limit |

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode : TX 2402 MHz\_CH00\_1Mbps

### Vertical




| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|---------|
| 1   |     | 4803.678     | 50.00                    | -9.07                   | 40.93                      | 74.00           | -33.07     | peak     |         |
| 2   | *   | 4803.820     | 38.48                    | -9.07                   | 29.41                      | 54.00           | -24.59     | AVG      |         |

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode : TX 2402 MHz\_CH00\_1Mbps



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment  |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|----------|
| 1   |     | 2390.000     | 23.09                    | 33.24                   | 56.33                      | 74.00           | -17.67     | peak     |          |
| 2   |     | 2390.000     | 9.13                     | 33.24                   | 42.37                      | 54.00           | -11.63     | AVG      |          |
| 3   | *   | 2401.950     | 57.30                    | 33.28                   | 90.58                      | 54.00           | 36.58      | AVG      | No Limit |
| 4   | X   | 2402.100     | 58.14                    | 33.28                   | 91.42                      | 74.00           | 17.42      | peak     | No Limit |


**REMARKS:**

(1) Measurement Value = Reading Level + Correct Factor.

(2) Margin Level = Measurement Value - Limit Value.

Test Mode : TX 2402 MHz\_CH00\_1Mbps

### Horizontal




| No. | Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measurement dBuV/m | Limit dBuV/m | Over dB | Detector | Comment |
|-----|-----|-----------|--------------------|-------------------|--------------------|--------------|---------|----------|---------|
| 1   | *   | 4803.998  | 37.96              | -9.07             | 28.89              | 54.00        | -25.11  | AVG      |         |
| 2   |     | 4801.545  | 50.62              | -9.08             | 41.54              | 74.00        | -32.46  | peak     |         |

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode : TX 2440 MHz\_CH19\_1Mbps




| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment  |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|----------|
| 1   | *   | 2440.000     | 54.23                    | 33.39                   | 87.62                      | 54.00           | 33.62      | AVG      | No Limit |
| 2   | X   | 2440.200     | 55.17                    | 33.39                   | 88.56                      | 74.00           | 14.56      | peak     | No Limit |

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.



Test Mode : TX 2440 MHz\_CH19\_1Mbps




| No. Mk. | Freq. MHz | Reading Level dBuV | Correct Factor dB | Measurement dBuV/m | Limit dBuV/m | Over dB | Detector | Comment |
|---------|-----------|--------------------|-------------------|--------------------|--------------|---------|----------|---------|
| 1       | 4879.672  | 50.31              | -8.78             | 41.53              | 74.00        | -32.47  | peak     |         |
| 2 *     | 4879.948  | 39.19              | -8.78             | 30.41              | 54.00        | -23.59  | AVG      |         |

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode : TX 2440 MHz\_CH19\_1Mbps

### Horizontal




| No. | Mk. | Freq.    | Reading Level | Correct Factor | Measurement | Limit  | Over  | Detector | Comment  |
|-----|-----|----------|---------------|----------------|-------------|--------|-------|----------|----------|
|     |     | MHz      | dBuV          | dB             | dBuV/m      | dBuV/m | dB    |          |          |
| 1   | *   | 2440.000 | 57.83         | 33.39          | 91.22       | 54.00  | 37.22 | AVG      | No Limit |
| 2   | X   | 2440.250 | 58.87         | 33.39          | 92.26       | 74.00  | 18.26 | peak     | No Limit |

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode : TX 2440 MHz\_CH19\_1Mbps

### Horizontal




| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|---------|
| 1   | *   | 4879.790     | 38.43                    | -8.78                   | 29.65                      | 54.00           | -24.35     | AVG      |         |
| 2   |     | 4879.648     | 49.92                    | -8.78                   | 41.14                      | 74.00           | -32.86     | peak     |         |

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode : TX 2480 MHz\_CH39\_1Mbps




| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment  |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|----------|
| 1   | X   | 2479.750     | 54.64                    | 33.50                   | 88.14                      | 74.00           | 14.14      | peak     | No Limit |
| 2   | *   | 2480.000     | 53.61                    | 33.51                   | 87.12                      | 54.00           | 33.12      | AVG      | No Limit |
| 3   |     | 2483.500     | 22.82                    | 33.51                   | 56.33                      | 74.00           | -17.67     | peak     |          |
| 4   |     | 2483.500     | 8.82                     | 33.51                   | 42.33                      | 54.00           | -11.67     | AVG      |          |

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode : TX 2480 MHz\_CH39\_1Mbps




| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|---------|
| 1   |     | 4959.748     | 51.51                    | -8.47                   | 43.04                      | 74.00           | -30.96     | peak     |         |
| 2   | *   | 4959.898     | 39.26                    | -8.47                   | 30.79                      | 54.00           | -23.21     | AVG      |         |

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode : TX 2480 MHz\_CH39\_1Mbps

### Horizontal




| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment  |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|----------|
| 1   | *   | 2480.000     | 57.86                    | 33.51                   | 91.37                      | 54.00           | 37.37      | AVG      | No Limit |
| 2   | X   | 2480.200     | 58.84                    | 33.51                   | 92.35                      | 74.00           | 18.35      | peak     | No Limit |
| 3   |     | 2483.500     | 21.74                    | 33.51                   | 55.25                      | 74.00           | -18.75     | peak     |          |
| 4   |     | 2483.500     | 9.77                     | 33.51                   | 43.28                      | 54.00           | -10.72     | AVG      |          |

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.

Test Mode : TX 2480 MHz\_CH39\_1Mbps

### Horizontal



| No. | Mk. | Freq.<br>MHz | Reading<br>Level<br>dBuV | Correct<br>Factor<br>dB | Measure-<br>ment<br>dBuV/m | Limit<br>dBuV/m | Over<br>dB | Detector | Comment |
|-----|-----|--------------|--------------------------|-------------------------|----------------------------|-----------------|------------|----------|---------|
| 1   | *   | 4959.453     | 38.35                    | -8.48                   | 29.87                      | 54.00           | -24.13     | AVG      |         |
| 2   |     | 4959.650     | 50.68                    | -8.47                   | 42.21                      | 74.00           | -31.79     | peak     |         |

**REMARKS:**

- (1) Measurement Value = Reading Level + Correct Factor.
- (2) Margin Level = Measurement Value - Limit Value.


## APPENDIXE - BANDWIDTH




Test Mode: CH00, CH19 , CH39 - 1Mbps

| Channel | Frequency (MHz) | 6dB Bandwidth (MHz) | 99 % Emission Bandwidth (MHz) | 6 dB Bandwidth Min. Limit (kHz) | Test Result |
|---------|-----------------|---------------------|-------------------------------|---------------------------------|-------------|
| 00      | 2402            | 0.700               | 1.040                         | 500                             | Pass        |
| 19      | 2440            | 0.704               | 1.044                         | 500                             | Pass        |
| 39      | 2480            | 0.688               | 1.036                         | 500                             | Pass        |


**6dB Bandwidth**



Date: 17\_JUL.2019 15:40:53




Date: 17\_JUL.2019 15:43:10




Date: 17\_JUL.2019 15:45:10

**99 % Emission Bandwidth**



Date: 13\_SEP.2019 00:51:24



Date: 13\_SEP.2019 00:55:07




Date: 13\_SEP.2019 00:56:46


## **APPENDIX F - MAXIMUM OUTPUT POWER & E.I.R.P.**

Test Mode : CH00, CH19 , CH39 - 1Mbps


| Frequency (MHz) | Output Power (dBm) | Output Power (W) | Max. Limit (dBm) | Max. Limit (W) | Test Result |
|-----------------|--------------------|------------------|------------------|----------------|-------------|
| 2402            | 4.96               | 0.0031           | 30.00            | 1.00           | Pass        |
| 2440            | 4.82               | 0.0030           | 30.00            | 1.00           | Pass        |
| 2480            | 5.50               | 0.0035           | 30.00            | 1.00           | Pass        |



Date: 23.AUG.2019 15:08:29



Date: 23.AUG.2019 15:09:28




Date: 23.AUG.2019 15:10:20

**APPENDIXG - CONDUCTED SPURIOUS EMISSION**


Test Mode : CH00, CH19 , CH39 - 1Mbps

### Bandedge- CH00 (Lower)




Date: 17\_JUL2019 15:41:17

### Bandedge CH39(Upper)




Date: 17\_JUL2019 15:45:17


### CH00-10th Harmonic of the fundamental frequency



Date: 17\_JUL2019 15:41:30




Date: 17\_JUL2019 15:41:37




Date: 17\_JUL2019 15:41:44


### CH19-10th Harmonic of the fundamental frequency



Date: 17\_JUL2019 15:43:30




Date: 17\_JUL2019 15:43:38




Date: 17\_JUL2019 15:43:45


### CH39-10th Harmonic of the fundamental frequency



Date: 17\_JUL2019 15:45:30



Date: 17\_JUL2019 15:45:37





Date: 17\_JUL2019 15:45:44

## APPENDIXH - POWER SPECTRAL DENSITY

Test Mode: CH00, CH19 , CH39 - 1Mbps

| Channel | Frequency (MHz) | Power SpectralDensity (dBm/3 kHz) | Max. Limit (dBm/3 kHz) | Test Result |
|---------|-----------------|-----------------------------------|------------------------|-------------|
| 00      | 2402            | -11.080                           | 8.00                   | Pass        |
| 19      | 2440            | -11.380                           | 8.00                   | Pass        |
| 39      | 2480            | -10.590                           | 8.00                   | Pass        |



End of Test Report