

FCC 47 CFR PART 15 SUBPART C INDUSTRY CANADA RSS-210 ISSUE 8

BLUETOOTH LOW ENERGY CERTIFICATION TEST REPORT

FOR

HEALTH TRACKING BAND

MODEL NUMBERS: FTJ10001, FTJ10002, FTJ10003, FTJ10004, FTJ10011, FTJ10012, FTJ10013, FTJ10014. FTJ50001, FTJ50011, FTJ50012, FTJ50013, FTJ50014

> FCC ID: 2AB8ZND5 IC: 1000X-ND5

REPORT NUMBER: 15U20336-E2A

ISSUE DATE: June 4, 2015

Prepared for INTEL CORPORATION 2200 MISSION COLLEGE BOULEVARD SANTA CLARA, CA 95052, U.S.A.

Prepared by UL VERIFICATION SERVICES INC. 47173 BENICIA STREET FREMONT, CA 94538, U.S.A. TEL: (510) 771-1000 FAX: (510) 661-0888

NVLAP LAB CODE 200065-0

Revision History

Rev.	Issue Date	Revisions	Revised By
	06/02/2015	Initial Issue	T. Chan
А	06/04/2015	Updated Section 10.1, 10.2 and 10.3	D. Weaver

Page 2 of 62

TABLE OF CONTENTS

1. A	ATTESTATION OF TEST RESULTS	4
2. T	TEST METHODOLOGY	5
3. F	FACILITIES AND ACCREDITATION	5
4. C	CALIBRATION AND UNCERTAINTY	5
4.1.	. MEASURING INSTRUMENT CALIBRATION	5
4.2.	. SAMPLE CALCULATION	5
4.3.	. MEASUREMENT UNCERTAINTY	6
5. E	EQUIPMENT UNDER TEST	7
5.1.	DESCRIPTION OF EUT	7
5.2.	. MANUFACTURER'S DESCRIPTION OF MODEL DIFFERENCES	7
5.3.	. MAXIMUM OUTPUT POWER	7
5.4.	DESCRIPTION OF AVAILABLE ANTENNAS	7
5.5.	. SOFTWARE AND FIRMWARE	7
5.6.	. WORST-CASE CONFIGURATION AND MODE	7
5.7.	DESCRIPTION OF TEST SETUP	8
6. T	EST AND MEASUREMENT EQUIPMENT	10
7. N	MEASUREMENT METHODS	11
7. N 8. C	MEASUREMENT METHODS	11
7. M 8. C 9. A	MEASUREMENT METHODS ON TIME, DUTY CYCLE AND MEASUREMENT METHODS	11 12 14
7. N 8. C 9. A 9.1.	MEASUREMENT METHODS ON TIME, DUTY CYCLE AND MEASUREMENT METHODS ANTENNA PORT TEST RESULTS	11 12 14 14
 7. M 8. C 9. A 9.1. 9.2. 	MEASUREMENT METHODS ON TIME, DUTY CYCLE AND MEASUREMENT METHODS ANTENNA PORT TEST RESULTS	11 12 14 14 16
 7. M 8. C 9. A 9.1. 9.2. 9.3. 	MEASUREMENT METHODS ON TIME, DUTY CYCLE AND MEASUREMENT METHODS ANTENNA PORT TEST RESULTS 6 dB BANDWIDTH 99% BANDWIDTH 0 UTPUT POWER	11 12 14 14 16 18
 7. M 8. C 9. A 9.1. 9.2. 9.3. 9.4. 	MEASUREMENT METHODS ON TIME, DUTY CYCLE AND MEASUREMENT METHODS ANTENNA PORT TEST RESULTS	11 12 14 14 16 18 20
 7. M 8. C 9. A 9.1. 9.2. 9.3. 9.4. 9.5. 	MEASUREMENT METHODS ON TIME, DUTY CYCLE AND MEASUREMENT METHODS ANTENNA PORT TEST RESULTS	11 12 14 14 16 18 20 21
 7. M 8. C 9. A 9.1. 9.2. 9.3. 9.4. 9.5. 9.6. 	MEASUREMENT METHODS ON TIME, DUTY CYCLE AND MEASUREMENT METHODS	11 12 14 14 16 18 20 21 23
 7. M 8. C 9. A 9.3. 9.4. 9.5. 9.6. 	MEASUREMENT METHODS ON TIME, DUTY CYCLE AND MEASUREMENT METHODS ANTENNA PORT TEST RESULTS	11 12 14 14 16 18 20 21 23 23
 7. M 8. C 9. A 9.1. 9.2. 9.3. 9.4. 9.5. 9.6. 10. 	MEASUREMENT METHODS ON TIME, DUTY CYCLE AND MEASUREMENT METHODS ANTENNA PORT TEST RESULTS	11 12 14 14 16 18 20 21 23 27 27
 7. M 8. C 9. A 9.1. 9.2. 9.3. 9.4. 9.5. 9.6. 10. 10.2 	MEASUREMENT METHODS ON TIME, DUTY CYCLE AND MEASUREMENT METHODS ANTENNA PORT TEST RESULTS	11 12 14 14 14 16 18 20 21 23 27 27 28
 7. M 8. C 9. A 9.1. 9.2. 9.3. 9.4. 9.5. 9.6. 10. 10.2 10.3 	MEASUREMENT METHODS ON TIME, DUTY CYCLE AND MEASUREMENT METHODS ANTENNA PORT TEST RESULTS	11 12 14 14 16 18 20 21 23 27 27 27 28
 7. M 8. C 9. A 9.1. 9.2. 9.3. 9.4. 9.5. 9.6. 10. 10.2 10.2 10.3 10.4 	MEASUREMENT METHODS ON TIME, DUTY CYCLE AND MEASUREMENT METHODS ANTENNA PORT TEST RESULTS antenna Port Test results 6 dB BANDWIDTH. 99% BANDWIDTH. 0UTPUT POWER AVERAGE POWER. POWER SPECTRAL DENSITY. CONDUCTED SPURIOUS EMISSIONS RADIATED TEST RESULTS. 1. LIMITS AND PROCEDURE. 2. TRANSMITTER ABOVE 1 GHz – EUT WITHOUT WRISTBAND 3. WORST-CASE BELOW 1 GHz – EUT WITHOUT WRISTBAND 4. TRANSMITTER ABOVE 1 GHz – EUT WITH METAL WRISTBAND	11 12 14 14 14 14 14 14 14 14 14 12
 7. M 8. C 9. A 9.1. 9.2. 9.3. 9.4. 9.5. 9.6. 10. 10.2 10.2 10.4 10.4 10.4 	MEASUREMENT METHODS ON TIME, DUTY CYCLE AND MEASUREMENT METHODS ANTENNA PORT TEST RESULTS 6 dB BANDWIDTH. 99% BANDWIDTH. 0UTPUT POWER 0UTPUT POWER AVERAGE POWER POWER SPECTRAL DENSITY. CONDUCTED SPURIOUS EMISSIONS RADIATED TEST RESULTS 1. LIMITS AND PROCEDURE 2. TRANSMITTER ABOVE 1 GHz – EUT WITHOUT WRISTBAND 3. WORST-CASE BELOW 1 GHz – EUT WITH METAL WRISTBAND 5. WORST-CASE BELOW 1 GHz – EUT WITH METAL WRISTBAND	11 12 14 14 14 16 18 20 21 23 27 27 27 28 38 38 31

Page 3 of 62

1. ATTESTATION OF TEST RESULTS

COMPANY NAME:	INTEL CORPORATION 2200 MISSION COLLEGE BOULEVARD SANTA CLARA, CA 95052, U.S.A
EUT DESCRIPTION:	HEALTH TRACKING BAND
MODEL:	FTJ10001, FTJ10002, FTJ10003, FTJ10004, FTJ10011, FTJ10012, FTJ10013, FTJ10014. FTJ50001, FTJ50011, FTJ50012, FTJ50013, FTJ50014
SERIAL NUMBER:	LS4794FZ516008V

DATE TESTED: MAY 21 to 27, 2015

APPLICABLE STANDARDS						
STANDARD	TEST RESULTS					
CFR 47 Part 15 Subpart C	Pass					
INDUSTRY CANADA RSS-210 Issue 8 Annex 8	Pass					
INDUSTRY CANADA RSS-GEN Issue 4	Pass					

UL Verification Services Inc. tested the above equipment in accordance with the requirements set forth in the above standards. All indications of Pass/Fail in this report are opinions expressed by UL Verification Services Inc. based on interpretations and/or observations of test results. Measurement Uncertainties were not taken into account and are published for informational purposes only. The test results show that the equipment tested is capable of demonstrating compliance with the requirements as documented in this report.

Note: The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein. This document may not be altered or revised in any way unless done so by UL Verification Services Inc. and all revisions are duly noted in the revisions section. Any alteration of this document not carried out by UL Verification Services Inc. will constitute fraud and shall nullify the document. This report must not be used by the client to claim product certification, approval, or endorsement by NVLAP, NIST, any agency of the Federal Government, or any agency of any government.

Approved & Released For UL Verification Services Inc. By:

THU CHAN PROGRAM MANAGER UL Verification Services Inc. Tested By:

Jude Semana EMC LABORATORY TECHNICIAN UL Verification Services Inc.

Page 4 of 62

UL VERIFICATION SERVICES INC. 47173 BENICIA STREET, FREMONT, CA 94538, USA This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

2. TEST METHODOLOGY

The tests documented in this report were performed in accordance with FCC CFR 47 Part 2, FCC CFR 47 Part 15, RSS-GEN Issue 4, and RSS-247, Issue 1, and ANSI C63.10-2009 for FCC test and ANSI C63.10:2013 deviation of measurement height of 0.8m rather than 1.5m for IC test.

3. FACILITIES AND ACCREDITATION

The test sites and measurement facilities used to collect data are located at 47173 and 47266 Benicia Street, Fremont, California, USA. Line conducted emissions are measured only at the 47173 address. The following table identifies which facilities were utilized for radiated emission measurements documented in this report. Specific facilities are also identified in the test results sections.

47173 Benicia Street	47266 Benicia Street		
🖂 Chamber A	Chamber D		
🖂 Chamber B	Chamber E		
🛛 Chamber C	Chamber F		
	Chamber G		
	Chamber H		

The above test sites and facilities are covered under FCC Test Firm Registration # 208313.

Chambers A through H are covered under Industry Canada company address code 2324B with site numbers 2324B -1 through 2324B-8, respectively.

UL Verification Services Inc. is accredited by NVLAP, Laboratory Code 200065-0. The full scope of accreditation can be viewed at <u>http://ts.nist.gov/standards/scopes/2000650.htm</u>.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations, and is traceable to recognized national standards.

4.2. SAMPLE CALCULATION

Where relevant, the following sample calculation is provided: Field Strength (dBuV/m) = Measured Voltage (dBuV) + Antenna Factor (dB/m) + Cable Loss (dB) – Preamp Gain (dB) 36.5 dBuV + 18.7 dB/m + 0.6 dB – 26.9 dB = 28.9 dBuV/m

Page 5 of 62

4.3. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

PARAMETER	UNCERTAINTY
Conducted Disturbance, 0.15 to 30 MHz	± 3.52 dB
Radiated Disturbance, 30 to 1000 MHz	± 4.94 dB
Radiated Disturbance, 1 to 6 GHz	± 3.86 dB

Uncertainty figures are valid to a confidence level of 95%.

Page 6 of 62

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

The EUT is a wearable device intended for heath tracking. The device incorporates a BLE radio with an integral antenna.

The EUT is battery powered and incorporates wireless charging.

5.2. MANUFACTURER'S DESCRIPTION OF MODEL DIFFERENCES

Model numbers FTJ10001, FTJ10002, FTJ10003, FTJ10004, FTJ10011, FTJ10012, FTJ10013, FTJ10014. FTJ50001, FTJ50011, FTJ50012, FTJ50013 and FTJ50014 are the same except for band style and color.

5.3. MAXIMUM OUTPUT POWER

The transmitter has a maximum peak conducted output power as follows:

Frequency Range	Mode	Output Power	Output Power
(MHz)		(dBm)	(mW)
2402 - 2480	BLE	4.53	2.84

5.4. DESCRIPTION OF AVAILABLE ANTENNAS

The radio utilizes a PCB antenna, with a maximum gain of 0 dBi.

5.5. SOFTWARE AND FIRMWARE

The firmware installed in the EUT during testing was DVT, rev. build 1883.

5.6. WORST-CASE CONFIGURATION AND MODE

Radiated emission was performed with the EUT set to transmit at the channel with highest output power as worst-case scenario.

The fundamental of the EUT was investigated in three orthogonal orientations X,Y,Z, it was determined that X orientation was worst-case orientation for the EUT without metal band and the Y orientation was worst-case orientation for the EUT with metal band, therefore, all final radiated testing was performed with the EUT in X orientation without metal band and Y orientation with metal band.

Page 7 of 62

5.7. DESCRIPTION OF TEST SETUP

SUPPORT EQUIPMENT

Support Equipment List							
Description	Manufacturer	Model	Serial Number	FCC ID			
Laptop	Lenovo	20332	YB04282152				
Pass Thru Board 1	Intel						
(Connected to Laptop)							
Pass Thru Board 2	Intel						
(Connected to EUT)							

I/O CABLES

	I/O Cable List								
Cable No	Port	# of identical ports	Connector Type	Cable Type	Cable Length (m)	Remarks			
1	USB	1	USB B	shielded	1	Laptop to Pass Thru Board 2			
2	DATA	1	Multi Pin	Unshielded	0.15	Pass Thru Board 1 to Pass Thru Board 2			
3	DATA	1	Soldered Pins	Unshielded	0.03	Pass Thru Board 2 to EUT			

TEST SETUP

The EUT is continuously transmitting during the tests.

Page 8 of 62

SETUP DIAGRAM FOR TESTS



UL VERIFICATION SERVICES INC. 47173 BENICIA STREET, FREMONT, CA 94538, USA TEL: (510) 771-1000 FAX: (510) 661-0888 This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

Page 9 of 62

6. TEST AND MEASUREMENT EQUIPMENT

The following test and measurement equipment was utilized for the tests documented in this report:

Test Equipment List					
Description	Manufacturer	Model	T No.	Cal Date	Cal Due
Radiated Software	UL	UL EMC		Ver 9.5, July 22	, 2014
Antenna, Horn 1-18GHz	ETS	3117	345	03/03/2015	03/03/2016
Antenna, Horn 1-18GHz	ETS	3117	119	01/25/2015	01/15/2016
Spectrum Analyzer, PXA, 3Hz- 44GHz	Agilent	N9030A	907	05/15/2015	05/15/2016
Spectrum Analyzer, PXA, 3Hz- 44GHz	Agilent	N8030A	342	06/25/2014	06/25/2015
Spectrum Analyzer, PXA, 3Hz- 44GHz	Agilent	E4446A	99	06/03/2014	06/03/2015
Antenna, Broadband Hybrid, 30Mhz - 1000Mhz	Sunol Sciences	JB1	243	12/08/2014	12/08/2015
Power Meter, P-series single channel	Agilent	N1911A	229	08/07/2014	08/07/2015
Power Sensor, Peak and average, 50MHz-6 GHz, 5MHz BW	Agilent	E9323A	117	03/09/2015	03/09/2016

Page 10 of 62

7. MEASUREMENT METHODS

<u>6 dB BW</u>: KDB 558074 D01 v03r02, Section 8.1.

Output Power: KDB 558074 D01 v03r02, Section 9.1.2.

Power Spectral Density: KDB 558074 D01 v03r02, Section 10.2.

Out-of-band emissions in non-restricted bands: KDB 558074 D01 v03r02, Section 11.0.

Out-of-band emissions in restricted bands: KDB 558074 D01 v03r02, Section 12.1.

Band-edge: KDB 558074 D01 v03r02, Section 12.1

Page 11 of 62

8. ON TIME, DUTY CYCLE AND MEASUREMENT METHODS

LIMITS

None; for reporting purposes only.

PROCEDURE

KDB 558074 Zero-Span Spectrum Analyzer Method.

8.1. ON TIME AND DUTY CYCLE RESULTS

Mode	ON Time	Period	Duty Cycle	Duty	Duty Cycle	1/B
	В		х	Cycle	Correction Factor	Minimum VBW
	(msec)	(msec)	(linear)	(%)	(dB)	(kHz)
BLE	0.427	0.626	0.682	68.21%	1.66	2.342

Page 12 of 62

DUTY CYCLE PLOTS

Ref 11.15 (dBm	#Atten 20 dB		A Mkr2 626 μs 1.81 dB	Certer Freq 2.44000000 GHz
Log 10 dB/		28			Start Freq 2.43850000 GHz
10.1 dB		↓ praval		wather wat	Stop Freq 2.44150000 GHz
#PAvg					CF Step 300.000000 kHz <u>Auto Mar</u>
Center 2.4 #Res BW 8	40 000 GHz 8 MHz	<u>.</u>	¥VBW 50 MHz	Span 3 MHz Sweep 1 ms (1001 pts)	Freq Offset
Marker 1R 1∆ 2R 2∆	Trace (1) (1) (1) (1)	Type Time Time Time Time	X Axis 298 μs 427 μs 298 μs 626 μs	Amplitude -3.12 dBm 6.67 dB -3.12 dBm 1.81 dB	Signal Track
Copyright 2	000-2010 A	gilent Technol	ogies		_

Page 13 of 62

9. ANTENNA PORT TEST RESULTS

9.1. 6 dB BANDWIDTH

LIMITS

FCC §15.247 (a) (2)

IC RSS-210 A8.2 (a)

The minimum 6 dB bandwidth shall be at least 500 kHz.

RESULTS

Channel	Frequency (MHz)	6 dB Bandwidth (MHz)	Minimum Limit (MHz)
Low	2402	0.6910	0.5
Middle	2440	0.7080	0.5
High	2480	0.7070	0.5

6 dB BANDWIDTH PLOTS

LOW CHANNEL



Page 14 of 62

MID CHANNEL



HIGH CHANNEL



Page 15 of 62

9.2. 99% **BANDWIDTH**

<u>LIMITS</u>

None; for reporting purposes only.

TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. The RBW is set to 1% to 3% of the 99 % bandwidth and to 1% of the span. The VBW is set to 3 times the RBW. The sweep time is coupled. The spectrum analyzer internal 99% bandwidth function is utilized.

RESULTS

Channel	Frequency (MHz)	99% Bandwidth (MHz)
Low	2402	1.0164
Middle	2440	1.0150
High	2480	1.0154

99% BANDWIDTH PLOTS



LOW CHANNEL

Page 16 of 62

MID CHANNEL



HIGH CHANNEL



Page 17 of 62

9.3. OUTPUT POWER

LIMITS

FCC §15.247 (b)

IC RSS-210 A8.4

The maximum antenna gain is less than or equal to 6 dBi, therefore the limit is 30 dBm.

RESULTS

Channel	Frequency	Peak Power Reading	Limit	Margin
	(MHz)	(dBm)	(dBm)	(dB)
Low	2402	4.528	30	-25.472
Middle	2440	4.493	30	-25.507
High	2480	4.385	30	-25.615

OUTPUT POWER PLOTS



LOW CHANNEL

Page 18 of 62

MID CHANNEL



HIGH CHANNEL



Page 19 of 62

9.4. AVERAGE POWER

<u>LIMITS</u>

None; for reporting purposes only.

RESULTS

The cable assembly insertion loss of 11 dB (including 10 dB pad and 1 dB cable) was entered as an offset in the power meter to allow for direct reading of power.

Channel	Frequency (MHz)	AV power (dBm)
Low	2402	4.18
Middle	2440	4.19
High	2480	4.11

Page 20 of 62

9.5. POWER SPECTRAL DENSITY

LIMITS

FCC §15.247 (e)

IC RSS-210 A8.2 (b)

The power spectral density conducted from the transmitter to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.

RESULTS

Channel	Frequency (MHz)	PSD (dBm)	Limit (dBm)	Margin (dB)
Low	2402	-7.01	8	-15.01
Middle	2440	-7.08	8	-15.08
High	2480	-7.61	8	-15.61

POWER SPECTRAL DENSITY PLOTS



LOW CHANNEL

Page 21 of 62



MID CHANNEL

HIGH CHANNEL



Page 22 of 62

9.6. CONDUCTED SPURIOUS EMISSIONS

<u>LIMITS</u>

FCC §15.247 (d)

IC RSS-210 A8.5

Output power was measured based on the use of a peak measurement, therefore the required attenuation is 20 dB.

RESULTS

SPURIOUS EMISSIONS, LOW CHANNEL



LOW CHANNEL BANDEDGE

Page 23 of 62

🔆 Agi	ilent 17	:39:30	May 29,	2015					F	₹Т	Freq/Channel
Ref 20 #Peak	dBm		Atten 2	0 dB				Mk	.r3 7.20 -51.94	05 GHz dBm	Center Freq 13.0150000 GHz
Log 10 dB/ Offst	¢	×									Start Freq 30.0000000 MHz
11.1 dB DI		2	3								Stop Freq 26.000000 GHz
-15.3 dBm #PAvg	er le gentite			~~~		, 11 - 11 - 11					CF Step 2.59700000 GHz <u>Auto Man</u>
Start 30 #Res B) MHz W 100 I	kHz		#VE	3W 300	kHz	Swee	Sto p 2.482	p 26.00 s (8192	0 GHz pts)	Freq Clfset
Marker 1 2 3	т	race (1) (1) (1)	Type Fieq Fieq Fieq		X 2.4 4.8 7.2	Axis 102 GHz 105 GHz 205 GHz			Amplitu 3.35 dB -43.49 dB -51.94 dB	ude im im	Signal Track On <u>C</u> !f
Copyrig	ht 2000	-2010 Ag	gilent Teo	chnologi	es						

LOW CHANNEL SPURIOUS

SPURIOUS EMISSIONS, MID CHANNEL

MID CHANNEL BANDEDGE



Page 24 of 62

MID CHANNEL SPURIOUS

1 # 510	16-1	1 HUGE JWY	a, ion Airts	104-46-59 PM Map 21, 3015	Freedomen
	PNO: Fast G	Trig: Free Run Atten: 20 dB	#Avg Type: RMS Avg[Held: 32/100	THREE WWWWWW DET P P P P P	requirey
Ref Offset 11. 0 dBidly Ref 20.00 d	16 dB Bm		M	r3 7.319 1 GHz -51.266 dBm	Auto Tune
00 01				·	Center Free
0.00				34.00.00	13.015000000 GH
200					Start Free 30.000000 MH:
	-				Stop Free 26.00000000 GH
itart 30 MHz Res BW 100 kHz	#VB	W 300 kHz	Sweep 95	Stop 26.00 GHz 7.3 ms (40001 pts)	CF Step 2.597000000 GH: Auto Mar
	2.440 0 GHz 4.880 5 GHz 7.319 1 GHz	4.179 dBm -46.976 dBm -51.266 dBm	RCTON FOR TORMETH	SUMMON SUBS	Freq Offset 0 Ha
7 8 9 10 11					
1					

UL VERIFICATION SERVICES INC. 47173 BENICIA STREET, FREMONT, CA 94538, USA This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

Page 25 of 62

SPURIOUS EMISSIONS, HIGH CHANNEL



HIGH CHANNEL BANDEDGE

HIGH CHANNEL SPURIOUS



Page 26 of 62

10. RADIATED TEST RESULTS

10.1. LIMITS AND PROCEDURE

LIMITS

FCC §15.205 and §15.209

IC RSS-GEN Clause 8.9 (Transmitter)

IC RSS-GEN Clause 7.1.2 (Receiver)

Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m
30 - 88	100	40
88 - 216	150	43.5
216 - 960	200	46
Above 960	500	54

TEST PROCEDURE

The EUT is placed on a non-conducting table 80 cm above the ground plane. The antenna to EUT distance is 3 meters. The EUT is configured in accordance with ANSI C63.10. The EUT is set to transmit in a continuous mode.

For measurements below 1 GHz the resolution bandwidth is set to 100 kHz for peak detection measurements or 120 kHz for quasi-peak detection measurements. Peak detection is used unless otherwise noted as quasi-peak.

For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 3MHz video bandwidth with average detector for average measurements.

The spectrum from 30 MHz to 26 GHz is investigated with the transmitter set to the lowest, middle, and highest channels in the 2.4 GHz band.

The frequency range of interest is monitored at a fixed antenna height and EUT azimuth. The EUT is rotated through 360 degrees to maximize emissions received. The antenna is scanned from 1 to 4 meters above the ground plane to further maximize the emission. Measurements are made with the antenna polarized in both the vertical and the horizontal positions.

Page 27 of 62

10.2. TRANSMITTER ABOVE 1 GHz – EUT WITHOUT WRISTBAND

RESTRICTED BANDEDGE (LOW CHANNEL)



HORIZONTAL PEAK AND AVERAGE PLOT

HORIZONTAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/Fit r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	39.21	PK	32	-22.6	0	48.61	-	-	74	-25.39	320	290	Н
2	* 2.383	46.53	PK	32	-22.6	0	55.93	-	-	74	-18.07	320	290	Н
3	* 2.39	28.74	RMS	32	-22.6	1.7	39.84	54	-14.16	-	-	320	290	Н
4	* 2.382	30.48	RMS	32	-22.6	1.7	41.58	54	-12.42	-	-	320	290	Н

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band PK - Peak detector

RMS - RMS detection



VERTICAL PEAK AND AVERAGE PLOT

VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/Flt r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	37.48	PK	32	-22.6	0	46.88	-	-	74	-27.12	343	346	V
2	* 2.383	42.55	PK	32	-22.6	0	51.95	-	-	74	-22.05	343	346	V
3	* 2.39	28.76	RMS	32	-22.6	1.7	39.86	54	-14.14	•	-	343	346	V
4	* 2.383	29.65	RMS	32	-22.6	1.7	40.75	54	-13.25	-	-	343	346	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band PK - Peak detector

RMS - RMS detection

Page 29 of 62

AUTHORIZED BANDEDGE (HIGH CHANNEL) - EUT WITHOUT WRISTBAND



HORIZONTAL PEAK AND AVERAGE PLOT

HORIZONTAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/Flt r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	38.24	PK	32.5	-22.4	0	48.34	-	-	74	-25.66	356	223	н
3	* 2.484	28.99	RMS	32.5	-22.4	1.7	40.79	54	-13.21	-	-	356	223	н
2	2.506	44.35	PK	32.5	-22.4	0	54.45	-	-	74	-19.55	356	223	Н
4	2.506	30.4	RMS	32.5	-22.4	1.7	42.2	54	-11.8	-	-	356	223	н

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

RMS - RMS detection



VERTICAL PEAK AND AVERAGE PLOT

VERTICAL DATA

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/Flt r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	37.77	PK	32.5	-22.4	0	47.87	-	-	74	-26.13	3	320	V
3	* 2.484	28.33	RMS	32.5	-22.4	1.7	40.13	54	-13.87	-	-	3	320	V
2	2.506	44.65	PK	32.5	-22.4	0	54.75	-	-	74	-19.25	3	320	V
4	2.506	30.15	RMS	32.5	-22.4	1.7	41.95	54	-12.05	-	-	3	320	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band PK - Peak detector **RMS - RMS detection**

UL VERIFICATION SERVICES INC. FORM NO: CCSUP4701I 47173 BENICIA STREET, FREMONT, CA 94538, USA TEL: (510) 771-1000 FAX: (510) 661-0888 This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

Page 31 of 62

HARMONICS AND SPURIOUS EMISSIONS - EUT WITHOUT WRISTBAND



LOW CHANNEL HORIZONTAL

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.



LOW CHANNEL VERTICAL

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Page 32 of 62

LOW CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/Flt r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.326	39.98	PK	31.7	-22.7	0	48.98	-	-	74	-25.02	0-360	199	Н
4	1.861	33.93	PK	31.4	-23.3	0	42.03	-	-	74	-31.97	0-360	199	V
2	3.101	33.02	PK	32.7	-31.4	0	34.32	-	-	74	-39.68	0-360	101	н
3	5.688	31.72	PK	34.9	-29.2	0	37.42	-	-	74	-36.58	0-360	199	н
5	6.336	30.95	PK	35.6	-29	0	37.55	-	-	74	-36.45	0-360	199	V
6	10.058	27.79	PK	37.2	-23.6	0	41.39	-	-	74	-32.61	0-360	101	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/Fl tr/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
* 2.326	46.79	PK2	31.7	-22.7	0	55.79	-	-	74	-18.21	307	250	Н
* 2.327	31.11	MAv1	31.7	-22.7	1.7	41.81	54	-12.19	-	-	307	250	Н

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band PK2 - KDB558074 Method: Maximum Peak MAv1 - KDB558074 Option 1 Maximum RMS Average

UL VERIFICATION SERVICES INC. 47173 BENICIA STREET, FREMONT, CA 94538, USA This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

Page 33 of 62



MID CHANNEL HORIZONTAL – EUT WITHOUT WRISTBAND

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.



MID CHANNEL VERTICAL – EUT WITHOUT WRISTBAND

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Page 34 of 62

MID CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/Fit r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	1.854	34.41	PK	31.3	-23.3	0	42.41	-	-	74	-31.59	0-360	199	Н
4	2.104	34.82	PK	31.8	-23	0	43.62	-	-	74	-30.38	0-360	101	V
2	3.15	32.45	PK	32.5	-31	0	33.95	-	-	74	-40.05	0-360	101	Н
3	6.059	32.46	PK	35.6	-29.7	0	38.36	-	-	74	-35.64	0-360	101	Н
5	4.454	32.13	PK	33.9	-28.9	0	37.13	-	-	74	-36.87	0-360	199	V
6	9.92	28.68	PK	37.1	-23.6	0	42.18	-	-	74	-31.82	0-360	199	V
7	13.822	26.93	PK	38.9	-21.9	0	43.93	-	-	74	-30.07	0-360	199	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band PK - Peak detector

BLE_HARM_2440.dat 30915 7 Jul 2014 Rev 9.5 09 May 2014

Page 35 of 62



HIGH CHANNEL HORIZONTAL – EUT WITHOUT WRISTBAND

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.



HIGH CHANNEL VERTICAL - EUT WITHOUT WRISTBAND

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Page 36 of 62

HIGH CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/Flt r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	1.841	35.62	PK	31.2	-23.3	0	43.52	-	-	74	-30.48	0-360	101	н
2	2.076	35.46	PK	31.9	-23.1	0	44.26	-	-	74	-29.74	0-360	101	Н
3	2.444	42.15	PK	32.3	-22.5	0	51.95	-	-	74	-22.05	0-360	101	н
4	2.577	40	PK	32.7	-22.3	0	50.4	-	-	74	-23.6	0-360	101	н
5	6.557	30.84	PK	35.9	-28.1	0	38.64	-	-	74	-35.36	0-360	101	V
6	14.716	25.54	PK	39.8	-20.8	0	44.54	-	-	74	-29.46	0-360	101	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

Radiated Emissions

Frequency (GHz)	Meter Reading (dBuV)	Det	AF T345 (dB/m)	Amp/Cbl/F ltr/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2.444	48.47	PK2	32.3	-22.5	0	58.27	-	-	74	-15.73	297	229	Н
2.444	33.14	MAv1	32.3	-22.5	1.7	44.64	54	-9.36	-	-	297	229	Н
2.576	48.8	PK2	32.7	-22.3	0	59.2	-	-	74	-14.8	280	309	Н
2.577	31.87	MAv1	32.7	-22.3	1.7	43.97	54	-10.03	-	-	280	309	Н

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band PK2 - KDB558074 Method: Maximum Peak

MAv1 - KDB558074 Option 1 Maximum RMS Average

Page 37 of 62

10.3. WORST-CASE BELOW 1 GHz – EUT WITHOUT WRISTBAND

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)



HORIZONTAL PLOT

UL VERIFICATION SERVICES INC. 47173 BENICIA STREET, FREMONT, CA 94538, USA This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc. FORM NO: CCSUP4701I TEL: (510) 771-1000 FAX: (510) 661-0888 This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

Page 38 of 62

VERTICAL PLOT



Page 39 of 62

BELOW 1 GHz TABLE

Trace Markers

Marker	Frequency (MHz)	Meter Reading (dBuV)	Det	AF T243 (dB/m)	Amp/Cbl (dB)	Corrected Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 73.7325	47.23	PK	8	-28.4	26.83	40	-13.17	0-360	101	Н
5	35.8225	38.27	PK	16.9	-28.8	26.37	40	-13.63	0-360	101	V
6	92.305	41.61	PK	8.2	-28.1	21.71	43.52	-21.81	0-360	101	V
2	100.3375	52.67	PK	10.3	-28.1	34.87	43.52	-8.65	0-360	101	Н
3	152.8675	41.84	PK	12.4	-27.5	26.74	43.52	-16.78	0-360	101	Н
7	199.1075	34.38	PK	12.6	-27	19.98	43.52	-23.54	0-360	101	V
8	463.7	44.07	PK	17.2	-25.9	35.37	46.02	-10.65	0-360	101	V
9	712.7	41.31	PK	20.4	-24.5	37.21	46.02	-8.81	0-360	101	V
4	825	38.8	PK	21.8	-23.6	37	46.02	-9.02	0-360	101	Н

* - indicates frequency in CFR 47, Part 15 and Industry Canada RSS-Restricted Band.

PK - Peak detector

Page 40 of 62

10.4. TRANSMITTER ABOVE 1 GHz – EUT WITH METAL WRISTBAND

RESTRICTED BANDEDGE (LOW CHANNEL)



HORIZONTAL PEAK AND AVERAGE PLOT

HORIZONTAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Flt r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.39	41.35	PK	32	-23.1	0	50.25	-	-	74	-23.75	293	272	Н
2	* 2.358	42.81	PK	31.9	-23.1	0	51.61	-	-	74	-22.39	293	272	Н
3	* 2.39	30.65	RMS	32	-23.1	1.7	41.25	54	-12.75	-	-	293	272	Н
4	* 2.383	31.01	RMS	32	-23.1	1.7	41.61	54	-12.39	-	-	293	272	Н

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band PK - Peak detector

RMS - RMS detection



VERTICAL PEAK AND AVERAGE PLOT

VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Flt r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
2	* 2.38	43.04	PK	31.9	-23.1	0	51.84	-	-	74	-22.16	309	247	V
4	* 2.389	31.14	RMS	32	-23.1	1.7	41.74	54	-12.26	-	-	309	247	V
1	* 2.39	39.86	PK	32	-23.1	0	48.76	-	-	74	-25.24	309	247	V
3	* 2.39	30.25	RMS	32	-23.1	1.7	40.85	54	-13.15	-	-	309	247	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band PK - Peak detector **RMS - RMS detection**

UL VERIFICATION SERVICES INC. FORM NO: CCSUP4701I 47173 BENICIA STREET, FREMONT, CA 94538, USA TEL: (510) 771-1000 FAX: (510) 661-0888 This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

Page 42 of 62

AUTHORIZED BANDEDGE (HIGH CHANNEL) - EUT WITH METAL WRISTBAND



HORIZONTAL PEAK AND AVERAGE PLOT

HORIZONTAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Flt r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	39.6	PK	32.3	-22.8	0	49.1	-	-	74	-24.9	285	304	н
3	* 2.484	30.5	RMS	32.3	-22.8	1.7	41.7	54	-12.3	-	-	285	304	Н
4	2.531	30.93	RMS	32.4	-22.6	1.7	42.43	54	-11.57	-	-	285	304	Н
2	2.542	42.56	PK	32.4	-22.6	0	52.36	-	-	74	-21.64	285	304	н

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band PK - Peak detector

RMS - RMS detection

Page 43 of 62



VERTICAL PEAK AND AVERAGE PLOT

VERTICAL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Fit r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Average Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	* 2.484	40.08	PK	32.3	-22.8	0	49.58	-	-	74	-24.42	321	321	V
2	* 2.492	43.12	PK	32.3	-22.9	0	52.52	-	-	74	-21.48	321	321	V
3	* 2.484	30.23	RMS	32.3	-22.8	1.67	41.4	54	-12.6	-	-	321	321	V
4	2.527	31.12	RMS	32.4	-22.7	1.67	42.49	54	-11.51	-	-	321	321	V

* - indicates frequency in CFR 47, Part 15 and Industry Canada RSS-Restricted Band. PK - Peak detector

RMS - RMS detection

Page 44 of 62

HARMONICS AND SPURIOUS EMISSIONS - WITH METAL WRISTBAND



LOW CHANNEL HORIZONTAL

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.



LOW CHANNEL VERTICAL

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Page 45 of 62

LOW CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Flt r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	1.835	32.84	PK	30.5	-23.3	0	40.04	•	-	74	-33.96	0-360	100	Н
2	3.163	31.33	PK	32.7	-31	0	33.03	-	-	74	-40.97	0-360	100	н
3	5.758	30.78	PK	34.8	-30.5	0	35.08	-	-	74	-38.92	0-360	100	Н
4	4.459	31.14	PK	33.7	-30.9	0	33.94	•	-	74	-40.06	0-360	200	V
5	8.663	27.94	PK	35.9	-26.9	0	36.94	-	-	74	-37.06	0-360	100	V
6	10.192	26.17	PK	37	-24.6	0	38.57	-	-	74	-35.43	0-360	200	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

Page 46 of 62



MID CHANNEL HORIZONTAL - METAL WRISTBAND

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.



MID CHANNEL VERTICAL- WITH METAL WRISTBAND

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Page 47 of 62

MID CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Flt r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	1.833	33.11	PK	30.5	-23.3	0	40.31	-	-	74	-33.69	0-360	100	Н
4	2.046	32.73	PK	31.5	-23.2	0	41.03	-	-	74	-32.97	0-360	200	V
2	3.412	31.61	PK	32.7	-31.8	0	32.51	-	-	74	-41.49	0-360	100	Н
3	7.862	28.98	PK	35.8	-27.2	0	37.58	•	-	74	-36.42	0-360	200	Н
5	5.909	30.69	PK	35	-30.4	0	35.29	-	-	74	-38.71	0-360	200	V
6	10.143	26.36	PK	37	-25.1	0	38.26	-	-	74	-35.74	0-360	200	V

 * - indicates frequency in CFR15.205/IC7.2.2 Restricted Band PK - Peak detector

Page 48 of 62



HIGH CHANNEL HORIZONTAL – WITH METAL WRISTBAND

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.



HIGH CHANNEL VERTICAL- WITH METAL WRISTBAND

Note: Emission was scanned up to 26GHz; No emissions were detected above the noise floor which was at least 20dB below the specification limit.

Page 49 of 62

HIGH CHANNEL DATA

Trace Markers

Marker	Frequency (GHz)	Meter Reading (dBuV)	Det	AF T119 (dB/m)	Amp/Cbl/Flt r/Pad (dB)	DC Corr (dB)	Corrected Reading (dBuV/m)	Avg Limit (dBuV/m)	Margin (dB)	Peak Limit (dBuV/m)	PK Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
1	1.821	33.39	PK	30.4	-23.3	0	40.49	-	-	74	-33.51	0-360	100	Н
4	2.059	33.54	PK	31.5	-23.2	0	41.84	-	-	74	-32.16	0-360	200	V
2	6.328	30.13	PK	35.4	-29	0	36.53	-	-	74	-37.47	0-360	100	Н
3	10.023	26.2	PK	36.9	-25.5	0	37.6	-	-	74	-36.4	0-360	200	Н
5	3.211	31.19	PK	32.6	-31.3	0	32.49	-	-	74	-41.51	0-360	200	V
6	5.873	29.37	PK	35	-29.7	0	34.67	-	-	74	-39.33	0-360	200	V

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK – Peak detector

Page 50 of 62

10.5. WORST-CASE BELOW 1 GHz –EUT WITH METAL WRISTBAND

SPURIOUS EMISSIONS 30 TO 1000 MHz (WORST-CASE CONFIGURATION, HORIZONTAL)



HORIZONTAL PLOT

UL VERIFICATION SERVICES INC. 47173 BENICIA STREET, FREMONT, CA 94538, USA This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

Page 51 of 62

VERTICAL PLOT



UL VERIFICATION SERVICES INC. 47173 BENICIA STREET, FREMONT, CA 94538, USA This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc. FORM NO: CCSUP47011 TEL: (510) 771-1000 FAX: (510) 661-0888 This report shall not be reproduced except in full, without the written approval of UL Verification Services Inc.

Page 52 of 62

BELOW 1 GHz TABLE

Trace Markers

Marker	Frequenc y (MHz)	Meter Reading (dBuV)	Det	AF T243 (dB/m)	Amp/Cbl (dB)	Correcte d Reading (dBuV/m)	QPk Limit (dBuV/m)	Margin (dB)	Azimuth (Degs)	Height (cm)	Polarity
5	35.8225	38.27	PK	16.9	-28.8	26.37	40	-13.63	0-360	101	V
1	74.71	46.61	PK	8	-28.4	26.21	40	-13.79	0-360	101	Н
6	92.305	41.61	PK	8.2	-28.1	21.71	43.52	-21.81	0-360	101	V
2	100.3375	52.67	PK	10.3	-28.1	34.87	43.52	-8.65	0-360	101	Н
3	152.8675	41.84	PK	12.4	-27.5	26.74	43.52	-16.78	0-360	101	Н
7	200.4	28.58	PK	12.6	-27	14.18	43.52	-29.34	0-360	200	V
8	712.7	41.31	PK	20.4	-24.5	37.21	46.02	-8.81	0-360	101	V
4	825	38.8	PK	21.8	-23.6	37	46.02	-9.02	0-360	101	Н

* - indicates frequency in CFR15.205/IC7.2.2 Restricted Band

PK - Peak detector

Page 53 of 62