

Company: Intel Corporation
FCC ID:2AB8ZND5

Request for transmitter limited modular approval

Transmitter Module Characteristics

Item	Requirements	EUT
1	Have its own RF shielding	Device is not equipped with Metal shielding to cover RF section.
2	Have buffered modulation/data inputs (if such inputs are provided),	All inputs to the modules are buffered through logic or microprocessor inputs.
3	Have it own power supply regulation	Internal 1.8V power regulator. Refer to Block diagram
4	Meet the antenna requirements of Section 15.203	Device is equipped with on PCB trace antenna
5	Be tested in a stand-alone configuration, i.e., the antenna, AC or DC power and data input/output lines must be connected to the module but, the module must not be inside another case during testing	Device was tested as stand alone and also it was tested with bracelet
6	Be labeled with its own FCC ID number, and if the FCC ID is not visible when the module is installed inside another device, then the outside of the device into which the module is installed must also display a label referring to the enclosed module.	FCC ID will be placed on the module back cover, refer to artwork drawing
7	The modular transmitter is manufactured so that the user cannot influence the operation of the transmitter that will operate outside of the scope of the regulations.	The module is installed in a bracelet in normal use and the user has no access to module functionality
8	Address compliance with the Commission's RF exposure limits in Sections 1.1310 and 2.1093. In addition, spread spectrum transmitters operating under Section 15.247 are required to address RF exposure compliance in accordance with Section 15.247(b)(4).	The module contains only Bluetooth BLE with output power less than 4dBm which falls under the FCC threshold and is except from RF exposure.