

FCC Test Report

Report No.: AGC00275180604FE03

FCC ID : 2AB9SM63F

APPLICATION PURPOSE: Original Equipment

PRODUCT DESIGNATION: BLUETOOTH SPEAKER

BRAND NAME : JONTER, boAt, alphasonik

MODEL NAME : M63F, Aavante 15, Phantom

CLIENT: Shenzhen Jonter Digital Co., Ltd

DATE OF ISSUE : Jun. 21, 2018

STANDARD(S)

TEST PROCEDURE(S)

: FCC Part 15 Subpart C Section 15.249

REPORT VERSION 'V1.0

Attestation of Global Compliance (Shenzhen) Co., Ltd

CAUTION:

This report shall not be reproduced except in full without the written permission of the test laboratory and shall not be quoted out of context.



The results spower this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.

Attestation of Global Compliance

Tel: +86-755 2908 1955 Fax: +86-755 2600 8484 E-mail: agc@agc-cert.com @ 400 089 2118 Add: 2/F., Building 2, No.1-4,Chaxi Sanwei Technical Industrial Park,Gushu, Xixiang, Baoan District, Shenzhen, Guangdong China



Page 2 of 66

Report Revise Record

Report Version	Revise Time	Issued Date	Valid Version	Notes
V1.0	plience / © Marie	Jun. 21, 2018	Valid	Initial release

The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by KGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.agc.gett.com.



TABLE OF CONTENTS

1. VERIFICATION OF CONFORMITY	
2. GENERAL INFORMATION	5
2.1. PRODUCT DESCRIPTION	5
3. MEASUREMENT UNCERTAINTY	
4. DESCRIPTION OF TEST MODES	6
5. SYSTEM TEST CONFIGURATION	8
5.1. CONFIGURATION OF EUT SYSTEM	8 8
6. TEST FACILITY	10
7.TEST METHOD	
8. TEST EQUIPMENT LIST	
9. RADIATED EMISSION	12
9.1TEST LIMIT 9.2. MEASUREMENT PROCEDURE 9.3. TEST SETUP 9.4. TEST RESULT	12 13
10. BAND EDGE EMISSION	39
10.1. MEASUREMENT PROCEDURE 10.2 TEST SETUP 10.3 RADIATED TEST RESULT	39 40
11. 20DB BANDWIDTH	44
11.1. MEASUREMENT PROCEDURE	44 44
12. FCC LINE CONDUCTED EMISSION TEST	51
12.1. LIMITS OF LINE CONDUCTED EMISSION TEST	51 52 52
APPENDIX A: PHOTOGRAPHS OF TEST SETUP	
APPENDIX B. PHOTOGRAPHS OF FUT	50



Page 4 of 66

1. VERIFICATION OF CONFORMITY

Applicant	Shenzhen Jonter Digital Co., Ltd				
Address	3F/4B, Hezhou Jinfo Industrial Park, Hezhou, Xixiang Street, Baoan District, Shenzhen, Guangdong, China				
Manufacturer	Shenzhen Jonter Digital Co., Ltd				
Address	3F/4B, Hezhou Jinfo Industrial Park, Hezhou, Xixiang Street, Baoan District, Shenzhen, Guangdong, China				
Product Designation	BLUETOOTH SPEAKER				
Brand Name	JONTER, boAt, alphasonik				
Test Model	M63F				
Series Model	Aavante 15, Phantom				
Difference description	All the same except for the model name.				
Date of test	Jun. 11, 2018 to Jun. 18, 2018				
Deviation	None None				
Condition of Test Sample	Normal				
Report Template	AGCRT-US-BR/RF				

We hereby certify that:

The above equipment was tested by Attestation of Global Compliance (Shenzhen) Co., Ltd. The test data, the energy emitted by the sample tested as described in this report is in compliance with the requirements of FCC Rules Part 15.249. The test results of this report relate only to the tested sample identified in this report.

Tested By	Jorden Wand	
A Captal Compliance	Jonhen Wang(Wang Yonghuan)	Jun.18, 2018
	and change	
Reviewed By_		oal Con.
	Cool Cheng(Cheng Mengguo)	Jun.21, 2018
Approved By	Formers con	
America Samuel S	Forrest Lei(Lei Yonggang) Authorized Officer	Jun.21, 2018

The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 5 of 66

2. GENERAL INFORMATION

2.1. PRODUCT DESCRIPTION

A major technical description of EUT is described as following

Operation Frequency	2.402 GHz to 2.480GHz
RF Output Power	-2.44dBm(Max EIRP Power=Max radiation field-95.2)
Bluetooth Version	V4.2
Modulation	BR ⊠GFSK, EDR ⊠π /4-DQPSK, ⊠8DPSK BLE □GFSK
Number of channels	79 for BR/EDR
Hardware Version	V1, The state of t
Software Version	V2.0
Antenna Designation	PCB Antenna
Antenna Gain	0dBi
Power Supply	DC 7.4V by battery
Note: 1.The micro USB p	ort only used for charging and can't be used to transfer data with PC.

The Standard USB port only used for power supply for other device and can't be used to transfer data with PC.

2.2. TABLE OF CARRIER FREQUENCYS

BR/EDR channel List

Frequency Band	Channel Number	Frequency
The Mariane	The state of the s	2402MHz
(C) Allestrifon of Global (C)		2403MHz
GO YOU		A State of the sta
加	38	2440 MHz
2400~2483.5MHz	39	2441 MHz
CO N	40	2442 MHz
		O The state of the
The Compliance	77	2479 MHz
© Management Clobs	78	2480 MHz



Page 6 of 66

3. MEASUREMENT UNCERTAINTY

The reported uncertainty of measurement y ±U, where expended uncertainty U is based on a standard uncertainty multiplied by a coverage factor of k=2, providing a level of confidence of approximately 95%.


- Uncertainty of Conducted Emission, Uc = ±3.2 dB
- Uncertainty of Radiated Emission below 1GHz, Uc = ±3.9 dB
- Uncertainty of Radiated Emission above 1GHz, Uc = ±4.8 dB

4. DESCRIPTION OF TEST MODES

NO.	TEST MODE DESCRIPTION
8 American Section 8	Low channel GFSK
2 60	Middle channel GFSK
3	High channel GFSK
4 展	Low channel π /4-DQPSK
® 5 nd cloud	Middle channel π /4-DQPSK
6	High channel π /4-DQPSK
7	Low channel 8DPSK
The state of the s	Middle channel 8DPSK
90	High channel 8DPSK
10	BT Link with charging
11th his rolling	BT Link
(1) 100c, INV	

Note:

- 1. All the test modes can be supply by battery, only the result of the worst case was recorded in the report, if no other cases.
- 2. For Radiated Emission, 3axis were chosen for testing for each applicable mode.
- 3. The EUT used fully-charged battery when tested.







The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true www.ago.gent.com.




Page 8 of 66

5. SYSTEM TEST CONFIGURATION


5.1. CONFIGURATION OF EUT SYSTEM

Configure 1: (Normal hopping)



Note: Owing to the EUT has own battery, testing may be performed while PC or adapter removed.

Configure 2: (Control continuous TX)



5.2. EQUIPMENT USED IN EUT SYSTEM

			- All	The Management of Management o	
Item	Equipment	Mfr/Brand	Model/Type No.	Remark	
1玩 完了	BLUETOOTH SPEAKER	JONTER	M63F	EUT	
2	Battery	HKD	HKD-4070	Accessory	
3	PC	APPLE	A1465	A.E	
4	Control box	SERIAL	N/A	A.E	
5	Adapter	IPRO	NTR-S01	A.E	
6	USB Cable	N/A	1m unshielded	A.E	
7	AUX in Cable	N/A	0.6m unshielded	Accessory	
8	USB Cable	N/A	0.6m unshielded	Accessory	
9	IPOD	APPLE	A1367	A.E	
10	Load	HPX	RX27	A.E	



Page 9 of 66

5.3. SUMMARY OF TEST RESULTS

FCC RULES	DESCRIPTION OF TEST	RESULT	
§15.249(a) §15.209	Radiated Emission	Compliant	
§15.249(d)	Band Edges	Compliant	
§15.207	Conduction Emission	Compliant	
§15.215	Bandwidth	Compliant	



Page 10 of 66

6. TEST FACILITY

Test Site	Attestation of Global Compliance (Shenzhen) Co., Ltd		
Location	1-2F., Bldg.2, No.1-4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Bao'an District B112-B113, Bldg.12, Baoan Bldg Materials Center, No.1 of Xixiang Inner Ring Road, Baoan District, Shenzhen 518012		
NVLAP Lab Code	600153-0		
Designation Number	CN5028		
Test Firm Registration Number	682566		
Description	Attestation of Global Compliance(Shenzhen) Co., Ltd is accredited by National Voluntary Laboratory Accreditation program, NVLAP Code 600153-0		



Page 11 of 66

7. TEST METHOD

All measurements contained in this report were conducted with ANSI C63.10-2013

8. TEST EQUIPMENT LIST

TEST EQUIPMENT OF CONDUCTED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESPI	101206	Jun.20, 2017	Jun.19, 2018
LISN	R&S	ESH2-Z5	100086	Aug.21, 2017	Aug.20, 2018

TEST EQUIPMENT OF RADIATED EMISSION TEST

Equipment	Manufacturer	Model	S/N	Cal. Date	Cal. Due
Test Receiver	R&S	ESCI	10096	Jun.20, 2017	Jun.19, 2018
EXA Signal Analyzer	Aglient	N9010A	MY53470504	Dec.08, 2017	Dec.07, 2018
Horn antenna	SCHWARZBECK	BBHA 9170	#768	Sep.20, 2017	Sep.19, 2018
preamplifier	ChengYi	EMC184045SE	980508	Sep.15, 2017	Sep.14, 2018
Double-Ridged Waveguide Horn	ETS LINDGREN	3117	00034609	May 18, 2017	May 17, 2019
Broadband Preamplifier	SCHWARZBECK	BBV 9718	9718-205	Jun.20, 2017	Jun.19, 2018
Antenna	SCHWARZBECK	VULB9168	D69250	Sep.28, 2017	Sep.27, 2018
Loop Antenna	A.H.Systems,Inc	SAS-562B	G	Mar. 01, 2018	Feb. 28, 2019
Radiation Cable 1	MXT	RS1	R005	June 6, 2018	June 5, 2019
Radiation Cable 2	MXT	RS1	R006	June 6, 2018	June 5, 2019
Filter (2.4-2.483GHz)	Micro-tronics	087	20	Jun.20, 2017	Jun.19, 2018



Page 12 of 66

9. RADIATED EMISSION

9.1TEST LIMIT

Standard FCC15.249

Fundamental	Field Strength of Fundamental	Field Strength of Harmonics
Frequency	(millivolts/meter)	(microvolts/meter)
900-928MHz	50	500
2400-2483.5MHz	50	500
5725-5875MHz	50	500
24.0-24.25GHz	250	2500

Standard FCC 15.209

Frequency	Distance	Field Str	engths Limit
(MHz)	Meters	μ V/m	dB(μV)/m
0.009 ~ 0.490	300	2400/F(kHz)	9
0.490 ~ 1.705	30	24000/F(kHz)	技訓
1.705 ~ 30	30	30 (1)	E Cobaco (Color of Color of Co
30 ~ 88	3 F 1000	100	40.0
88 ~ 216	3 - 6	150	43.5
216 ~ 960	3	200	46.0
960 ~ 1000	3	500	54.0
Above 1000	3. I	Other:74.0 dB(μV)/m (Average)	(Peak) 54.0 dB(μV)/m

Remark:

- (1) Emission level dB μ V = 20 log Emission level μ V/m
- (2) The smaller limit shall apply at the cross point between two frequency bands.
- (3) Distance is the distance in meters between the measuring instrument, antenna and the closest point of any part of the device or system.



Page 13 of 66

9.2. MEASUREMENT PROCEDURE

- 1. The measuring distance of 3m shall be used for measurements. The EUT was placed on the top of a rotating table 0.8 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Below 1GHz)
- 2. The measuring distance of 3m shall used for measurements. The EUT was placed on the top of a rotating table 1.5 meter above the ground at a 3 meter semi-anechoic chamber. The table was rotated 360 degrees to determine the position of the highest radiation(Above 1GHz)
- 3. The height of the test antenna shall vary between 1m to 4m.Both horizontal and vertical polarization Of the antenna are set to make the measurement.
- 4. The initial step in collecting radiated emission data is a receive peak detector mode. Pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured.
- All readings are peak unless otherwise stated QP in column of Note. Peak denoted that the Peak reading compliance with the QP limits and then QP Mode measurement didn't perform(Below 1GHz)
- 6. All readings are Peak mode value unless otherwise stated AVG in column of Note. If the Peak mode measured value compliance with the Peak limits and lower than AVG Limits, the EUT shall be deemed to meet Peak & AVG limits and then only Peak mode was measured, but AVG mode didn't perform.(Above 1GHz)

The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 14 of 66


The following table is the setting of spectrum analyzer and receiver.

Spectrum Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP
Start ~Stop Frequency	Fundamental: 2.4~2.483GHz RBW 2MHz/ VBW 6MHz for Peak, RBW 2MHz/ VBW 10Hz for Average Harmonics: 1GHz~25GHz RBW 1MHz/ VBW 3MHz for Peak, RBW 1MHz/ VBW 10Hz for Average
Receiver Parameter	Setting
Start ~Stop Frequency	9KHz~150KHz/RB 200Hz for QP
Start ~Stop Frequency	150KHz~30MHz/RB 9KHz for QP
Start ~Stop Frequency	30MHz~1000MHz/RB 120KHz for QP




9.3. TEST SETUP

Radiated Emission Test-Setup Frequency Below 30MHz



RADIATED EMISSION TEST SETUP 30MHz-1000MHz




The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 16 of 66

RADIATED EMISSION TEST SETUP ABOVE 1000MHz





Page 17 of 66

9.4. TEST RESULT

FOR BR/EDR

(Worst modulation: 8DPSK)

RADIATED EMISSION BELOW 30MHz

No emission found between lowest internal used/generated frequencies to 30MHz.


The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by KGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true www.agc. gent.com.



Page 18 of 66

RADIATED EMISSION BELOW 1GHz

RADIATED EMISSION TEST- (30MHz-1GHz)-LOW CHANNEL-HORIZONTAL




A. Suspected List:

, ,	Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(u√/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
	221.090	Н	18.3	14.8	33.1	46.0	12.9	Pass	100.0	1.1
	245.825	Н	14.9	16.2	31.1	46.0	14.9	Pass	100.0	206.1
*	282.685	Н	14.6	17.7	32.3	46.0	13.7	Pass	100.0	165.8
	356.405	Н	13.2	19.1	32.3	46.0	13.7	Pass	100.0	200.9
	381.140	Н	13.8	20.1	33.9	46.0	12.1	Pass	200.0	178.7
	786.600	Н	8.6	28.4	37.0	46.0	9.0	Pass	100.0	239.6

RESULT: PASS



RADIATED EMISSION TEST- (30MHz-1GHz)-LOW CHANNEL -VERTICAL




A. Suspected List:

	Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(u∀/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
	48.915	v	14.9	17.1	32.0	40.0	8.0	Pass	200.0	58.1
	184.230	v	11.9	14.1	26.0	43.5	17.5	Pass	150.0	250.7
	191.990	v	11.9	13.7	25.6	43.5	17.9	Pass	100.0	288.6
Š	570.290	v	6.3	24.3	30.6	46.0	15.4	Pass	200.0	22.3
	741.495	v	6.5	27.3	33.8	46.0	12.2	Pass	100.0	288.6
	967.990	v	6.1	30.8	36.9	54.0	17.1	Pass	100.0	288.6

RESULT: PASS


Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.





RADIATED EMISSION TEST- (30MHz-1GHz)-MIDDLE CHANNEL-HORIZONTAL



A. Suspected List:


	quency //Hz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(uV/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
22	1.090	H	18.0	14.8	32.8	46.0	13.2	Pass	200.0	267.7
319	9.545	Н	14.1	17.8	31.9	46.0	14.1	Pass	150.0	143.6
35	6.405	Н	13.9	19.1	33.0	46.0	13.0	Pass	200.0	341.1
38	1.140	Н	13.0	20.1	33.1	46.0	12.9	Pass	100.0	142.2
413	8.000	Н	10.8	21.4	32.2	46.0	13.8	Pass	150.0	215.0
78	6.600	Н	8.6	28.4	37.0	46.0	9.0	Pass	100.0	36.5

RESULT: PASS



Page 21 of 66

RADIATED EMISSION TEST- (30MHz-1GHz)- MIDDLE CHANNEL -VERTICAL




A. Suspected List:

Frequency MHz	Polarization	Reading dB(uV)	Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(uV/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
48.915	v	17.4	17.1	34.5	40.0	5.5	Pass	200.0	71.2
191.990	v	16.5	13.7	30.2	43.5	13.3	Pass	200.0	215.5
208.965	v	10.6	13.8	24.4	43.5	19.1	Pass	150.0	213.1
319.545	v	8.1	17.8	25.9	46.0	20.1	Pass	100.0	90.9
649.830	v	8.1	25.6	33.7	46.0	12.3	Pass	200.0	71.2
874.870	v	6.6	29.9	36.5	46.0	9.5	Pass	150.0	71.7

RESULT: PASS


Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.





RADIATED EMISSION TEST- (30MHz-1GHz)-HIGH CHANNEL-HORIZONTAL




A. Suspected List:

3	Frequency MHz	Polarization	Polarization Reading Factor dB (1/m)		Level dB(uV/m) PK	dB(uV/m) dB(uV/m)		Pass/Fail	Height cm	Angle deg
	89.655	Н	20.9	12.3	33.2	43.5	10.3	Pass	200.0	305.8
	122.635	Н	24.4	15.6	40.0	43.5	3.5	Pass	150.0	67.5
	169.195	Н	22.8	16.0	38.8	43.5	4.7	Pass	150.0	186.1
4	182.775	Н	23.0	14.3	37.3	43.5	6.2	Pass	150.0	190.4
0)	221.090	Н	18.4	14.8	33.2	46.0	12.8	Pass	150.0	213.9
	418.000	Н	11.4	21.4	32.8	46.0	13.2	Pass	200.0	192.2

RESULT: PASS



RADIATED EMISSION TEST- (30MHz-1GHz)-HIGH CHANNEL -VERTICAL



A. Suspected List:

Frequency MHz			Factor dB (1/m)	Level dB(uV/m) PK	Limit dB(uV/m) QP	Margin dB	Pass/Fail	Height cm	Angle deg
48.915	V	16.7	17.1	33.8	40.0	6.2	Pass	100.0	92.1
84.805	V	18.9	12.3	31.2	40.0	8.8	Pass	100.0	160.3
122.150	v	19.6	15.6	35.2	43.5	8.3	Pass	100.0	120.5
169.195	v	19.8	16.0	35.8	43.5	7.7	Pass	200.0	164.5
177.440	V	17.6	14.9	32.5	43.5	11.0	Pass	100.0	133.1
666.805	v	5.8	25.8	31.6	46.0	14.4	Pass	100.0	45.3

RESULT: PASS

Note: 1. Factor=Antenna Factor + Cable loss, Margin=Measurement-Limit.

2. The "Factor" value can be calculated automatically by software of measurement system.




Page 24 of 66

RADIATED EMISSION ABOVE 1GHz FOR BR/EDR

(Worst modulation: 8DPSK)

For Fundamental

RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL-HORIZONTAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu√/m	dBu∀/m	dB		cm	degree	
1		2402.000	82.44	10.32	92.76	114.00	-21.24	peak			
2	*	2402.000	74.49	10.32	84.81	94.00	-9.19	AVG	100	263	

RESULT: PASS



Page 25 of 66

RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL- VERTICAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
4	-	MHz	dBu∀	dB/m	dBu√/m	dBu∀/m	dB		cm	degree	
1		2402.000	81.97	10.32	92.29	114.00	-21.71	peak			
2	*	2402.000	74.03	10.32	84.35	94.00	-9.65	AVG	100	133	

RESULT: PASS



Page 26 of 66

RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL-HORIZONTAL




No).	Иk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		-	MHz	dBu∀	dB/m	dBu∀/m	dBu\//m	dB		cm	degree	
1			2441.000	81.87	10.36	92.23	114.00	-21.77	peak			
2		*	2441.000	73.95	10.36	84.31	94.00	-9.69	AVG	100	252	

RESULT: PASS



Page 27 of 66

RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL- VERTICAL




1	No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		-	MHz	dBu∀	dB/m	dBuV/m	dBuV/m	dB		cm	degree	
	1		2441.000	81.52	10.36	91.88	114.00	-22.12	peak			
	2	*	2441.000	73.45	10.36	83.81	94.00	-10.19	AVG	100	119	

RESULT: PASS



Page 28 of 66

RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL-HORIZONTAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
		MHz	dBu∀	dB/m	dBu√/m	dBuV/m	dB		cm	degree	
1		2480.000	81.10	10.41	91.51	114.00	-22.49	peak			
2	*	2480.000	73.12	10.41	83.53	94.00	-10.47	AVG	100	244	

RESULT: PASS



Page 29 of 66

RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL- VERTICAL



No	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2480.000	80.60	10.41	91.01	114.00	-22.99	peak			
2	*	2480.000	72.64	10.41	83.05	94.00	-10.95	AVG	100	·	

RESULT: PASS

Note: Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.



Page 30 of 66

Field strength of the fundamental signal

3Mbps Result:

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna	
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization	
2402	82.44	10.32	92.76	114	-21.24	Horizontal	
2402	81.97	10.32	92.29	114	-21.71	Vertical	
2441	81.87	10.36	92.23	114	-21.77	Horizontal	
2441	81.52	10.36	91.88	114	-22.12	Vertical	
2480	81.10	10.41	91.51	114	-22.49	Horizontal	
2480	80.60	10.41	91.01	114	-22.99	Vertical	

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna	
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization	
2402	74.49	10.32	84.81	94	-9.19	Horizontal	
2402	74.03	10.32	84.35	94	-9.65	Vertical	
2441	73.95	10.36	84.31	94	-9.69	Horizontal	
2441	73.45	10.36	83.81	94	-10.19	Vertical	
2480	73.12	10.41	83.53	94	-10.47	Horizontal	
2480	72.64	10.41	83.05	94	-10.95	Vertical	



Page 31 of 66

2Mbps Result:

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	82.00	10.32	92.32	114	-21.68	Horizontal
2402	81.71	10.32	92.03	114	-21.97	Vertical
2441	81.52	10.36	91.88	114	-22.12	Horizontal
2441	81.06	10.36	91.42	114	-22.58	Vertical
2480	80.64	10.41	91.05	114	-22.95	Horizontal
2480	80.14	10.41	90.55	114	-23.45	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	74.13	10.32	84.45	94	-9.55	Horizontal
2402	73.65	10.32	83.97	94	-10.03	Vertical
2441	73.51	10.36	83.87	94	-10.13	Horizontal
2441	73.10	10.36	83.46	94	-10.54	Vertical
2480	72.67	10.41	83.08	94	-10.92	Horizontal
2480	72.19	10.41	82.60	94	-11.40	Vertical



Page 32 of 66

1Mbps Result:

Peak value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization
2402	81.50	10.32	91.82	114	-22.18	Horizontal
2402	81.28	10.32	91.60	114	-22.40	Vertical
2441	81.15	10.36	91.51	114	-22.49	Horizontal
2441	80.57	10.36	90.93	114	-23.07	Vertical
2480	80.31	10.41	90.72	114	-23.28	Horizontal
2480	79.82	10.41	90.23	114	-23.77	Vertical

Average value

Frequency	Reading Level	Factor	Measurement	Limit	Over	Antenna	
(MHz)	(dBuv)	(dB/m)	(dBuv/m)	(dBuv/m)	(dB)	Polarization	
2402	73.73	10.32	84.05	94	-9.95	Horizontal	
2402	73.29	10.32	83.61	94	-10.39	Vertical	
2441	73.08	10.36	83.44	94	-10.56	Horizontal	
2441	72.69	10.36	83.05	94	-10.95	Vertical	
2480	72.23	10.41	82.64	94	-11.36	Horizontal	
2480	71.71	10.41	82.12	94	-11.88	Vertical	




Page 33 of 66

FOR BR/EDR

(Worst modulation: 8DPSK)

For Harmonics

RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL-HORIZONTAL




No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu√/m	dBuV/m	dB		cm	degree	
1		2583.333	33.87	10.63	44.50	74.00	-29.50	peak			
2		3616.667	33.05	12.83	45.88	74.00	-28.12	peak			
3	*	4804.000	42.21	7.69	49.90	74.00	-24.10	peak			

RESULT: PASS



Page 34 of 66

RADIATED EMISSION TEST- (ABOVE 1GHz)-LOW CHANNEL- VERTICAL



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	- [MHz	dBu∀	dB/m	dBu∀/m	dBuV/m	dB		cm	degree	
1		2033.333	33.59	9.92	43.51	74.00	-30.49	peak			
2		3433.333	32.54	12.05	44.59	74.00	-29.41	peak			
3	*	4804.000	41.05	7.69	48.74	74.00	-25.26	peak			


RESULT: PASS

The results shown in this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by KGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.



Page 35 of 66

RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL-HORIZONTAL




No	o. I	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		-	MHz	dBu∀	dB/m	dBu√/m	dBu∀/m	dB		cm	degree	
1			1658.333	38.10	6.29	44.39	74.00	-29.61	peak			
2	2		3375.000	33.64	11.99	45.63	74.00	-28.37	peak			
3	;	*	4882.000	42.66	7.89	50.55	74.00	-23.45	peak			

RESULT: PASS



Page 36 of 66

RADIATED EMISSION TEST- (ABOVE 1GHz)-MIDDLE CHANNEL- VERTICAL



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
		MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1		2266.667	34.83	10.17	45.00	74.00	-29.00	peak			
2		3775.000	32.45	13.80	46.25	74.00	-27.75	peak			
3	*	4882.000	41.89	7.89	49.78	74.00	-24.22	peak			


RESULT: PASS

The results showed the sample (s) tested unless otherwise stated and the sample (s) are retained for 30 days only. The document is issued by (SC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago-gent.com.



Page 37 of 66

RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL-HORIZONTAL



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBuV/m	dBu∀/m	dB		cm	degree	
1		1841.667	36.07	8.21	44.28	74.00	-29.72	peak			
2		3525.000	32.79	12.26	45.05	74.00	-28.95	peak			
3	*	4960.000	41.60	8.09	49.69	74.00	-24.31	peak			


RESULT: PASS

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.



Page 38 of 66

RADIATED EMISSION TEST- (ABOVE 1GHz)-HIGH CHANNEL- VERTICAL



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height		Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBuV/m	dB		cm	degree	
1		2283.333	34.05	10.19	44.24	74.00	-29.76	peak			
2		3925.000	31.33	14.73	46.06	74.00	-27.94	peak			
3	*	4960.000	41.91	8.09	50.00	74.00	-24.00	peak			

RESULT: PASS

Note: 6~25GHz at least have 20dB margin. No recording in the test report.

Factor=Antenna Factor + Cable loss - Amplifier gain, Margin=Measurement-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 39 of 66

10. BAND EDGE EMISSION


10.1. MEASUREMENT PROCEDURE

- The EUT operates at hopping-off test mode. The lowest or highest channels are tested to verify the largest transmission and spurious emissions power at the continuous transmission mode.
- 2. Max hold the trace of the setup 1, and the EUT operates at hopping-on test mode to verify the largest spurious emissions power.
- 3. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission.

	Start frequenc	y(MHz)		Stop frequency(MHz)				
	2200	Kingliance	The Compilers	© A station	2405	100°		
8 M. H	2478	Global Co	attestation of Glob	-,0 "	2500			

10.2 TEST SETUP

RADIATED EMISSION TEST SETUP



The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 40 of 66

10.3 RADIATED TEST RESULT

FOR BR/EDR

(Worst modulation: 8DPSK)

TEST PLOT OF BAND EDGE FOR LOW CHANNEL-Horizontal



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu√/m	dBu∀/m	dB		cm	degree	
1		2373.567	31.43	10.29	41.72	74.00	-32.28	peak			
2		2390.000	32.50	10.31	42.81	74.00	-31.19	peak			
3		2400.000	40.97	10.32	51.29	74.00	-22.71	peak			
4	*	2402.000	82.72	10.32	93.04	74.00	19.04	peak			
5	Х	2402.000	74.63	10.32	84.95	74.00	10.95	AVG	100	257	

The results spowth this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gott.com.



Page 41 of 66

TEST PLOT OF BAND EDGE FOR LOW CHANNEL -Vertical




N	lo.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
			MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
	1		2372.883	32.02	10.29	42.31	74.00	-31.69	peak			
	2		2390.000	31.21	10.31	41.52	74.00	-32.48	peak			
	3		2400.000	35.56	10.32	45.88	74.00	-28.12	peak			
	4	*	2402.000	82.09	10.32	92.41	74.00	18.41	peak			
	5	Х	2402.000	74.19	10.32	84.51	74.00	10.51	AVG	100	·	

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.



Page 42 of 66

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL -Horizontal




No	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBuV/m	dB		cm	degree	
1	*	2480.000	81.55	10.41	91.96	74.00	17.96	peak			
2	Х	2480.000	73.31	10.41	83.72	74.00	9.72	AVG	100	255	
3		2483.500	34.19	10.41	44.60	74.00	-29.40	peak			
4		2490.797	33.18	10.42	43.60	74.00	-30.40	peak			

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.



Page 43 of 66

TEST PLOT OF BAND EDGE FOR HIGH CHANNEL-Vertical



No.	Mk	Freq.	Reading	Factor	Measurement	Limit	Over	Detector	Antenna Height	Table Degree	Comment
	-	MHz	dBu∀	dB/m	dBu∀/m	dBu∀/m	dB		cm	degree	
1	*	2480.000	81.32	10.41	91.73	74.00	17.73	peak			
2	Х	2480.000	72.84	10.41	83.25	74.00	9.25	AVG	100	127	
3		2483.500	33.26	10.41	43.67	74.00	-30.33	peak			
4		2485.957	33.98	10.41	44.39	74.00	-29.61	peak			

RESULT: PASS

Note: Factor=Antenna Factor + Cable loss - Amplifier gain, Over=Measure-Limit.

The "Factor" value can be calculated automatically by software of measurement system.

Hopping on mode and Hopping off mode have been tested, but only worst case reported.

The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.




Page 44 of 66

11. 20DB BANDWIDTH

11.1. MEASUREMENT PROCEDURE

- 1. Set the EUT Work on the top, the middle and the bottom operation frequency individually.
- 2. Set Span = approximately 2 to 3 times the 20 dB bandwidth, centered on a hoping channel RBW ≥ 1% of the 20 dB bandwidth, VBW ≥ 3RBW; Sweep = auto; Detector function = peak
- 3. Set SPA Trace 1 Max hold, then View.

11.2. TEST SET-UP



11.3. LIMITS AND MEASUREMENT RESULTS

FOR BR/EDR

BLUET	OOTH 1MBPS LIN	MITS AND MEASU	REMENT RESULT						
		Measurement Result							
Applicable Limits		Result							
		99%OBW (MHz)	-20dB BW(MHz)	Nesuit					
Solar Complete C State and on the	Low Channel	0.942	1.077	PASS					
N/A	Middle Channel	0.945	1.072	PASS					
	High Channel	0.958	1.081	PASS					


The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gent.com.




TEST PLOT OF BANDWIDTH FOR LOW CHANNEL



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL




The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.





TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Report No.: AGC00275180604FE03 Page 47 of 66

BLUETO	BLUETOOTH 2MBPS LIMITS AND MEASUREMENT RESULT									
	Measurement Result									
Applicable Limits		D								
		99%OBW (MHz)	-20dB BW(MHz)	Result						
The plants of the plants	Low Channel	1.214	1.399	PASS						
N/A	Middle Channel	1.225	1.379	PASS						
	High Channel	1.224	1.395	PASS						


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL




The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 49 of 66

Aller Control of the	The second second		and the wall	-01/- 7 Co.								
BLUET	BLUETOOTH 3MBPS LIMITS AND MEASUREMENT RESULT											
		Measure	ement Result									
Applicable Limits		Doorle										
	99%OBW (MHz) -20dB BW(MHz)		Result									
不 整 测 不 整 测	Low Channel	1.229	1.373	PASS								
N/A	Middle Channel	1.232	1.392	PASS								
	High Channel	1.232	1.401	PASS								


TEST PLOT OF BANDWIDTH FOR LOW CHANNEL




The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



TEST PLOT OF BANDWIDTH FOR MIDDLE CHANNEL



TEST PLOT OF BANDWIDTH FOR HIGH CHANNEL



The results spowford this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



age 51 of 66

12. FCC LINE CONDUCTED EMISSION TEST


12.1. LIMITS OF LINE CONDUCTED EMISSION TEST

F	Maximum RF	Line Voltage
Frequency	Q.P.(dBuV)	Average(dBuV)
150kHz~500kHz	66-56	56-46
500kHz~5MHz	8 gg 200 56 gg 100 00 00 00 00 00 00 00 00 00 00 00 00	46 / W
5MHz~30MHz	60	50

Note:

- 1. The lower limit shall apply at the transition frequency.
- 2. The limit decreases linearly with the logarithm of the frequency in the range 0.15 MHz to 0.50 MHz

12.2. BLOCK DIAGRAM OF LINE CONDUCTED EMISSION TEST



The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.



Page 52 of 66

12.3. PRELIMINARY PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. The equipment was set up as per the test configuration to simulate typical actual usage per the user's manual. When the EUT is a tabletop system, a wooden table with a height of 0.8 meters is used and is placed on the ground plane as per ANSI C63.10 (see Test Facility for the dimensions of the ground plane used). When the EUT is a floor-standing equipment, it is placed on the ground plane which has a 3-12 mm non-conductive covering to insulate the EUT from the ground plane.
- 2. Support equipment, if needed, was placed as per ANSI C63.10.
- 3. All I/O cables were positioned to simulate typical actual usage as per ANSI C63.10.
- 4. All support equipments received AC120V/60Hz power from a LISN, if any.
- 5. The EUT received DC charging voltage by adapter or PC which received 120V/60Hzpower by a LISN.
- 6. The test program was started. Emissions were measured on each current carrying line of the EUT using a spectrum Analyzer / Receiver connected to the LISN powering the EUT. The LISN has two monitoring points: Line 1 (Hot Side) and Line 2 (Neutral Side). Two scans were taken: one with Line 1 connected to Analyzer / Receiver and Line 2 connected to a 50 ohm load; the second scan had Line 1 connected to a 50 ohm load and Line 2 connected to the Analyzer / Receiver.
- 7. Analyzer / Receiver scanned from 150 kHz to 30MHz for emissions in each of the test modes.
- 8. During the above scans, the emissions were maximized by cable manipulation.
- 9. The test mode(s) were scanned during the preliminary test.

Then, the EUT configuration and cable configuration of the above highest emission level were recorded for reference of final testing.

12.4. FINAL PROCEDURE OF LINE CONDUCTED EMISSION TEST

- 1. EUT and support equipment was set up on the test bench as per step 2 of the preliminary test.
- 2. A scan was taken on both power lines, Line 1 and Line 2, recording at least the six highest emissions. Emission frequency and amplitude were recorded into a computer in which correction factors were used to calculate the emission level and compare reading to the applicable limit. If EUT emission level was less –2dB to the A.V. limit in Peak mode, then the emission signal was re-checked using Q.P and Average detector.
- 3. The test data of the worst case condition(s) was reported on the Summary Data page.

The results spound this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XCC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a trp://www.ago.go.tt.com.


Page 53 of 66

12.5. TEST RESULT OF LINE CONDUCTED EMISSION TEST

By adapter(worst case)

FOR BR/EDR

Line Conducted Emission Test Line 1-L



MEASUREMENT RESULT:

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.434000 0.850000 1.314000 2.182000 2.662000 3.686000	36.80 30.50 31.80 32.40 31.80 30.70	10.0 10.1 10.1 9.9 9.9 10.1	57 56 56 56 56	20.4 25.5 24.2 23.6 24.2 25.3	QP QP	L1 L1 L1 L1 L1 L1	FLO FLO FLO FLO FLO


MEASUREMENT RESULT:

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.434000 0.934000 1.254000 2.154000 2.658000 3.626000	24.00 19.40 20.10 21.50 18.50 19.40	10.0 10.1 10.1 9.9 9.9 10.1	47 46 46 46 46 46	23.2 26.6 25.9 24.5 27.5 26.6	AV AV	L1 L1 L1 L1 L1 L1	FLO FLO FLO FLO FLO

The results spowth this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gott.com.

Report No.: AGC00275180604FE03 Page 54 of 66

Line Conducted Emission Test Line 2-N




MEASUREMENT RESULT:

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.434000	40.00	10.0	57	17.2	QP	N	FLO
0.522000	34.10	9.9	56	21.9	QP	N	FLO
0.858000	32.50	10.1	56	23.5	QP	N	FLO
1.250000	32.70	10.1	56	23.3	QP	N	FLO
2.274000	35.80	9.9	56	20.2	QP	N	FLO
3.538000	32.30	10.0	56	23.7	QP	N	FLO

MEASUREMENT RESULT:

Frequency MHz	Level dBuV	Transd dB	Limit dBuV	Margin dB	Detector	Line	PE
0.438000	29.10	10.0	47	18.0	AV	N	FLO
0.934000	22.30	10.1	46	23.7	AV	N	FLO
1.090000	22.60	10.1	46	23.4	AV	N	FLO
2.130000	26.40	9.9	46	19.6	AV	N	FLO
2.646000	22.60	9.9	46	23.4	AV	N	FLO
3.602000	22.80	10.0	46	23.2	AV	N	FLO

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGE, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at all the confirmed at a confirmed





APPENDIX A: PHOTOGRAPHS OF TEST SETUP

FCC LINE CONDUCTED EMISSION TEST SETUP




FCC RADIATED EMISSION TEST SETUP




The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.go.tt.com.

Attestation of Global Compliance

Tel: +86-755 2908 1955 Fax: +86-755 2600 8484 E-mail: agc@agc-cert.com @ 400 089 2118 Add: 2/F., Building 2, No.1-4,Chaxi Sanwei Technical Industrial Park,Gushu, Xixiang, Baoan District, Shenzhen, Guangdong China








The results shown in this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true; //www.agc.gett.com.



Report No.: AGC00275180604FE03 Page 57 of 66



The results shown this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by (60°, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.agc.gett.com.





APPENDIX B: PHOTOGRAPHS OF EUT

TOTAL VIEW OF EUT



TOP VIEW OF EUT



The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by 100°C, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at all the confirmed at a little; I www.agc gett.com.

Attestation of Global Compliance

Tel: +86-755 2908 1955 Fax: +86-755 2600 8484 E-mail: agc@agc-cert.com @ 400 089 2118 Add: 2/F., Building 2, No.1-4,Chaxi Sanwei Technical Industrial Park,Gushu, Xixiang, Baoan District, Shenzhen, Guangdong China



BOTTOM VIEW OF EUT



FRONT VIEW OF EUT




The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.agc.gett.com.



BACK VIEW OF EUT



LEFT VIEW OF EUT



The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attr://www.agc.cett.com.

Attestation of Global Compliance

AGC 8

Tel: +86-755 2908 1955 Fax: +86-755 2600 8484 E-mail: agc@agc-cert.com @ 400 089 2118 Add: 2/F., Building 2, No.1-4,Chaxi Sanwei Technical Industrial Park,Gushu, Xixiang, Baoan District, Shenzhen, Guangdong China



RIGHT VIEW OF EUT



VIEW OF EUT (Port)




The results shown in this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true of the confirmed at a true of true of the confirmed at a true of the confirmed at a

Attestation of Global Compliance


Tel: +86-755 2908 1955 Fax: +86-755 2600 8484 E-mail: agc@agc-cert.com @ 400 089 2118 Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Baoan District, Shenzhen, Guangdong China



OPEN VIEW OF EUT-1



OPEN VIEW OF EUT-2




The results shown in this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true of the confirmed at a true of true of the confirmed at a true of the confirmed at a



VIEW OF BATTERY




INTERNAL VIEW OF EUT-1




The results spowd this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attr://www.agc-gent.com.



INTERNAL VIEW OF EUT-2



INTERNAL VIEW OF EUT-3




The results spoured this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by XOC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at attp://www.ago.go.tt.com.

Attestation of Global Compliance


Tel: +86-755 2908 1955 Fax: +86-755 2600 8484 E-mail: agc@agc-cert.com @ 400 089 2118 Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Baoan District, Shenzhen, Guangdong China



INTERNAL VIEW OF EUT-4



INTERNAL VIEW OF EUT-5



The results showing this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by AGC, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at a true www.agc. att.com.

Attestation of Global Compliance

Tel: +86-755 2908 1955 Fax: +86-755 2600 8484 E-mail: agc@agc-cert.com @ 400 089 2118 Add: 2/F., Building 2, No.1-4, Chaxi Sanwei Technical Industrial Park, Gushu, Xixiang, Baoan District, Shenzhen, Guangdong China



Page 66 of 66

@ 400 089 2118

VIEW OF ADAPTER(AE)



The adapter was supplied by AGC

-END OF REPORT-

The results showed this jest report refer only to the sample(s) tested unless otherwise stated and the sample(s) are retained for 30 days only. The document is issued by 1000, this document cannot be reproduced except in full with our prior written permission. The more details and the authenticity of the report will be confirmed at http://www.agc.cent.com.