



FCC RF EXPOSURE REPORT

FCC ID: 2ABAMPLLB

Project No. : 1608247

Equipment: Pill

Test Model : PB15226

Series Model: N/A

Applicant : Hello Inc.

Address : 438 Shotwell St, San Francisco, CA 94110, USA

According: : FCC Guidelines for Human Exposure IEEE C95.1

Technical Manager

(Jell Tally)

BTL INC.

B1, No. 37, Lane 365, Yang-Guang St., Nei-Hu District, Taipei City 114, Taiwan.

TEL: +886-2-2657-3299 FAX: +886-2-2657-3331





Table for Filed Antenna

Ant.	Brand	Model Name	Antenna Type	Connector	Gain(dBi)
1	Hello	N/A	PCB_Meander- IFA type	N/A	1.4

GENERAL CONCULUSION:

Maximum measured transmitter power:

OutputPower	Output Power	Limit (mW)	
(dBm)	(mW)		
3.91	2.5	10	

According to FCC KDB447498 V06, Appendix A, SAR Test Exclusion Thresholds for 100 MHz - 6 GHz and \leq 50 mm

The maximum measured output peak power of this EUT is 2.5mW, less than 10mW at 5mm distance.

Conclusion: No SAR evaluation required since transmitter power is below FCC threshold