



# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT

Report No. : AT0008947(6) Date : 05 Feb 2015

Application No. : LT002836(8)

Applicant : C-MAX Asia Limited  
Room 117, 1/F, Liven House,  
61-63 King Yip Street, Kwun Tong, Hong Kong

Sample Description : One(1) item of submitted sample stated to be 2.4GHz Module of Model No. CMM-9209-V4.0  
Sample registration No. : RT005659-002, RT007719-001  
Radio Frequency : 2408MHz – 2474 MHz Transceiver  
Rating : 2 x 1.5V AA size batteries  
No. of submitted sample : Five (5) piece (s)

Date Received : 17 Jan 2015, 30 Jan 2015

Test Period : 17 Jan 2015 to 05 Feb 2015.

Test Requested : FCC Part 15 Certificate (15.249)

Test Method : 47 CFR Part 15 (10-1-12 Edition), ANSI C63. 4 – 2009


Test Engineer : Mr. LEUNG Shu-kan, Ken

Test Result : See attached sheet(s) from page 2 to 27.

Conclusion : The submitted sample was found to comply with requirement of FCC Part 15 Subpart B and C.

For and on behalf of  
CMA Industrial Development Foundation Limited

Authorized Signature : \_\_\_\_\_

  
Mr. WONG Lap-pong, Andrew  
Manager  
Electrical Division

Page 1 of 27

FCC ID: 2ABBXCM9209V402015



# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT

Report No. : AT0008947(6)

Date : 05 Feb 2015

### Table of Contents

1	General Information .....	3
1.1	General Description .....	3
1.2	Location of the test site .....	4
1.3	List of measuring equipment.....	5
1.4	Measurement Uncertainty.....	6
2	Description of the radiated emission test .....	7
2.1	Test Procedure .....	7
2.2	Test Result .....	8
2.3	Radiated Emission Measurement Data .....	9
3	Description of the Line-conducted Test .....	12
3.1	Test Procedure .....	12
3.2	Test Result .....	12
3.3	Graph and Table of Conducted Emission Measurement Data .....	12
4	Photograph .....	13
4.1	Photographs of the Test Setup for Radiated Emission and Conducted Emission.....	13
4.2	Photographs of the External and Internal Configurations of the EUT.....	13
5	Supplementary document.....	14
5.1	Bandwidth.....	14
5.2	Duty cycle.....	14
5.3	Transmission time.....	14
5.4	Power Spectral Density.....	14
5.5	Average on time.....	14
6	Appendices.....	15



# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT

Report No. : AT0008947(6)

Date : 05 Feb 2015

### 1 General Information

#### 1.1 General Description

The equipment under test (EUT) is a transceiver module for 2.4GHz wireless device. The EUT is power by 3V dc. The EUT contain shielding, internal grounding and built in with a folded-dipole PCB antenna. The EUT can mount on other device through surface mount or plug in through 9-pin 1.27 mm connector.

The brief circuit description is listed as follows:

- X1 and its associated circuit act as oscillator
- L1, R1, C6, C7 and its associated circuit act as antenna matching
- U1 and its associated circuit act as controller



# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT

Report No. : AT0008947(6)

Date : 05 Feb 2015

### 1.2 Location of the test site

FCC Registered Test Site Number: 552221

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2009. A Semi-Anechoic Chamber Testing Site is set up for investigation and located at:

Ground Floor, Yan Hing Centre,  
9 – 13 Wong Chuk Yeung Street,  
Fo Tan, Shatin,  
New Territories,  
Hong Kong.

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2009. A shielded room is located at :

Ground Floor, Yan Hing Centre,  
9 – 13 Wong Chuk Yeung Street,  
Fo Tan, Shatin,  
New Territories,  
Hong Kong.



# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT

Report No. : AT0008947(6)

Date : 05 Feb 2015

### 1.3 List of measuring equipment

Equipment	Manufacturer	Model No.	Serial No.	Calibration Due Date	Calibration Period
EMI Test Receiver	R&S	ESCI	100152	28 Aug 2015	1 Year
Spectrum Analyzer	R&S	FSP30	100628	24 Nov 2015	1 Year
Broadband Antenna	Schaffner	CBL6112B	2718	06 Jan 2015	1 Year
Loop Antenna	EMCO	6502	00056620	28 Oct 2015	1 Year
Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-531	24 Nov 2016	2 Years
Horn Antenna	Schwarzbeck	BBHA 9170	BBHA9170442	18 Jun 2015	2 Years
Broadband Pre-Amplifier	Schwarzbeck	BBV 9718	9718-119	24 Nov 2016	2 Years
Broadband Pre-Amplifier	Schwarzbeck	BBV 9719	9719-010	17 Jun 2015	2 Years
Coaxial Cable	Suhner	Sucoflex_104	N/A	24 Nov 2015	1 Year



# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT

Report No. : AT0008947(6)

Date : 05 Feb 2015

### 1.4 Measurement Uncertainty

The reported uncertainty is based on a standard uncertainty multiplied by a coverage factor  $k=2$ , providing a level of confidence of approximately 95%.

#### Radiated emissions

Frequency	Uncertainty ( $U_{lab}$ )
30MHz ~ 200MHz (Horizontal)	4.63dB
30MHz ~ 200MHz (Vertical)	4.65dB
200MHz ~1000MHz (Horizontal)	4.45dB
200MHz ~1000MHz (Vertical)	4.41dB

#### Conducted emissions

Frequency	Uncertainty ( $U_{lab}$ )
150kHz~30MHz	2.47dB



# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT

Report No. : AT0008947(6)

Date : 05 Feb 2015

### 2 Description of the radiated emission test

#### 2.1 Test Procedure

Radiated emissions measurements are investigated and taken pursuant to the procedures of ANSI C63.4 – 2009.

The equipment under test (EUT) was placed on a non-conductive turntable with dimensions of 1.5m x 1m and 0.8m high above the ground. 3m from the EUT, a broadband antenna mounting on the mast received the signal strength. The turntable was rotated to maximize the emission level. The antenna was then moving along the mast from 1m up to 4m until no more higher value was found. Both horizontal and vertical polarization of the antenna were placed and investigated.

For below 30MHz, a loop antenna with its vertical plane is placed 3m from the EUT and rotated about its vertical axis for maximum response at each azimuth about the EUT. And the centre of the loop shall be 1 m above the ground.

For 30MHz to 1GHz, broadband antenna with its vertical and horizontal plane is placed 3m from the EUT and rotated about its vertical and horizontal axis for maximum response at each azimuth about the EUT. And the reference point of antenna shall be 1 m above the ground.

For above 1GHz, horn antenna with its vertical and horizontal plane is placed 3m from the EUT and rotated about its vertical and horizontal axis for maximum response at each azimuth about the EUT. Preamplifier and High Pass filter was used for measurements. The reference point of antenna shall be 1 m above the ground.

The device was rotated through three orthogonal to determine which attitude and configuration produce the highest emission during measurement for Radiated Emission measurement.



# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT

Report No. : AT0008947(6)

Date : 05 Feb 2015

### 2.2 Test Result

#### Subpart C

Peak Detector data were measured unless otherwise stated.

“#” means emissions appear within the restricted bands shall follow the requirement of section 15.205.

The frequencies from fundamental up to that tenth harmonics were investigated, and emissions more 20dB below limit were not reported. Thus, those highest emissions were presented in next page (section 2.3).

It was found that the EUT meet the FCC requirement.

#### Subpart B

The emissions meeting the requirement of section 15.109 are based on measurements employing the CISPR quasi-peak detector below 1000MHz and average detector for frequencies above 1000MHz.

The frequencies from 30MHz to 1000MHz were investigated and emissions more 20 dB below limited were not reported. Thus, those higher emissions were presented on next page (section 2.3).

It was found that the EUT meet the FCC requirement.





# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT

Report No. : AT0008947(6)

Date : 05 Feb 2015

### 2.3 Radiated Emission Measurement Data

#### Radiated emission

pursuant to

the requirement of FCC Part 15 subpart C

Environmental conditions:

Parameter	Recorded value	
Ambient temperature:	20	°C
Relative humidity:	62	%

Measurement: Peak RBW: 1MHz VBW: 3MHz

Testing frequency range: 9kHz to 25GHz

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBμV)	Transducer Factor (dB/m)	Field Strength at 3m (dBμV/m)	Limit at 3m (dBμV/m)	Margin (dB)
2408.032	H	97.1	- 6.3	93.0	114.0	- 21.0
#4815.818	H	46.9	2.4	50.7	74.0	- 23.3
#4816.036	V	48.3	10.8	52.1	74.0	- 21.9
7223.740	H	38.3	10.8	50.0	74.0	- 24.0
2442.044	H	97.8	- 6.3	93.7	114.0	- 20.3
#4884.016	H	48.2	2.4	52.0	74.0	- 22.0
#4884.036	V	49.1	10.8	52.9	74.0	- 21.1
#7326.180	H	39.5	10.8	51.2	74.0	- 22.8
2473.938	H	92.7	- 6.3	88.4	114.0	- 25.6
#4947.980	H	43.0	2.4	47.1	74.0	- 26.9
#4948.055	V	43.5	2.4	47.6	74.0	- 26.4
#7421.840	H	37.4	10.8	49.1	74.0	- 24.9

Remark: Peak measurement values are lower than average limit, therefore average measurement is not necessary

Other emissions more than 20dB below the limit are not reported.

Page 9 of 27

FCC ID: 2ABBXCM9209V402015

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: info@cmatcl.com Web Site: http://www.cmatcl.com



# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT

Report No. : AT0008947(6)

Date : 05 Feb 2015

### 2.3 Radiated Emission Measurement Data (Con't)

#### Radiated emission

pursuant to

the requirement of FCC Part 15 subpart C

Environmental conditions:

Parameter	Recorded value	
Ambient temperature:	19	° C
Relative humidity:	55	%

Detector: Quasi-peak, RBW: 120KHz, VBW: 300KHz

Testing frequency range: 9kHz to 25GHz      Operation mode: Transmission

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBµV)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBµV/m)	Limit at 3m (dBµV/m)	Margin (dB)
78.823	H	7.2	8.3	15.5	40.0	- 24.5
116.567	H	8.4	12.7	21.1	43.5	- 22.4
155.763	H	62.	13.7	19.9	43.5	- 23.6
193.532	H	7.0	11.7	18.7	43.5	- 24.8
243.862	H	8.6	13.0	21.6	46.0	- 24.4
291.265	H	8.0	15.7	23.7	46.0	- 22.3
332.641	H	8.1	17.1	25.2	46.0	- 20.8

Remark: Other emissions more than 20dB below the limit are not reported.



# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT

Report No. : AT0008947(6)

Date : 05 Feb 2015

### 2.3 Radiated Emission Measurement Data (Con't)

#### Radiated emission

pursuant to

**the requirement of FCC Part 15 subpart C**

Environmental conditions:

Parameter	Recorded value	
Ambient temperature:	19	° C
Relative humidity:	55	%

Detector: Quasi-peak, RBW: 120KHz, VBW: 300KHz

Testing frequency range: 9kHz to 25GHz      Operation mode: Receiving

Frequency (MHz)	Polarity (H/V)	Reading at 3m (dBµV)	Antenna Factor and Cable Loss (dB/m)	Field Strength at 3m (dBµV/m)	Limit at 3m (dBµV/m)	Margin (dB)
75.871	H	7.0	8.3	15.3	40.0	- 24.7
110.633	H	8.0	12.7	20.7	43.5	- 22.8
149.122	H	6.5	13.7	20.2	43.5	- 23.3
189.889	H	6.9	11.7	18.6	43.5	- 24.9
237.939	H	7.7	13.0	20.7	46.0	- 25.3
293.441	H	8.0	15.7	23.7	46.0	- 22.3
351.908	H	9.7	17.1	26.8	46.0	- 19.2

Remark: Other emissions more than 20dB below the limit are not reported.



# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT

Report No. : AT0008947(6)

Date : 05 Feb 2015

### **3 Description of the Line-conducted Test**

#### **3.1 Test Procedure**

Conducted emissions measurements are investigated and also taken pursuant to the procedures of ANSI C63.4 – 2009. The EUT was setup as described in the procedures, and both lines were measured.

#### **3.2 Test Result**

No measurement is required as the EUT is a battery-operated product.

#### **3.3 Graph and Table of Conducted Emission Measurement Data**

Not Applicable



# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT

Report No. : AT0008947(6)

Date : 05 Feb 2015

### **4 Photograph**

#### **4.1 Photographs of the Test Setup for Radiated Emission and Conducted Emission**

For electronic filing, the photos are saved with filename TSup1.jpg to TSup8.jpg.

#### **4.2 Photographs of the External and Internal Configurations of the EUT**

For electronic filing, the photos are saved with filename ExPho1.jpg to ExPho4.jpg and InPho1.jpg to InPho2.jpg.



# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT

Report No. : AT0008947(6)

Date : 05 Feb 2015

### 5 Supplementary document

The following document were submitted by applicant, and for electronic filing, the document are saved with the following filenames:

Document	Filename
ID Label/Location	LabelSmp.jpg
Block Diagram	BlkDia.pdf
Schematic Diagram	Schem.pdf
Users Manual	UserMan.pdf
Operational Description	OpDes.pdf

#### 5.1 Bandwidth

The plot saved in TestRpt2.pdf shows the fundamental emission is confined in the specified band. It shows the 20dB bandwidth met the 15.215 requirement for frequency band 2400 to 2483.5 MHz.

The plot saved in TestRpt3.pdf shows the band edge is fulfil 15.209 requirement.

#### 5.2 Duty cycle

Not Applicable

#### 5.3 Transmission time

Not Applicable

#### 5.4 Power Spectral Density

Not Applicable

#### 5.5 Average on time

Not Applicable



# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT

Report No. : AT0008947(6)

Date : 05 Feb 2015

### 6 Appendices

A1	Photos of the set-up of Radiated Emissions	4	pages
A2	Photos of External Configurations	2	pages
A3	Photos of Internal Configurations	1	page
A4	ID Label/Location	1	page
A5	Band Edge	2	pages
A6	20dB Bandwidth Plot	2	pages



# CMA Testing and Certification Laboratories


廠商會檢定中心

## TEST REPORT


Report No. : AT0008947(6)

Date : 05 Feb 2015

### A1. Photos of the set-up of Radiated Emissions



(Front view, 30MHz – 1GHz)



(Back view, 30MHz – 1GHz)

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew





# CMA Testing and Certification Laboratories


廠商會檢定中心

## TEST REPORT


Report No. : AT0008947(6)

Date : 05 Feb 2015

### A1. Photos of the set-up of Radiated Emissions



(Front view, 9kHz – 30MHz)



(Back view, 9kHz – 30MHz)

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew



# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT


Report No. : AT0008947(6)

Date : 05 Feb 2015

### A1. Photos of the set-up of Radiated Emissions



(Front view, above 1GHz)



(Back view, above 1GHz)

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew

FCC ID: 2AABXCM9029V402015

Page 18 of 27

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website [www.cmatcl.com](http://www.cmatcl.com).  
This document shall not be reproduced except in full or with written approval by CMA Testing

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: [info@cmatcl.com](mailto:info@cmatcl.com) Web Site: <http://www.cmatcl.com>



# CMA Testing and Certification Laboratories


廠商會檢定中心

## TEST REPORT

Report No. : AT0008947(6)

Date : 05 Feb 2015

### A1. Photos of the set-up of Radiated Emissions



(Top view, EUT with evaluation board)



(Back view, EUT with evaluation board)

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew

FCC ID: 2AABXCM9029V402015

Page 19 of 27

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website [www.cmatcl.com](http://www.cmatcl.com). This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: [info@cmatcl.com](mailto:info@cmatcl.com) Web Site: <http://www.cmatcl.com>



# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT


Report No. : AT0008947(6)

Date : 05 Feb 2015

### A2 Photos of External Configurations



External Configuration 1 (Module with pin header)



External Configuration 2 (Module with pin header)

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew

FCC ID: 2AABXCM9029V402015

Page 20 of 27

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website [www.cmatcl.com](http://www.cmatcl.com). This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: [info@cmactl.com](mailto:info@cmactl.com) Web Site: <http://www.cmatcl.com>



# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT


Report No. : AT0008947(6)

Date : 05 Feb 2015

### A2 Photos of External Configurations



External Configuration 3 (Module without pin header)



External Configuration 4 (Module without pin header)

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew

FCC ID: 2AABXCM9029V402015

Page 21 of 27

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website [www.cmatcl.com](http://www.cmatcl.com). This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: [info@cmatcl.com](mailto:info@cmatcl.com) Web Site: <http://www.cmatcl.com>



# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT

Report No. : AT0008947(6)

Date : 05 Feb 2015

### A3. Photos of Internal Configurations



Internal Configuration 1 (with pin header)



Internal Configuration 2 (without pin header)

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew

FCC ID: 2AABXCM9029V402015

Page 22 of 27

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website [www.cmatcl.com](http://www.cmatcl.com). This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: [info@cmatcl.com](mailto:info@cmatcl.com) Web Site: <http://www.cmatcl.com>



# CMA Testing and Certification Laboratories

廠商會檢定中心

## TEST REPORT

Report No. : AT0008947(6)

Date : 05 Feb 2015

### A4. ID Label / Location



ID Label 1 (with pin header)



ID Label 2 (without pin header)

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew

FCC ID: 2AABXCM9029V402015

Page 23 of 27

This document is issued subject to the latest CMA Testing General Terms and Conditions of Testing and Inspection Services, available on request or accessible at website [www.cmatcl.com](http://www.cmatcl.com). This document shall not be reproduced except in full or with written approval by CMA Testing.

CMA Industrial Development Foundation Limited

Room 1302, Yan Hing Centre, 9-13 Wong Chuk Yeung St., Fo Tan, Shatin, N.T., Hong Kong.

Tel: (852) 2698 8198 Fax: (852) 2695 4177 E-mail: [info@cmatcl.com](mailto:info@cmatcl.com) Web Site: <http://www.cmatcl.com>



# CMA Testing and Certification Laboratories


廠商會檢定中心

## TEST REPORT


Report No. : AT0008947(6)

Date : 05 Feb 2015

### A5. Band Edge



Lower edge (Peak measurement)



Lower edge (Average measurement)

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew

FCC ID: 2AABXCM9029V402015





# CMA Testing and Certification Laboratories


廠商會檢定中心

## TEST REPORT


Report No. : AT0008947(6)

Date : 05 Feb 2015

### A5. Band Edge



Higher edge (Peak measurement)



Higher edge (Average measurement)

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew



# CMA Testing and Certification Laboratories


廠商會檢定中心

## TEST REPORT


Report No. : AT0008947(6)

Date : 05 Feb 2015

### A6. 20dB Bandwidth Plot



Bandwidth 1 (2408MHz)



Bandwidth 2 (2442MHz)

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew

FCC ID: 2AABXCM9029V402015



# CMA Testing and Certification Laboratories


廠商會檢定中心

## TEST REPORT

Report No. : AT0008947(6)

Date : 05 Feb 2015

### A6. 20dB Bandwidth Plot



Bandwidth 3 (2474MHz)

\*\*\*\*\* End of Report \*\*\*\*\*

Tested by:

Mr. LEUNG Shu-kan, Ken

Reviewed by:

Mr. WONG Lap-pong, Andrew