



element[®]

CINCH Systems

RF-ARGB

FCC 15.231:2017

Low Power Transmitter

Report # CINC0005



NVLAP Lab Code: 200881-0

This report must not be used to claim product certification, approval, or endorsement by NVLAP, NIST, or any agency of the federal government of the United States of America. This Report shall not be reproduced, except in full without written approval of the laboratory.



CERTIFICATE OF TEST

Last Date of Test: February 9, 2017
CINCH Systems
Model: RF-ARGB

Radio Equipment Testing

Standards

Specification	Method
FCC 15.231:2017	ANSI C63.10:2013

Results

Method Clause	Test Description	Applied	Results	Comments
6.2	Powerline Conducted Emissions	No	N/A	Not required for battery powered equipment.
6.5, 6.6	Field Strength of Fundamental	Yes	Pass	
6.5, 6.6	Spurious Radiated Emissions	Yes	Pass	
6.9.2	Occupied Bandwidth	Yes	Pass	
7.5	Duty Cycle	Yes	Pass	

Deviations From Test Standards

None

Approved By:

Dean Ghizzone, General Manager

Product compliance is the responsibility of the client; therefore, the tests and equipment modes of operation represented in this report were agreed upon by the client, prior to testing. The results of this test pertain only to the sample(s) tested. The specific description is noted in each of the individual sections of the test report supporting this certificate of test. This report reflects only those tests from the referenced standards shown in the certificate of test. It does not include inspection or verification of labels, identification, marking or user information.

REVISION HISTORY



2017.1.25

Revision Number	Description	Date	Page Number
00	None		

ACCREDITATIONS AND AUTHORIZATIONS



United States

FCC - Designated by the FCC as a Telecommunications Certification Body (TCB). Certification chambers, Open Area Test Sites, and conducted measurement facilities are listed with the FCC.

A2LA - Accredited by A2LA to ISO / IEC 17065 as a product certifier. This allows Element to certify transmitters to FCC and IC specifications.

NVLAP - Each laboratory is accredited by NVLAP to ISO 17025

Canada

ISED - Recognized by Innovation, Science and Economic Development Canada as a Certification Body (CB). Certification chambers and Open Area Test Sites are filed with ISED.

European Union

European Commission – Validated by the European Commission as a Notified Body under the R&TTE Directive.

Australia/New Zealand

ACMA - Recognized by ACMA as a CAB for the acceptance of test data.

Korea

MSIP / RRA - Recognized by KCC's RRA as a CAB for the acceptance of test data.

Japan

VCCI - Associate Member of the VCCI. Conducted and radiated measurement facilities are registered.

Taiwan

BSMI – Recognized by BSMI as a CAB for the acceptance of test data.

NCC - Recognized by NCC as a CAB for the acceptance of test data.

Singapore

IDA – Recognized by IDA as a CAB for the acceptance of test data.

Israel

MOC – Recognized by MOC as a CAB for the acceptance of test data.

Hong Kong

OFCA – Recognized by OFCA as a CAB for the acceptance of test data.

Vietnam

MIC – Recognized by MIC as a CAB for the acceptance of test data.

SCOPE

For details on the Scopes of our Accreditations, please visit:


<http://portlandcustomer.element.com/ts/scope/scope.htm>

<http://gsi.nist.gov/global/docs/cabs/designations.html>

FACILITIES



California Labs OC01-13 41 Tesla Irvine, CA 92618 (949) 861-8918	Minnesota Labs MN01-08, MN10 9349 W Broadway Ave. Brooklyn Park, MN 55445 (612)-638-5136	New York Labs NY01-04 4939 Jordan Rd. Elbridge, NY 13060 (315) 554-8214	Oregon Labs EV01-12 22975 NW Evergreen Pkwy Hillsboro, OR 97124 (503) 844-4066	Texas Labs TX01-09 3801 E Plano Pkwy Plano, TX 75074 (469) 304-5255	Washington Labs NC01-05 19201 120 th Ave NE Bothell, WA 98011 (425)984-6600
NVLAP					
NVLAP Lab Code: 200676-0	NVLAP Lab Code: 200881-0	NVLAP Lab Code: 200761-0	NVLAP Lab Code: 200630-0	NVLAP Lab Code:201049-0	NVLAP Lab Code: 200629-0
Innovation, Science and Economic Development Canada					
2834B-1, 2834B-3	2834E-1	N/A	2834D-1, 2834D-2	2834G-1	2834F-1
VCCI					
A-0029	A-0109	N/A	A-0108	A-0201	A-0110
Recognized Phase I CAB for ACMA, BSMI, IDA, KCC/RRA, MIC, MOC, NCC, OFCA					
US0158	US0175	N/A	US0017	US0191	US0157



MEASUREMENT UNCERTAINTY



Measurement Uncertainty

When a measurement is made, the result will be different from the true or theoretically correct value. The difference is the result of tolerances in the measurement system that cannot be completely eliminated. To the extent that technology allows us, it has been our aim to minimize this error. Measurement uncertainty is a statistical expression of measurement error qualified by a probability distribution.

A measurement uncertainty estimation has been performed for each test per our internal quality document QM205.4.6. The estimation is used to compare the measured result with its "true" or theoretically correct value. The expanded measurement uncertainty (K=2) can be found included as part of the applicable test description page. Our measurement data meets or exceeds the measurement uncertainty requirements of the applicable specification; therefore, the test data can be compared directly to the specification limit to determine compliance. The calculations for estimating measurement uncertainty are based upon ETSI TR 100 028 (or CISPR 16-4-2 as applicable), and are available upon request.

The following table represents the Measurement Uncertainty (MU) budgets for each of the tests that may be contained in this report.


Test	+ MU	- MU
Frequency Accuracy (Hz)	0.0007%	-0.0007%
Amplitude Accuracy (dB)	1.2 dB	-1.2 dB
Conducted Power (dB)	0.3 dB	-0.3 dB
Radiated Power via Substitution (dB)	0.7 dB	-0.7 dB
Temperature (degrees C)	0.7°C	-0.7°C
Humidity (% RH)	2.5% RH	-2.5% RH
Voltage (AC)	1.0%	-1.0%
Voltage (DC)	0.7%	-0.7%
Field Strength (dB)	5.2 dB	-5.2 dB
AC Powerline Conducted Emissions (dB)	2.4 dB	-2.4 dB

Test Setup Block Diagrams




2017.1.25


Antenna Port Conducted Measurements



Near Field Test Fixture Measurements



Spurious Radiated Emissions





PRODUCT DESCRIPTION

Client and Equipment Under Test (EUT) Information

Company Name:	CINCH Systems
Address:	Suite 300 12075 43rd Street NE
City, State, Zip:	St. Michael, MN 55376
Test Requested By:	Jibril Aga
Model:	RF-ARGB
First Date of Test:	February 9, 2017
Last Date of Test:	February 9, 2017
Receipt Date of Samples:	February 9, 2017
Equipment Design Stage:	Production
Equipment Condition:	No Damage
Purchase Authorization:	Verified

Information Provided by the Party Requesting the Test

Functional Description of the EUT:

Low power transmitter with 1 antenna type operating at 319.508 MHz.

Testing Objective:

To demonstrate compliance to FCC 15.231 specifications.

CONFIGURATIONS



Configuration CINC0005- 1

EUT			
Description	Manufacturer	Model/Part Number	Serial Number
Glassbreak Sensor	CINCH Systems	RF-ARGB	G5

Configuration CINC0005- 2

EUT			
Description	Manufacturer	Model/Part Number	Serial Number
Glassbreak Sensor	CINCH Systems	RF-ARGB	G1

MODIFICATIONS



Equipment Modifications

Item	Date	Test	Modification	Note	Disposition of EUT
1	2/9/2017	Duty Cycle	Tested as delivered to Test Station.	No EMI suppression devices were added or modified during this test.	EUT remained at Element following the test.
2	2/9/2017	Occupied Bandwidth	Tested as delivered to Test Station.	No EMI suppression devices were added or modified during this test.	EUT remained at Element following the test.
3	2/9/2017	Field Strength of Fundamental	Modified from delivered configuration.	Client removed 6 in. from the antenna in order to pass HF Spurious. Modification authorized by Jibril Aga.	EUT remained at Element following the test.
4	2/9/2017	Spurious Radiated Emissions	Tested as delivered to Test Station.	No EMI suppression devices were added or modified during this test.	Scheduled testing was completed.

FIELD STRENGTH OF FUNDAMENTAL



PSA-ESCI 2017.01.26

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data. The test data represents the configuration / operating mode/ model that produced the highest emission levels as compared to the specification limit.

MODES OF OPERATION

Tx(319.5MHz) CW.

POWER SETTINGS INVESTIGATED

Battery

CONFIGURATIONS INVESTIGATED

CINC0005 - 2

FREQUENCY RANGE INVESTIGATED

Start Frequency | 319 MHz | Stop Frequency | 320 MHz

SAMPLE CALCULATIONS

Radiated Emissions: Field Strength = Measured Level + Antenna Factor + Cable Factor - Amplifier Gain + Distance Adjustment Factor + External Attenuation

TEST EQUIPMENT

Description	Manufacturer	Model	ID	Last Cal.	Interval
Analyzer - Spectrum Analyzer	Agilent	N9010A	AFI	1/6/2017	12 mo
Cable	ESM Cable Corp.	Bilog Cables	MNH	12/1/2016	12 mo
Antenna - Biconilog	Teseq	CBL 6141B	AYD	1/6/2016	24 mo

MEASUREMENT BANDWIDTHS

Frequency Range (MHz)	Peak Data (kHz)	Quasi-Peak Data (kHz)	Average Data (kHz)
0.01 - 0.15	1.0	0.2	0.2
0.15 - 30.0	10.0	9.0	9.0
30.0 - 1000	100.0	120.0	120.0
Above 1000	1000.0	N/A	1000.0

TEST DESCRIPTION

The antennas to be used with the EUT were tested. The EUT was configured for continuous un-modulated CW operation at its single transmit frequency. The field strength of the transmit frequency was maximized by rotating the EUT, adjusting the measurement antenna height and polarization, and manipulating the EUT in 3 orthogonal planes (per ANSI C63.10:2013).

To derive average emission measurements, a duty cycle correction factor was utilized:

Duty Cycle = On time/100 milliseconds (or the period, whichever is less)

Where "On time" = N1L1 + N2L2 + ...

Where N1 is the number of type 1 pulses, L1 is length of type 1 pulses, N2 is the number of type 2 pulses, L2 is the length of type 2 pulses, etc.

Therefore, Duty Cycle = (N1L1 + N2L2 + ...)/100mS or T, whichever is less. (Where T is the period of the pulse train.)

The measured values for the EUT's pulse train are as follows:

Period = 100 mSec
 Pulsewidth of Type 1 Pulse = 24.53 uSec
 Pulsewidth of Type 2 Pulse = 127.3 uSec
 Pulsewidth of Type 3 Pulse = 493.7 uSec
 Number of Type 1 Pulses = 1
 Number of Type 2 Pulses = 78
 Number of Type 3 Pulses = 1

Duty Cycle = $20 \log \left[\frac{(1)(0.02453) + (78)(0.1273) + (1)(0.4937)}{100} \right] = -19.6 \text{ dB}$

The duty cycle correction factor of -19.6 dB was added to the peak readings to mathematically derive the average levels. Peak measurements were made with a resolution bandwidth of 100kHz and a video bandwidth of 300kHz.

FIELD STRENGTH OF FUNDAMENTAL




EmiR5 2017.01.25 PSA-ESCI 2017.01.26

Work Order:	CINC0005	Date:	02/09/17	<i>Trevor Buls</i>
Project:	None	Temperature:	22.5 °C	
Job Site:	MN05	Humidity:	13% RH	
Serial Number:	G1	Barometric Pres.:	1029 mbar	Tested by: Trevor Buls, Chris Patterson
EUT:	RF-ARGB			
Configuration:	2			
Customer:	CINCH Systems			
Attendees:	Jibril Aga			
EUT Power:	Battery			
Operating Mode:	Tx(319.5MHz) CW.			
Deviations:	None			
Comments:	None			

Test Specifications	FCC 15.231:2017	Test Method	ANSI C63.10:2013
---------------------	-----------------	-------------	------------------

Run #	17	Test Distance (m)	3	Antenna Height(s)	1 to 4(m)	Results	Pass
-------	----	-------------------	---	-------------------	-----------	---------	------



Freq (MHz)	Amplitude (dBuV)	Factor (dB)	Antenna Height (meters)	Azimuth (degrees)	Duty Cycle Correction Factor (dB)	External Attenuation (dB)	Polarity/Transducer Type	Detector	Distance Adjustment (dB)	Adjusted (dBuV/m)	Spec. Limit (dBuV/m)	Compared to Spec. (dB)	Comments
319.508	59.7	-1.5	1.0	37.1	-19.6	0.0	Horz	AV	0.0	38.6	75.9	-37.3	EUT On Side
319.508	59.7	-1.5	1.0	37.1	-19.6	0.0	Horz	PK	0.0	58.2	95.9	-37.7	EUT On Side
319.508	58.7	-1.5	1.0	201.0	-19.6	0.0	Horz	AV	0.0	37.6	75.9	-38.3	EUT Horizontal
319.508	58.7	-1.5	1.0	201.0	-19.6	0.0	Horz	PK	0.0	57.2	95.9	-38.7	EUT Horizontal
319.506	56.7	-1.5	1.0	307.0	-19.6	0.0	Horz	AV	0.0	35.6	75.9	-40.3	EUT Vertical
319.503	56.7	-1.5	1.7	282.0	-19.6	0.0	Vert	AV	0.0	35.6	75.9	-40.3	EUT Vertical
319.506	56.7	-1.5	1.0	307.0	-19.6	0.0	Horz	PK	0.0	55.2	95.9	-40.7	EUT Vertical
319.503	56.7	-1.5	1.7	282.0	-19.6	0.0	Vert	PK	0.0	55.2	95.9	-40.7	EUT Vertical
319.508	52.9	-1.5	1.5	58.1	-19.6	0.0	Vert	AV	0.0	31.8	75.9	-44.1	EUT Horizontal
319.508	52.9	-1.5	1.5	58.1	-19.6	0.0	Vert	PK	0.0	51.4	95.9	-44.5	EUT Horizontal
319.508	49.5	-1.5	1.5	253.0	-19.6	0.0	Vert	AV	0.0	28.4	75.9	-47.5	EUT On Side
319.508	49.5	-1.5	1.5	253.0	-19.6	0.0	Vert	PK	0.0	48.0	95.9	-47.9	EUT On Side

SPURIOUS RADIATED EMISSIONS



PSA-ESCI 2017.01.26

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data. The test data represents the configuration / operating mode/ model that produced the highest emission levels as compared to the specification limit.

MODES OF OPERATION

Tx(319.5MHz) CW.

POWER SETTINGS INVESTIGATED

Battery

CONFIGURATIONS INVESTIGATED

CINC0005 - 2

FREQUENCY RANGE INVESTIGATED

Start Frequency	30 MHz	Stop Frequency	4000 MHz
-----------------	--------	----------------	----------

SAMPLE CALCULATIONS

Radiated Emissions: Field Strength = Measured Level + Antenna Factor + Cable Factor - Amplifier Gain + Distance Adjustment Factor + External Attenuation

TEST EQUIPMENT

Description	Manufacturer	Model	ID	Last Cal.	Interval
Analyzer - Spectrum Analyzer	Agilent	N9010A	AFI	1/6/2017	12 mo
Cable	ESM Cable Corp.	Double Ridge Guide Horn Cables	MNI	12/1/2016	12 mo
Amplifier - Pre-Amplifier	Miteq	AM-1616-1000	AVO	12/1/2016	12 mo
Amplifier - Pre-Amplifier	Miteq	AMF-3D-00100800-32-13P	AVT	3/1/2016	12 mo
Antenna - Double Ridge	ETS Lindgren	3115	AJA	6/23/2016	24 mo
Cable	ESM Cable Corp.	Bilog Cables	MNH	12/1/2016	12 mo
Antenna - Biconilog	Teseq	CBL 6141B	AYD	1/6/2016	24 mo
Attenuator	Fairview Microwave	SA18E-10	TYA	9/23/2016	12 mo

MEASUREMENT BANDWIDTHS

Frequency Range (MHz)	Peak Data (kHz)	Quasi-Peak Data (kHz)	Average Data (kHz)
0.01 - 0.15	1.0	0.2	0.2
0.15 - 30.0	10.0	9.0	9.0
30.0 - 1000	100.0	120.0	120.0
Above 1000	1000.0	N/A	1000.0

TEST DESCRIPTION

The highest gain antenna of each type to be used with the EUT was tested. The EUT was configured for the required transmit frequency in each operational band and the modes as showed in the data sheets.

For each configuration, the spectrum was scanned throughout the specified range as part of the exploratory investigation of the emissions. These "pre-scans" are not included in the report. Final measurements on individual emissions were then made and included in this test report.

The individual emissions from the EUT were maximized by rotating the EUT on a turntable, adjusting the position of the EUT and EUT antenna in three orthogonal axis, and adjusting the measurement antenna height and polarization (per ANSI C63.10). A preamp and high pass filter (and notch filter) were used for this test in order to provide sufficient measurement sensitivity.

Measurements were made with the required detectors and annotated on the data for each individual point using the following annotation:

QP = Quasi-Peak Detector
PK = Peak Detector
AV = RMS Detector

To derive average emission measurements, a duty cycle correction factor was utilized:

Duty Cycle = On time/100 milliseconds (or the period, whichever is less)

Where "On time" = $N1L1 + N2L2 + \dots$

Where N1 is the number of type 1 pulses, L1 is length of type 1 pulses, N2 is the number of type 2 pulses, L2 is the length of type 2 pulses, etc.

Therefore, Duty Cycle = $(N1L1 + N2L2 + \dots)/100\text{mS}$ or T, whichever is less. Where T is the period of the pulse train.

The measured values for the EUT's pulse train are as follows:

Period = 100 mSec
Pulsewidth of Type 1 Pulse = 24.53 uSec
Pulsewidth of Type 2 Pulse = 127.3 uSec
Pulsewidth of Type 3 Pulse = 493.7 uSec
Number of Type 1 Pulses = 1
Number of Type 2 Pulses = 78
Number of Type 3 Pulses = 1
Duty Cycle = $20 \log [(1)(0.02453) + (78)(0.1273) + (1)(0.4937)]/100 = -19.6 \text{ dB}$

The duty cycle correction factor of -19.6 dB was added to the peak readings to mathematically derive the average levels. Peak measurements were made with a resolution bandwidth of 100kHz and a video bandwidth of 300kHz for measurements at or below 1GHz. Above 1GHz, a resolution bandwidth of 1MHz and a video bandwidth of 3MHz was used.

SPURIOUS RADIATED EMISSIONS




EmiR5 2017.01.25

PSA-ESCI 2017.01.26

Work Order:	CINC0005	Date:	02/09/17	<i>Trevor Buls</i>
Project:	None	Temperature:	22.5 °C	
Job Site:	MN05	Humidity:	13% RH	
Serial Number:	G1	Barometric Pres.:	1029 mbar	
EUT:	RF-ARGB			
Configuration:	2			
Customer:	CINCH Systems			
Attendees:	Jibril Aga			
EUT Power:	Battery			
Operating Mode:	Tx(319.5MHz) CW.			
Deviations:	None			
Comments:	None			

Test Specifications	FCC 15.231:2017	Test Method	ANSI C63.10:2013
----------------------------	-----------------	--------------------	------------------

Run #	14	Test Distance (m)	3	Antenna Height(s)	1 to 4(m)	Results	Pass
--------------	----	--------------------------	---	--------------------------	-----------	----------------	------



Freq (MHz)	Amplitude (dBuV)	Factor (dB)	Antenna Height (meters)	Azimuth (degrees)	Duty Cycle Correction Factor (dB)	External Attenuation (dB)	Polarity/Transducer Type	Detector	Distance Adjustment (dB)	Adjusted (dBuV/m)	Spec. Limit (dBuV/m)	Compared to Spec. (dB)	Comments
1597.542	77.7	-5.2	1.2	153.0	-19.6	0.0	Vert	AV	0.0	52.9	54.0	-1.1	EUT On Side
1597.542	77.7	-5.2	1.2	153.0	0.0	0.0	Vert	PK	0.0	72.5	74.0	-1.5	EUT On Side
1597.592	76.2	-5.2	1.2	257.9	-19.6	0.0	Horz	AV	0.0	51.4	54.0	-2.6	EUT Vertical
1597.575	76.0	-5.2	1.2	107.0	-19.6	0.0	Horz	AV	0.0	51.2	54.0	-2.8	EUT Horizontal
1597.592	76.2	-5.2	1.2	257.9	0.0	0.0	Horz	PK	0.0	71.0	74.0	-3.0	EUT Vertical
1597.575	76.0	-5.2	1.2	107.0	0.0	0.0	Horz	PK	0.0	70.8	74.0	-3.2	EUT Horizontal
1597.550	74.4	-5.2	1.3	147.0	-19.6	0.0	Vert	AV	0.0	49.6	54.0	-4.4	EUT Horizontal
1597.525	74.2	-5.2	1.2	268.9	-19.6	0.0	Horz	AV	0.0	49.4	54.0	-4.6	EUT On Side
1597.550	74.4	-5.2	1.3	147.0	0.0	0.0	Vert	PK	0.0	69.2	74.0	-4.8	EUT Horizontal
1597.525	74.2	-5.2	1.2	268.9	0.0	0.0	Horz	PK	0.0	69.0	74.0	-5.0	EUT On Side
1917.008	73.1	-3.3	1.2	343.0	-19.6	0.0	Vert	AV	0.0	50.2	55.9	-5.7	EUT On Side
1597.550	73.0	-5.2	1.3	118.0	-19.6	0.0	Vert	AV	0.0	48.2	54.0	-5.8	EUT Vertical
1917.008	73.1	-3.3	1.2	343.0	0.0	0.0	Vert	PK	0.0	69.8	75.9	-6.1	EUT On Side
1597.550	73.0	-5.2	1.3	118.0	0.0	0.0	Vert	PK	0.0	67.8	74.0	-6.2	EUT Vertical

Freq (MHz)	Amplitude (dBuV)	Factor (dB)	Antenna Height (meters)	Azimuth (degrees)	Duty Cycle Correction Factor (dB)	External Attenuation (dB)	Polarity/Transducer Type	Detector	Distance Adjustment (dB)	Adjusted (dBuV/m)	Spec. Limit (dBuV/m)	Compared to Spec. (dB)	Comments
1917.058	72.1	-3.3	1.2	25.0	-19.6	0.0	Horz	AV	0.0	49.2	55.9	-6.7	EUT Vertical
1917.058	72.1	-3.3	1.2	25.0		0.0	Horz	PK	0.0	68.8	75.9	-7.1	EUT Vertical
958.514	39.7	13.3	1.2	129.0	-19.6	10.0	Vert	AV	0.0	43.4	55.9	-12.5	EUT On Side
958.514	39.7	13.3	1.2	129.0		10.0	Vert	PK	0.0	63.0	75.9	-12.9	EUT On Side
958.516	37.4	13.3	2.0	21.0	-19.6	10.0	Horz	AV	0.0	41.1	55.9	-14.8	EUT Vertical
958.516	37.4	13.3	2.0	21.0		10.0	Horz	PK	0.0	60.7	75.9	-15.2	EUT Vertical
639.008	36.0	7.0	1.0	154.0	-19.6	10.0	Vert	AV	0.0	33.4	55.9	-22.5	EUT On Side
639.008	36.0	7.0	1.0	154.0		10.0	Vert	PK	0.0	53.0	75.9	-22.9	EUT On Side
639.018	35.2	7.0	1.2	247.9	-19.6	10.0	Horz	AV	0.0	32.6	55.9	-23.3	EUT Vertical
639.018	35.2	7.0	1.2	247.9		10.0	Horz	PK	0.0	52.2	75.9	-23.7	EUT Vertical

OCCUPIED BANDWIDTH



XMI 2017.01.26

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

TEST EQUIPMENT

Description	Manufacturer	Model	ID	Last Cal.	Cal. Due
Cable	ESM Cable Corp.	Bilog Cables	MNH	12/1/2016	12/1/2017
Antenna - Biconilog	Teseq	CBL 6141B	AYD	1/6/2016	1/6/2018
Analyzer - Spectrum Analyzer	Agilent	N9010A	AFI	1/6/2017	1/6/2018

TEST DESCRIPTION

The measurement was made in a radiated configuration of the fundamental with the carrier fully maximized for its highest radiated power. The EUT was transmitting at its maximum data rate.

The 20 dB occupied bandwidth is required to be no wider than 0.25% of the center frequency for devices operating above 70 MHz and below 900 MHz.

OCCUPIED BANDWIDTH



XMit 2017.01.26


EUT: RF-ARGB		Work Order: CINC0005	
Serial Number: G5		Date: 02/09/17	
Customer: CINCH Systems		Temperature: 22.9 °C	
Attendees: Jibril Aga		Humidity: 13.6% RH	
Project: None		Barometric Pres.: 1029 mbar	
Tested by: Trevor Buls, Chris Patterson		Power: Battery	Job Site: MN05
TEST SPECIFICATIONS		Test Method	
FCC 15.231:2017		ANSI C63.10:2013	
COMMENTS			
None			
DEVIATIONS FROM TEST STANDARD			
None			
Configuration #	1	Signature <i>Trevor Buls</i>	
		Value (kHz)	Limit < (kHz) Result
319.508MHz		44.37	798.77 Pass

OCCUPIED BANDWIDTH



XMT 2017.01.26

319.508MHz				Value	Limit	Result
				(kHz)	< (kHz)	
				44.37	798.77	Pass



DUTY CYCLE



XMIT 2017.01.26

Testing was performed using the mode(s) of operation and configuration(s) noted within the report. The individuals and/or the organization requesting the test provided the modes, configurations and settings used to complete the evaluation. The actual test parameters are specified in the test data, this includes items such as investigated frequency range (scanned) and test levels. The testing methods and performance specifications, as well as the test site used for the evaluation are indicated in the test data.

TEST EQUIPMENT

Description	Manufacturer	Model	ID	Last Cal.	Cal. Due
Analyzer - Spectrum Analyzer	Agilent	N9010A	AFQ	12/22/2016	12/22/2017
Cable	ESM Cable Corp.	Bilog Cables	MNH	12/1/2016	12/1/2017
Antenna - Biconilog	Teseq	CBL 6141B	AYD	1/6/2016	1/6/2018
Probe - Near Field Set	ETS Lindgren	7405	IPO	NCR	NCR
Analyzer - Spectrum Analyzer	Agilent	N9010A	AFI	1/6/2017	1/6/2018

TEST DESCRIPTION

The measurement was made in a radiated configuration of the fundamental with the carrier fully maximized for its highest radiated power. For software controlled or pre-programmed devices, the manufacturer shall declare the duty cycle class or classes for the equipment under test. For manually operated or event dependant devices, with or without software controlled functions, the manufacturer shall declare whether the device once triggered, follows a pre-programmed cycle, or whether the transmission is constant until the trigger is released or manually reset. The manufacturer shall also give a description of the application for the device and include a typical usage pattern. The typical usage pattern as declared by the manufacturer shall be used to determine the duty cycle and hence the duty class.

Where an acknowledgement is required, the additional transmitter on-time shall be included and declared by the manufacturer.

To derive average emission measurements, a duty cycle correction factor was utilized:

Duty Cycle = On time/100 milliseconds (or the period, whichever is less)

Where "On time" = $N1L1 + N2L2 + \dots$

Where N1 is the number of type 1 pulses, L1 is length of type 1 pulses, N2 is the number of type 2 pulses, L2 is the length of type 2 pulses, etc.

Therefore, Duty Cycle = $(N1L1 + N2L2 + \dots)/100\text{mS}$ or T, whichever is less. (Where T is the period of the pulse train.)

The measured values for the EUT's pulse train are as follows:

Period = 100 mSec
Pulsewidth of Type 1 Pulse = 24.53 uSec
Pulsewidth of Type 2 Pulse = 127.3 uSec
Pulsewidth of Type 3 Pulse = 493.7 uSec
Number of Type 1 Pulses = 1
Number of Type 2 Pulses = 78
Number of Type 3 Pulses = 1

Duty Cycle = $20 \log \left[\frac{(1)(0.02453) + (78)(0.1273) + (1)(0.4937)}{100} \right] = -19.6 \text{ dB}$

The duty cycle correction factor of -19.6 dB was added to the peak readings to mathematically derive the average levels. Peak measurements were made with a resolution bandwidth of 100kHz and a video bandwidth of 300kHz.

DUTY CYCLE



XMH 2017.01.26

EUT: RF-ARGB		Work Order: CINC0005	
Serial Number: G5		Date: 02/09/17	
Customer: CINCH Systems		Temperature: 22.5 °C	
Attendees: Jibril Aga		Humidity: 13.9% RH	
Project: None		Barometric Pres.: 1029 mbar	
Tested by: Trevor Buls, Chris Patterson		Power: Battery	Job Site: MN05
TEST SPECIFICATIONS		Test Method	
FCC 15.231:2017		ANSI C63.10:2013	
COMMENTS			
None			
DEVIATIONS FROM TEST STANDARD			
None			
Configuration #	1	Signature <i>Trevor Buls</i>	

	Value	Limit	Result
Time Window 10 seconds	See Test Description	N/A	N/A
Time Window 4 seconds	See Test Description	N/A	N/A
Time Window 30 milliseconds	See Test Description	N/A	N/A


DUTY CYCLE



XMI 2017.01.26


Time Window 10 seconds

	Value	Limit	Result
	See Test Description	N/A	N/A



Time Window 4 seconds

	Value	Limit	Result
	See Test Description	N/A	N/A



DUTY CYCLE



XMR 2017.01.26

Time Window 30 milliseconds			
	Value	Limit	Result
	See Test Description	N/A	N/A

