

**CFR 47 FCC PART 15 SUBPART E
ISED RSS-247 Issue 3**

TEST REPORT

For

Briefcase Smart Screen

MODEL NUMBER: AP2718T

FCC ID: 2ABC5-E0048

REPORT NUMBER: 4791136142.3-1-RF-2

ISSUE DATE: January 24, 2024

Prepared for

**SHENZHEN ELECTRON TECHNOLOGY CO., LTD.
Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Baoan,
Shenzhen, China.**

Prepared by

UL Verification Services (Guangzhou) Co., Ltd, Song Shan Lake Branch

Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China

Tel: +86 769 22038881

Fax: +86 769 33244054

Website: www.ul.com

Revision History

Rev.	Issue Date	Revisions	Revised By
V0	January 24, 2024	Initial Issue	

Summary of Test Results

Test Item	Clause	Limit/Requirement	Result
On Time And Duty Cycle	ANSI C63.10-2013, Clause 12.2	None; for reporting purposes only.	Pass
6db AND 26db EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH	KDB 789033 D02 v02r01 Section C.1	FCC Part 15.407 (a)/(e), RSS-247 Issue 3, Clause 6.2.1.2 RSS-Gen Clause 6.7	Pass
Conducted Output Power	KDB 789033 D02 v02r01 Section E.3.a (Method PM)	FCC 15.407 (a) RSS-247 Clause 6.2	Pass
Power Spectral Density	KDB 789033 D02 v02r01 Section F	FCC 15.407 (a) RSS-247 Clause 6.2	Pass
Ac Power Line Conducted Emission	ANSI C63.10-2013, Clause 6.2.	FCC 15.207 RSS-GEN Clause 8.8	Pass
Radiated Emissions And Band Edge Measurement	KDB 789033 D02 v02r01 Section G.3, G.4, G.5, and G.6	FCC 15.407 (b) FCC 15.209 FCC 15.205 RSS-247 Clause 6.2 RSS-GEN Clause 8.9	Pass
Frequency Stability	ANSI C63.10-2013, Clause 6.8	FCC 15.407 (g)	Pass
Antenna Requirement	/	FCC 47 CFR Part 15.203/ 15.407(a)(1) (2), RSS-Gen Issue 5, Clause 6.8	Pass

*This test report is only published to and used by the applicant, and it is not for evidence purpose in China.

*The measurement result for the sample received is <Pass> according to <CFR 47 FCC PART 15 SUBPART E and ISED RSS-247 Issue 3> when <Simple Acceptance> decision rule is applied.

CONTENTS

1. ATTESTATION OF TEST RESULTS.....	6
2. TEST METHODOLOGY.....	7
3. FACILITIES AND ACCREDITATION.....	7
4. CALIBRATION AND UNCERTAINTY	8
4.1. <i>MEASURING INSTRUMENT CALIBRATION</i>	<i>8</i>
4.2. <i>MEASUREMENT UNCERTAINTY.....</i>	<i>8</i>
5. EQUIPMENT UNDER TEST	9
5.1. <i>DESCRIPTION OF EUT</i>	<i>9</i>
5.2. <i>CHANNEL LIST</i>	<i>9</i>
5.3. <i>MAXIMUM POWER.....</i>	<i>10</i>
5.4. <i>TEST CHANNEL CONFIGURATION.....</i>	<i>11</i>
5.5. <i>THE WORSE CASE POWER SETTING PARAMETER.....</i>	<i>12</i>
5.6. <i>WORSE CASE CONFIGURATIONS.....</i>	<i>13</i>
5.7. <i>DESCRIPTION OF AVAILABLE ANTENNAS</i>	<i>14</i>
5.8. <i>SUPPORT UNITS FOR SYSTEM TEST.....</i>	<i>15</i>
6. MEASURING EQUIPMENT AND SOFTWARE USED.....	16
7. ANTENNA PORT TEST RESULTS	18
7.1. <i>ON TIME AND DUTY CYCLE.....</i>	<i>18</i>
7.2. <i>6DB AND 26DB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH ...</i>	<i>19</i>
7.3. <i>CONDUCTED OUTPUT POWER.....</i>	<i>21</i>
7.4. <i>POWER SPECTRAL DENSITY</i>	<i>23</i>
7.5. <i>FREQUENCY STABILITY.....</i>	<i>25</i>
8. RADIATED TEST RESULTS.....	27
8.1. <i>RESTRICTED BANDEDGE</i>	<i>37</i>
8.2. <i>SPURIOUS EMISSIONS (1 GHZ ~ 7 GHZ)</i>	<i>73</i>
8.3. <i>SPURIOUS EMISSIONS (7 GHZ ~ 18 GHZ)</i>	<i>85</i>
8.4. <i>SPURIOUS EMISSIONS (9 KHZ ~ 30 MHZ).....</i>	<i>145</i>
8.5. <i>SPURIOUS EMISSIONS (18 GHZ ~ 26 GHZ)</i>	<i>148</i>
8.6. <i>SPURIOUS EMISSIONS (26 GHZ ~ 40 GHZ)</i>	<i>150</i>
8.7. <i>SPURIOUS EMISSIONS (30 MHZ ~ 1 GHZ).....</i>	<i>152</i>
9. AC POWER LINE CONDUCTED EMISSION	154
10. ANTENNA REQUIREMENT	157
11. TEST DATA.....	158

11.1.	<i>APPENDIX A: EMISSION BANDWIDTH</i>	158
11.1.1.	Test Result.....	158
11.1.2.	Test Graphs	160
11.2.	<i>APPENDIX B: OCCUPIED CHANNEL BANDWIDTH</i>	177
11.2.1.	Test Result.....	177
11.2.2.	Test Graphs	179
11.3.	<i>APPENDIX C: MIN EMISSION BANDWIDTH</i>	196
11.3.1.	Test Result.....	196
11.3.2.	Test Graphs	197
11.4.	<i>APPENDIX D: MAXIMUM AVERAGE CONDUCTED OUTPUT POWER</i>	206
11.4.1.	Test Result.....	206
11.5.	<i>APPENDIX E: MAXIMUM POWER SPECTRAL DENSITY</i>	208
11.5.1.	Test Result.....	208
11.5.2.	Test Graphs	210
11.6.	<i>APPENDIX F: FREQUENCY STABILITY</i>	227
11.6.1.	Test Result.....	227
11.7.	<i>APPENDIX G: DUTY CYCLE</i>	228
11.7.1.	Test Result.....	228
11.7.2.	Test Graphs	229

1. ATTESTATION OF TEST RESULTS

Applicant Information

Company Name: SHENZHEN ELECTRON TECHNOLOGY CO., LTD.
Address: Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Baoan, Shenzhen, China.

Manufacturer Information


Company Name: SHENZHEN ELECTRON TECHNOLOGY CO., LTD.
Address: Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Baoan, Shenzhen, China.

EUT Information

EUT Name: Briefcase Smart Screen
Model: AP2718T
Brand: ApoloSign
Sample Received Date: January 3, 2024
Sample ID: 6796683
Date of Tested: January 3, 2024 to January 16, 2024


APPLICABLE STANDARDS	
STANDARD	TEST RESULTS
CFR 47 FCC PART 15 SUBPART E ISED RSS-247 Issue 3	Pass

Prepared By:



Denny Huang
Senior Project Engineer

Checked By:



Kebo Zhang
Senior Project Engineer

Approved By:



Stephen Guo
Operations Manager

2. TEST METHODOLOGY

All tests were performed in accordance with the standard CFR 47 FCC PART 15 SUBPART E ISED RSS-247 Issue 3, ANSI C63.10-2013, CFR 47 FCC Part 2, KDB 789033 D02 v02r01, RSS-GEN Issue 5, KDB414788 D01 Radiated Test Site v01, KDB 662911 D01 Multiple Transmitter Output v02r01, KDB 905462 D02 UNII DFS Compliance Procedures New Rules v02, KDB 905462 D03 UNII clients without radar detection New Rules v01r02, KDB 905462 D04 Operational Modes for DFS Testing New Rules v01 and KDB 905462 D06 802 11 Channel Plans New Rules v02.

3. FACILITIES AND ACCREDITATION

Accreditation Certificate	<p>A2LA (Certificate No.: 4102.01) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with A2LA.</p> <p>FCC (FCC Designation No.: CN1187) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. Has been recognized to perform compliance testing on equipment subject to the Commission's Declaration of Conformity (DoC) and Certification rules</p> <p>ISED (Company No.: 21320) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been registered and fully described in a report filed with ISED. The Company Number is 21320 and the test lab Conformity Assessment Body Identifier (CABID) is CN0046.</p> <p>VCCI (Registration No.: G-20192, C-20153, T-20155 and R-20202) UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch. has been assessed and proved to be in compliance with VCCI, the Membership No. is 3793. Facility Name: Chamber D, the VCCI registration No. is G-20192 and R-20202 Shielding Room B, the VCCI registration No. is C-20153 and T-20155</p>
---------------------------	---

Note 1:

All tests measurement facilities use to collect the measurement data are located at Building 10, Innovation Technology Park, No. 1, Li Bin Road, Song Shan Lake Hi-Tech Development Zone Dongguan, 523808, People's Republic of China.

Note 2:

The test anechoic chamber in UL Verification Services (Guangzhou) Co., Ltd. Song Shan Lake Branch had been calibrated and compared to the open field sites and the test anechoic chamber is shown to be equivalent to or worst case from the open field site.

Note 3:

For below 30 MHz, lab had performed measurements at test anechoic chamber and comparing to measurements obtained on an open field site. And these measurements below 30 MHz had been correlated to measurements performed on an OFS.

4. CALIBRATION AND UNCERTAINTY

4.1. MEASURING INSTRUMENT CALIBRATION

The measuring equipment utilized to perform the tests documented in this report has been calibrated in accordance with the manufacturer's recommendations and is traceable to recognized national standards.

4.2. MEASUREMENT UNCERTAINTY

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the apparatus:

Test Item	Uncertainty
Conduction emission	3.62 dB
Radiated Emission (Included Fundamental Emission) (9 kHz ~ 30 MHz)	2.2 dB
Radiated Emission (Included Fundamental Emission) (30 MHz ~ 1 GHz)	4.00 dB
Radiated Emission (Included Fundamental Emission) (1 GHz to 40 GHz)	5.78 dB (1 GHz ~ 18 GHz)
	5.23 dB (18 GHz ~ 26 GHz)
	5.37 dB (26 GHz ~ 40 GHz)
Duty Cycle	±0.028%
Emission Bandwidth and 99% Occupied Bandwidth	±0.0196%
Maximum Conducted Output Power	±0.766 dB
Maximum Power Spectral Density Level	±1.22 dB
Frequency Stability	±2.76%
Dynamic Frequency Selection	±1.01 dB
Conducted Band-edge Compliance	±1.328 dB
Conducted Unwanted Emissions In Non-restricted Frequency Bands	±0.746 dB (9 kHz ~ 1 GHz)
	±1.328dB (1 GHz ~ 26 GHz)
Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

5. EQUIPMENT UNDER TEST

5.1. DESCRIPTION OF EUT

EUT Name	Briefcase Smart Screen
Model	AP2718T
Frequency Band:	5150 MHz to 5250 MHz (U-NII-1) 5 725 MHz to 5 850 MHz (U-NII-3)
Frequency Range:	5180 MHz to 5240 MHz 5 745 MHz to 5 825 MHz
Type of Modulation:	IEEE 802.11a: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11n: OFDM (64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ac: OFDM (256QAM, 64QAM, 16QAM, QPSK, BPSK) IEEE 802.11ax: OFDMA (1024QAM, 256QAM, 64QAM, 16QAM, QPSK, BPSK)
Radio Technology:	IEEE802.11a/ n HT20/n HT40/ ac VHT20/ac VHT40/ac VHT80/ ax HE20/ax HE40/ax HE80
Normal Test Voltage:	AC 120 V, 60 Hz

5.2. CHANNEL LIST

UNII-1 (For Bandwidth=20MHz)		UNII-1 (For Bandwidth=40MHz)		UNII-1 (For Bandwidth=80MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
36	5180	38	5190	42	5210
40	5200	46	5230		
44	5220				
48	5240				

UNII-3 (For Bandwidth=20MHz)		UNII-3 (For Bandwidth=40MHz)		UNII-3 (For Bandwidth=80MHz)	
Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
149	5745	151	5755	155	5775
153	5765	159	5795		
157	5785				
161	5805				
165	5825				

5.3. MAXIMUM POWER

UNII-1 BAND(FCC&ISED)

IEEE Std. 802.11	Frequency (MHz)	Maximum Average Conducted Power (dBm)	Max Average EIRP (dBm)
a	5150 ~ 5250	11.73	14.52
n HT20		11.63	14.41
n HT40		14.86	17.65
ac VHT80		17.81	20.60
ax HE20		13.57	16.36
ax HE40		13.49	16.28
ax HE80		13.35	16.14

UNII-3 BAND(FCC&ISED)

IEEE Std. 802.11	Frequency (MHz)	Maximum Average Conducted Power (dBm)
a	5725 ~ 5850	19.89
n HT20		19.75
n HT40		19.99
ac VHT80		16.12
ax HE20		20.03
ax HE40		19.85
ax HE80		16.41

5.4. TEST CHANNEL CONFIGURATION

UNII-1 Test Channel Configuration		
IEEE Std.	Test Channel Number	Frequency
802.11a	CH 36(Low Channel), CH 40(MID Channel), CH 48(High Channel)	5180 MHz, 5200 MHz, 5240 MHz
802.11n HT20	CH 36(Low Channel), CH 40(MID Channel), CH 48(High Channel)	5180 MHz, 5200 MHz, 5240 MHz
802.11n HT40	CH 38(Low Channel), CH 46(High Channel)	5190 MHz, 5230 MHz
802.11ac VHT80	CH 42(Low Channel)	5210 MHz
802.11ax HE20	CH 36(Low Channel), CH 40(MID Channel), CH 48(High Channel)	5180 MHz, 5200 MHz, 5240 MHz
802.11ax HE40	CH 38(Low Channel), CH 46(High Channel)	5190 MHz, 5230 MHz
802.11ax HE80	CH 42(Low Channel)	5210 MHz

UNII-3 Test Channel Configuration		
IEEE Std.	Test Channel Number	Frequency
802.11a	CH 149(Low Channel), CH 157(MID Channel), CH 165(High Channel)	5745 MHz, 5785 MHz, 5825 MHz
802.11n HT20	CH 149(Low Channel), CH 157(MID Channel), CH 165(High Channel)	5745 MHz, 5785 MHz, 5825 MHz
802.11n HT40	CH 151(Low Channel), CH 159(High Channel)	5755MHz, 5795MHz
802.11ac VHT80	CH 155(Low Channel)	5775 MHz
802.11ax HE20	CH 149(Low Channel), CH 157(MID Channel), CH 165(High Channel)	5745 MHz, 5785 MHz, 5825 MHz
802.11ax HE40	CH 151(Low Channel), CH 159(High Channel)	5755MHz, 5795MHz
802.11ax HE80	CH 155(Low Channel)	5775 MHz

5.5. THE WORSE CASE POWER SETTING PARAMETER

The Worst Case Power Setting Parameter	
Test Software	adb

UNII-1

Mode	Rate	Channel	Soft set value	
			ANT 1	ANT 2
11a	6M	36	8	8
		40	8	8
		48	9	9
11n HT20	MCS0	36	8	8
		40	8	8
		48	9	9
11n HT40	MCS0	38	13	13
		46	14	14
11ac VHT20	MCS0	36	Cover by 11n HT20	
		40		
		48		
11ac VHT40	MCS0	38	Cover by 11n HT40	
		46		
11ac VHT80	MCS0	42	16	16
11ax HE20	MCS0	36	9	9
		40	9	9
		48	11	11
11ax HE40	MCS0	38	10	10
		46	11	11
11ax HE80	MCS0	42	11	11

UNII-3

Mode	Rate	Channel	Soft set value	
			ANT 1	ANT 2
11a	6M	149	14	14
		157	14	14
		165	14	14
11n HT20	MCS0	149	14	14
		157	14	14
		165	14	14
11n HT40	MCS0	151	15	15
		159	15	15
11ac VHT20	MCS0	149	Cover by 11n HT20	
		157		
		165		
11ac VHT40	MCS0	151	Cover by 11n HT40	
		159		
11ac VHT80	MCS0	155	12	12
11ax HE20	MCS0	149	14	14
		157	14	14
		165	14	14
11ax HE40	MCS0	151	14	14
		159	14	14
11ax HE80	MCS0	155	11	11

5.6. WORSE CASE CONFIGURATIONS

The EUT was tested in the following configuration(s):

Controlled in test mode using a software application on the EUT supplied by customer. The application was used to enable a continuous transmission and to select the mode, test channels, bandwidth, data rates as required.

Test channels referring to section 5.4.

Maximum power setting referring to section 5.5.

Worst case Data Rates declared by the customer:

802.11a 20 mode: 6 Mbps
802.11n HT20 mode: MCS0
802.11n HT40 mode: MCS0
802.11ac VHT20 mode: MCS0
802.11ac VHT40 mode: MCS0
802.11ac VHT80 mode: MCS0
802.11ax HE20 mode: MCS0
802.11ax HE40 mode: MCS0
802.11ax HE80 mode: MCS0

802.11ac VHT20 and VHT40 mode are different from 802.11n HT20 and HT40 only in control messages, so for these 4 modes, only 802.11n HT20 and 802.11n HT40 worst case power modes radiated emission test data are recorded in the report.

The EUT has 2 separate antennas which correspond to 2 separate antenna ports. Core 1 and Core 2 correspond to antenna 1 and antenna 2 respectively.

The measured additional path loss was included in any path loss calculations for all RF cable used during tested.

Conducted output power, power spectral density tests separately on each port with all supported SISO & MIMO port combinations.

Radiated emissions tests were performed with the MIMO modes. These were found to be the worst modulation scheme with regards to emissions after preliminary investigations and, as this mode emits the highest conducted output power level, it was deemed to be the worst case.

For 802.11n/ac/ax mode, the EUT support Cyclic Shift Diversity (CDD) and TX Beamforming. The power setting of TX Beamforming mode is reduced 3 by CDD mode. The conducted power of CDD mode is higher than TX Beamforming mode, and the EIRP of CDD is the same as TX Beamforming mode, so we only chose the worst-case mode CDD for final testing.

5.7. DESCRIPTION OF AVAILABLE ANTENNAS

Antenna No.	Frequency Band	Antenna Type	Maximum Antenna Gain (dBi)
1	5150-5850	FPC	2.52
2	5150-5850	FPC	2.79

The EUT support Cyclic Shift Diversity(CDD) mode.

MIMO output power port and MIMO PSD port summing were performed in accordance with KDB 662911 D01. For the CDD results the Directional Gain was calculated in accordance with the following method.

For output power measurements:

Directional gain= $G_{ANT} + \text{Array Gain} = 2.79$ dBi

G_{ANT} : equal to the gain of the antenna having the highest gain

Array Gain = 0 dB (i.e., no array gain) for $N_{ANT} \leq 4$

For power spectral density (PSD) measurements:

Directional gain= $G_{ANT} + \text{Array Gain} = 5.80$ dBi

Array Gain = $10 \log(N_{ANT}/N_{SS})$ dB.

N_{ANT} : number of transmit antennas

N_{SS} : number of spatial streams, The worst case directional gain will occur when $N_{SS} = 1$

IEE Std. 802.11	Transmit and Receive Mode	Description
802.11a	<input checked="" type="checkbox"/> 2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.
802.11n HT20	<input checked="" type="checkbox"/> 2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.
802.11n HT40	<input checked="" type="checkbox"/> 2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.
802.11ac VHT20	<input checked="" type="checkbox"/> 2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.
802.11ac VHT40	<input checked="" type="checkbox"/> 2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.
802.11ac VHT80	<input checked="" type="checkbox"/> 2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.
802.11ax HE20	<input checked="" type="checkbox"/> 2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.
802.11ax HE40	<input checked="" type="checkbox"/> 2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.
802.11ax HE80	<input checked="" type="checkbox"/> 2TX, 2RX	ANT 1 and ANT 2 can be used as transmitting/receiving antenna.
Note: BT&WLAN 2.4G, BT & WLAN 5G, WLAN 2.4G & WLAN 5G can't transmit simultaneously (Declared by client)		

5.8. SUPPORT UNITS FOR SYSTEM TEST

SUPPORT EQUIPMENT

Item	Equipment	Brand Name	Model Name	Remarks
1	Laptop	ThinkPad	X230i	/

I/O CABLES

Cable No	Port	Connector Type	Cable Type	Cable Length(m)	Remarks
1	USB	/	Unshielded	1.0	/
2	USB	/	Unshielded	1.0	/
3	USB	/	Unshielded	1.0	/
4	HDMI	/	Unshielded	1.0	/
5	AC In	/	Unshielded	1.0	/


ACCESSORIES

Item	Accessory	Brand Name	Model Name	Description
/	/	/	/	/

TEST SETUP

The EUT can work in engineering mode with a software through a laptop.

SETUP DIAGRAM FOR TESTS



6. MEASURING EQUIPMENT AND SOFTWARE USED

R&S TS 8997 Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
Power sensor, Power Meter	R&S	OSP120	100921	Mar.31,2023	Mar.30,2024
Vector Signal Generator	R&S	SMBV100A	261637	Oct.12, 2023	Oct.11, 2024
Signal Generator	R&S	SMB100A	178553	Oct.12, 2023	Oct.11, 2024
Signal Analyzer	R&S	FSV40	101118	Oct.12, 2023	Oct.11, 2024
Software					
Description	Manufacturer	Name	Version		
For R&S TS 8997 Test System	Rohde & Schwarz	EMC 32	10.60.10		
Tonsend RF Test System					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due. Date
PXA Signal Analyzer	Keysight	N9030A	MY55410512	Oct.12, 2023	Oct.11, 2024
MXG Vector Signal Generator	Keysight	N5182B	MY56200284	Oct.12, 2023	Oct.11, 2024
MXG Vector Signal Generator	Keysight	N5172B	MY56200301	Oct.12, 2023	Oct.11, 2024
DC power supply	Keysight	E3642A	MY55159130	Oct.12, 2023	Oct.11, 2024
Temperature & Humidity Chamber	SANMOOD	SG-80-CC-2	2088	Oct.12, 2023	Oct.11, 2024
Attenuator	Aglient	8495B	2814a12853	Oct.12, 2023	Oct.11, 2024
RF Control Unit	Tonscend	JS0806-2	23B80620666	April 18, 2023	April 17, 2024
Software					
Description	Manufacturer	Name	Version		
Tonsend SRD Test System	Tonsend	JS1120-3 RF Test System	V3.2.22		

Conducted Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
EMI Test Receiver	R&S	ESR3	101961	Oct.13, 2023	Oct.12, 2024
Two-Line V-Network	R&S	ENV216	101983	Oct.13, 2023	Oct.12, 2024
Artificial Mains Networks	Schwarzbeck	NSLK 8126	8126465	Oct.13, 2023	Oct.12, 2024
Software					
Description	Manufacturer	Name	Version		
Test Software for Conducted Emissions	Farad	EZ-EMC	Ver. UL-3A1		

Radiated Emissions					
Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Due Date
MXE EMI Receiver	KESIGHT	N9038A	MY56400036	Oct.12, 2023	Oct.11, 2024
Hybrid Log Periodic Antenna	TDK	HLP-3003C	130959	Aug.02, 2021	Aug.01, 2024
Preamplifier	HP	8447D	2944A09099	Oct.12, 2023	Oct.11, 2024
EMI Measurement Receiver	R&S	ESR26	101377	Oct.12, 2023	Oct.11, 2024
Horn Antenna	TDK	HRN-0118	130940	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-0118	TRS-305-00067	Oct.12, 2023	Oct.11, 2024
Horn Antenna	Schwarzbeck	BBHA9170	697	July 20, 2021	July 19, 2024
Preamplifier	TDK	PA-02-2	TRS-307-00003	Oct.12, 2023	Oct.11, 2024
Preamplifier	TDK	PA-02-3	TRS-308-00002	Oct.12, 2023	Oct.11, 2024
Loop antenna	Schwarzbeck	1519B	00008	Dec.14, 2021	Dec.13, 2024
Preamplifier	TDK	PA-02-001-3000	TRS-302-00050	Oct.12, 2023	Oct.11, 2024
Highpass Filter	Wainwright	WHKX10-5850-6500-1800-40SS	4	Oct.12, 2023	Oct.11, 2024
Band Reject Filter	Wainwright	WRCJV12-5695-5725-5850-5880-40SS	4	Oct.12, 2023	Oct.11, 2024
Band Reject Filter	Wainwright	WRCJV20-5120-5150-5350-5380-60SS	2	Oct.12, 2023	Oct.11, 2024
Band Reject Filter	Wainwright	WRCJV20-5440-5470-5725-5755-60SS	1	Oct.12, 2023	Oct.11, 2024
Software					
Description			Manufacturer	Name	Version
Test Software for Radiated Emissions			Farad	EZ-EMC	Ver. UL-3A1

7. ANTENNA PORT TEST RESULTS

7.1. ON TIME AND DUTY CYCLE

LIMITS


None; for reporting purposes only.

TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.B.

The zero-span mode on a spectrum analyzer or EMI receiver, if the response time and spacing between bins on the sweep are sufficient to permit accurate measurements of the on and off times of the transmitted signal. Set the center frequency of the instrument to the center frequency of the transmission. Set RBW \geq EBW if possible; otherwise, set RBW to the largest available value. Set VBW \geq RBW. Set detector = peak or average. The zero-span measurement method shall not be used unless both RBW and VBW are $> 50/T$, where T is defined in II.B.1.a), and the number of sweep points across duration T exceeds 100. (For example, if VBW and/or RBW are limited to 3 MHz, then the zero-span method of measuring duty cycle shall not be used if $T \leq 16.7$ microseconds.)

TEST SETUP



TEST ENVIRONMENT

Temperature	24.5 °C	Relative Humidity	45.9%
Atmosphere Pressure	101 kPa	Test Voltage	AC 120 V, 60 Hz

TEST RESULTS

Please refer to section "Test Data" - Appendix G

7.2. 6DB AND 26DB EMISSION BANDWIDTH AND 99% OCCUPIED BANDWIDTH

LIMITS

CFR 47 FCC Part15, Subpart E ISED RSS-247 ISSUE 3		
Test Item	Limit	Frequency Range (MHz)
26 dB Emission Bandwidth	For reporting purposes only.	5150 ~ 5250
6 dB Emission Bandwidth	The minimum 6 dB emission bandwidth shall be 500 kHz.	5725 ~ 5850
99 % Occupied Bandwidth	For reporting purposes only.	5150 ~ 5825 (For ISED)

TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.C1. for 26 dB Emission Bandwidth; section II.C2. for 6 dB Emission Bandwidth; section II.D. for 99 % Occupied Bandwidth.

Connect the EUT to the spectrum analyser and use the following settings:

Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	For 6 dB Emission Bandwidth: RBW=100 kHz For 26 dB Emission bandwidth: approximately 1 % of the EBW. For 99 % Occupied Bandwidth: approximately 1 % ~ 5 % of the OBW.
VBW	For 6 dB Bandwidth: $\geq 3 \times \text{RBW}$ For 26 dB Bandwidth: $> 3 \times \text{RBW}$ For 99 % Bandwidth: $> 3 \times \text{RBW}$
Trace	Max hold
Sweep	Auto couple

a) Use the 99 % power bandwidth function of the instrument, allow the trace to stabilize and report the measured bandwidth.

b) Allow the trace to stabilize and measure the maximum width of the emission that is constrained by the frequencies associated with the two outermost amplitude points (upper and lower frequencies) that are attenuated by 6/26 dB relative to the maximum level measured in the fundamental emission.

Calculation for 99 % Bandwidth of UNII-2C and UNII-3 Straddle Channel:

For Example: Fundamental Frequency: 5720 MHz

99 % OBW: 21.00 MHz

Turning Frequency: 5725 MHz

99 % Bandwidth of UNII-2C Band Portion = $(5725 - (5720 - (21.00/2))) = 15.50 \text{ MHz}$

99 % Bandwidth of UNII-3 Band Portion = $(5720 + (21.00/2) - 5725) = 5.50 \text{ MHz}$

Calculation for 26 dB Bandwidth of UNII-2C Straddle Channel:

For Example: Fundamental frequency: 5720 MHz

26 dB BW: 20.00 MHz

FL: 5710.16 MHz

FH: 5730.16 MHz

Turning Frequency: 5725 MHz

26 dB Bandwidth of UNII-2C Band Portion = $5725 - 5710.16 = 14.84$ MHz

Calculation for 6dB Bandwidth of UNII-3 Straddle Channel:

For Example: Fundamental frequency: 5720 MHz

6 dB BW: 16.44 MHz


FL: 5711.76 MHz

FH: 5728.2 MHz

Turning Frequency: 5725 MHz

6 dB Bandwidth of UNII-3 band Portion = $5728.2 - 5725 = 3.2$ MHz

TEST SETUP



TEST ENVIRONMENT

Temperature	24.5 °C	Relative Humidity	45.9%
Atmosphere Pressure	101 kPa	Test Voltage	AC 120 V, 60 Hz

TEST RESULTS

Please refer to section "Test Data" - Appendix A&B&C

7.3. CONDUCTED OUTPUT POWER

LIMITS

CFR 47 FCC Part15, Subpart E		
Test Item	Limit	Frequency Range (MHz)
Conducted Output Power	<input type="checkbox"/> Outdoor Access Point: 1 W (30 dBm) <input type="checkbox"/> Indoor Access Point: 1 W (30 dBm) <input type="checkbox"/> Fixed Point-To-Point Access Points: 1 W (30 dBm) <input checked="" type="checkbox"/> Client Devices: 250 mW (24 dBm)	5150 ~ 5250
	Shall not exceed 1 Watt (30 dBm).	5725 ~ 5850

ISED RSS-247 ISSUE 3		
Test Item	Limit	Frequency Range (MHz)
Conducted Output Power or e.i.r.p.	The maximum e.i.r.p. shall not exceed 200 mW (23 dBm) or $10 + 10 \log_{10}B$, dBm, whichever power is less. B is the 99 % emission bandwidth in megahertz.	5150 ~ 5250
	Shall not exceed 1 Watt (30 dBm). The e.i.r.p. shall not exceed 4 W	5725 ~ 5850

Note:

The above limits are based upon the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, the maximum conducted output power shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.E.

Method SA-2 (trace averaging across ON and OFF times of the EUT transmissions, followed by duty cycle correction.):

- (a) Measure the duty cycle D of the transmitter output signal.
- (b) Set span to encompass the entire 26 dB EBW or 99% OBW of the signal.
- (c) Set RBW = 1 MHz.
- (d) Set VBW \geq 3 MHz.
- (e) Number of points in sweep \geq $[2 \times \text{span} / \text{RBW}]$. (This gives bin-to-bin spacing \leq RBW / 2, so that narrowband signals are not lost between frequency bins.)
- (f) Sweep time = auto.
- (g) Detector = RMS (i.e., power averaging), if available. Otherwise, use sample detector mode.
- (h) Do not use sweep triggering. Allow the sweep to "free run."
- (i) Trace average at least 100 traces in power averaging (rms) mode; however, the number of traces to be averaged shall be increased above 100 as needed such that the average accurately represents the true average over the ON and OFF periods of the transmitter.
- (j) Compute power by integrating the spectrum across the 26 dB EBW or 99% OBW of the signal using the instrument's band power measurement function with band limits set equal to the EBW or OBW band edges. If the instrument does not have a band power function, then sum the spectrum levels (in power units) at 1 MHz intervals extending across the 26 dB EBW or 99% OBW of the spectrum.

k) Add $[10 \log (1 / D)]$, where D is the duty cycle, to the measured power to compute the average power during the actual transmission times (because the measurement represents an average over both the ON and OFF times of the transmission). For example, add $[10 \log (1 / 0.25)] = 6 \text{ dB}$ if the duty cycle is 25%.

Method PM (Measurement using an RF average power meter):

(i) Measurements may be performed using a wideband RF power meter with a thermocouple detector or equivalent if all of the following conditions are satisfied:

a. The EUT is configured to transmit continuously or to transmit with a constant duty cycle.
 b. At all times when the EUT is transmitting, it must be transmitting at its maximum power control level.

c. The integration period of the power meter exceeds the repetition period of the transmitted signal by at least a factor of five.


(ii) If the transmitter does not transmit continuously, measure the duty cycle, x, of the transmitter output signal as described in II.B.

(iii) Measure the average power of the transmitter. This measurement is an average over both the on and off periods of the transmitter.

(iv) Adjust the measurement in dBm by adding $10 \log (1/x)$ where x is the duty cycle (e.g., $10 \log (1/0.25)$ if the duty cycle is 25 %).

Note: Method SA-2 was used for straddle channel output power test, and Method PM was used for testing rest channels

TEST SETUP



TEST ENVIRONMENT

Temperature	24.5 °C	Relative Humidity	45.9%
Atmosphere Pressure	101 kPa	Test Voltage	AC 120 V, 60 Hz

TEST RESULTS

Please refer to section "Test Data" - Appendix D

7.4. POWER SPECTRAL DENSITY

LIMITS

CFR 47 FCC Part15, Subpart E		
Test Item	Limit	Frequency Range (MHz)
Power Spectral Density	<input type="checkbox"/> Outdoor Access Point: 17 dBm/MHz <input type="checkbox"/> Indoor Access Point: 17 dBm/MHz <input type="checkbox"/> Fixed Point-To-Point Access Points: 17 dBm/MHz <input checked="" type="checkbox"/> Client Devices: 11 dBm/MHz	5150 ~ 5250
	30 dBm/500kHz	5725 ~ 5850

ISED RSS-247 ISSUE 3		
Test Item	Limit	Frequency Range (MHz)
Power Spectral Density	The e.i.r.p. spectral density shall not exceed 10 dBm in any 1.0 MHz band.	5150 ~ 5250
	30 dBm / 500 kHz	5725 ~ 5850

Note:

The above limits are based upon the maximum antenna gain does not exceed 6 dBi. If transmitting antennas of directional gain greater than 6 dBi are used, maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

TEST PROCEDURE

Refer to KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.F.

Connect the EUT to the spectrum analyzer and use the following settings:

For U-NII-1, U-NII-2A and U-NII-2C band:

Center Frequency	The center frequency of the channel under test
Detector	RMS
RBW	1 MHz
VBW	$\geq 3 \times \text{RBW}$
Span	Encompass the entire emissions bandwidth (EBW) of the signal
Trace	Max hold
Sweep time	Auto

For U-NII-3:


Center Frequency	The center frequency of the channel under test
Detector	RMS
RBW	500 kHz
VBW	$\geq 3 \times \text{RBW}$

Span	Encompass the entire emissions bandwidth (EBW) of the signal
Trace	Max hold
Sweep time	Auto

Allow trace to fully stabilize and use the peak search function on the instrument to find the peak of the spectrum and record its value.

Add $10 \log(1/x)$, where x is the duty cycle, to the peak of the spectrum, the result is the Maximum PSD over 1 MHz / 500 kHz reference bandwidth.

TEST SETUP



TEST ENVIRONMENT

Temperature	24.5 °C	Relative Humidity	45.9%
Atmosphere Pressure	101 kPa	Test Voltage	AC 120 V, 60 Hz

TEST RESULTS

Please refer to section "Test Data" - Appendix E

7.5. FREQUENCY STABILITY

LIMITS

The frequency of the carrier signal shall be maintained within band of operation.

TEST PROCEDURE

1. The EUT was placed inside an environmental chamber as the temperature in the chamber was varied between -30 °C ~ 85 °C (declared by customer).
2. The temperature was incremented by 10 °C intervals and the unit allowed to stabilize at each temperature before each measurement. The center frequency of the transmitting channel was evaluated at each temperature and the frequency deviation from the channel's center frequency was recorded.
3. The primary supply voltage is varied from 85 % to 115 % of the nominal value for non hand-carried battery and AC powered equipment. For hand-carried, battery-powered equipment, primary supply voltage is reduced to the battery operating end point which shall be specified by the manufacturer.

Connect the EUT to the spectrum analyzer and use the following settings:


Center Frequency	The center frequency of the channel under test
Detector	Peak
RBW	10 kHz
VBW	$\geq 3 \times \text{RBW}$
Span	Encompass the entire emissions bandwidth (EBW) of the signal
Trace	Max hold
Sweep time	Auto

4. While maintaining a constant temperature inside the environmental chamber, turn the EUT on and record the operating frequency at startup, and at 2 minutes, 5minutes, and 10 minutes after the EUT is energized.
5. Allow the trace to stabilize, find the peak value of the power envelope and record the frequency, then calculated the frequency drift.

TEST ENVIRONMENT

	Normal Test Conditions	Extreme Test Conditions
Relative Humidity	20 % ~ 75 %	/
Atmospheric Pressure	100 kPa ~ 102 kPa	/
Temperature	T _N (Normal Temperature): 25.1 °C	T _L (Low Temperature): 0 °C
		T _H (High Temperature): 40 °C
Supply Voltage	V _N (Normal Voltage): AC 120 V	V _L (Low Voltage): AC 102 V
		V _H (High Voltage): AC 138 V

TEST SETUP



TEST ENVIRONMENT

Temperature	24.5 °C	Relative Humidity	45.9%
Atmosphere Pressure	101 kPa	Test Voltage	AC 120 V, 60 Hz

TEST RESULTS

Please refer to section "Test Data" - Appendix F

8. RADIATED TEST RESULTS

LIMITS

Refer to CFR 47 FCC §15.205, §15.209 and §15.407 (b).

Refer to ISED RSS-GEN Clause 8.9, Clause 8.10 and ISED RSS-247 6.2.

Radiation Disturbance Test Limit for FCC (Class B) (9 kHz ~ 1 GHz)

Emissions radiated outside of the specified frequency bands above 30 MHz			
Frequency Range (MHz)	Field Strength Limit (uV/m) at 3 m	Field Strength Limit (dBuV/m) at 3 m	
		Quasi-Peak	
30 - 88	100	40	
88 - 216	150	43.5	
216 - 960	200	46	
Above 960	500	54	
Above 1000	500	Peak	Average
		74	54

FCC Emissions radiated outside of the specified frequency bands below 30 MHz		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009-0.490	2400/F(kHz)	300
0.490-1.705	24000/F(kHz)	30
1.705-30.0	30	30

ISED General field strength limits at frequencies below 30 MHz

Table 6 – General field strength limits at frequencies below 30 MHz		
Frequency	Magnetic field strength (H-Field) (µA/m)	Measurement distance (m)
9 - 490 kHz ^{Note 1}	6.37/F (F in kHz)	300
490 - 1705 kHz	63.7/F (F in kHz)	30
1.705 - 30 MHz	0.08	30

Note 1: The emission limits for the ranges 9-90 kHz and 110-490 kHz are based on measurements employing a linear average detector.

ISED Restricted bands refer to ISED RSS-GEN Clause 8.10

MHz	MHz	GHz
0.090 - 0.110	149.9 - 150.05	9.0 - 9.2
0.495 - 0.505	156.52475 - 156.52525	9.3 - 9.5
2.1735 - 2.1905	156.7 - 156.9	10.6 - 12.7
3.020 - 3.026	162.0125 - 167.17	13.25 - 13.4
4.125 - 4.128	167.72 - 173.2	14.47 - 14.5
4.17725 - 4.17775	240 - 285	15.35 - 16.2
4.20725 - 4.20775	322 - 335.4	17.7 - 21.4
5.677 - 5.683	369.9 - 410	22.01 - 23.12
6.215 - 6.218	608 - 614	23.6 - 24.0
6.26775 - 6.26825	960 - 1427	31.2 - 31.8
6.31175 - 6.31225	1435 - 1626.5	36.43 - 36.5
8.291 - 8.294	1645.5 - 1646.5	Above 38.6
8.362 - 8.366	1660 - 1710	
8.37625 - 8.38675	1718.8 - 1722.2	
8.41425 - 8.41475	2200 - 2300	
12.29 - 12.293	2310 - 2390	
12.51975 - 12.52025	2483.5 - 2500	
12.57675 - 12.57725	2655 - 2900	
13.36 - 13.41	3260 - 3267	
16.42 - 16.423	3332 - 3339	
16.80475 - 16.80525	3345.8 - 3358	
16.80425 - 16.80475	3500 - 4400	
25.5 - 25.67	4500 - 5150	
37.5 - 38.25	5350 - 5480	
73 - 74.6	7250 - 7750	
74.8 - 75.2	8025 - 8500	
108 - 138		

Note 1: Certain frequency bands listed in table 7 and in bands above 38.6 GHz are designated for licence-exempt applications. These frequency bands and the requirements that apply to related devices are set out in the 200 and 300 series of RSSs.

FCC Restricted bands of operation refer to FCC §15.205 (a):

MHz	MHz	MHz	GHz
0.090-0.110	16.42-16.423	399.9-410	4.5-5.15
¹ 0.495-0.505	16.69475-16.69525	608-614	5.35-5.46
2.1735-2.1905	16.80425-16.80475	960-1240	7.25-7.75
4.125-4.128	25.5-25.67	1300-1427	8.025-8.5
4.17725-4.17775	37.5-38.25	1435-1626.5	9.0-9.2
4.20725-4.20775	73-74.6	1645.5-1646.5	9.3-9.5
6.215-6.218	74.8-75.2	1660-1710	10.6-12.7
6.26775-6.26825	108-121.94	1718.8-1722.2	13.25-13.4
6.31175-6.31225	123-138	2200-2300	14.47-14.5
8.291-8.294	149.9-150.05	2310-2390	15.35-16.2
8.362-8.366	156.52475-156.52525	2483.5-2500	17.7-21.4
8.37625-8.38675	156.7-156.9	2690-2900	22.01-23.12
8.41425-8.41475	162.0125-167.17	3260-3267	23.6-24.0
12.29-12.293	167.72-173.2	3332-3339	31.2-31.8
12.51975-12.52025	240-285	3345.8-3358	36.43-36.5
12.57675-12.57725	322-335.4	3600-4400	(²)
13.36-13.41			

Note: ¹Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.
²Above 38.6c

Limits of unwanted/undesirable emission out of the restricted bands refer to CFR 47 FCC §15.407 (b) and ISSED RSS-247 6.2.

LIMITS OF RADIATED EMISSION MEASUREMENT (Above 1GHz)		
Frequency Range (MHz)	EIRP Limit	Field Strength Limit (dBuV/m) at 3 m
5150~5250 MHz	PK: -27 (dBm/MHz)	PK:68.2(dBμV/m)
5725~5850 MHz	PK: -27 (dBm/MHz) *1 PK: 10 (dBm/MHz) *2 PK: 15.6 (dBm/MHz) *3 PK: 27 (dBm/MHz) *4	PK: 68.2(dBμV/m) *1 PK: 105.2 (dBμV/m) *2 PK: 110.8(dBμV/m) *3 PK: 122.2 (dBμV/m) *4
Note: *1 beyond 75 MHz or more above of the band edge. *2 below the band edge increasing linearly to 10 dBm/MHz at 25 MHz above. *3 below the band edge increasing linearly to a level of 15.6 dBm/MHz at 5 MHz above. *4 from 5 MHz above or below the band edge increasing linearly to a level of 27 dBm/MHz at the band edge.		

TEST PROCEDURE

Below 30 MHz

The setting of the spectrum analyzer

RBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
VBW	200 Hz (From 9 kHz to 0.15 MHz)/ 9 kHz (From 0.15 MHz to 30 MHz)
Sweep	Auto

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.4.
2. The EUT was arranged to its worst case and then turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both Horizontal, Face-on and Face-off polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a 1 m height antenna tower.
5. The radiated emission limits are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9-90 kHz, 110-490 kHz and above 1000 MHz Radiated emission limits in these three bands are based on measurements employing an average detector.
6. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak and average detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak and average detector and reported.
7. Although these tests were performed other than open field site, adequate comparison measurements were confirmed against 30m open field site. Therefore sufficient tests were made to demonstrate that the alternative site produces results that correlate with the ones of tests made in an open field site based on KDB 414788.
8. The limits in CFR 47, Part 15, Subpart C, paragraph 15.209 (a), are identical to those in RSS-GEN Section 8.9, Table 6, since the measurements are performed in terms of magnetic field strength and converted to electric field strength levels (as reported in the table) using the free space impedance of 377Ω . For example, the measurement frequency X kHz resulted in a level of Y dBuV/m, which is equivalent to $Y-51.5 = Z$ dBuA/m, which has the same margin, W dB, to the corresponding RSS-GEN Table 6 limit as it has to be 15.209(a) limit.

Below 1 GHz and above 30 MHz

The setting of the spectrum analyzer

RBW	120 kHz
VBW	300 kHz
Sweep	Auto
Detector	Peak/QP
Trace	Max hold

1. The testing follows the guidelines in ANSI C63.10-2013 clause 6.5.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 80 cm above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement below 1 GHz, the initial step in collecting conducted emission data is a spectrum analyzer peak detector mode pre-scanning the measurement frequency range. Significant peaks are then marked and then Quasi Peak detector mode re-measured. If the emission level of the EUT measured by the peak detector is 3 dB lower than the applicable limit, the peak emission level will be reported. Otherwise, the emission measurement will be repeated using the quasi-peak detector and reported.

Above 1 GHz

The setting of the spectrum analyzer

RBW	1 MHz
VBW	PEAK: 3 MHz AVG: see note 6
Sweep	Auto
Detector	Peak
Trace	Max hold

1. The testing follows the guidelines in KDB 789033 D02 General U-NII Test Procedures New Rules v02r01 section II.G.3 ~ II.G.6.
2. The EUT was arranged to its worst case and then tune the antenna tower (from 1 m to 4 m) and turntable (from 0 degree to 360 degrees) to find the maximum reading. A pre-amp and a high pass filter are used for the test in order to get better signal level. Both horizontal and vertical polarizations of the antenna are set to make the measurement.
3. The EUT was placed on a turntable with 1.5 m above ground.
4. The EUT was set 3 meters from the interference receiving antenna, which was mounted on the top of a variable height antenna tower.
5. For measurement above 1 GHz, the emission measurement will be measured by the peak detector. This peak level, once corrected, must comply with the limit specified in Section 15.209.
6. For measurements above 1 GHz the resolution bandwidth is set to 1 MHz, then the video bandwidth is set to 3 MHz for peak measurements and 1 MHz resolution bandwidth with 1/T video bandwidth with peak detector for average measurements. For the Duty Cycle please refer to clause 7.1. ON TIME AND DUTY CYCLE.

Note: The EUT was fully exercised with external accessories during the test. In the case of multiple accessory external ports, an external accessory shall be connected to one of each type of port.

For Restricted Bandedge:

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. PK=Peak: Peak detector.
4. AV=Average: $VBW=1/Ton$, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.1.
6. Only the worst data was recorded, if it complies with the limit, the other emissions deemed to comply with the limit.
7. Both horizontal and vertical have been tested, only the worst data was recorded in the report.
8. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (9 kHz ~ 30 MHz):

Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All 3 polarizations (Horizontal, Face-on and Face-off) of the loop antenna had been tested, but only the worst data recorded in the report.
4. All modes have been tested, but only the worst data was recorded in the report.
5. $dBuA/m = dBuV/m - 20\log_{10}[120\pi] = dBuV/m - 51.5$

For Radiate Spurious Emission (30 MHz ~ 1 GHz):

Note:

1. Result Level = Read Level + Correct Factor.
2. If the peak values are less than the QP limit, the QP result is deemed to comply with QP limit.
3. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (1 GHz ~ 7 GHz):

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.1.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for Band reject filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27 dBm/MHz (68.2 dBuV/m) limit.
9. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious Emission (7 GHz ~ 18 GHz):

Note:

1. Peak Result = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. AVG: $VBW=1/Ton$, where: Ton is the transmitting duration.
5. For the transmitting duration, please refer to clause 7.1.
6. Filter losses were only considered in the spurious frequency bands and the authorized band was not corrected for High Pass Filter losses.
7. Proper operation of the transmitter prior to adding the filter to the measurement chain.
8. Since non-restricted band peak emissions are less than the average limit, they also comply with the -27 dBm/MHz (68.2 dBuV/m) limit.
9. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (18 GHz ~ 26 GHz):

Note:


1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All modes have been tested, but only the worst data was recorded in the report.

For Radiate Spurious emission (26 GHz ~ 40 GHz):


Note:

1. Measurement = Reading Level + Correct Factor.
2. If the peak values are less than the average limit of 54 dBuV/m, the average result is deemed to comply with average limit.
3. Peak: Peak detector.
4. All modes have been tested, but only the worst data was recorded in the report.


TEST SETUP



Below 1 GHz and above 30 MHz



Above 1 GHz




TEST ENVIRONMENT

Temperature	24.5 °C	Relative Humidity	57%
Atmosphere Pressure	101 kPa	Test Voltage	AC 120 V, 60 Hz

TEST RESULTS


8.1. RESTRICTED BANDEDGE

Test Mode:	802.11a 20 PK	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5146.050	32.26	40.27	72.53	74.00	-1.47	peak
2	5150.000	32.00	40.27	72.27	74.00	-1.73	peak

Test Mode:	802.11a 20 AV	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5146.050	10.87	40.27	51.14	54.00	-2.86	AVG
2	5150.000	12.34	40.27	52.61	54.00	-1.39	AVG

Test Mode:	802.11a 20 PK	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	17.34	40.27	57.61	74.00	-16.39	peak
2	5350.000	16.44	40.49	56.93	74.00	-17.07	peak

Test Mode:	802.11a 20 AV	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	8.35	40.27	48.62	54.00	-5.38	AVG
2	5350.000	8.44	40.49	48.93	54.00	-5.07	AVG

Test Mode:	802.11a 20 PK	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5627.030	18.36	41.00	59.36	68.20	-8.84	peak
2	5725.000	42.62	41.27	83.89	122.20	-38.31	peak

Test Mode:	802.11a 20 PK	Frequency(MHz):	5825
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	39.10	41.60	80.70	122.20	-41.50	peak
2	5951.490	18.83	41.87	60.70	68.20	-7.50	peak

Test Mode:	802.11n HT20 PK	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	31.30	40.27	71.57	74.00	-2.43	peak

Test Mode:	802.11n HT20 AV	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	7.12	40.27	47.39	54.00	-6.61	AVG

Test Mode:	802.11n HT20 PK	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	20.48	40.27	60.75	74.00	-13.25	peak
2	5350.000	20.95	40.49	61.44	74.00	-12.56	peak

Test Mode:	802.11n HT20 AV	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	8.85	40.27	49.12	54.00	-4.88	AVG
2	5350.000	9.18	40.49	49.67	54.00	-4.33	AVG

Test Mode:	802.11n HT20 PK	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5643.350	19.00	41.04	60.04	68.20	-8.16	peak
2	5725.000	47.85	41.27	89.12	122.20	-33.08	peak

Test Mode:	802.11n HT20 PK	Frequency(MHz):	5825
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	38.11	41.60	79.71	122.20	-42.49	peak
2	5927.760	19.50	41.81	61.31	68.20	-6.89	peak

Test Mode:	802.11n HT40 PK	Frequency(MHz):	5190
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5145.320	31.59	40.27	71.86	74.00	-2.14	peak
2	5150.000	28.18	40.27	68.45	74.00	-5.55	peak

Test Mode:	802.11n HT40 AV	Frequency(MHz):	5190
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5145.320	8.60	40.27	48.87	54.00	-5.13	AVG
2	5150.000	10.30	40.27	50.57	54.00	-3.43	AVG

Test Mode:	802.11n HT40 PK	Frequency(MHz):	5230
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5146.080	26.08	40.27	66.35	74.00	-7.65	peak
2	5150.000	24.79	40.27	65.06	74.00	-8.94	peak
3	5350.000	23.62	40.49	64.11	74.00	-9.89	peak

Test Mode:	802.11n HT40 AV	Frequency(MHz):	5230
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5146.080	10.48	40.27	50.75	54.00	-3.25	AVG
2	5150.000	10.58	40.27	50.85	54.00	-3.15	AVG
3	5350.000	10.05	40.49	50.54	54.00	-3.46	AVG

Test Mode:	802.11n HT40 PK	Frequency(MHz):	5755
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5647.500	24.22	41.06	65.28	68.20	-2.92	peak
2	5725.000	43.08	41.27	84.35	122.20	-37.85	peak

Test Mode:	802.11n HT40 PK	Frequency(MHz):	5795
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	33.25	41.60	74.85	122.20	-47.35	peak
2	5924.790	20.35	41.79	62.14	68.35	-6.21	peak
3	5932.150	19.63	41.82	61.45	68.20	-6.75	peak

Test Mode:	802.11ac VHT80 PK	Frequency(MHz):	5210
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5147.010	32.70	40.27	72.97	74.00	-1.03	peak
2	5150.000	28.09	40.27	68.36	74.00	-5.64	peak

Test Mode:	802.11ac VHT80 AV	Frequency(MHz):	5210
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5147.010	11.26	40.27	51.53	54.00	-2.47	AVG
2	5150.000	11.88	40.27	52.15	54.00	-1.85	AVG

Test Mode:	802.11ac VHT80 PK	Frequency(MHz):	5775
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5627.200	22.52	41.00	63.52	68.20	-4.68	peak
2	5725.000	30.08	41.27	71.35	122.20	-50.85	peak
3	5850.000	26.99	41.60	68.59	122.20	-53.61	peak
4	5930.000	23.64	41.81	65.45	68.20	-2.75	peak

Test Mode:	802.11ax HE20 PK	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5146.780	32.58	40.27	72.85	74.00	-1.15	peak
2	5150.000	32.31	40.27	72.58	74.00	-1.42	peak

Test Mode:	802.11ax HE20 AV	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5146.780	11.70	40.27	51.97	54.00	-2.03	AVG
2	5150.000	12.29	40.27	52.56	54.00	-1.44	AVG

Test Mode:	802.11ax HE20 PK	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5144.160	24.28	40.27	64.55	74.00	-9.45	peak
2	5150.000	23.75	40.27	64.02	74.00	-9.98	peak
3	5350.000	23.21	40.49	63.70	74.00	-10.30	peak
4	5353.440	23.67	40.50	64.17	74.00	-9.83	peak

Test Mode:	802.11ax HE20 AV	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5144.160	10.68	40.27	50.95	54.00	-3.05	AVG
2	5150.000	11.27	40.27	51.54	54.00	-2.46	AVG
3	5350.000	10.75	40.49	51.24	54.00	-2.76	AVG
4	5353.440	10.41	40.50	50.91	54.00	-3.09	AVG

Test Mode:	802.11ax HE20 PK	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5646.920	21.85	41.06	62.91	68.20	-5.29	peak
2	5725.000	50.53	41.27	91.80	122.20	-30.40	peak

Test Mode:	802.11ax HE20 PK	Frequency(MHz):	5825
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	45.48	41.60	87.08	122.20	-35.12	peak
2	5932.800	20.43	41.82	62.25	68.20	-5.95	peak

Test Mode:	802.11ax HE40 PK	Frequency(MHz):	5190
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5147.510	32.60	40.28	72.88	74.00	-1.12	peak
2	5150.000	30.45	40.27	70.72	74.00	-3.28	peak

Test Mode:	802.11ax HE40 AV	Frequency(MHz):	5190
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5147.510	9.64	40.28	49.92	54.00	-4.08	AVG
2	5150.000	10.71	40.27	50.98	54.00	-3.02	AVG

Test Mode:	802.11ax HE40 PK	Frequency(MHz):	5230
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	28.47	40.27	68.74	74.00	-5.26	peak
2	5350.000	25.87	40.49	66.36	74.00	-7.64	peak

Test Mode:	802.11ax HE40 AV	Frequency(MHz):	5230
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5150.000	11.62	40.27	51.89	54.00	-2.11	AVG
2	5350.000	10.33	40.49	50.82	54.00	-3.18	AVG

Test Mode:	802.11ax HE40 PK	Frequency(MHz):	5755
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5725.000	45.20	41.27	86.47	122.20	-35.73	peak
2	5641.230	26.10	41.04	67.14	68.20	-1.06	peak

Test Mode:	802.11ax HE40 PK	Frequency(MHz):	5795
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5850.000	43.51	41.60	85.11	122.20	-37.09	peak
2	5939.280	22.41	41.84	64.25	68.20	-3.95	peak

Test Mode:	802.11ax HE80 PK	Frequency(MHz):	5210
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5146.220	27.79	40.27	68.06	74.00	-5.94	peak
2	5150.000	26.97	40.27	67.24	74.00	-6.76	peak

Test Mode:	802.11ax HE80 AV	Frequency(MHz):	5210
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5146.220	10.54	40.27	50.81	54.00	-3.19	AVG
2	5150.000	11.14	40.27	51.41	54.00	-2.59	AVG


Test Mode:	802.11ax HE80 PK	Frequency(MHz):	5755
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	5638.800	23.23	41.03	64.26	68.20	-3.94	peak
2	5725.000	31.21	41.27	72.48	122.20	-49.72	peak
3	5850.000	28.05	41.60	69.65	122.20	-52.55	peak
4	5934.000	23.99	41.82	65.81	68.20	-2.39	peak


8.2. SPURIOUS EMISSIONS (1 GHZ ~ 7 GHZ)

Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1588.000	48.29	-12.42	35.87	74.00	-38.13	peak
2	3364.000	44.10	-6.16	37.94	74.00	-36.06	peak
3	4768.000	42.43	-1.07	41.36	74.00	-32.64	peak
4	5134.000	47.92	0.00	47.92	74.00	-26.08	peak
5	5926.000	39.82	1.64	41.46	74.00	-32.54	peak
6	6970.000	38.12	6.05	44.17	74.00	-29.83	peak

Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1570.000	48.49	-12.48	36.01	74.00	-37.99	peak
2	2050.000	47.89	-10.80	37.09	74.00	-36.91	peak
3	3364.000	46.51	-6.16	40.35	74.00	-33.65	peak
4	4354.000	44.26	-2.82	41.44	74.00	-32.56	peak
5	5122.000	45.07	-0.02	45.05	74.00	-28.95	peak
6	6664.000	38.60	4.54	43.14	74.00	-30.86	peak

Test Mode:	802.11a 20	Frequency(MHz):	5200
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3358.000	43.99	-6.17	37.82	74.00	-36.18	peak
2	3886.000	43.20	-4.79	38.41	74.00	-35.59	peak
3	4930.000	46.10	-0.43	45.67	74.00	-28.33	peak
4	5128.000	50.09	0.00	50.09	74.00	-23.91	peak
5	5410.000	44.90	0.32	45.22	74.00	-28.78	peak
6	6478.000	43.33	3.64	46.97	74.00	-27.03	peak

Test Mode:	802.11a 20	Frequency(MHz):	5200
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1240.000	50.08	-13.91	36.17	74.00	-37.83	peak
2	1576.000	49.05	-12.46	36.59	74.00	-37.41	peak
3	4552.000	41.67	-1.93	39.74	74.00	-34.26	peak
4	5128.000	44.48	0.00	44.48	74.00	-29.52	peak
5	5734.000	40.61	1.08	41.69	74.00	-32.31	peak
6	6790.000	38.62	5.15	43.77	74.00	-30.23	peak

Test Mode:	802.11a 20	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1246.000	50.05	-13.88	36.17	74.00	-37.83	peak
2	4354.000	43.33	-2.82	40.51	74.00	-33.49	peak
3	4894.000	44.08	-0.57	43.51	74.00	-30.49	peak
4	5122.000	48.30	-0.02	48.28	74.00	-25.72	peak
5	5416.000	45.05	0.32	45.37	74.00	-28.63	peak
6	6478.000	42.17	3.64	45.81	74.00	-28.19	peak

Test Mode:	802.11a 20	Frequency(MHz):	5240
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1240.000	50.06	-13.91	36.15	74.00	-37.85	peak
2	1726.000	50.09	-11.97	38.12	74.00	-35.88	peak
3	3352.000	47.50	-6.19	41.31	74.00	-32.69	peak
4	4492.000	42.92	-2.19	40.73	74.00	-33.27	peak
5	5128.000	42.70	0.00	42.70	74.00	-31.30	peak
6	6838.000	38.33	5.40	43.73	74.00	-30.27	peak

Test Mode:	802.11a 20	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	3388.000	45.96	-6.10	39.86	74.00	-34.14	peak
2	4936.000	44.48	-0.40	44.08	74.00	-29.92	peak
3	5590.000	43.63	0.68	44.31	74.00	-29.69	peak
4	5746.000	49.17	1.12	50.29	74.00	-23.71	peak
5	5908.000	47.28	1.59	48.87	74.00	-25.13	peak
6	6874.000	37.94	5.57	43.51	74.00	-30.49	peak

Test Mode:	802.11a 20	Frequency(MHz):	5745
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1234.000	49.99	-13.94	36.05	74.00	-37.95	peak
2	4114.000	43.69	-3.94	39.75	74.00	-34.25	peak
3	4888.000	41.20	-0.60	40.60	74.00	-33.40	peak
4	5710.000	45.23	1.02	46.25	74.00	-27.75	peak
5	5746.000	48.68	1.12	49.80	74.00	-24.20	peak
6	6838.000	37.39	5.40	42.79	74.00	-31.21	peak

Test Mode:	802.11a 20	Frequency(MHz):	5785
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	2578.000	44.61	-8.26	36.35	74.00	-37.65	peak
2	4636.000	41.59	-1.59	40.00	74.00	-34.00	peak
3	5704.000	43.08	1.00	44.08	74.00	-29.92	peak
4	5782.000	48.46	1.23	49.69	74.00	-24.31	peak
5	5884.000	42.75	1.52	44.27	74.00	-29.73	peak
6	6874.000	37.97	5.57	43.54	74.00	-30.46	peak

Test Mode:	802.11a 20	Frequency(MHz):	5785
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1588.000	51.20	-12.42	38.78	74.00	-35.22	peak
2	3400.000	46.95	-6.08	40.87	74.00	-33.13	peak
3	5704.000	43.53	1.00	44.53	74.00	-29.47	peak
4	5782.000	48.42	1.23	49.65	74.00	-24.35	peak
5	5878.000	42.30	1.51	43.81	74.00	-30.19	peak
6	6874.000	37.69	5.57	43.26	74.00	-30.74	peak

Test Mode:	802.11a 20	Frequency(MHz):	5825
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1438.000	49.94	-13.00	36.94	74.00	-37.06	peak
2	4450.000	42.65	-2.37	40.28	74.00	-33.72	peak
3	5668.000	42.27	0.91	43.18	74.00	-30.82	peak
4	5830.000	48.76	1.36	50.12	74.00	-23.88	peak
5	5884.000	43.00	1.52	44.52	74.00	-29.48	peak
6	6844.000	37.69	5.43	43.12	74.00	-30.88	peak


Test Mode:	802.11a 20	Frequency(MHz):	5825
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	1240.000	51.81	-13.91	37.90	74.00	-36.10	peak
2	1576.000	50.70	-12.46	38.24	74.00	-35.76	peak
3	3400.000	47.97	-6.08	41.89	74.00	-32.11	peak
4	4636.000	42.12	-1.59	40.53	74.00	-33.47	peak
5	5830.000	47.05	1.36	48.41	74.00	-25.59	peak
6	6802.000	38.74	5.21	43.95	74.00	-30.05	peak


8.3. SPURIOUS EMISSIONS (7 GHZ ~ 18 GHZ)

Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8980.000	37.72	10.21	47.93	74.00	-26.07	peak
2	10003.000	37.92	11.77	49.69	74.00	-24.31	peak
3	11785.000	32.79	17.30	50.09	74.00	-23.91	peak
4	12225.000	32.15	17.75	49.90	74.00	-24.10	peak
5	13842.000	28.61	21.49	50.10	74.00	-23.90	peak
6	17989.000	24.62	26.04	50.66	74.00	-23.34	peak

Test Mode:	802.11a 20	Frequency(MHz):	5180
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9354.000	36.27	10.56	46.83	74.00	-27.17	peak
2	10223.000	35.98	12.24	48.22	74.00	-25.78	peak
3	11796.000	32.25	17.32	49.57	74.00	-24.43	peak
4	12698.000	31.39	18.08	49.47	74.00	-24.53	peak
5	13479.000	30.00	20.55	50.55	74.00	-23.45	peak
6	17989.000	24.43	26.04	50.47	74.00	-23.53	peak

Test Mode:	802.11a 20	Frequency(MHz):	5200
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9332.000	37.83	10.54	48.37	74.00	-25.63	peak
2	11059.000	34.51	14.96	49.47	74.00	-24.53	peak
3	11664.000	33.53	17.08	50.61	74.00	-23.39	peak
4	13039.000	32.11	18.62	50.73	74.00	-23.27	peak
5	13468.000	30.02	20.50	50.52	74.00	-23.48	peak
6	17879.000	25.52	25.29	50.81	74.00	-23.19	peak

Test Mode:	802.11a 20	Frequency(MHz):	5200
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10564.000	36.29	13.06	49.35	74.00	-24.65	peak
2	11059.000	35.42	14.96	50.38	74.00	-23.62	peak
3	11774.000	33.12	17.28	50.40	74.00	-23.60	peak
4	12698.000	32.57	18.08	50.65	74.00	-23.35	peak
5	13600.000	29.46	20.89	50.35	74.00	-23.65	peak
6	17945.000	24.72	25.75	50.47	74.00	-23.53	peak

Test Mode:	802.11a 20	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9343.000	37.55	10.55	48.10	74.00	-25.90	peak
2	10168.000	37.44	12.13	49.57	74.00	-24.43	peak
3	11763.000	33.62	17.26	50.88	74.00	-23.12	peak
4	12676.000	32.70	18.05	50.75	74.00	-23.25	peak
5	13908.000	29.07	21.66	50.73	74.00	-23.27	peak
6	17989.000	24.44	26.04	50.48	74.00	-23.52	peak

Test Mode:	802.11a 20	Frequency(MHz):	5240
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9112.000	37.91	10.41	48.32	74.00	-25.68	peak
2	10003.000	37.49	11.77	49.26	74.00	-24.74	peak
3	11213.000	34.77	15.59	50.36	74.00	-23.64	peak
4	13127.000	31.91	19.01	50.92	74.00	-23.08	peak
5	13622.000	29.87	20.95	50.82	74.00	-23.18	peak
6	17989.000	24.96	26.04	51.00	74.00	-23.00	peak

Test Mode:	802.11a 20	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9178.000	37.18	10.45	47.63	74.00	-26.37	peak
2	10300.000	36.16	12.40	48.56	74.00	-25.44	peak
3	11796.000	32.46	17.32	49.78	74.00	-24.22	peak
4	12676.000	31.42	18.05	49.47	74.00	-24.53	peak
5	13490.000	29.27	20.60	49.87	74.00	-24.13	peak
6	17934.000	23.56	25.67	49.23	74.00	-24.77	peak

Test Mode:	802.11a 20	Frequency(MHz):	5745
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9189.000	36.45	10.46	46.91	74.00	-27.09	peak
2	10355.000	36.04	12.52	48.56	74.00	-25.44	peak
3	11059.000	34.77	14.96	49.73	74.00	-24.27	peak
4	12720.000	31.04	18.09	49.13	74.00	-24.87	peak
5	13864.000	28.05	21.53	49.58	74.00	-24.42	peak
6	17868.000	24.36	25.22	49.58	74.00	-24.42	peak

Test Mode:	802.11a 20	Frequency(MHz):	5785
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9057.000	37.79	10.38	48.17	74.00	-25.83	peak
2	9992.000	37.58	11.75	49.33	74.00	-24.67	peak
3	10388.000	37.37	12.59	49.96	74.00	-24.04	peak
4	12709.000	31.84	18.09	49.93	74.00	-24.07	peak
5	13677.000	29.37	21.08	50.45	74.00	-23.55	peak
6	17934.000	24.52	25.67	50.19	74.00	-23.81	peak

Test Mode:	802.11a 20	Frequency(MHz):	5785
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8914.000	37.82	9.75	47.57	74.00	-26.43	peak
2	10399.000	35.71	12.61	48.32	74.00	-25.68	peak
3	11048.000	34.07	14.91	48.98	74.00	-25.02	peak
4	12698.000	31.18	18.08	49.26	74.00	-24.74	peak
5	13875.000	28.27	21.57	49.84	74.00	-24.16	peak
6	17989.000	24.18	26.04	50.22	74.00	-23.78	peak

Test Mode:	802.11a 20	Frequency(MHz):	5825
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9068.000	37.67	10.39	48.06	74.00	-25.94	peak
2	10443.000	36.88	12.70	49.58	74.00	-24.42	peak
3	11268.000	34.74	15.83	50.57	74.00	-23.43	peak
4	12258.000	32.72	17.77	50.49	74.00	-23.51	peak
5	13699.000	29.43	21.14	50.57	74.00	-23.43	peak
6	17923.000	25.00	25.60	50.60	74.00	-23.40	peak

Test Mode:	802.11a 20	Frequency(MHz):	5825
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9233.000	36.82	10.48	47.30	74.00	-26.70	peak
2	10157.000	36.53	12.10	48.63	74.00	-25.37	peak
3	11037.000	34.93	14.87	49.80	74.00	-24.20	peak
4	12698.000	32.20	18.08	50.28	74.00	-23.72	peak
5	13864.000	28.66	21.53	50.19	74.00	-23.81	peak
6	17978.000	24.81	25.97	50.78	74.00	-23.22	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	7770.000	39.35	6.63	45.98	74.00	-28.02	peak
2	9750.000	37.31	11.21	48.52	74.00	-25.48	peak
3	11070.000	35.32	15.01	50.33	74.00	-23.67	peak
4	12236.000	32.67	17.76	50.43	74.00	-23.57	peak
5	13974.000	28.46	21.82	50.28	74.00	-23.72	peak
6	17923.000	25.05	25.60	50.65	74.00	-23.35	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5180
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9255.000	37.14	10.51	47.65	74.00	-26.35	peak
2	10553.000	36.96	13.02	49.98	74.00	-24.02	peak
3	11400.000	34.14	16.36	50.50	74.00	-23.50	peak
4	12676.000	32.19	18.05	50.24	74.00	-23.76	peak
5	13391.000	30.22	20.16	50.38	74.00	-23.62	peak
6	17769.000	25.95	24.53	50.48	74.00	-23.52	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5200
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9068.000	36.45	10.39	46.84	74.00	-27.16	peak
2	10234.000	36.62	12.26	48.88	74.00	-25.12	peak
3	11400.000	33.47	16.36	49.83	74.00	-24.17	peak
4	12269.000	32.53	17.77	50.30	74.00	-23.70	peak
5	13501.000	29.11	20.64	49.75	74.00	-24.25	peak
6	17989.000	23.78	26.04	49.82	74.00	-24.18	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5200
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9244.000	37.33	10.49	47.82	74.00	-26.18	peak
2	10168.000	36.95	12.13	49.08	74.00	-24.92	peak
3	10993.000	34.35	14.70	49.05	74.00	-24.95	peak
4	12599.000	32.06	17.95	50.01	74.00	-23.99	peak
5	13545.000	28.44	20.75	49.19	74.00	-24.81	peak
6	18000.000	23.60	26.12	49.72	74.00	-24.28	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9266.000	37.96	10.51	48.47	74.00	-25.53	peak
2	11081.000	35.03	15.05	50.08	74.00	-23.92	peak
3	11400.000	33.73	16.36	50.09	74.00	-23.91	peak
4	12665.000	32.76	18.04	50.80	74.00	-23.20	peak
5	13952.000	28.50	21.76	50.26	74.00	-23.74	peak
6	17989.000	24.61	26.04	50.65	74.00	-23.35	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5240
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9101.000	37.27	10.40	47.67	74.00	-26.33	peak
2	10212.000	36.59	12.21	48.80	74.00	-25.20	peak
3	11433.000	33.66	16.50	50.16	74.00	-23.84	peak
4	11994.000	32.29	17.69	49.98	74.00	-24.02	peak
5	13886.000	28.63	21.60	50.23	74.00	-23.77	peak
6	17934.000	24.31	25.67	49.98	74.00	-24.02	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8936.000	37.83	9.90	47.73	74.00	-26.27	peak
2	10201.000	36.58	12.19	48.77	74.00	-25.23	peak
3	11059.000	34.80	14.96	49.76	74.00	-24.24	peak
4	12698.000	31.89	18.08	49.97	74.00	-24.03	peak
5	13589.000	28.76	20.86	49.62	74.00	-24.38	peak
6	17956.000	23.76	25.82	49.58	74.00	-24.42	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5745
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9387.000	37.45	10.58	48.03	74.00	-25.97	peak
2	10300.000	36.88	12.40	49.28	74.00	-24.72	peak
3	11851.000	33.28	17.43	50.71	74.00	-23.29	peak
4	12731.000	32.86	18.12	50.98	74.00	-23.02	peak
5	13116.000	31.57	18.96	50.53	74.00	-23.47	peak
6	18000.000	24.34	26.12	50.46	74.00	-23.54	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5785
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8859.000	38.21	9.36	47.57	74.00	-26.43	peak
2	10212.000	36.71	12.21	48.92	74.00	-25.08	peak
3	11070.000	34.32	15.01	49.33	74.00	-24.67	peak
4	12687.000	31.83	18.05	49.88	74.00	-24.12	peak
5	13325.000	29.28	19.88	49.16	74.00	-24.84	peak
6	17956.000	24.16	25.82	49.98	74.00	-24.02	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5785
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9299.000	37.32	10.53	47.85	74.00	-26.15	peak
2	11081.000	34.66	15.05	49.71	74.00	-24.29	peak
3	12170.000	32.28	17.75	50.03	74.00	-23.97	peak
4	12632.000	32.16	17.99	50.15	74.00	-23.85	peak
5	13985.000	28.17	21.85	50.02	74.00	-23.98	peak
6	17989.000	24.74	26.04	50.78	74.00	-23.22	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5825
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9101.000	37.39	10.40	47.79	74.00	-26.21	peak
2	10190.000	36.99	12.18	49.17	74.00	-24.83	peak
3	11862.000	33.24	17.45	50.69	74.00	-23.31	peak
4	12698.000	32.80	18.08	50.88	74.00	-23.12	peak
5	13974.000	28.10	21.82	49.92	74.00	-24.08	peak
6	17989.000	24.55	26.04	50.59	74.00	-23.41	peak

Test Mode:	802.11n HT20	Frequency(MHz):	5825
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9552.000	37.91	10.76	48.67	74.00	-25.33	peak
2	10003.000	37.00	11.77	48.77	74.00	-25.23	peak
3	11048.000	34.36	14.91	49.27	74.00	-24.73	peak
4	12698.000	31.20	18.08	49.28	74.00	-24.72	peak
5	14007.000	27.82	21.85	49.67	74.00	-24.33	peak
6	17967.000	23.81	25.89	49.70	74.00	-24.30	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5190
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9354.000	37.31	10.56	47.87	74.00	-26.13	peak
2	9992.000	36.89	11.75	48.64	74.00	-25.36	peak
3	11620.000	32.54	16.99	49.53	74.00	-24.47	peak
4	12577.000	31.75	17.93	49.68	74.00	-24.32	peak
5	13457.000	28.72	20.46	49.18	74.00	-24.82	peak
6	17758.000	24.82	24.46	49.28	74.00	-24.72	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5190
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9321.000	37.70	10.53	48.23	74.00	-25.77	peak
2	10443.000	36.87	12.70	49.57	74.00	-24.43	peak
3	10861.000	35.59	14.20	49.79	74.00	-24.21	peak
4	12687.000	32.73	18.05	50.78	74.00	-23.22	peak
5	13897.000	29.01	21.62	50.63	74.00	-23.37	peak
6	17912.000	24.96	25.52	50.48	74.00	-23.52	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5230
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9376.000	38.01	10.58	48.59	74.00	-25.41	peak
2	10377.000	36.85	12.56	49.41	74.00	-24.59	peak
3	11411.000	33.54	16.41	49.95	74.00	-24.05	peak
4	12709.000	32.33	18.09	50.42	74.00	-23.58	peak
5	13919.000	28.70	21.68	50.38	74.00	-23.62	peak
6	17945.000	24.48	25.75	50.23	74.00	-23.77	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5230
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	10003.000	37.12	11.77	48.89	74.00	-25.11	peak
2	11400.000	33.07	16.36	49.43	74.00	-24.57	peak
3	12236.000	32.31	17.76	50.07	74.00	-23.93	peak
4	13556.000	29.58	20.78	50.36	74.00	-23.64	peak
5	13908.000	28.85	21.66	50.51	74.00	-23.49	peak
6	17934.000	24.76	25.67	50.43	74.00	-23.57	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5755
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9387.000	37.57	10.58	48.15	74.00	-25.85	peak
2	10212.000	36.60	12.21	48.81	74.00	-25.19	peak
3	11048.000	34.66	14.91	49.57	74.00	-24.43	peak
4	13116.000	30.62	18.96	49.58	74.00	-24.42	peak
5	13930.000	27.98	21.71	49.69	74.00	-24.31	peak
6	18000.000	24.00	26.12	50.12	74.00	-23.88	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5755
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9310.000	37.44	10.54	47.98	74.00	-26.02	peak
2	10234.000	36.55	12.26	48.81	74.00	-25.19	peak
3	11521.000	33.41	16.82	50.23	74.00	-23.77	peak
4	12269.000	32.01	17.77	49.78	74.00	-24.22	peak
5	13435.000	29.91	20.35	50.26	74.00	-23.74	peak
6	17692.000	25.40	24.01	49.41	74.00	-24.59	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5795
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9189.000	37.41	10.46	47.87	74.00	-26.13	peak
2	11059.000	35.07	14.96	50.03	74.00	-23.97	peak
3	12302.000	32.26	17.78	50.04	74.00	-23.96	peak
4	12698.000	32.55	18.08	50.63	74.00	-23.37	peak
5	13930.000	28.49	21.71	50.20	74.00	-23.80	peak
6	17934.000	24.92	25.67	50.59	74.00	-23.41	peak

Test Mode:	802.11n HT40	Frequency(MHz):	5795
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9321.000	36.91	10.53	47.44	74.00	-26.56	peak
2	10608.000	35.83	13.23	49.06	74.00	-24.94	peak
3	11510.000	32.41	16.79	49.20	74.00	-24.80	peak
4	12676.000	31.39	18.05	49.44	74.00	-24.56	peak
5	13985.000	27.87	21.85	49.72	74.00	-24.28	peak
6	17934.000	24.05	25.67	49.72	74.00	-24.28	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5210
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9299.000	37.07	10.53	47.60	74.00	-26.40	peak
2	11070.000	34.84	15.01	49.85	74.00	-24.15	peak
3	11840.000	32.53	17.40	49.93	74.00	-24.07	peak
4	12621.000	32.16	17.98	50.14	74.00	-23.86	peak
5	13875.000	28.89	21.57	50.46	74.00	-23.54	peak
6	17934.000	24.78	25.67	50.45	74.00	-23.55	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5210
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9299.000	37.50	10.53	48.03	74.00	-25.97	peak
2	10443.000	36.48	12.70	49.18	74.00	-24.82	peak
3	11400.000	33.36	16.36	49.72	74.00	-24.28	peak
4	12709.000	32.11	18.09	50.20	74.00	-23.80	peak
5	13930.000	28.16	21.71	49.87	74.00	-24.13	peak
6	17989.000	24.09	26.04	50.13	74.00	-23.87	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5775
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9189.000	37.28	10.46	47.74	74.00	-26.26	peak
2	11081.000	34.42	15.05	49.47	74.00	-24.53	peak
3	11873.000	32.09	17.46	49.55	74.00	-24.45	peak
4	12665.000	31.65	18.04	49.69	74.00	-24.31	peak
5	13809.000	28.73	21.41	50.14	74.00	-23.86	peak
6	17989.000	23.94	26.04	49.98	74.00	-24.02	peak

Test Mode:	802.11ac VHT80	Frequency(MHz):	5775
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9266.000	37.25	10.51	47.76	74.00	-26.24	peak
2	10333.000	36.58	12.47	49.05	74.00	-24.95	peak
3	11279.000	34.41	15.86	50.27	74.00	-23.73	peak
4	12698.000	32.13	18.08	50.21	74.00	-23.79	peak
5	13864.000	28.48	21.53	50.01	74.00	-23.99	peak
6	18000.000	24.00	26.12	50.12	74.00	-23.88	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5180
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9266.000	37.44	10.51	47.95	74.00	-26.05	peak
2	10223.000	36.84	12.24	49.08	74.00	-24.92	peak
3	11895.000	33.15	17.51	50.66	74.00	-23.34	peak
4	12643.000	32.49	18.01	50.50	74.00	-23.50	peak
5	13600.000	29.65	20.89	50.54	74.00	-23.46	peak
6	17923.000	24.30	25.60	49.90	74.00	-24.10	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5180
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9244.000	37.55	10.49	48.04	74.00	-25.96	peak
2	11059.000	35.01	14.96	49.97	74.00	-24.03	peak
3	11818.000	32.66	17.36	50.02	74.00	-23.98	peak
4	13116.000	31.60	18.96	50.56	74.00	-23.44	peak
5	13578.000	30.15	20.83	50.98	74.00	-23.02	peak
6	17945.000	24.91	25.75	50.66	74.00	-23.34	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5200
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9299.000	37.49	10.53	48.02	74.00	-25.98	peak
2	10333.000	36.66	12.47	49.13	74.00	-24.87	peak
3	11246.000	34.04	15.73	49.77	74.00	-24.23	peak
4	11796.000	32.86	17.32	50.18	74.00	-23.82	peak
5	13930.000	28.88	21.71	50.59	74.00	-23.41	peak
6	18000.000	24.57	26.12	50.69	74.00	-23.31	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5200
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9310.000	37.25	10.54	47.79	74.00	-26.21	peak
2	9816.000	36.98	11.37	48.35	74.00	-25.65	peak
3	11356.000	34.16	16.19	50.35	74.00	-23.65	peak
4	12676.000	32.64	18.05	50.69	74.00	-23.31	peak
5	13567.000	29.32	20.80	50.12	74.00	-23.88	peak
6	17934.000	24.52	25.67	50.19	74.00	-23.81	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5240
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9167.000	37.22	10.45	47.67	74.00	-26.33	peak
2	10872.000	34.83	14.23	49.06	74.00	-24.94	peak
3	11521.000	32.88	16.82	49.70	74.00	-24.30	peak
4	12676.000	32.48	18.05	50.53	74.00	-23.47	peak
5	13930.000	28.47	21.71	50.18	74.00	-23.82	peak
6	17989.000	24.01	26.04	50.05	74.00	-23.95	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5240
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9805.000	36.53	11.34	47.87	74.00	-26.13	peak
2	10454.000	36.13	12.73	48.86	74.00	-25.14	peak
3	11246.000	33.76	15.73	49.49	74.00	-24.51	peak
4	12654.000	31.70	18.01	49.71	74.00	-24.29	peak
5	13919.000	28.45	21.68	50.13	74.00	-23.87	peak
6	17934.000	25.20	25.67	50.87	74.00	-23.13	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9266.000	37.36	10.51	47.87	74.00	-26.13	peak
2	10443.000	36.35	12.70	49.05	74.00	-24.95	peak
3	11455.000	33.63	16.58	50.21	74.00	-23.79	peak
4	13127.000	31.71	19.01	50.72	74.00	-23.28	peak
5	13864.000	28.63	21.53	50.16	74.00	-23.84	peak
6	18000.000	24.83	26.12	50.95	74.00	-23.05	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5745
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9321.000	37.13	10.53	47.66	74.00	-26.34	peak
2	10003.000	37.11	11.77	48.88	74.00	-25.12	peak
3	11400.000	34.14	16.36	50.50	74.00	-23.50	peak
4	12698.000	32.71	18.08	50.79	74.00	-23.21	peak
5	13424.000	30.31	20.30	50.61	74.00	-23.39	peak
6	18000.000	24.62	26.12	50.74	74.00	-23.26	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5785
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9057.000	37.40	10.38	47.78	74.00	-26.22	peak
2	10388.000	36.33	12.59	48.92	74.00	-25.08	peak
3	11048.000	34.76	14.91	49.67	74.00	-24.33	peak
4	11884.000	31.54	17.48	49.02	74.00	-24.98	peak
5	13600.000	28.74	20.89	49.63	74.00	-24.37	peak
6	17989.000	23.93	26.04	49.97	74.00	-24.03	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5785
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9387.000	37.17	10.58	47.75	74.00	-26.25	peak
2	10421.000	36.31	12.66	48.97	74.00	-25.03	peak
3	11070.000	34.71	15.01	49.72	74.00	-24.28	peak
4	12511.000	31.83	17.84	49.67	74.00	-24.33	peak
5	13809.000	28.36	21.41	49.77	74.00	-24.23	peak
6	17615.000	26.72	23.49	50.21	74.00	-23.79	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5825
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9299.000	36.89	10.53	47.42	74.00	-26.58	peak
2	10201.000	35.88	12.19	48.07	74.00	-25.93	peak
3	10883.000	34.46	14.27	48.73	74.00	-25.27	peak
4	11730.000	31.95	17.19	49.14	74.00	-24.86	peak
5	13105.000	30.51	18.91	49.42	74.00	-24.58	peak
6	18000.000	24.39	26.12	50.51	74.00	-23.49	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5825
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9354.000	36.95	10.56	47.51	74.00	-26.49	peak
2	10421.000	35.92	12.66	48.58	74.00	-25.42	peak
3	11334.000	33.52	16.09	49.61	74.00	-24.39	peak
4	13094.000	31.49	18.87	50.36	74.00	-23.64	peak
5	13930.000	28.09	21.71	49.80	74.00	-24.20	peak
6	17989.000	24.58	26.04	50.62	74.00	-23.38	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5190
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	8903.000	37.62	9.66	47.28	74.00	-26.72	peak
2	9563.000	36.72	10.79	47.51	74.00	-26.49	peak
3	10333.000	35.70	12.47	48.17	74.00	-25.83	peak
4	11356.000	33.11	16.19	49.30	74.00	-24.70	peak
5	13105.000	30.90	18.91	49.81	74.00	-24.19	peak
6	18000.000	23.23	26.12	49.35	74.00	-24.65	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5190
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9365.000	37.82	10.57	48.39	74.00	-25.61	peak
2	10641.000	35.59	13.36	48.95	74.00	-25.05	peak
3	12258.000	32.05	17.77	49.82	74.00	-24.18	peak
4	12643.000	31.56	18.01	49.57	74.00	-24.43	peak
5	13919.000	28.63	21.68	50.31	74.00	-23.69	peak
6	17934.000	24.21	25.67	49.88	74.00	-24.12	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5230
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9992.000	37.12	11.75	48.87	74.00	-25.13	peak
2	11059.000	34.49	14.96	49.45	74.00	-24.55	peak
3	11686.000	33.56	17.12	50.68	74.00	-23.32	peak
4	12654.000	32.81	18.01	50.82	74.00	-23.18	peak
5	13996.000	28.52	21.87	50.39	74.00	-23.61	peak
6	18000.000	24.64	26.12	50.76	74.00	-23.24	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5230
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9244.000	37.70	10.49	48.19	74.00	-25.81	peak
2	10498.000	36.43	12.82	49.25	74.00	-24.75	peak
3	11312.000	33.60	16.00	49.60	74.00	-24.40	peak
4	11796.000	32.37	17.32	49.69	74.00	-24.31	peak
5	13875.000	28.31	21.57	49.88	74.00	-24.12	peak
6	17879.000	25.45	25.29	50.74	74.00	-23.26	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5755
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9299.000	37.45	10.53	47.98	74.00	-26.02	peak
2	11048.000	35.03	14.91	49.94	74.00	-24.06	peak
3	11422.000	33.07	16.46	49.53	74.00	-24.47	peak
4	12643.000	32.31	18.01	50.32	74.00	-23.68	peak
5	13897.000	28.18	21.62	49.80	74.00	-24.20	peak
6	17956.000	24.66	25.82	50.48	74.00	-23.52	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5755
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9244.000	37.24	10.49	47.73	74.00	-26.27	peak
2	10168.000	37.32	12.13	49.45	74.00	-24.55	peak
3	11422.000	33.53	16.46	49.99	74.00	-24.01	peak
4	12247.000	32.38	17.77	50.15	74.00	-23.85	peak
5	13347.000	29.66	19.97	49.63	74.00	-24.37	peak
6	17912.000	24.36	25.52	49.88	74.00	-24.12	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5795
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9299.000	37.47	10.53	48.00	74.00	-26.00	peak
2	10520.000	36.25	12.90	49.15	74.00	-24.85	peak
3	11268.000	34.85	15.83	50.68	74.00	-23.32	peak
4	12236.000	32.52	17.76	50.28	74.00	-23.72	peak
5	13974.000	28.01	21.82	49.83	74.00	-24.17	peak
6	17978.000	24.05	25.97	50.02	74.00	-23.98	peak

Test Mode:	802.11ax HE40	Frequency(MHz):	5795
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9178.000	37.09	10.45	47.54	74.00	-26.46	peak
2	10300.000	36.14	12.40	48.54	74.00	-25.46	peak
3	12093.000	32.59	17.72	50.31	74.00	-23.69	peak
4	12632.000	32.65	17.99	50.64	74.00	-23.36	peak
5	13622.000	29.59	20.95	50.54	74.00	-23.46	peak
6	17989.000	24.69	26.04	50.73	74.00	-23.27	peak

Test Mode:	802.11ax HE80	Frequency(MHz):	5210
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9651.000	36.89	10.99	47.88	74.00	-26.12	peak
2	10201.000	35.80	12.19	47.99	74.00	-26.01	peak
3	11246.000	34.09	15.73	49.82	74.00	-24.18	peak
4	11697.000	33.20	17.13	50.33	74.00	-23.67	peak
5	13611.000	29.60	20.92	50.52	74.00	-23.48	peak
6	17956.000	24.49	25.82	50.31	74.00	-23.69	peak

Test Mode:	802.11ax HE80	Frequency(MHz):	5210
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9255.000	37.67	10.51	48.18	74.00	-25.82	peak
2	11059.000	34.72	14.96	49.68	74.00	-24.32	peak
3	11785.000	33.51	17.30	50.81	74.00	-23.19	peak
4	12621.000	32.91	17.98	50.89	74.00	-23.11	peak
5	13402.000	30.55	20.20	50.75	74.00	-23.25	peak
6	18000.000	24.52	26.12	50.64	74.00	-23.36	peak

Test Mode:	802.11ax HE80	Frequency(MHz):	5775
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9651.000	37.24	10.99	48.23	74.00	-25.77	peak
2	11334.000	34.04	16.09	50.13	74.00	-23.87	peak
3	11862.000	33.03	17.45	50.48	74.00	-23.52	peak
4	12731.000	31.99	18.12	50.11	74.00	-23.89	peak
5	13963.000	28.71	21.78	50.49	74.00	-23.51	peak
6	17923.000	24.28	25.60	49.88	74.00	-24.12	peak


Test Mode:	802.11ax HE80	Frequency(MHz):	5775
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	9233.000	37.55	10.48	48.03	74.00	-25.97	peak
2	11059.000	34.77	14.96	49.73	74.00	-24.27	peak
3	11697.000	32.36	17.13	49.49	74.00	-24.51	peak
4	12632.000	31.91	17.99	49.90	74.00	-24.10	peak
5	13853.000	28.35	21.52	49.87	74.00	-24.13	peak
6	17989.000	24.44	26.04	50.48	74.00	-23.52	peak


8.4. SPURIOUS EMISSIONS (9 KHZ ~ 30 MHZ)

Test Mode:	802.11ax HE20	Frequency(MHz):	5745
Polarity:	Loop Antenna Face On To The EUT	Test Voltage:	AC 120 V, 60 Hz




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.0100	78.72	-101.40	-22.68	47.60	-70.28	peak
2	0.0114	77.88	-101.40	-23.52	46.46	-69.98	peak
3	0.0160	73.47	-101.37	-27.90	43.52	-71.42	peak
4	0.0222	70.86	-101.35	-30.49	40.67	-71.16	peak
5	0.0466	63.67	-101.46	-37.79	34.23	-72.02	peak
6	0.0882	60.09	-101.70	-41.61	28.69	-70.30	peak

Test Mode:	802.11ax HE20	Frequency(MHz):	5745
Polarity:	Loop Antenna Face On To The EUT	Test Voltage:	AC 120 V, 60 Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.1554	75.27	-101.65	-26.38	23.77	-50.15	peak
2	0.1647	74.76	-101.66	-26.90	23.27	-50.17	peak
3	0.1800	73.65	-101.68	-28.03	22.50	-50.53	peak
4	0.2190	68.27	-101.75	-33.48	20.79	-54.27	peak
5	0.3163	62.20	-101.87	-39.67	17.60	-57.27	peak
6	0.3684	59.48	-101.93	-42.45	16.27	-58.72	peak


Test Mode:	802.11ax HE20	Frequency(MHz):	5745
Polarity:	Loop Antenna Face On To The EUT	Test Voltage:	AC 120 V, 60 Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	0.6590	64.38	-62.10	2.28	31.22	-28.94	peak
2	1.5564	59.18	-62.02	-2.84	23.76	-26.60	peak
3	3.7100	56.70	-61.41	-4.71	29.54	-34.25	peak
4	5.2705	55.04	-61.45	-6.41	29.54	-35.95	peak
5	7.9560	53.52	-61.08	-7.56	29.54	-37.10	peak
6	12.0282	52.33	-60.89	-8.56	29.54	-38.10	peak


8.5. SPURIOUS EMISSIONS (18 GHZ ~ 26 GHZ)

Test Mode:	802.11ax HE20	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18568.000	48.80	-5.30	43.50	74.00	-30.50	peak
2	19904.000	48.83	-5.37	43.46	74.00	-30.54	peak
3	21456.000	48.69	-4.70	43.99	74.00	-30.01	peak
4	22160.000	48.08	-4.31	43.77	74.00	-30.23	peak
5	24208.000	46.71	-2.81	43.90	74.00	-30.10	peak
6	25616.000	45.68	-1.24	44.44	74.00	-29.56	peak


Test Mode:	802.11ax HE20	Frequency(MHz):	5745
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	18576.000	48.29	-5.30	42.99	74.00	-31.01	peak
2	20240.000	49.32	-5.61	43.71	74.00	-30.29	peak
3	21544.000	47.76	-4.63	43.13	74.00	-30.87	peak
4	22976.000	46.76	-3.46	43.30	74.00	-30.70	peak
5	24632.000	45.96	-2.31	43.65	74.00	-30.35	peak
6	25136.000	45.42	-1.87	43.55	74.00	-30.45	peak


8.6. SPURIOUS EMISSIONS (26 GHZ ~ 40 GHZ)

Test Mode:	802.11ax HE20	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	26490.000	53.79	-4.74	49.05	74.00	-24.95	peak
2	31012.000	49.33	-0.71	48.62	74.00	-25.38	peak
3	33644.000	47.81	0.42	48.23	74.00	-25.77	peak
4	35870.000	44.83	3.75	48.58	74.00	-25.42	peak
5	37228.000	44.73	3.14	47.87	74.00	-26.13	peak
6	39958.000	43.58	5.12	48.70	74.00	-25.30	peak


Test Mode:	802.11ax HE20	Frequency(MHz):	5745
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	28828.000	49.13	-0.79	48.34	74.00	-25.66	peak
2	31320.000	50.11	-0.93	49.18	74.00	-24.82	peak
3	33602.000	48.01	0.46	48.47	74.00	-25.53	peak
4	35254.000	46.12	2.65	48.77	74.00	-25.23	peak
5	35828.000	45.25	3.67	48.92	74.00	-25.08	peak
6	38110.000	44.33	3.53	47.86	74.00	-26.14	peak


8.7. SPURIOUS EMISSIONS (30 MHZ ~ 1 GHZ)

Test Mode:	802.11ax HE20	Frequency(MHz):	5745
Polarity:	Horizontal	Test Voltage:	AC 120 V, 60 Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	58.1300	46.21	-19.82	26.39	40.00	-13.61	QP
2	213.3300	41.06	-16.49	24.57	43.50	-18.93	QP
3	256.9800	43.78	-17.88	25.90	46.00	-20.10	QP
4	343.3100	37.79	-12.82	24.97	46.00	-21.03	QP
5	490.7500	49.70	-10.56	39.14	46.00	-6.86	QP
6	755.5600	33.22	-6.61	26.61	46.00	-19.39	QP

Test Mode:	802.11ax HE20	Frequency(MHz):	5745
Polarity:	Vertical	Test Voltage:	AC 120 V, 60 Hz



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark
1	58.1300	51.30	-19.82	31.48	40.00	-8.52	QP
2	95.9600	53.55	-21.22	32.33	43.50	-11.17	QP
3	444.1900	44.42	-11.48	32.94	46.00	-13.06	QP
4	468.4400	46.35	-10.98	35.37	46.00	-10.63	QP
5	490.7500	48.17	-10.56	37.61	46.00	-8.39	QP
6	753.6200	35.10	-6.65	28.45	46.00	-17.55	QP

9. AC POWER LINE CONDUCTED EMISSION

LIMITS

Please refer to CFR 47 FCC §15.207 (a) and ISED RSS-Gen Clause 8.8

FREQUENCY (MHz)	Quasi-peak	Average
0.15 -0.5	66 - 56 *	56 - 46 *
0.50 -5.0	56.00	46.00
5.0 -30.0	60.00	50.00


TEST PROCEDURE

Refer to ANSI C63.10-2013 clause 6.2.

The EUT is put on a table of non-conducting material that is 80 cm high. The vertical conducting wall of shielding is located 40 cm to the rear of the EUT. The power line of the EUT is connected to the AC mains through a Artificial Mains Network (A.M.N.). A EMI Measurement Receiver (R&S Test Receiver ESR3) is used to test the emissions from both sides of AC line. According to the requirements in Section 6.2 of ANSI C63.10-2013. Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30 MHz using CISPR Quasi-Peak and average detector mode. The bandwidth of EMI test receiver is set at 9 kHz.

The arrangement of the equipment is installed to meet the standards and operating in a manner, which tends to maximize its emission characteristics in a normal application.

TEST SETUP




TEST ENVIRONMENT

Temperature	22.5°C	Relative Humidity	57.8%
Atmosphere Pressure	101kPa	Test Voltage	AC 120 V, 60 Hz

TEST RESULTS

Test Mode:	802.11ax HE20	Frequency(MHz):	5745
Line	L		




No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1836	34.61	9.59	44.20	64.32	-20.12	QP
2	0.1836	26.95	9.59	36.54	54.32	-17.78	AVG
3	0.2231	37.99	9.59	47.58	62.70	-15.12	QP
4	0.2231	35.28	9.59	44.87	52.70	-7.83	AVG
5	0.2909	35.59	9.59	45.18	60.50	-15.32	QP
6	0.2909	31.06	9.59	40.65	50.50	-9.85	AVG
7	0.5855	25.29	9.60	34.89	56.00	-21.11	QP
8	0.5855	19.12	9.60	28.72	46.00	-17.28	AVG
9	9.3943	22.21	9.72	31.93	60.00	-28.07	QP
10	9.3943	15.70	9.72	25.42	50.00	-24.58	AVG
11	13.5671	31.53	9.76	41.29	60.00	-18.71	QP
12	13.5671	25.33	9.76	35.09	50.00	-14.91	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Test Mode:	802.11ax HE20	Frequency(MHz):	5745
Line	N		



No.	Frequency (MHz)	Reading (dBuV)	Correct (dB)	Result (dBuV)	Limit (dBuV)	Margin (dB)	Remark
1	0.1849	36.27	9.56	45.83	64.26	-18.43	QP
2	0.1849	32.69	9.56	42.25	54.26	-12.01	AVG
3	0.2238	39.10	9.58	48.68	62.68	-14.00	QP
4	0.2238	35.89	9.58	45.47	52.68	-7.21	AVG
5	0.2907	36.44	9.56	46.00	60.50	-14.50	QP
6	0.2907	31.36	9.56	40.92	50.50	-9.58	AVG
7	0.3631	32.59	9.54	42.13	58.66	-16.53	QP
8	0.3631	24.47	9.54	34.01	48.66	-14.65	AVG
9	0.5871	26.07	9.50	35.57	56.00	-20.43	QP
10	0.5871	19.32	9.50	28.82	46.00	-17.18	AVG
11	13.5671	31.80	9.66	41.46	60.00	-18.54	QP
12	13.5671	25.75	9.66	35.41	50.00	-14.59	AVG

Note:

1. Result = Reading + Correct Factor.
2. If QP Result complies with AV limit, AV Result is deemed to comply with AV limit.
3. Test setup: RBW: 200 Hz (9 kHz ~ 150 kHz), 9 kHz (150 kHz ~ 30 MHz).
4. Step size: 80 Hz (0.009 MHz ~ 0.15 MHz), 4 kHz (0.15 MHz ~ 30 MHz), Scan time: auto.

Note: All the modes have been tested, only the worst data was recorded in the report.

10. ANTENNA REQUIREMENT

REQUIREMENT

Please refer to FCC part 15.203

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

Please refer to FCC part 15.407(a)

For an indoor access point operating in the band 5.15-5.25 GHz, the maximum conducted output power over the frequency band of operation shall not exceed 1 W provided the maximum antenna gain does not exceed 6 dBi. In addition, the maximum power spectral density shall not exceed 17 dBm in any 1 megahertz band. If transmitting antennas of directional gain greater than 6 dBi are used, both the maximum conducted output power and the maximum power spectral density shall be reduced by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

DESCRIPTION

Pass

11. TEST DATA



11.1. APPENDIX A: EMISSION BANDWIDTH


11.1.1. Test Result

Test Mode	Antenna	Frequency[MHz]	26db EBW [MHz]	FL[MHz]	FH[MHz]	Verdict
11A-CDD	Ant1	5180	21.04	5169.44	5190.48	PASS
	Ant2	5180	20.20	5169.92	5190.12	PASS
	Ant1	5200	20.88	5189.68	5210.56	PASS
	Ant2	5200	20.72	5189.60	5210.32	PASS
	Ant1	5240	20.80	5229.60	5250.40	PASS
	Ant2	5240	21.00	5229.56	5250.56	PASS
	Ant1	5745	20.96	5734.48	5755.44	PASS
	Ant2	5745	20.48	5734.84	5755.32	PASS
	Ant1	5785	21.24	5774.28	5795.52	PASS
	Ant2	5785	20.40	5774.96	5795.36	PASS
	Ant1	5825	20.84	5814.56	5835.40	PASS
Ant2	5825	20.48	5814.84	5835.32	PASS	
11N20MIMO	Ant1	5180	21.52	5169.28	5190.80	PASS
	Ant2	5180	21.12	5169.48	5190.60	PASS
	Ant1	5200	21.28	5189.44	5210.72	PASS
	Ant2	5200	20.92	5189.56	5210.48	PASS
	Ant1	5240	20.88	5229.76	5250.64	PASS
	Ant2	5240	21.04	5229.36	5250.40	PASS
	Ant1	5745	21.48	5734.28	5755.76	PASS
	Ant2	5745	21.12	5734.32	5755.44	PASS
	Ant1	5785	21.52	5774.16	5795.68	PASS
	Ant2	5785	21.08	5774.64	5795.72	PASS
	Ant1	5825	21.08	5814.40	5835.48	PASS
Ant2	5825	21.24	5814.40	5835.64	PASS	
11N40MIMO	Ant1	5190	39.60	5170.24	5209.84	PASS
	Ant2	5190	39.04	5170.56	5209.60	PASS
	Ant1	5230	39.60	5210.24	5249.84	PASS
	Ant2	5230	39.12	5210.56	5249.68	PASS
	Ant1	5755	39.84	5735.16	5775.00	PASS
	Ant2	5755	39.20	5735.48	5774.68	PASS
	Ant1	5795	39.76	5775.08	5814.84	PASS
	Ant2	5795	39.12	5775.64	5814.76	PASS
11AC80MIMO	Ant1	5210	81.12	5169.68	5250.80	PASS
	Ant2	5210	80.80	5169.84	5250.64	PASS
	Ant1	5775	80.96	5734.84	5815.80	PASS
	Ant2	5775	81.28	5734.84	5816.12	PASS
11AX20MIMO	Ant1	5180	21.16	5169.52	5190.68	PASS
	Ant2	5180	21.40	5169.36	5190.76	PASS
	Ant1	5200	21.08	5189.44	5210.52	PASS
	Ant2	5200	21.56	5189.24	5210.80	PASS
	Ant1	5240	21.52	5229.24	5250.76	PASS
	Ant2	5240	21.20	5229.40	5250.60	PASS
	Ant1	5745	21.32	5734.48	5755.80	PASS
	Ant2	5745	22.80	5734.36	5757.16	PASS
	Ant1	5785	22.40	5774.44	5796.84	PASS
	Ant2	5785	23.04	5774.44	5797.48	PASS
	Ant1	5825	21.60	5814.24	5835.84	PASS
	Ant2	5825	21.16	5814.52	5835.68	PASS
11AX40MIMO	Ant1	5190	40.56	5169.76	5210.32	PASS
	Ant2	5190	40.16	5170.00	5210.16	PASS
	Ant1	5230	40.48	5209.84	5250.32	PASS
	Ant2	5230	40.08	5210.00	5250.08	PASS
	Ant1	5755	40.48	5734.84	5775.32	PASS
	Ant2	5755	40.48	5734.84	5775.32	PASS
	Ant1	5795	40.32	5774.92	5815.24	PASS
	Ant2	5795	40.48	5775.00	5815.48	PASS

11AX80MIMO	Ant1	5210	82.08	5169.20	5251.28	PASS
	Ant2	5210	81.44	5169.36	5250.80	PASS
	Ant1	5775	81.92	5734.20	5816.12	PASS
	Ant2	5775	89.92	5734.04	5823.96	PASS


11.1.2. Test Graphs






Date: 11.JAN.2024 08:00:14

11A-CDD Ant2 5200



Date: 11.JAN.2024 08:03:52

11A-CDD Ant1 5240



Date: 11.JAN.2024 08:04:28

11A-CDD Ant2 5240



Date: 11.JAN.2024 08:25:54