

RF EXPOSURE EVALUATION

According to FCC 1.1310: The criteria listed in the following table shall be used to evaluate the environment impact of human exposure to radio frequency(RF) Radiation as specified in §1.1307(b)

FCC ID: 2ABC5-E0053

EUT Specification

| | |
|-----------------------------------|---|
| EUT | Android Tablet |
| Frequency band (Operating) | <input checked="" type="checkbox"/> WLAN: 2.412GHz ~ 2.462GHz <input checked="" type="checkbox"/> WLAN: 5.150GHz ~ 5.250GHz <input checked="" type="checkbox"/> WLAN: 5.725GHz ~ 5.850GHz <input checked="" type="checkbox"/> Others: 2.402GHz~2.480GHz <input checked="" type="checkbox"/> Others: 13.56MHz&125KHz |
| Device category | <input type="checkbox"/> Portable (<20cm separation) <input checked="" type="checkbox"/> Mobile (>20cm separation) <input type="checkbox"/> Others _____ |
| Exposure classification | <input type="checkbox"/> Occupational/Controlled exposure (S = 5mW/cm ²) <input checked="" type="checkbox"/> General Population/Uncontrolled exposure (S=1mW/cm ²) |
| Antenna diversity | <input type="checkbox"/> Single antenna <input checked="" type="checkbox"/> Multiple antennas <input type="checkbox"/> Tx diversity <input type="checkbox"/> Rx diversity <input type="checkbox"/> Tx/Rx diversity |
| Max. output power | BLE: 5.39dBm (0.0035W) BT: 6.28dBm (0.0042W) 2.4G WiFi: 14.28dBm (0.0268W) 5.1G WiFi: 12.89dBm (0.0195W) 5.8G WiFi: 13.00dBm (0.0200W) |
| Antenna gain (Max) | BLE&BT: 4.13 dBi 2.4G WiFi: 4.13 dBi 5.1G WiFi: 3.14 dBi 5.8G WiFi: 2.59 dBi NFC&RFID: 0 dBi |
| Evaluation applied | <input checked="" type="checkbox"/> MPE Evaluation <input type="checkbox"/> SAR Evaluation |

Limits for Maximum Permissible Exposure(MPE)

| Frequency Range(MHz) | Electric Field Strength(V/m) | Magnetic Field Strength(A/m) | Power Density(mW/cm ²) | Average Time |
|--|------------------------------|------------------------------|------------------------------------|--------------|
| (A) Limits for Occupational/Control Exposures | | | | |
| 300-1500 | -- | -- | F/300 | 6 |
| 1500-100000 | -- | -- | 5 | 6 |
| (B) Limits for General Population/Uncontrol Exposures | | | | |

| | | | | |
|--------------------|----|----|---------------|-----------|
| 300-1500 | -- | -- | F/1500 | 6 |
| 1500-100000 | -- | -- | 1 | 30 |

Friis transmission formula: $Pd=(Pout*G)\backslash(4*pi*R^2)$

Where

Pd= Power density in mW/cm²

Pout=output power to antenna in Mw

G= gain of antenna in linear scale

Pi=3.1416

R= distance between observation point and center of the radiator in cm

Pd the limit of MPE, 1mW/cm². If we know the maximum gain of the antenna and total power input to the antenna, through the calculation, we will know the distance where the MPE limit is reached.

Measurement Result

2.4GHz WiFi worst case:

| Operating Mode | Channel Frequency | Measured Power | Tune up tolerance | Max. Tune up Power | Antenna Gain | Power density at 20cm | Power density Limits |
|----------------|-------------------|----------------|-------------------|--------------------|--------------|------------------------|-----------------------|
| | (MHz) | (dBm) | (dBm) | (dBm) | (dBi) | (mW/ cm ²) | (mW/cm ²) |
| 802.11b | 2462 | 14.28 | 14.28±1 | 15.28 | 4.13 | 0.0174 | 1 |

5GHz WiFi worst case:

| Operating Mode | Channel Frequency | Measured Power | Tune up tolerance | Max. Tune up Power | Antenna Gain | Power density at 20cm | Power density Limits |
|----------------|-------------------|----------------|-------------------|--------------------|--------------|------------------------|-----------------------|
| | (MHz) | (dBm) | (dBm) | (dBm) | (dBi) | (mW/ cm ²) | (mW/cm ²) |
| 802.11a | 5180 | 12.89 | 12.89±1 | 13.89 | 3.14 | 0.0100 | 1 |
| | 5785 | 13.00 | 13.00±1 | 14.00 | 2.59 | 0.0091 | 1 |

BT&BLE worst case:

| Operating Mode | Channel Frequency | Measured Power | Tune up tolerance | Max. Tune up Power | Antenna Gain | Power density at 20cm | Power density Limits |
|----------------|-------------------|----------------|-------------------|--------------------|--------------|------------------------|-----------------------|
| | (MHz) | (dBm) | (dBm) | (dBm) | (dBi) | (mW/ cm ²) | (mW/cm ²) |
| BDR&ED R | 2480 | 6.28 | 6.28±1 | 7.28 | 4.13 | 0.0028 | 1 |
| BLE | 2440 | 5.39 | 5.39±1 | 6.39 | 4.13 | 0.0022 | 1 |

Note: BT and WIFI and NFC&RFID cannot support simultaneous transmission.

Result: No Standalone SAR test is required.