



TEST REPORT

Report No. SST240416006EF03

Applicant: SHENZHEN ELECTRON TECHNOLOGY CO., LTD.

Address of Applicant: Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Bao'an, Shenzhen, China.

Product Name: Android Tablet

Trade Mark: /

Standard(s): FCC CFR Title 47 Part 15 Subpart E Section 15.247

FCC ID: 2ABC5-E0059

Test Report Form No: SST-RD-7.5-02-E01(A/0)

Date of sample receipt: 2024/4/18

Date of Test: 2024/4/19 - 2024/5/21

Date of report issued: 2024/5/23

*The equipment complies with the requirements according to the standard(s) or Specification above, it is applicable only to the tested sample identified in the report.

Prepared by:

Bob

Reviewed by:

Seven Zhan

Approved by:

Tiger



*The test report merely corresponds to the test sample. It is not permitted to copy extracts of these test result without the written permission of the test laboratory.

Revision History

Version	Description	Date of Issue
V1.0	Original	2024/5/23



2 Contents

	Page
1 COVER PAGE	1
2 CONTENTS	3
3 TEST SUMMARY	4
4 MEASUREMENT UNCERTAINTY	4
5 GENERAL INFORMATION	5
5.1 CLIENT INFORMATION	5
5.2 GENERAL DESCRIPTION OF EUT	5
5.3 TEST MODE(S).....	6
5.4 TEST FACILITY	7
5.5 DESCRIPTION OF SUPPORT UNITS	7
5.6 ADDITIONAL INSTRUCTIONS	7
5.7 ANTENNA INFORMATION	7
5.8 OTHERS.....	7
6 TECHNICAL REQUIREMENT AND MEASUREMENT DATA	8
6.1 GENERALLY REQUIREMENT	8
6.2 DUTY CYCLE	9
6.3 CONDUCTED PEAK OUTPUT POWER.....	10
6.4 CHANNEL BANDWIDTH.....	11
6.5 POWER SPECTRAL DENSITY	12
6.6 CONDUCTED EMISSION	13
6.7 RADIATED SPURIOUS EMISSION	14
6.8 CONDUCTED EMISSIONS	38
7 TEST SETUP PHOTO	41
8 EUT CONSTRUCTIONAL DETAILS	41
ANNEX A --TEST INSTRUMENTS LIST	42

3 Test Summary

Test items	Basics standards	Result
Antenna requirement	FCC part 15.203/15.247 (c)	Pass
AC Power Line Conducted Emission	FCC part 15.207	Pass
Conducted Peak Output Power	FCC part 15.247 (b)(3)	Pass
Channel Bandwidth & 99% OCB	FCC part 15.247 (a)(2)	Pass
Power Spectral Density	FCC part 15.247 (e)	Pass
Band Edge	FCC part 15.247(d)	Pass
Spurious Emission	FCC part 15.205/15.209	Pass

Notes:

1: NA =Not Applicable

2: Determining compliance based on the results of the compliance measurement, not taking into account measurement uncertainty. If necessary, the applicant shall informing test lab in advance

3: Additions, Deviations and Exclusions from Standards: None.

4 Measurement Uncertainty

Where relevant, the following measurement uncertainty levels have been estimated for tests performed on the EUT as specified in CISPR 16-4-2:

The measurement uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.

Item	Uncertainty (\pm) (k=2, 95%)	
Output Power, Conducted	0.54	
Power Spectral Density, Conducted	1.28	
Spurious Emissions, Conducted	1.28	
Radiated Emissions(<1GHz)	9kHz~30MHz	2.6
	30MHz~1GHz	5.08
Radiated Emissions(>1GHz)	1GHz~6GHz	4.02
	6GHz~18GHz	4.62
	18GHz~40GHz	4.7
Occupied Bandwidth	1.14	
Conducted Emissions—AC mains	9kHz~150KHz	1.76
	150kHz~30MHz	2.52
Conducted Emissions—Telecom	2.64	

5 General Information

5.1 Client Information

Applicant: SHENZHEN ELECTRON TECHNOLOGY CO., LTD.
Address of applicant: Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Bao'an, Shenzhen, China.
Manufacturer: Same as applicant
Address of Manufacturer: Same as applicant
Factory: Same as applicant
Address of Factory: Same as applicant

5.2 General Description of EUT

Product Name:	Android Tablet
Model No.:	EP1095T
Test sample(s) ID:	24041600602
Sample(s) Status:	Continuously transmitter
S/N:	/
Hardware version:	T30-T616-V2.0
Software version:	039_ums9230_6h10_Natv_k515__t30_full_YLD_EP1095T_20240410
Operation Frequency:	2412MHz~2462MHz
Technic and Modulation:	802.11b: DSSS 802.11g/802.11n: OFDM
Supported bandwidth:	20MHz, 40MHz
Antenna gain:	Refer to section 5.7 for details
Power supply:	AC/DC Adapter Model No.: JHD-AP013U-050200BB-B INPUT: AC 100-240V, 50/60Hz, 0.35A OUTPUT: DC 5V, 2.0A Or 7000mAh, 3.8V, 26.6Wh Lithium-ion Rechargeable Battery

5.3 Test mode(s)

Mode 1:	continuously transmitting, with its lowest data rate which emit the max power level
Mode 2:	
Mode 3:	

Channel list for 802.11							
Channel	Frequency	Channel	Frequency	Channel	Frequency	Channel	Frequency
1	2412MHz	4	2427MHz	7	2442MHz	10	2457MHz
2	2417MHz	5	2432MHz	8	2447MHz	11	2462MHz
3	2422MHz	6	2437MHz	9	2452MHz	X	



5.4 Test Facility

The test facility is recognized, certified, or accredited by these organizations:	FCC Accredited Lab Test Firm Registration Number: 638130 Designation Number: CN1359
	IC Registration Lab CAB Identifier No. CN0154
	A2LA Accreditation Lab Certificate No.:7057.01

Test Performed at:	Name GuangDong Set Sail Testing Co., Ltd.
	Address 101, No.19, Tianxin Hudie 1st Road, Huangjiang Town, Dongguan, Guangdong, China

5.5 Description of Support Units

None

5.6 Additional Instructions

Test Software	Test software built-in by manufacturer
Power level setup	Default

5.7 Antenna Information

Ant	Manufacturer	Model	Antenna Type	Antenna Gain (dBi)
1	SHENZHEN Xingyuanchuang TECHNOLOGY CO.,LTD	/	/	1.36

All above information provided by the applicant which is fully responsible for those information.

5.8 Others

<p>The laboratory responsible for all the information provided in the report, except those information provided by the applicant. The applicant shall fully responsible for the information they provided. The report would be invalid without a stamp of test laboratory and the signatures of compiler and approver. The laboratory has not been responsible for the sampling stage; the test report merely corresponds to the test sample received. Any objection to the test report shall submitted to the test laboratory within 15 days from the date of receipt of the report. It is not permitted to copy extracts of these test result without the written permission of the test laboratory.</p>

6 Technical Requirement and Measurement Data

6.1 Generally requirement

15.203 requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.


15.247(c) (1)(i) requirement:

An intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section. The manufacturer may design the unit so that a broken antenna can be replaced by the user, but the use of a standard antenna jack or electrical connector is prohibited.

EUT Antenna:


Reference to the appendix II for details

6.2 Duty Cycle


Limit
Report for use
Block diagram of Test Setup
 <p>The diagram illustrates the test setup. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p>
Test Instrument
Refer to Annex A for details
Test Procedures
<p>The transmitter output connected to the Spectrum Analyzer. Test according to Procedure 6.0)b in KDB 558074 v05r02.</p> <ol style="list-style-type: none"> 1.RBW=8 MHz(the largest available value) 2.VBW=8 MHz(>RBW) 3.SPAN = 0 Hz 4.Detector = Peak 5.Number of points in sweep: 30001 6.Trace mode: Clear write 7.Measure T_{total} and T_{on} 8.Calculate Duty Cycle = T_{on}/T_{total} and Duty Cycle Factor = $10\log(1/Duty\ Cycle)$
Verdict
Pass

Measurement Data: The detailed test data see Appendix


6.3 Conducted Peak Output Power

Limit
1W(30dBm)
Block diagram of Test Setup
 <p>The diagram illustrates the test setup. A Power Meter is connected to an E.U.T. (Equipment Under Test) via a red cable. Both are placed on a Non-Conducted Table. Below the table is a Ground Reference Plane.</p>
Test Instrument
Refer to Annex A for details
Test Procedures
Test applies to KDB558074 D01 15.247 Meas Guidance v05r02
Verdict
Pass

Measurement Data: The detailed test data see Appendix




6.4 Channel Bandwidth

Limit
>500KHz
Block diagram of Test Setup
 <p>The diagram shows a Spectrum Analyzer and an E.U.T (Equipment Under Test) connected by a red cable. They are positioned on a 'Non-Conducted Table' which is supported by a 'Ground Reference Plane'.</p>
Test Instrument
Refer to Annex A for details
Test Procedures
Test applies to KDB558074 D01 15.247 Meas Guidance v05r02
Verdict
Pass


Measurement Data: The detailed test data see Appendix

6.5 Power Spectral Density

Limit
8dBm/3kHz
Block diagram of Test Setup
 <p>The diagram shows a Spectrum Analyzer on the left and an E.U.T. on the right, connected by a red cable. They are both on a table labeled 'Non-Conducted Table'. Below the table is a 'Ground Reference Plane'.</p>
Test Instrument
Refer to Annex A for details
Test Procedures
Test applies to KDB558074 D01 15.247 Meas Guidance v05r02
Verdict
Pass

Measurement Data: The detailed test data see Appendix

6.6 Conducted Emission

<p>Limit</p> <p>In any 100 kHz bandwidth outside the frequency band in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement.</p>
<p>Block diagram of Test Setup</p>  <p>The diagram illustrates the test setup for conducted emission. A Spectrum Analyzer is connected via a red cable to an E.U.T. (Equipment Under Test). Both are placed on a Non-Conducted Table, which is supported by a Ground Reference Plane.</p>
<p>Test Instrument</p> <p>Refer to Annex A for details</p>
<p>Test Procedures</p> <p>Test applies to KDB558074 D01 15.247 Meas Guidance v05r02</p>
<p>Verdict</p> <p>Pass</p>

Measurement Data: The detailed test data see Appendix

6.7 Radiated Spurious Emission


Limit		
Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
0.009–0.490	2400/F(kHz)	300
0.490–1.705	24000/F(kHz)	30
1.705–30.0	30	30
30–88	100 **	3
88–216	150 **	3
216–960	200 **	3
Above 960	500	3


** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54–72 MHz, 76–88 MHz, 174–216 MHz or 470–806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.

Block diagram of Test Setup


For table-top equipment
 For floor standing equipment


For radiated emissions from 9kHz to 30MHz







For radiated emissions from 30MHz to 1GHz





For radiated emissions above 1GHz






Test Instrument

Refer to Annex A for details
Test Procedures
Test applies to KDB558074 D01 15.247 Meas Guidance v05r02 & C63.10
Verdict
Pass

*Note: The emission from 9 kHz to 30MHz was pre-tested and found the result was 20dB lower than the limit, and according to 15.31(o), the test result no need to reported.
The emissions above 18GHz is same as ambient noise so no report*




Test Result(30M~1GHz)			
Test mode	Mode 1	Polarity	Horizontal
Test voltage	AC 120V/60Hz	Temp. /Hum.	25 °C/60%



NO.	Freq. [MHz]	Factor [dB]	QP Value [dBµV/m]	QP Limit [dBµV/m]	QP Margin [dB]	Polarity	Verdict
1	354.5857	-12.79	32.32	46.00	13.68	Horizontal	PASS
2	358.6487	-12.69	33.22	46.00	12.78	Horizontal	PASS
3	366.9151	-12.46	33.43	46.00	12.57	Horizontal	PASS
4	415.9057	-11.34	31.15	46.00	14.85	Horizontal	PASS
5	465.6884	-10.66	36.44	46.00	9.56	Horizontal	PASS
6	767.4523	-6.58	33.32	46.00	12.68	Horizontal	PASS

Note: Final Level = Receiver Read level + Factor
 Factor = Antenna Factor + Cable Loss - Preamplifier Factor
 Only the worst case report (802.11b 2462MHz)

Test Result(30M~1GHz)			
Test mode	Mode 1	Polarity	Vertical
Test voltage	AC 120V/60Hz	Temp. /Hum.	25 °C/60%



NO.	Freq. [MHz]	Factor [dB]	QP Value [dBμV/m]	QP Limit [dBμV/m]	QP Margin [dB]	Polarity	Verdict
1	30.7992	-18.59	24.75	40.00	15.25	Vertical	PASS
2	33.768	-18.23	27.65	40.00	12.35	Vertical	PASS
3	54.9709	-16.04	25.38	40.00	14.62	Vertical	PASS
4	84.2358	-20.73	25.95	40.00	14.05	Vertical	PASS
5	124.8525	-19.33	28.55	43.50	14.95	Vertical	PASS
6	128.2912	-19.72	27.27	43.50	16.23	Vertical	PASS

Note: Final Level = Receiver Read level + Factor
 Factor = Antenna Factor + Cable Loss – Preamplifier Factor
 Only the worst case repor (802.11b 2462MHz)

Test Result(Emissions in Non-restricted band)								
Test mode	Mode 1			Temp. /Hum.	25 °C/60%			
Test voltage	AC 120V/60Hz			Test channel	802.11b, lowest			
Peak value:								
Frequency (MHz)	Read Level (dBUV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBUV/m)	Limit Line (dBUV/m)	Over Limit (dB)	polarization
4824	53.99	33.63	7.78	53.71	41.69	74	-32.31	Vertical
7236	53.16	36.57	9.66	53.27	46.12	74	-27.88	Vertical
9648	53.07	39.12	11.41	53.24	50.36	74	-23.64	Vertical
4824	53.78	33.63	7.78	53.71	41.48	74	-32.52	Horizontal
7236	53.38	36.57	9.66	53.27	46.34	74	-27.66	Horizontal
9648	53.95	39.12	11.41	53.24	51.24	74	-22.76	Horizontal
Average value:								
Frequency (MHz)	Read Level (dBUV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBUV/m)	Limit Line (dBUV/m)	Over Limit (dB)	polarization
4824	46.56	33.63	7.78	53.71	34.26	54	-19.74	Vertical
7236	47.65	36.57	9.66	53.27	40.61	54	-13.39	Vertical
9648	46.82	39.12	11.41	53.24	44.11	54	-9.89	Vertical
4824	46.28	33.63	7.78	53.71	33.98	54	-20.02	Horizontal
7236	46.76	36.57	9.66	53.27	39.72	54	-14.28	Horizontal
9648	46.24	39.12	11.41	53.24	43.53	54	-10.47	Horizontal
Note: Final Level = Receiver Read level + Factor Factor = Antenna Factor + Cable Loss – Pre-amplifier Factor								

Test Result(Emissions in Non-restricted band)								
Test mode	Mode 1			Temp. /Hum.	25 °C/60%			
Test voltage	AC 120V/60Hz			Test channel	802.11b, Middle			
Peak value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874	54.52	33.55	7.76	53.71	42.12	74	-31.88	Vertical
7311	53.23	36.56	9.63	53.26	46.16	74	-27.84	Vertical
9748	53.14	39.1	11.38	53.25	50.37	74	-23.63	Vertical
4874	53.17	33.55	7.76	53.71	40.77	74	-33.23	Horizontal
7311	55.1	36.56	9.63	53.26	48.03	74	-25.97	Horizontal
9748	53.1	39.1	11.38	53.25	50.33	74	-23.67	Horizontal
Average value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874	48.39	33.55	7.76	53.71	35.99	54	-18.01	Vertical
7311	47.48	36.56	9.63	53.26	40.41	54	-13.59	Vertical
9748	49.45	39.1	11.38	53.25	46.68	54	-7.32	Vertical
4874	48.75	33.55	7.76	53.71	36.35	54	-17.65	Horizontal
7311	47.97	36.56	9.63	53.26	40.9	54	-13.1	Horizontal
9748	49.7	39.1	11.38	53.25	46.93	54	-7.07	Horizontal
Note: Final Level =Receiver Read level + Factor Factor= Antenna Factor + Cable Loss – Preamplifier Factor								

Test Result(Emissions in Non-restricted band)								
Test mode	Mode 1			Temp. /Hum.	25 °C/60%			
Test voltage	AC 120V/60Hz			Test channel	802.11b, Highest			
Peak value:								
Frequency (MHz)	Read Level (dBUV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBUV/m)	Limit Line (dBUV/m)	Over Limit (dB)	polarization
4924	53.87	33.69	7.8	53.71	41.65	74	-32.35	Vertical
7386	53.98	36.58	9.68	53.28	46.96	74	-27.04	Vertical
9848	53.95	39.14	11.44	53.23	51.3	74	-22.7	Vertical
4924	53.01	33.69	7.8	53.71	40.79	74	-33.21	Horizontal
7386	54.38	36.58	9.68	53.28	47.36	74	-26.64	Horizontal
9848	53.12	39.14	11.44	53.23	50.47	74	-23.53	Horizontal
Average value:								
Frequency (MHz)	Read Level (dBUV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBUV/m)	Limit Line (dBUV/m)	Over Limit (dB)	polarization
4924	48.47	33.69	7.8	53.71	36.25	54	-17.75	Vertical
7386	46.23	36.58	9.68	53.28	39.21	54	-14.79	Vertical
9848	46.82	39.14	11.44	53.23	44.17	54	-9.83	Vertical
4924	47.59	33.69	7.8	53.71	35.37	54	-18.63	Horizontal
7386	46.74	36.58	9.68	53.28	39.72	54	-14.28	Horizontal
9848	46.74	39.14	11.44	53.23	44.09	54	-9.91	Horizontal
Note: Final Level = Receiver Read level + Factor Factor = Antenna Factor + Cable Loss – Pre-amplifier Factor								

Test Result(Emissions in Non-restricted band)								
Test mode	Mode 1			Temp. /Hum.	25 °C/60%			
Test voltage	AC 120V/60Hz			Test channel	802.11g, lowest			
Peak value:								
Frequency (MHz)	Read Level (dBUV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBUV/m)	Limit Line (dBUV/m)	Over Limit (dB)	polarization
4824	53.69	33.41	7.72	53.72	41.1	74	-32.9	Vertical
7236	53.64	36.55	9.58	53.25	46.52	74	-27.48	Vertical
9648	53.32	39.06	11.32	53.27	50.43	74	-23.57	Vertical
4824	53.15	33.41	7.72	53.72	40.56	74	-33.44	Horizontal
7236	54.39	36.55	9.58	53.25	47.27	74	-26.73	Horizontal
9648	53.9	39.06	11.32	53.27	51.01	74	-22.99	Horizontal
Average value:								
Frequency (MHz)	Read Level (dBUV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBUV/m)	Limit Line (dBUV/m)	Over Limit (dB)	polarization
4824	47.46	33.41	7.72	53.72	34.87	54	-19.13	Vertical
7236	47.48	36.55	9.58	53.25	40.36	54	-13.64	Vertical
9648	47.66	39.06	11.32	53.27	44.77	54	-9.23	Vertical
4824	49.69	33.41	7.72	53.72	37.1	54	-16.9	Horizontal
7236	49.23	36.55	9.58	53.25	42.11	54	-11.89	Horizontal
9648	48.67	39.06	11.32	53.27	45.78	54	-8.22	Horizontal
Note: Final Level = Receiver Read level + Factor Factor = Antenna Factor + Cable Loss – Pre-amplifier Factor								

Test Result(Emissions in Non-restricted band)								
Test mode	Mode 1			Temp. /Hum.	25 °C/60%			
Test voltage	AC 120V/60Hz			Test channel	802.11b, Middle			
Peak value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874	54.38	33.55	7.76	53.71	41.98	74	-32.02	Vertical
7311	53.73	36.56	9.63	53.26	46.66	74	-27.34	Vertical
9748	53.92	39.1	11.38	53.25	51.15	74	-22.85	Vertical
4874	54.91	33.55	7.76	53.71	42.51	74	-31.49	Horizontal
7311	54.71	36.56	9.63	53.26	47.64	74	-26.36	Horizontal
9748	53.29	39.1	11.38	53.25	50.52	74	-23.48	Horizontal
Average value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874	47.9	33.55	7.76	53.71	35.5	54	-18.5	Vertical
7311	48.68	36.56	9.63	53.26	41.61	54	-12.39	Vertical
9748	49.58	39.1	11.38	53.25	46.81	54	-7.19	Vertical
4874	50.99	33.55	7.76	53.71	38.59	54	-15.41	Horizontal
7311	48.56	36.56	9.63	53.26	41.49	54	-12.51	Horizontal
9748	48.07	39.1	11.38	53.25	45.3	54	-8.7	Horizontal
Note: Final Level = Receiver Read level + Factor Factor = Antenna Factor + Cable Loss – Pre-amplifier Factor								

Test Result(Emissions in Non-restricted band)								
Test mode	Mode 1			Temp. /Hum.	25 °C/60%			
Test voltage	AC 120V/60Hz			Test channel	802.11g, Highest			
Peak value:								
Frequency (MHz)	Read Level (dBUV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBUV/m)	Limit Line (dBUV/m)	Over Limit (dB)	polarization
4924	54.69	33.69	7.8	53.71	42.47	74	-31.53	Vertical
7386	53.68	36.58	9.68	53.28	46.66	74	-27.34	Vertical
9848	53.85	39.14	11.44	53.23	51.2	74	-22.8	Vertical
4924	53.68	33.69	7.8	53.71	41.46	74	-32.54	Horizontal
7386	54.27	36.58	9.68	53.28	47.25	74	-26.75	Horizontal
9848	53.85	39.14	11.44	53.23	51.2	74	-22.8	Horizontal
Average value:								
Frequency (MHz)	Read Level (dBUV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBUV/m)	Limit Line (dBUV/m)	Over Limit (dB)	polarization
4924	46.36	33.69	7.8	53.71	34.14	54	-19.86	Vertical
7386	48.17	36.58	9.68	53.28	41.15	54	-12.85	Vertical
9848	47.71	39.14	11.44	53.23	45.06	54	-8.94	Vertical
4924	46.02	33.69	7.8	53.71	33.8	54	-20.2	Horizontal
7386	47.67	36.58	9.68	53.28	40.65	54	-13.35	Horizontal
9848	46.69	39.14	11.44	53.23	44.04	54	-9.96	Horizontal
<p>Note: Final Level =Receiver Read level + Factor Factor= Antenna Factor + Cable Loss – Preamplifier Factor</p>								

Test Result(Emissions in Non-restricted band)								
Test mode	Mode 1			Temp. /Hum.	25 °C/60%			
Test voltage	AC 120V/60Hz			Test channel	802.11n20, lowest			
Peak value:								
Frequency (MHz)	Read Level (dBUV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBUV/m)	Limit Line (dBUV/m)	Over Limit (dB)	polarization
4824	53.6	33.41	7.72	53.72	41.01	74	-32.99	Vertical
7236	54.9	36.55	9.58	53.25	47.78	74	-26.22	Vertical
9648	54.8	39.06	11.32	53.27	51.91	74	-22.09	Vertical
4824	53.84	33.41	7.72	53.72	41.25	74	-32.75	Horizontal
7236	54.47	36.55	9.58	53.25	47.35	74	-26.65	Horizontal
9648	53.11	39.06	11.32	53.27	50.22	74	-23.78	Horizontal
Average value:								
Frequency (MHz)	Read Level (dBUV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBUV/m)	Limit Line (dBUV/m)	Over Limit (dB)	polarization
4824	47.66	33.41	7.72	53.72	35.07	54	-18.93	Vertical
7236	48.44	36.55	9.58	53.25	41.32	54	-12.68	Vertical
9648	50.97	39.06	11.32	53.27	48.08	54	-5.92	Vertical
4824	48.15	33.41	7.72	53.72	35.56	54	-18.44	Horizontal
7236	47.79	36.55	9.58	53.25	40.67	54	-13.33	Horizontal
9648	49.38	39.06	11.32	53.27	46.49	54	-7.51	Horizontal
Note: Final Level = Receiver Read level + Factor Factor = Antenna Factor + Cable Loss – Pre-amplifier Factor								

Test Result(Emissions in Non-restricted band)								
Test mode	Mode 1			Temp. /Hum.	25 °C/60%			
Test voltage	AC 120V/60Hz			Test channel	802.11n20, Middle			
Peak value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874	53.08	33.55	7.76	53.71	40.68	74	-33.32	Vertical
7311	54.64	36.56	9.63	53.26	47.57	74	-26.43	Vertical
9748	53.35	39.1	11.38	53.25	50.58	74	-23.42	Vertical
4874	53.12	33.55	7.76	53.71	40.72	74	-33.28	Horizontal
7311	53.94	36.56	9.63	53.26	46.87	74	-27.13	Horizontal
9748	53.24	39.1	11.38	53.25	50.47	74	-23.53	Horizontal
Average value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874	48.48	33.55	7.76	53.71	36.08	54	-17.92	Vertical
7311	48.12	36.56	9.63	53.26	41.05	54	-12.95	Vertical
9748	48.95	39.1	11.38	53.25	46.18	54	-7.82	Vertical
4874	49.15	33.55	7.76	53.71	36.75	54	-17.25	Horizontal
7311	48.91	36.56	9.63	53.26	41.84	54	-12.16	Horizontal
9748	48.42	39.1	11.38	53.25	45.65	54	-8.35	Horizontal
<p>Note: Final Level =Receiver Read level + Factor Factor= Antenna Factor + Cable Loss – Preamplifier Factor</p>								

Test Result(Emissions in Non-restricted band)								
Test mode	Mode 1			Temp. /Hum.	25 °C/60%			
Test voltage	AC 120V/60Hz			Test channel	802.11n20, Highest			
Peak value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924	55.86	33.69	7.8	53.71	43.64	74	-30.36	Vertical
7386	54.5	36.58	9.68	53.28	47.48	74	-26.52	Vertical
9848	53.09	39.14	11.44	53.23	50.44	74	-23.56	Vertical
4924	53.05	33.69	7.8	53.71	40.83	74	-33.17	Horizontal
7386	53.3	36.58	9.68	53.28	46.28	74	-27.72	Horizontal
9848	53.17	39.14	11.44	53.23	50.52	74	-23.48	Horizontal
Average value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4924	47.55	33.69	7.8	53.71	35.33	54	-18.67	Vertical
7386	47.26	36.58	9.68	53.28	40.24	54	-13.76	Vertical
9848	47.94	39.14	11.44	53.23	45.29	54	-8.71	Vertical
4924	49.01	33.69	7.8	53.71	36.79	54	-17.21	Horizontal
7386	47.01	36.58	9.68	53.28	39.99	54	-14.01	Horizontal
9848	47.78	39.14	11.44	53.23	45.13	54	-8.87	Horizontal
<p>Note: Final Level = Receiver Read level + Factor Factor = Antenna Factor + Cable Loss – Pre-amplifier Factor</p>								

Test Result(Emissions in Non-restricted band)								
Test mode	Mode 1			Temp. /Hum.	25 °C/60%			
Test voltage	AC 120V/60Hz			Test channel	802.11n40, lowest			
Peak value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4844	54.41	33.46	7.74	53.72	41.89	74	-32.11	Vertical
7266	54.73	36.55	9.6	53.25	47.63	74	-26.37	Vertical
9688	53.16	39.08	11.34	53.26	50.32	74	-23.68	Vertical
4844	53.52	33.46	7.74	53.72	41	74	-33	Horizontal
7266	55.63	36.55	9.6	53.25	48.53	74	-25.47	Horizontal
9688	54.46	39.08	11.34	53.26	51.62	74	-22.38	Horizontal
Average value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4844	47.77	33.46	7.74	53.72	35.25	54	-18.75	Vertical
7266	48.37	36.55	9.6	53.25	41.27	54	-12.73	Vertical
9688	48.29	39.08	11.34	53.26	45.45	54	-8.55	Vertical
4844	47.89	33.46	7.74	53.72	35.37	54	-18.63	Horizontal
7266	49.3	36.55	9.6	53.25	42.2	54	-11.8	Horizontal
9688	49	39.08	11.34	53.26	46.16	54	-7.84	Horizontal
Note: Final Level =Receiver Read level + Factor Factor= Antenna Factor + Cable Loss – Preamplifier Factor								

Test Result(Emissions in Non-restricted band)								
Test mode	Mode 1			Temp. /Hum.	25 °C/60%			
Test voltage	AC 120V/60Hz			Test channel	802.11n40, Middle			
Peak value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874	53.43	33.55	7.76	53.71	41.03	74	-32.97	Vertical
7311	53.34	36.56	9.63	53.26	46.27	74	-27.73	Vertical
9748	53.07	39.1	11.38	53.25	50.3	74	-23.7	Vertical
4874	54.35	33.55	7.76	53.71	41.95	74	-32.05	Horizontal
7311	54.71	36.56	9.63	53.26	47.64	74	-26.36	Horizontal
9748	53.6	39.1	11.38	53.25	50.83	74	-23.17	Horizontal
Average value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4874	47.09	33.55	7.76	53.71	34.69	54	-19.31	Vertical
7311	49.8	36.56	9.63	53.26	42.73	54	-11.27	Vertical
9748	47.34	39.1	11.38	53.25	44.57	54	-9.43	Vertical
4874	49.57	33.55	7.76	53.71	37.17	54	-16.83	Horizontal
7311	47.52	36.56	9.63	53.26	40.45	54	-13.55	Horizontal
9748	48.43	39.1	11.38	53.25	45.66	54	-8.34	Horizontal
Note: Final Level =Receiver Read level + Factor Factor= Antenna Factor + Cable Loss – Preamplifier Factor								

Test Result(Emissions in Non-restricted band)								
Test mode	Mode 1			Temp. /Hum.	25 °C/60%			
Test voltage	AC 120V/60Hz			Test channel	802.11n40, Highest			
Peak value:								
Frequency (MHz)	Read Level (dBUV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBUV/m)	Limit Line (dBUV/m)	Over Limit (dB)	polarization
4904	53.94	33.63	7.78	53.71	41.64	74	-32.36	Vertical
7356	54.75	36.57	9.66	53.27	47.71	74	-26.29	Vertical
9808	54.01	39.12	11.41	53.24	51.3	74	-22.7	Vertical
4904	53.47	33.63	7.78	53.71	41.17	74	-32.83	Horizontal
7356	53.53	36.57	9.66	53.27	46.49	74	-27.51	Horizontal
9808	53.03	39.12	11.41	53.24	50.32	74	-23.68	Horizontal
Average value:								
Frequency (MHz)	Read Level (dBUV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBUV/m)	Limit Line (dBUV/m)	Over Limit (dB)	polarization
4904	46.93	33.63	7.78	53.71	34.63	54	-19.37	Vertical
7356	47.46	36.57	9.66	53.27	40.42	54	-13.58	Vertical
9808	45.15	39.12	11.41	53.24	42.44	54	-11.56	Vertical
4904	45.07	33.63	7.78	53.71	32.77	54	-21.23	Horizontal
7356	47.78	36.57	9.66	53.27	40.74	54	-13.26	Horizontal
9808	45.86	39.12	11.41	53.24	43.15	54	-10.85	Horizontal
<p>Note: Final Level = Receiver Read level + Factor Factor = Antenna Factor + Cable Loss – Pre-amplifier Factor</p>								

Test Result(Emissions in Restricted band)								
Test mode	Mode 1			Temp. /Hum.	25 °C/60%			
Test voltage	AC 120V/60Hz			Test channel	802.11b, lowest			
Peak value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310	58.89	27.71	5.3	53.84	38.06	74	-35.94	Horizontal
2390	66.06	27.91	5.4	53.82	45.55	74	-28.45	Horizontal
2310	61.24	27.71	5.3	53.84	40.41	74	-33.59	Vertical
2390	70.43	27.91	5.4	53.82	49.92	74	-24.08	Vertical
Average value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310	47.51	27.71	5.3	53.84	26.68	54	-27.32	Horizontal
2390	53.8	27.91	5.4	53.82	33.29	54	-20.71	Horizontal
2310	50.28	27.71	5.3	53.84	29.45	54	-24.55	Vertical
2390	56.47	27.91	5.4	53.82	35.96	54	-18.04	Vertical
<p>Note: Final Level =Receiver Read level + Factor Factor= Antenna Factor + Cable Loss – Pre-amplifier Factor The emission levels of other frequencies are very lower than the limit and not show in test report.</p>								

Test Result(Emissions in Restricted band)								
Test mode	Mode 1		Temp. /Hum.		25 °C/60%			
Test voltage	AC 120V/60Hz		Test channel		802.11b, Highest			
Peak value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	60.19	28.16	5.51	53.8	40.06	74	-33.94	Horizontal
2500	54.21	28.2	5.53	53.8	34.14	74	-39.86	Horizontal
2483.5	62.73	28.16	5.51	53.8	42.6	74	-31.4	Vertical
2500	55.38	28.2	5.53	53.8	35.31	74	-38.69	Vertical
Average value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	52.84	28.16	5.51	53.8	32.71	54	-21.29	Horizontal
2500	44.17	28.2	5.53	53.8	24.1	54	-29.9	Horizontal
2483.5	53.67	28.16	5.51	53.8	33.54	54	-20.46	Vertical
2500	48.15	28.2	5.53	53.8	28.08	54	-25.92	Vertical
<p>Note: Final Level = Receiver Read level + Factor Factor = Antenna Factor + Cable Loss – Pre-amplifier Factor The emission levels of other frequencies are very lower than the limit and not show in test report.</p>								

Test Result(Emissions in Restricted band)								
Test mode	Mode 1			Temp. /Hum.	25 °C/60%			
Test voltage	AC 120V/60Hz			Test channel	802.11g, lowest			
Peak value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310	59.06	27.71	5.3	53.84	38.23	74	-35.77	Horizontal
2390	66.5	27.91	5.4	53.82	45.99	74	-28.01	Horizontal
2310	61.06	27.71	5.3	53.84	40.23	74	-33.77	Vertical
2390	68.6	27.91	5.4	53.82	48.09	74	-25.91	Vertical
Average value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310	51.73	27.71	5.3	53.84	30.9	54	-23.1	Horizontal
2390	54.56	27.91	5.4	53.82	34.05	54	-19.95	Horizontal
2310	50.81	27.71	5.3	53.84	29.98	54	-24.02	Vertical
2390	56.7	27.91	5.4	53.82	36.19	54	-17.81	Vertical
<p>Note: Final Level = Receiver Read level + Factor Factor = Antenna Factor + Cable Loss – Pre-amplifier Factor The emission levels of other frequencies are very lower than the limit and not show in test report.</p>								

Test Result(Emissions in Restricted band)								
Test mode	Mode 1		Temp. /Hum.	25 °C/60%				
Test voltage	AC 120V/60Hz		Test channel	802.11g, Highest				
Peak value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	60.76	28.16	5.51	53.8	40.63	74	-33.37	Horizontal
2500	52.8	28.2	5.53	53.8	32.73	74	-41.27	Horizontal
2483.5	62.06	28.16	5.51	53.8	41.93	74	-32.07	Vertical
2500	55.59	28.2	5.53	53.8	35.52	74	-38.48	Vertical
Average value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	50.32	28.16	5.51	53.8	30.19	54	-23.81	Horizontal
2500	45.76	28.2	5.53	53.8	25.69	54	-28.31	Horizontal
2483.5	50.52	28.16	5.51	53.8	30.39	54	-23.61	Vertical
2500	46.63	28.2	5.53	53.8	26.56	54	-27.44	Vertical
<p>Note: Final Level = Receiver Read level + Factor Factor = Antenna Factor + Cable Loss - Pre-amplifier Factor The emission levels of other frequencies are very lower than the limit and not show in test report.</p>								

Test Result(Emissions in Restricted band)								
Test mode	Mode 1			Temp. /Hum.	25 °C/60%			
Test voltage	AC 120V/60Hz			Test channel	802.11n20, lowest			
Peak value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310	58.46	27.71	5.3	53.84	37.63	74	-36.37	Horizontal
2390	66.62	27.91	5.4	53.82	46.11	74	-27.89	Horizontal
2310	58.67	27.71	5.3	53.84	37.84	74	-36.16	Vertical
2390	69.33	27.91	5.4	53.82	48.82	74	-25.18	Vertical
Average value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310	51.79	27.71	5.3	53.84	30.96	54	-23.04	Horizontal
2390	58.24	27.91	5.4	53.82	37.73	54	-16.27	Horizontal
2310	52.53	27.71	5.3	53.84	31.7	54	-22.3	Vertical
2390	58.7	27.91	5.4	53.82	38.19	54	-15.81	Vertical
<p>Note: Final Level = Receiver Read level + Factor Factor = Antenna Factor + Cable Loss – Preamplifier Factor The emission levels of other frequencies are very lower than the limit and not show in test report.</p>								

Test Result(Emissions in Restricted band)								
Test mode	Mode 1		Temp. /Hum.		25 °C/60%			
Test voltage	AC 120V/60Hz		Test channel		802.11n20, Highest			
Peak value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	60.28	28.16	5.51	53.8	40.15	74	-33.85	Horizontal
2500	51.53	28.2	5.53	53.8	31.46	74	-42.54	Horizontal
2483.5	60.75	28.16	5.51	53.8	40.62	74	-33.38	Vertical
2500	56.18	28.2	5.53	53.8	36.11	74	-37.89	Vertical
Average value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	49.68	28.16	5.51	53.8	29.55	54	-24.45	Horizontal
2500	45.89	28.2	5.53	53.8	25.82	54	-28.18	Horizontal
2483.5	53	28.16	5.51	53.8	32.87	54	-21.13	Vertical
2500	46.77	28.2	5.53	53.8	26.7	54	-27.3	Vertical
<p>Note: Final Level = Receiver Read level + Factor Factor = Antenna Factor + Cable Loss – Pre-amplifier Factor The emission levels of other frequencies are very lower than the limit and not show in test report.</p>								



Test Result(Emissions in Restricted band)								
Test mode	Mode 1			Temp. /Hum.	25 °C/60%			
Test voltage	AC 120V/60Hz			Test channel	802.11n40, lowest			
Peak value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310	60.68	27.71	5.3	53.84	39.85	74	-34.15	Horizontal
2390	66.06	27.91	5.4	53.82	45.55	74	-28.45	Horizontal
2310	60.07	27.71	5.3	53.84	39.24	74	-34.76	Vertical
2390	71.48	27.91	5.4	53.82	50.97	74	-23.03	Vertical
Average value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamplifier Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2310	49.4	27.71	5.3	53.84	28.57	54	-25.43	Horizontal
2390	55.74	27.91	5.4	53.82	35.23	54	-18.77	Horizontal
2310	52.84	27.71	5.3	53.84	32.01	54	-21.99	Vertical
2390	58.96	27.91	5.4	53.82	38.45	54	-15.55	Vertical
<p>Note: Final Level = Receiver Read level + Factor Factor = Antenna Factor + Cable Loss – Preamplifier Factor The emission levels of other frequencies are very lower than the limit and not show in test report.</p>								

Test Result(Emissions in Restricted band)								
Test mode	Mode 1		Temp. /Hum.		25 °C/60%			
Test voltage	AC 120V/60Hz		Test channel		802.11n40, Highest			
Peak value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	59.73	28.16	5.51	53.8	39.6	74	-34.4	Horizontal
2500	54.29	28.2	5.53	53.8	34.22	74	-39.78	Horizontal
2483.5	60	28.16	5.51	53.8	39.87	74	-34.13	Vertical
2500	56	28.2	5.53	53.8	35.93	74	-38.07	Vertical
Average value:								
Frequency (MHz)	Read Level (dBuV)	Antenna Factor (dB/m)	Cable Loss (dB)	Preamp Factor (dB)	Level (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	Polarization
2483.5	49.58	28.16	5.51	53.8	29.45	54	-24.55	Horizontal
2500	46.35	28.2	5.53	53.8	26.28	54	-27.72	Horizontal
2483.5	51.67	28.16	5.51	53.8	31.54	54	-22.46	Vertical
2500	46.52	28.2	5.53	53.8	26.45	54	-27.55	Vertical
<p>Note: Final Level = Receiver Read level + Factor Factor = Antenna Factor + Cable Loss – Pre-amplifier Factor The emission levels of other frequencies are very lower than the limit and not show in test report.</p>								


6.8 Conducted Emissions

Limit		
Frequency (MHz)	Quasi-peak	Average
0.15~0.50	66 to 56*	56 to 46*
0.50~5.0	56	46
5.0~30	60	50

*Decreases with the logarithm of the frequency.
 If the limit for the measurement with the average detector is met when using a receiver with a quasi-peak detector, the equipment under test shall be deemed to meet both limits and the measurement using the receiver with an average detector need not be carried out

Block diagram of Test Setup	
<input checked="" type="checkbox"/> For table-top equipment	<input type="checkbox"/> For floor standing equipment
	
Test Instrument	
Refer to Annex A for details	
Test Procedures	
<p>The measurement was performed in a shield room.</p> <p>Measured levels of ac power-line conducted emission shall be the radio-noise voltage from the voltage probe, where permitted, or across the 50 Ω LISN port (to which the EUT is connected), as terminated into a 50 Ω EMI receiver or spectrum analyzer. All radio-noise voltage and current measurements shall be made on each current-carrying conductor at the plug end of the EUT power cord or calibrated extension cord by the use of mating plugs and receptacles on the EUT and LISN, if used. The manufacturer shall test equipment with power cords that are normally supplied or recommended by the manufacturer and that have electrical and shielding characteristics that are the same as those cords normally supplied or recommended. For measurements using a LISN, the 50 Ω measuring port is terminated into a 50 Ω EMI receiver or spectrum analyzer. All other ports are terminated into 50 Ω loads.</p> <p>Table top devices shall be placed on a platform of nominal size 1 m by 1.5 m, raised 80 cm above the reference ground plane. The vertical conducting plane or wall of an RF-shielded (screened) room shall be located 40 cm to the rear of the EUT. Floor-standing devices shall be placed either directly on the reference ground-plane or on insulating material as described in ANSI C63.4. All other surfaces of tabletop or floor-standing EUTs shall be at least 80 cm from any other grounded conducting surface, including the case or cases of one or more LISNs.</p> <p>The bandwidth of the test receiver is set at 9 kHz.</p>	
Verdict	
Pass	


Test Result			
Test mode	Mode 1	Polarity	Line
Test voltage	AC 120V/60Hz	Temp. /Hum.	25 °C/60%



Final Data List									
NO.	Freq. [MHz]	QP Value [dBµV]	QP Limit [dBµV]	QP Margin [dB]	AV Value [dBµV]	AV Limit [dBµV]	AV Margin [dB]	Verdict	Type
1	0.15	60.85	66.00	5.15	41.70	56.00	14.30	PASS	L
2	0.168	60.39	65.06	4.67	36.27	55.06	18.79	PASS	L
3	0.1995	58.56	63.63	5.07	34.27	53.63	19.36	PASS	L
4	0.231	55.91	62.41	6.50	32.94	52.41	19.47	PASS	L
5	23.334	56.42	60.00	3.58	37.71	50.00	12.29	PASS	L
6	24.0585	56.12	60.00	3.88	39.25	50.00	10.75	PASS	L

Note: Final Level = Receiver Read level + Factor
 Factor = LISN Factor + Cable Loss
 Only the worst case report (802.11b 2462MHz)

Test Result			
Test mode	Mode 1	Polarity	Neutral
Test voltage	AC 120V/60Hz	Temp. /Hum.	25 °C/60%



Final Data List									
NO.	Freq. [MHz]	QP Value [dBµV]	QP Limit [dBµV]	QP Margin [dB]	AV Value [dBµV]	AV Limit [dBµV]	AV Margin [dB]	Verdict	Type
1	0.168	51.93	65.06	13.13	32.01	55.06	23.05	PASS	N
2	0.204	49.82	63.45	13.63	27.91	53.45	25.54	PASS	N
3	22.8975	51.65	60.00	8.35	36.76	50.00	13.24	PASS	N
4	23.3385	55.20	60.00	4.80	36.86	50.00	13.14	PASS	N
5	23.6355	52.90	60.00	7.10	37.22	50.00	12.78	PASS	N
6	24.0675	54.32	60.00	5.68	37.18	50.00	12.82	PASS	N

Note: Final Level = Receiver Read level + Factor
 Factor = LISN Factor + Cable Loss
 Only the worst case report (802.11b 2462MHz)

7 Test Setup Photo

Reference to the **appendix I** for details.

8 EUT Constructional Details

Reference to the **appendix II** for details.



Annex A --Test Instruments list

Radiated Emission:						
Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. cycle	Cal.Date
SST-E-SAC001	3m Semi- Anechoic Chamber	BOST	966	/	3 years	2023.01.07
SST-E-SCC001	Control Room	BOST	333	/	3 years	2023.01.07
SST-E-SAC002	Breiband TRILOG Messantenne	Schwarzbeck	VULB 9162	00556	1 year	2024.04.20
SST-E-SAC004	Broad-band Horn Antenna	Schwarzbeck	BBHA 9120 D	02783	1 year	2024.04.16
SST-E-SCC003	EMI Test Receiver	R&S	ESU 8	100372	1 year	2024.04.16
SST-E-SCC004	Amplifier	Schwarzbeck	BBV 9744	00327	1 year	2024.04.16
SST-E-SCC015	Amplifie (1-18GHz)	TSTPASS	LNA10180G45	TSAM2303003	1 year	2024.04.16
SST-E-SCC016	Amplifier (40G)	RFsystem	TRLA-180400G45B	23060801	1 year	2024.04.16
SST-E-SAC006	Broadband Horn Antenna (40G)	Schwarzbeck	BBHA9170	01306	1 year	2024.04.17
SST-E-RSC010	Spectrum analyzer	R&S	FSV40-N	/	1 year	2024.04.16
SST-E-SAC007	Loop Antenna	Schwarzbeck	FMZB 1513-60B	1513-60B 044	1 year	2024.04.17
SST-E-SAC005	5W 6dB attenuator	/	DC-6GHz	/	Internal calibration	/
SST-E-EMC006	Thermohyrometer	KTJ	TA218A	879030	1 year	2024.04.18
/	EMI Test Software	Tonscend	TS+	/	/	/

Conducted Emission						
Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. cycle	Cal.Date
SST-E-CSC001	Shielding Room	BOST	854	/	3 year	2023.01.07
SST-E-CSC002	EMI Test Receiver	R&S	ESR3	103057	1 year	2024.04.16
SST-E-CSC003	LISN	R&S	ENV 216	102832	1 year	2024.04.16
SST-E-CSC004	ISN	R&S	NTFM 8158	00347	1 year	2024.04.16
SST-E-CSC007	Antenna port test assembly	/	DC-3GHz	/	Internal calibration	/
SST-E-EMC011	Thermohyrometer	KTJ	TA218A	879036	1 year	2024.04.18
/	EMI Test Software	Tonscend	TS+	V4.0	/	/

RF conducted						
Equipment No.	Test Equipment	Manufacturer	Model No.	Serial No.	Cal. cycle	Cal.Date
SST-E-RSC001	Shielding Room	BOST	543	/	3 year	2023.01.07
SST-E-RSC007	Spectrum analyzer	keysight	N9020A	MY51280659	1 year	2024.04.16
SST-E-RSC008	Analog signal source	Agilent	N5181A	MY48180054	1 year	2024.04.16
SST-E-RSC009	Vector signal source	keysight	N5172B	MY57281610	1 year	2024.04.16
SST-E-EMC007	Thermohygrometer	KTJ	TA218A	879032	1 year	2024.04.18
SST-E-RSC010	Spectrum analyzer	R&S	FSV40-N	/	1 year	2024.04.16
SST-E-RSC015-1	Power meter 1	TST	TST V2	/	1 year	2024.04.16
/	Test Software	TST PASS	TST PASS	V2.0	/	/

▶▶▶ END OF REPORT ◀◀◀

