

FCC Test Report

Applicant**: SHENZHEN ELECTRON TECHNOLOGY
CO.,LTD.****Address****: Bld.2, Yingfeng Industrial Zone, Tantou
Community, Songgang Street, Bao'an,
Shenzhen, China.****Product Name****: Smart Home****Report Date****: Jun. 24, 2024****Shenzhen Anbotek Compliance Laboratory Limited****Shenzhen Anbotek Compliance Laboratory Limited**

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86)0755-26066440 Fax: (86)0755-26014772 Email: service@anbotek.com



Hotline
400-003-0500
www.anbotek.com.cn



Contents

1. General Information	6
1.1. Client Information	6
1.2. Description of Device (EUT)	6
1.3. Auxiliary Equipment Used During Test	8
1.4. Operation channel list	8
1.5. Description of Test Modes	8
1.6. Measurement Uncertainty	8
1.7. Test Summary	9
1.8. Description of Test Facility	10
1.9. Disclaimer	10
1.10. Test Equipment List	11
2. Antenna requirement	13
2.1. Conclusion	13
3. Conducted Emission at AC power line	14
3.1. EUT Operation	14
3.2. Test Setup	14
3.3. Test Data	15
4. Occupied Bandwidth	21
4.1. EUT Operation	21
4.2. Test Setup	21
4.3. Test Data	22
5. Maximum Conducted Output Power	23
5.1. EUT Operation	23
5.2. Test Setup	23
5.3. Test Data	23
6. Power Spectral Density	24
6.1. EUT Operation	24
6.2. Test Setup	24
6.3. Test Data	24
7. Emissions in non-restricted frequency bands	25
7.1. EUT Operation	25
7.2. Test Setup	25
7.3. Test Data	25
8. Band edge emissions (Radiated)	26
8.1. EUT Operation	26
8.2. Test Setup	26
8.3. Test Data	27
9. Emissions in frequency bands (below 1GHz)	28
9.1. EUT Operation	28
9.2. Test Setup	29
9.3. Test Data	30

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86)0755-26066440 Fax: (86)0755-26014772 Email: service@anbotek.com



Hotline
400-003-0500
www.anbotek.com.cn



10. Emissions in frequency bands (above 1GHz).....	36
10.1. EUT Operation.....	36
10.2. Test Setup.....	36
10.3. Test Data.....	37
APPENDIX I -- TEST SETUP PHOTOGRAPH.....	40
APPENDIX II -- EXTERNAL PHOTOGRAPH.....	40
APPENDIX III -- INTERNAL PHOTOGRAPH.....	40

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86)0755-26066440 Fax: (86)0755-26014772 Email: service@anbotek.com



Hotline
400-003-0500
www.anbotek.com.cn



Report No.: 18220WC40042205

FCC ID: 2ABC5-E0062

Page 4 of 40

TEST REPORT

Applicant : SHENZHEN ELECTRON TECHNOLOGY CO.,LTD.

Manufacturer : SHENZHEN ELECTRON TECHNOLOGY CO.,LTD.

Product Name : Smart Home

Test Model No. : SMT156

Reference Model No. : SMT97, SMT101

Trade Mark : N/A

Rating(s) : SMT156:
DC Input: 12V== 2A
POE Input: 48V==
SMT97/SMT101:
DC Input: 12V== 1.5A
POE Input: 48V==**Test Standard(s) : ANSI C63.10-2020
KDB 558074 D01 15.247 Meas Guidance v05r02**

The device described above is tested by Shenzhen Anbotek Compliance Laboratory Limited to determine the maximum emission levels emanating from the device and the severe levels of the device can endure and its performance criterion. The measurement results are contained in this test report and Shenzhen Anbotek Compliance Laboratory Limited is assumed full of responsibility for the accuracy and completeness of these measurements. Also, this report shows that the EUT (Equipment Under Test) is technically compliant with above listed standard(s) requirements. This report applies to above tested sample only and shall not be reproduced in part without written approval of Shenzhen Anbotek Compliance Laboratory Limited.


Date of Receipt:

Mar. 12, 2024

Date of Test:

Mar. 12, 2024 to May 21, 2024

Prepared By:



(Ella Liang)

Approved & Authorized Signer:



(Edward Pan)

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86)0755-26066440 Fax: (86)0755-26014772 Email: service@anbotek.com



Hotline
400-003-0500
www.anbotek.com.cn



Revision History

Report Version	Description	Issued Date
R00	Original Issue.	Jun. 24, 2024

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86)0755-26066440 Fax: (86)0755-26014772 Email: service@anbotek.com

 Hotline
400-003-0500
www.anbotek.com.cn



1. General Information

1.1. Client Information

Applicant	:	SHENZHEN ELECTRON TECHNOLOGY CO.,LTD.
Address	:	Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Bao'an, Shenzhen, China.
Manufacturer	:	SHENZHEN ELECTRON TECHNOLOGY CO.,LTD.
Address	:	Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Bao'an, Shenzhen, China.
Factory	:	SHENZHEN ELECTRON TECHNOLOGY CO.,LTD.
Address	:	Bld.2, Yingfeng Industrial Zone, Tantou Community, Songgang Street, Bao'an, Shenzhen, China.

1.2. Description of Device (EUT)

Product Name	:	Smart Home
Test Model No.	:	SMT156
Reference Model No.	:	SMT97, SMT101 (Note: According to the model differences on page 7, we prepare "SMT156" for all tests, and prepared SMT97, SMT101 for conducted emission and radiated spurious emissions (below 1GHz) difference testing.)
Trade Mark	:	N/A
Test Power Supply	:	DC 12V from adapter input AC 120V/60Hz
Test Sample No.	:	1-2-1(Normal Sample), 1-2-2(Engineering Sample)
RF Specification		
Operation Frequency	:	2405MHZ to 2480MHZ
Number of Channel	:	16
Modulation Type	:	O-QPSK
Antenna Type	:	FPC Antenna
Antenna Gain(Peak)	:	2.74dBi
Remark:		
(1) All of the RF specification are provided by customer.		
(2) For a more detailed features description, please refer to the manufacturer's specifications or the User's Manual.		

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86)0755-26066440 Fax: (86)0755-26014772 Email: service@anbotek.com



Hotline
400-003-0500
www.anbotek.com.cn



Model differences

Model	Display screen size	Input	Adapter
SMT156	15.6-inch	DC Input: 12V \Rightarrow 2A POE Input: 48V \Rightarrow	Manufacturer: SHENZHEN FUJIA APPLIANCE CO., LTD. Model No.: FJ-SW126G1202000U Input: 100-240V~50/60Hz 0.6A Max Output: 12V \Rightarrow 2A
SMT97	9.7-inch	DC Input: 12V \Rightarrow 1.5A POE Input: 48V \Rightarrow	Manufacturer: SHENZHEN FUJIA APPLIANCE CO., LTD. Model No.: FJ-SW126G1201500U Input: 100-240V~50/60Hz 0.6A Max Output: 12V \Rightarrow 1.5A
SMT101	10.1-inch		

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86)0755-26066440 Fax: (86)0755-26014772 Email: service@anbotek.com



Hotline
400-003-0500
www.anbotek.com.cn



1.3. Auxiliary Equipment Used During Test

Title	Manufacturer	Model No.	Serial No.
/	/	/	/

1.4. Operation channel list

Operation Band:

Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)	Channel	Frequency (MHz)
11	2405	15	2425	18	2445	23	2465
12	2410	16	2430	20	2450	24	2470
13	2415	17	2435	21	2455	25	2475
14	2420	18	2440	22	2460	26	2480

1.5. Description of Test Modes

Pretest Modes	Descriptions
TM1	Keep the EUT connect to AC power line and works in continuously transmitting mode with O-QPSK modulation.

1.6. Measurement Uncertainty

Parameter	Uncertainty
Conducted emissions (AMN 150kHz~30MHz)	3.4dB
Occupied Bandwidth	925Hz
Conducted Output Power	0.76dB
Power Spectral Density	0.76dB
Conducted Spurious Emission	1.24dB
Radiated spurious emissions (above 1GHz)	1G-6GHz: 4.78dB; 6G-18GHz: 4.88dB 18G-40GHz: 5.68dB
Radiated emissions (Below 30MHz)	3.53dB
Radiated spurious emissions (30MHz~1GHz)	Horizontal: 3.92dB; Vertical: 4.52dB
The measurement uncertainty and decision risk evaluated according to AB/WI-RF-F-032. This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.	

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86)0755-26066440 Fax: (86)0755-26014772 Email: service@anbotek.com



Hotline
400-003-0500
www.anbotek.com.cn



1.7. Test Summary

Test Items	Test Modes	Status
Antenna requirement	/	P
Conducted Emission at AC power line	Mode1	P
Occupied Bandwidth	Mode1	P
Maximum Conducted Output Power	Mode1	P
Power Spectral Density	Mode1	P
Emissions in non-restricted frequency bands	Mode1	P
Band edge emissions (Radiated)	Mode1	P
Emissions in frequency bands (below 1GHz)	Mode1	P
Emissions in frequency bands (above 1GHz)	Mode1	P
Note: P: Pass N: N/A, not applicable		

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86)0755-26066440 Fax: (86)0755-26014772 Email: service@anbotek.com



Hotline
400-003-0500
www.anbotek.com.cn



1.8. Description of Test Facility

The test facility is recognized, certified, or accredited by the following organizations:

FCC-Registration No.:434132

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration No. 434132.

ISED-Registration No.: 8058A

Shenzhen Anbotek Compliance Laboratory Limited, EMC Laboratory has been registered and fully described in a report filed with the (ISED) Innovation, Science and Economic Development Canada. The acceptance letter from the ISED is maintained in our files. Registration 8058A.

Test Location

Shenzhen Anbotek Compliance Laboratory Limited.

1/F, Building D, Sogood Science and Technology Park, Sanwei community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.

1.9. Disclaimer

1. The test report is invalid if not marked with the signatures of the persons responsible for preparing and approving the test report.
2. The test report is invalid if there is any evidence and/or falsification.
3. The results documented in this report apply only to the tested sample, under the conditions and modes of operation as described herein.
4. This document may not be altered or revised in any way unless done so by Anbotek and all revisions are duly noted in the revisions section.
5. Content of the test report, in part or in full, cannot be used for publicity and/or promotional purposes without prior written approval from the laboratory.
6. The authenticity of the information provided by the customer is the responsibility of the customer and the laboratory is not responsible for its authenticity.

The laboratory is only responsible for the data released by the laboratory, except for the part provided by the applicant.

Shenzhen Anbotek Compliance Laboratory Limited

Address:1/F.,Building D,Sogood Science and Technology Park, Sanwei Community,
Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel:(86)0755-26066440 Fax:(86)0755-26014772 Email:service@anbotek.com



Hotline
400-003-0500
www.anbotek.com.cn



1.10. Test Equipment List

Conducted Emission at AC power line						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.Due Date
1	L.I.S.N. Artificial Mains Network	Rohde & Schwarz	ENV216	100055	2024-01-18	2025-01-17
2	Three Phase V-type Artificial Power Network	CYBERTEK	EM5040DT	E215040D T001	2024-01-17	2025-01-16
3	Software Name EZ-EMC	Farad Technology	ANB-03A	N/A	/	/
4	EMI Test Receiver	Rohde & Schwarz	ESPI3	100926	2023-10-12	2024-10-11

Occupied Bandwidth Maximum Conducted Output Power Power Spectral Density Emissions in non-restricted frequency bands						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.Due Date
1	Constant Temperature Humidity Chamber	ZHONGJIAN	ZJ-KHWS80B	N/A	2023-10-16	2024-10-15
2	DC Power Supply	IVYTECH	IV3605	1804D360 510	2023-10-20	2024-10-19
3	Spectrum Analyzer	Rohde & Schwarz	FSV40-N	101792	2023-05-26	2024-05-25
4	MXA Spectrum Analysis	KEYSIGHT	N9020A	MY505318 23	2024-02-22	2025-02-21
5	Oscilloscope	Tektronix	MDO3012	C020298	2023-10-12	2024-10-11
6	MXG RF Vector Signal Generator	Agilent	N5182A	MY474206 47	2024-02-04	2025-02-03

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86)0755-26066440 Fax: (86)0755-26014772 Email: service@anbotek.com



Hotline
400-003-0500
www.anbotek.com.cn



Band edge emissions (Radiated) Emissions in frequency bands (above 1GHz)						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.Due Date
1	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	2024-01-23	2025-01-22
2	EMI Preamplifier	SKET Electronic	LNPA-0118G-45	SKET-PA-002	2024-01-17	2025-01-16
3	Double Ridged Horn Antenna	SCHWARZBECK	BBHA 9120D	02555	2022-10-16	2025-10-15
4	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	/	/
5	Horn Antenna	A-INFO	LB-180400-KF	J211060628	2023-10-12	2024-10-11
6	Spectrum Analyzer	Rohde & Schwarz	FSV40-N	101792	2023-05-26	2024-05-25
7	Amplifier	Talent Microwave	TLLA18G40 G-50-30	23022802	2023-05-25	2024-05-24

Emissions in frequency bands (below 1GHz)						
Item	Equipment	Manufacturer	Model No.	Serial No.	Last Cal.	Cal.Due Date
1	EMI Test Receiver	Rohde & Schwarz	ESR26	101481	2024-01-23	2025-01-22
2	Pre-amplifier	SONOMA	310N	186860	2024-01-17	2025-01-16
3	Bilog Broadband Antenna	Schwarzbeck	VULB9163	345	2022-10-23	2025-10-22
4	Loop Antenna (9K-30M)	Schwarzbeck	FMZB1519 B	00053	2023-10-12	2024-10-11
5	EMI Test Software EZ-EMC	SHURPLE	N/A	N/A	/	/

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
 Tel: (86)0755-26066440 Fax: (86)0755-26014772 Email: service@anbotek.com

Hotline 400-003-0500
 www.anbotek.com.cn



2. Antenna requirement

Test Requirement:

Refer to 47 CFR Part 15.203, an intentional radiator shall be designed to ensure that no antenna other than that furnished by the responsible party shall be used with the device. The use of a permanently attached antenna or of an antenna that uses a unique coupling to the intentional radiator shall be considered sufficient to comply with the provisions of this section.

2.1. Conclusion

The antenna is a FPC antenna which permanently attached, and the best case gain of the antenna is 2.74Bi. It complies with the standard requirement.

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86)0755-26066440 Fax: (86)0755-26014772 Email: service@anbotek.com



Hotline
400-003-0500
www.anbotek.com.cn




3. Conducted Emission at AC power line

Test Requirement:	Refer to 47 CFR 15.207(a), Except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies, within the band 150 kHz to 30 MHz, shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN).		
Test Limit:	Frequency of emission (MHz)	Conducted limit (dB μ V)	
		Quasi-peak	Average
	0.15-0.5	66 to 56*	56 to 46*
	0.5-5	56	46
	5-30	60	50
	*Decreases with the logarithm of the frequency.		
Test Method:	ANSI C63.10-2020 section 6.2		
Procedure:	Refer to ANSI C63.10-2020 section 6.2, standard test method for ac power-line conducted emissions from unlicensed wireless devices		

3.1. EUT Operation

Operating Environment:	
Test mode:	1: TX mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with O-QPSK modulation.


3.2. Test Setup



3.3. Test Data

Temperature:	24.8 °C	Humidity:	50.5 %	Atmospheric Pressure:	101 kPa
Test Model:	SMT156				

TM1 / Line: Line / Band: 2400-2483.5 MHz / BW: 5 / CH: H




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.3899	30.32	17.81	48.13	58.06	-9.93	QP	
2	0.3899	20.56	17.81	38.37	48.06	-9.69	AVG	
3	0.5620	13.72	17.86	31.58	46.00	-14.42	AVG	
4	0.6460	25.50	17.87	43.37	56.00	-12.63	QP	
5	0.8940	12.54	17.86	30.40	46.00	-15.60	AVG	
6	1.0460	25.47	17.86	43.33	56.00	-12.67	QP	
7	1.3619	14.52	17.86	32.38	46.00	-13.62	AVG	
8	1.6936	12.75	17.85	30.60	46.00	-15.40	AVG	
9	1.7900	24.29	17.86	42.15	56.00	-13.85	QP	
10	2.1179	12.33	17.85	30.18	46.00	-15.82	AVG	
11	2.2019	22.60	17.85	40.45	56.00	-15.55	QP	
12	4.4818	22.38	17.85	40.23	56.00	-15.77	QP	



Temperature:	24.8 °C	Humidity:	50.5 %	Atmospheric Pressure:	101 kPa
Test Model:	SMT156				

TM1 / Line: Neutral / Band: 2400-2483.5 MHz / BW: 5 / CH: H




No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dB)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.3899	29.32	17.81	47.13	58.06	-10.93	QP	
2	0.3899	19.06	17.81	36.87	48.06	-11.19	AVG	
3	0.6460	24.50	17.87	42.37	56.00	-13.63	QP	
4	0.6460	12.70	17.87	30.57	46.00	-15.43	AVG	
5	1.2780	24.77	17.86	42.63	56.00	-13.37	QP	
6	1.6255	13.36	17.85	31.21	46.00	-14.79	AVG	
7	1.7900	23.29	17.86	41.15	56.00	-14.85	QP	
8	2.1179	10.83	17.85	28.68	46.00	-17.32	AVG	
9	2.2019	22.60	17.85	40.45	56.00	-15.55	QP	
10	3.5659	10.22	17.86	28.08	46.00	-17.92	AVG	
11	4.1177	22.59	17.85	40.44	56.00	-15.56	QP	
12	4.7298	7.38	17.86	25.24	46.00	-20.76	AVG	

Note: Only record the worst data in the report.



Temperature:	24.1 °C	Humidity:	52.6 %	Atmospheric Pressure:	101 kPa
Test Model:	SMT97				

TM1 / Line: Line / Band: 2400-2483.5 MHz / BW: 5 / CH: H



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1660	17.16	17.83	34.99	55.15	-20.16	AVG	
2	0.1980	25.46	17.83	43.29	63.69	-20.40	QP	
3	0.4660	22.54	17.84	40.38	56.58	-16.20	QP	
4	0.4660	13.04	17.84	30.88	46.58	-15.70	AVG	
5	0.7780	12.78	17.86	30.64	46.00	-15.36	AVG	
6	1.2579	23.97	17.84	41.81	56.00	-14.19	QP	
7	1.2900	13.57	17.84	31.41	46.00	-14.59	AVG	
8	1.6660	19.82	17.84	37.66	56.00	-18.34	QP	
9	1.7780	9.87	17.84	27.71	46.00	-18.29	AVG	
10	2.0540	16.82	17.83	34.65	56.00	-21.35	QP	
11	2.1340	7.06	17.83	24.89	46.00	-21.11	AVG	
12	3.2860	11.81	17.84	29.65	56.00	-26.35	QP	

Shenzhen Anbotek Compliance Laboratory Limited


Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
 Tel: (86)0755-26066440 Fax: (86)0755-26014772 Email: service@anbotek.com

Hotline 400-003-0500
 www.anbotek.com.cn



Temperature:	24.1 °C	Humidity:	52.6 %	Atmospheric Pressure:	101 kPa
Test Model:	SMT97				

TM1 / Line: Neutral / Band: 2400-2483.5 MHz / BW: 5 / CH: H



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1700	26.44	17.83	44.27	64.96	-20.69	QP	
2	0.4580	12.35	17.83	30.18	46.73	-16.55	AVG	
3	0.7100	23.05	17.87	40.92	56.00	-15.08	QP	
4	0.7780	13.12	17.86	30.98	46.00	-15.02	AVG	
5	1.0460	23.21	17.85	41.06	56.00	-14.94	QP	
6	1.3380	12.99	17.84	30.83	46.00	-15.17	AVG	
7	1.3779	22.34	17.84	40.18	56.00	-15.82	QP	
8	1.6980	19.22	17.84	37.06	56.00	-18.94	QP	
9	1.6980	10.11	17.84	27.95	46.00	-18.05	AVG	
10	2.0059	8.22	17.83	26.05	46.00	-19.95	AVG	
11	2.1619	16.92	17.83	34.75	56.00	-21.25	QP	
12	3.1060	2.61	17.84	20.45	46.00	-25.55	AVG	

Note: Only record the worst data in the report.

Shenzhen Anbotek Compliance Laboratory Limited


Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
 Tel: (86)0755-26066440 Fax: (86)0755-26014772 Email: service@anbotek.com

Hotline 400-003-0500
 www.anbotek.com.cn



Temperature:	24.1 °C	Humidity:	52.6 %	Atmospheric Pressure:	101 kPa
Test Model:	SMT101				

TM1 / Line: Line / Band: 2400-2483.5 MHz / BW: 5 / CH: H



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1660	27.54	17.83	45.37	65.15	-19.78	QP	
2	0.1740	16.67	17.83	34.50	54.76	-20.26	AVG	
3	0.4340	23.74	17.82	41.56	57.18	-15.62	QP	
4	0.4340	13.52	17.82	31.34	47.18	-15.84	AVG	
5	0.7740	13.37	17.87	31.24	46.00	-14.76	AVG	
6	1.2740	24.07	17.84	41.91	56.00	-14.09	QP	
7	1.3940	13.10	17.84	30.94	46.00	-15.06	AVG	
8	1.6180	20.22	17.84	38.06	56.00	-17.94	QP	
9	1.8020	9.36	17.84	27.20	46.00	-18.80	AVG	
10	1.9820	18.42	17.83	36.25	56.00	-19.75	QP	
11	2.1420	6.76	17.83	24.59	46.00	-21.41	AVG	
12	2.3179	15.46	17.83	33.29	56.00	-22.71	QP	

Shenzhen Anbotek Compliance Laboratory Limited


Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
 Tel: (86)0755-26066440 Fax: (86)0755-26014772 Email: service@anbotek.com

Hotline 400-003-0500
 www.anbotek.com.cn



Temperature:	24.1 °C	Humidity:	52.6 %	Atmospheric Pressure:	101 kPa
Test Model:	SMT101				

TM1 / Line: Neutral / Band: 2400-2483.5 MHz / BW: 5 / CH: H



No.	Freq. (MHz)	Reading (dBuV)	Factor (dB)	Result (dBuV)	Limit (dBuV)	Over Limit (dB)	Detector	Remark
1	0.1700	26.62	17.83	44.45	64.96	-20.51	QP	
2	0.2860	22.88	17.83	40.71	60.64	-19.93	QP	
3	0.4300	14.01	17.82	31.83	47.25	-15.42	AVG	
4	0.4660	24.26	17.84	42.10	56.58	-14.48	QP	
5	0.7780	12.53	17.86	30.39	46.00	-15.61	AVG	
6	1.1539	23.55	17.85	41.40	56.00	-14.60	QP	
7	1.3580	13.44	17.84	31.28	46.00	-14.72	AVG	
8	1.6019	20.12	17.84	37.96	56.00	-18.04	QP	
9	1.7340	9.32	17.84	27.16	46.00	-18.84	AVG	
10	1.9020	18.01	17.83	35.84	56.00	-20.16	QP	
11	2.0740	7.42	17.83	25.25	46.00	-20.75	AVG	
12	3.2700	1.93	17.84	19.77	46.00	-26.23	AVG	

Note: Only record the worst data in the report.

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
 Tel: (86)0755-26066440 Fax: (86)0755-26014772 Email: service@anbotek.com



Hotline
 400-003-0500
 www.anbotek.com.cn




4. Occupied Bandwidth

Test Requirement:	47 CFR 15.247(a)(2)
Test Limit:	Refer to 47 CFR 15.247(a)(2), Systems using digital modulation techniques may operate in the 902-928 MHz, and 2400-2483.5 MHz bands. The minimum 6 dB bandwidth shall be at least 500 kHz.
Test Method:	ANSI C63.10-2020, section 11.8 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	<p>11.8.1 Option 1</p> <p>The steps for the first option are as follows:</p> <ul style="list-style-type: none"> a) Set RBW = shall be in the range of 1% to 5% of the OBW but not less than 100 kHz. b) Set the VBW $\geq [3 \times \text{RBW}]$. c) Detector = peak. d) Trace mode = max-hold. e) Sweep = No faster than coupled (auto) time. f) Allow the trace to stabilize. g) Measure the maximum width of the emission by placing two markers, one at the lowest frequency and the other at the highest frequency of the envelope of the spectral display, such that each marker is at or slightly below the “-6 dB down amplitude”. If a marker is below this “-6 dB down amplitude” value, then it shall be as close as possible to this value. <p>11.8.2 Option 2</p> <p>The automatic bandwidth measurement capability of an instrument may be employed using the X dB bandwidth mode with X set to 6 dB, if the functionality described in 11.8.1 (i.e., RBW = 100 kHz, VBW $\geq 3 \times \text{RBW}$, and peak detector with maximum hold) is implemented by the instrumentation function.</p> <p>When using this capability, care shall be taken so that the bandwidth measurement is not influenced by any intermediate power nulls in the fundamental emission that might be ≥ 6 dB.</p>

4.1. EUT Operation

Operating Environment:	
Test mode:	1: TX mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with O-QPSK modulation.

4.2. Test Setup



4.3. Test Data

Temperature:	25.3 °C	Humidity:	48 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------

Please Refer to Appendix for Details.

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86)0755-26066440 Fax: (86)0755-26014772 Email: service@anbotek.com



Hotline
400-003-0500
www.anbotek.com.cn




5. Maximum Conducted Output Power

Test Requirement:	47 CFR 15.247(b)(3)
Test Limit:	Refer to 47 CFR 15.247(b)(3), For systems using digital modulation in the 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz bands: 1 Watt. As an alternative to a peak power measurement, compliance with the one Watt limit can be based on a measurement of the maximum conducted output power. Maximum Conducted Output Power is defined as the total transmit power delivered to all antennas and antenna elements averaged across all symbols in the signaling alphabet when the transmitter is operating at its maximum power control level. Power must be summed across all antennas and antenna elements. The average must not include any time intervals during which the transmitter is off or is transmitting at a reduced power level. If multiple modes of operation are possible (e.g., alternative modulation methods), the maximum conducted output power is the highest total transmit power occurring in any mode.
Test Method:	ANSI C63.10-2020 section 11.9.1 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020, section 11.9.1 Maximum peak conducted output power

5.1. EUT Operation

Operating Environment:	
Test mode:	1: TX mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with O-QPSK modulation.

5.2. Test Setup



5.3. Test Data

Temperature:	25.3 °C	Humidity:	48 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------

Please Refer to Appendix for Details.




6. Power Spectral Density

Test Requirement:	47 CFR 15.247(e)
Test Limit:	Refer to 47 CFR 15.247(e), For digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission. This power spectral density shall be determined in accordance with the provisions of paragraph (b) of this section. The same method of determining the conducted output power shall be used to determine the power spectral density.
Test Method:	ANSI C63.10-2020, section 11.10 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020, section 11.10, Maximum power spectral density level in the fundamental emission

6.1. EUT Operation

Operating Environment:	
Test mode:	1: TX mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with O-QPSK modulation.

6.2. Test Setup



6.3. Test Data

Temperature:	25.3 °C	Humidity:	48 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------

Please Refer to Appendix for Details.




7. Emissions in non-restricted frequency bands

Test Requirement:	47 CFR 15.247(d), 15.209, 15.205
Test Limit:	Refer to 47 CFR 15.247(d), In any 100 kHz bandwidth outside the frequency band in which the spread spectrum or digitally modulated intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. If the transmitter complies with the conducted power limits based on the use of RMS averaging over a time interval, as permitted under paragraph (b)(3) of this section, the attenuation required under this paragraph shall be 30 dB instead of 20 dB. Attenuation below the general limits specified in § 15.209(a) is not required.
Test Method:	ANSI C63.10-2020 section 11.11 KDB 558074 D01 15.247 Meas Guidance v05r02
Procedure:	ANSI C63.10-2020 Section 11.11.1, Section 11.11.2, Section 11.11.3

7.1. EUT Operation

Operating Environment:	
Test mode:	1: TX mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with O-QPSK modulation.

7.2. Test Setup



7.3. Test Data

Temperature:	25.3 °C	Humidity:	48 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------

Please Refer to Appendix for Details.




8. Band edge emissions (Radiated)

Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
	<p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p> <p>In the emission table above, the tighter limit applies at the band edges.</p> <p>The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.</p>		
Test Method:	ANSI C63.10-2020 section 6.10 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2020 section 6.10.5.2		

8.1. EUT Operation


Operating Environment:	
Test mode:	1: TX mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with O-QPSK modulation.

8.2. Test Setup




8.3. Test Data

Temperature:	25.3 °C	Humidity:	48 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------



Peak Value(Vertical)

Peak Value(Horizontal)



Peak Value(Vertical)

Peak Value(Horizontal)

Note: When the PK measure result value is less than the AVG limit value, the AV measure result values test not applicable.

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
Tel: (86)0755-26066440 Fax: (86)0755-26014772 Email: service@anbotek.com

Hotline
400-003-0500
www.anbotek.com.cn



9. Emissions in frequency bands (below 1GHz)


Test Requirement:	Refer to 47 CFR 15.247(d), In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).`		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
	<p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p> <p>In the emission table above, the tighter limit applies at the band edges.</p> <p>The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.</p>		
Test Method:	ANSI C63.10-2020 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2020 section 6.6.4		

9.1. EUT Operation

Operating Environment:	
Test mode:	1: TX mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with O-QPSK modulation.



9.2. Test Setup




9.3. Test Data

The test results of 9kHz-30MHz was attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Temperature:	25.5 °C	Humidity:	47 %	Atmospheric Pressure:	101 kPa
Test Model:	SMT156				

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 5 / CH: H




No.	Freq. (MHz)	Reading (dBuV)	Factor ()	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	147.4036	39.16	-21.48	17.68	43.50	-25.82	QP			
2	169.5989	42.31	-20.26	22.05	43.50	-21.45	QP			
3	215.2677	44.90	-17.86	27.04	43.50	-16.46	QP			
4	303.5437	43.45	-15.20	28.25	46.00	-17.75	QP			
5	419.1080	41.19	-12.66	28.53	46.00	-17.47	QP			
6	776.8777	34.54	-7.17	27.37	46.00	-18.63	QP			



Temperature:	25.5 °C	Humidity:	47 %	Atmospheric Pressure:	101 kPa
Test Model:	SMT156				

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 5 / CH: H



No.	Freq. (MHz)	Reading (dBuV)	Factor ()	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	67.2022	41.25	-20.77	20.48	40.00	-19.52	QP			
2	124.5690	43.75	-20.42	23.33	43.50	-20.17	QP			
3	166.0680	41.35	-20.47	20.88	43.50	-22.62	QP			
4	281.0074	40.94	-15.72	25.22	46.00	-20.78	QP			
5	531.9634	38.08	-10.55	27.53	46.00	-18.47	QP			
6	833.3170	37.25	-6.39	30.86	46.00	-15.14	QP			

Note: Only record the worst data in the report.



Temperature:	25.5 °C	Humidity:	47 %	Atmospheric Pressure:	101 kPa
Test Model:	SMT97				

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 5 / CH: H




No.	Freq. (MHz)	Reading (dBuV)	Factor ()	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	42.8997	32.51	-17.22	15.29	40.00	-24.71	QP			
2	60.4919	33.75	-18.12	15.63	40.00	-24.37	QP			
3	212.2694	43.94	-17.98	25.96	43.50	-17.54	QP			
4	284.9766	40.25	-15.62	24.63	46.00	-21.37	QP			
5	431.0316	40.89	-12.44	28.45	46.00	-17.55	QP			
6	562.6624	36.34	-9.87	26.47	46.00	-19.53	QP			



Temperature:	25.5 °C	Humidity:	47 %	Atmospheric Pressure:	101 kPa
Test Model:	SMT97				

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 5 / CH: H




No.	Freq. (MHz)	Reading (dBuV)	Factor ()	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	60.4919	40.89	-18.12	22.77	40.00	-17.23	QP			
2	94.0979	41.44	-18.05	23.39	43.50	-20.11	QP			
3	121.1231	39.82	-20.00	19.82	43.50	-23.68	QP			
4	191.0738	45.45	-19.00	26.45	43.50	-17.05	QP			
5	212.2695	42.21	-17.98	24.23	43.50	-19.27	QP			
6	524.5541	43.68	-10.71	32.97	46.00	-13.03	QP			

Note: Only record the worst data in the report.



Temperature:	25.5 °C	Humidity:	47 %	Atmospheric Pressure:	101 kPa
Test Model:	SMT101				

TM1 / Polarization: Horizontal / Band: 2400-2483.5 MHz / BW: 5 / CH: H



No.	Freq. (MHz)	Reading (dBuV)	Factor ()	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	67.6751	36.44	-20.97	15.47	40.00	-24.53	QP			
2	212.2694	40.63	-17.98	22.65	43.50	-20.85	QP			
3	295.1469	40.33	-15.40	24.93	46.00	-21.07	QP			
4	404.6664	39.44	-12.90	26.54	46.00	-19.46	QP			
5	531.9634	36.38	-10.55	25.83	46.00	-20.17	QP			
6	771.4486	34.43	-7.24	27.19	46.00	-18.81	QP			

Shenzhen Anbotek Compliance Laboratory Limited


Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
 Tel: (86)0755-26066440 Fax: (86)0755-26014772 Email: service@anbotek.com

Hotline 400-003-0500
 www.anbotek.com.cn



Temperature:	25.5 °C	Humidity:	47 %	Atmospheric Pressure:	101 kPa
Test Model:	SMT101				

TM1 / Polarization: Vertical / Band: 2400-2483.5 MHz / BW: 5 / CH: H



No.	Freq. (MHz)	Reading (dBuV)	Factor ()	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	Detector	Height (cm)	degree (deg)	Remark
1	67.2022	41.15	-20.77	20.38	40.00	-19.62	QP			
2	94.0978	39.74	-18.05	21.69	43.50	-21.81	QP			
3	173.2050	40.79	-20.06	20.73	43.50	-22.77	QP			
4	191.0738	44.70	-19.00	25.70	43.50	-17.80	QP			
5	374.6225	40.09	-13.56	26.53	46.00	-19.47	QP			
6	524.5540	40.40	-10.71	29.69	46.00	-16.31	QP			

Note: Only record the worst data in the report.




10. Emissions in frequency bands (above 1GHz)

Test Requirement:	In addition, radiated emissions which fall in the restricted bands, as defined in § 15.205(a), must also comply with the radiated emission limits specified in § 15.209(a)(see § 15.205(c)).		
Test Limit:	Frequency (MHz)	Field strength (microvolts/meter)	Measurement distance (meters)
	0.009-0.490	2400/F(kHz)	300
	0.490-1.705	24000/F(kHz)	30
	1.705-30.0	30	30
	30-88	100 **	3
	88-216	150 **	3
	216-960	200 **	3
	Above 960	500	3
	<p>** Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this part, e.g., §§ 15.231 and 15.241.</p> <p>In the emission table above, the tighter limit applies at the band edges.</p> <p>The emission limits shown in the above table are based on measurements employing a CISPR quasi-peak detector except for the frequency bands 9–90 kHz, 110–490 kHz and above 1000 MHz. Radiated emission limits in these three bands are based on measurements employing an average detector.</p>		
Test Method:	ANSI C63.10-2020 section 6.6.4 KDB 558074 D01 15.247 Meas Guidance v05r02		
Procedure:	ANSI C63.10-2020 section 6.6.4		

10.1. EUT Operation

Operating Environment:	
Test mode:	1: TX mode: Keep the EUT connect to AC power line and works in continuously transmitting mode with O-QPSK modulation.

10.2. Test Setup



10.3. Test Data

Temperature:	25.3 °C	Humidity:	48 %	Atmospheric Pressure:	101 kPa
--------------	---------	-----------	------	-----------------------	---------

TM1 / CH: L						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4810.00	28.91	15.27	44.18	74.00	-29.82	Vertical
7215.00	30.62	18.09	48.71	74.00	-25.29	Vertical
9620.00	31.74	23.76	55.50	74.00	-18.50	Vertical
12025.00	*			74.00		Vertical
14430.00	*			74.00		Vertical
4810.00	29.40	15.27	44.67	74.00	-29.33	Horizontal
7215.00	31.01	18.09	49.10	74.00	-24.90	Horizontal
9620.00	29.82	23.76	53.58	74.00	-20.42	Horizontal
12025.00	*			74.00		Horizontal
14430.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4810.00	18.29	15.27	33.56	54.00	-20.44	Vertical
7215.00	19.65	18.09	37.74	54.00	-16.26	Vertical
9620.00	20.76	23.76	44.52	54.00	-9.48	Vertical
12025.00	*			54.00		Vertical
14430.00	*			54.00		Vertical
4810.00	17.75	15.27	33.02	54.00	-20.98	Horizontal
7215.00	20.07	18.09	38.16	54.00	-15.84	Horizontal
9620.00	19.13	23.76	42.89	54.00	-11.11	Horizontal
12025.00	*			54.00		Horizontal
14430.00	*			54.00		Horizontal

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
 Tel: (86)0755-26066440 Fax: (86)0755-26014772 Email: service@anbotek.com



Hotline
 400-003-0500
www.anbotek.com.cn



TM1 / CH: M						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4880.00	28.93	15.42	44.35	74.00	-29.65	Vertical
7320.00	30.47	18.02	48.49	74.00	-25.51	Vertical
9760.00	30.75	23.80	54.55	74.00	-19.45	Vertical
12200.00	*			74.00		Vertical
14640.00	*			74.00		Vertical
4880.00	29.10	15.42	44.52	74.00	-29.48	Horizontal
7320.00	31.00	18.02	49.02	74.00	-24.98	Horizontal
9760.00	29.52	23.80	53.32	74.00	-20.68	Horizontal
12200.00	*			74.00		Horizontal
14640.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4880.00	18.02	15.42	33.44	54.00	-20.56	Vertical
7320.00	19.75	18.02	37.77	54.00	-16.23	Vertical
9760.00	20.62	23.80	44.42	54.00	-9.58	Vertical
12200.00	*			54.00		Vertical
14640.00	*			54.00		Vertical
4880.00	17.66	15.42	33.08	54.00	-20.92	Horizontal
7320.00	19.63	18.02	37.65	54.00	-16.35	Horizontal
9760.00	19.64	23.80	43.44	54.00	-10.56	Horizontal
12200.00	*			54.00		Horizontal
14640.00	*			54.00		Horizontal

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
 Tel: (86)0755-26066440 Fax: (86)0755-26014772 Email: service@anbotek.com

Hotline 400-003-0500
 www.anbotek.com.cn



TM1 / CH: H						
Peak value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit Line (dBuV/m)	Over Limit (dB)	polarization
4960.00	29.20	15.58	44.78	74.00	-29.22	Vertical
7440.00	30.48	17.93	48.41	74.00	-25.59	Vertical
9920.00	31.30	23.83	55.13	74.00	-18.87	Vertical
12400.00	*			74.00		Vertical
14880.00	*			74.00		Vertical
4960.00	29.17	15.58	44.75	74.00	-29.25	Horizontal
7440.00	31.03	17.93	48.96	74.00	-25.04	Horizontal
9920.00	30.20	23.83	54.03	74.00	-19.97	Horizontal
12400.00	*			74.00		Horizontal
14880.00	*			74.00		Horizontal
Average value:						
Frequency (MHz)	Reading (dBuV)	Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Over Limit (dB)	polarization
4960.00	19.14	15.58	34.72	54.00	-19.28	Vertical
7440.00	20.76	17.93	38.69	54.00	-15.31	Vertical
9920.00	21.17	23.83	45.00	54.00	-9.00	Vertical
12400.00	*			54.00		Vertical
14880.00	*			54.00		Vertical
4960.00	19.10	15.58	34.68	54.00	-19.32	Horizontal
7440.00	21.00	17.93	38.93	54.00	-15.07	Horizontal
9920.00	19.54	23.83	43.37	54.00	-10.63	Horizontal
12400.00	*			54.00		Horizontal
14880.00	*			54.00		Horizontal

Remark:

1. Result = Reading + Factor
2. “*” means the test results were attenuated more than 20dB below the permissible limits, so the results don't record in the report.

Shenzhen Anbotek Compliance Laboratory Limited

Address: 1/F., Building D, Sogood Science and Technology Park, Sanwei Community, Hangcheng Street, Bao'an District, Shenzhen, Guangdong, China.
 Tel: (86)0755-26066440 Fax: (86)0755-26014772 Email: service@anbotek.com

Hotline
 400-003-0500
 www.anbotek.com.cn



APPENDIX I -- TEST SETUP PHOTOGRAPH

Please refer to separated files Appendix I -- Test Setup Photograph_RF

APPENDIX II -- EXTERNAL PHOTOGRAPH

Please refer to separated files Appendix II -- External Photograph

APPENDIX III -- INTERNAL PHOTOGRAPH

Please refer to separated files Appendix III -- Internal Photograph

----- End of Report -----

