

EMF TEST REPORT

Test Report No. : OT-236-RWD-035

Reception No. : 2305001470

Applicant : MCNEX CO.,LTD

Address : MCNEX Tower, 13-39, Songdogwahak-ro 16 beon-gi Yeonsu-gu, Incheon, Korea

Manufacturer : MCNEX CO.,LTD

Address : MCNEX Tower, 13-39, Songdogwahak-ro 16 beon-gi Yeonsu-gu, Incheon, Korea

Type of Equipment : 3CH Dashcam

FCC ID. : 2ABC6-MD-7205

Model Name : MD-7205

Multiple Model Name : N/A

Serial number : N/A

Total page of Report : 7 pages (including this page)

Date of Incoming : May 24, 2023

Date of issue : June 28, 2023

SUMMARY

The equipment complies with the regulation; *FCC CFR 47 PART 1.1310*

This test report only contains the result of a single test of the sample supplied for the examination.

It is not a generally valid assessment of the features of the respective products of the mass-production.



Tested by
Soon-Ki, Choi / Prj. Engineer
ONETECH Corp.

Reviewed by
Tae-Ho, Kim / Chief Engineer
ONETECH Corp.

Approved by
Jae-Ho, Lee / Chief Engineer
ONETECH Corp.

CONTENTS**PAGE**

1. VERIFICATION OF COMPLIANCE	4
2. GENERAL INFORMATION	5
2.1 PRODUCT DESCRIPTION.....	5
2.2 ALTERNATIVE TYPE(S)/MODEL(S); ALSO COVERED BY THIS TEST REPORT.....	5
3. EUT MODIFICATIONS.....	5
4. MAXIMUM PERMISSIBLE EXPOSURE	6
4.1 RF EXPOSURE CALCULATION	6
4.2 EUT DESCRIPTION.....	6
4.3 CALCULATED MPE SAFE DISTANCE.....	7

Revision History

Rev. No.	Issue Report No.	Issued Date	Revisions	Section Affected
0	OT-236-RWD-035	June 28, 2023	Initial Release	All

1. VERIFICATION OF COMPLIANCE

Applicant : MCNEX CO.,LTD
 Address : MCNEX Tower, 13-39, Songdogwahak-ro 16 beon-gi Yeonsu-gu, Incheon, Korea
 Contact Person : SEUNG JUN RO / Senior Research Engineer
 Telephone No. : +82-10-9274-1055
 FCC ID : 2ABC6-MD-7205
 Model Name : MD-7205
 Brand Name : Momento / Firstech, LLC
 Serial Number : N/A
 Date : June 28, 2023

EQUIPMENT CLASS	DTS – DIGITAL TRNSMISSION SYSTEM
E.U.T. DESCRIPTION	3CH Dashcam
THIS REPORT CONCERNS	Original Grant
MEASUREMENT PROCEDURES	KDB 447498 D01 General RF Exposure Guidance v06
TYPE OF EQUIPMENT TESTED	Pre-Production
KIND OF EQUIPMENT AUTHORIZATION REQUESTED	Certification
Modifications on the Equipment to Achieve Compliance	None

-. The above equipment was tested by ONETECH Corp. for compliance with the requirement set forth in the FCC Rules and Regulations. This said equipment in the configuration described in this report, shows the maximum emission levels emanating from equipment are within the compliance requirements.

2. GENERAL INFORMATION

2.1 Product Description

The MCNEX CO.,LTD, Model MD-7205 (referred to as the EUT in this report) is a 3CH Dashcam. The product specification described herein was obtained from product data sheet or user’s manual.

DEVICE TYPE	3CH Dashcam
Temperature Range	-20 °C ~ 60 °C
OPERATING FREQUENCY	2 412 MHz ~ 2 462 MHz (802.11b/g/n(HT20))
MODULATION TYPE	802.11b: DSSS Modulation(DBPSK/DQPSK/CCK) 802.11g/n(HT20): OFDM Modulation(BPSK/QPSK/16QAM/64QAM)
RF OUTPUT POWER	8.92 dBm(802.11b) 7.58 dBm(802.11g) 7.67 dBm(802.11n_HT20)
ANTENNA TYPE	Chip Antenna
ANTENNA GAIN	2.7 dBi
List of each Osc. or crystal Freq.(Freq. >= 1 MHz)	24 MHz, 26 MHz, 27 MHz
ELECTRICAL RATING	DC 12 V, DC 24 V

2.2 Alternative type(s)/model(s); also covered by this test report.

-. None

3. EUT MODIFICATIONS

-. None

4. MAXIMUM PERMISSIBLE EXPOSURE

4.1 RF Exposure Calculation

According to the FCC rule 1.1310 table 1B, the limit for the maximum permissible RF exposure for an uncontrolled environment are $f/1500$ mW/cm² for the frequency range between 300 MHz and 1 500 MHz and 1.0 mW/cm² for the frequency range between 1 500 MHz and 100 000 MHz.

The electric field generated for a 1 mW/cm² exposure is calculated as follows:

$$E = \sqrt{(30 * P * G) / d}, \text{ and } S = E^2 / Z = E^2 / 377, \text{ because } 1 \text{ mW/cm}^2 = 10 \text{ W/m}^2$$

Where

S = Power density in mW/cm², Z = Impedance of free space, 377 Ω

E = Electric field strength in V/m, G = Numeric antenna gain, and d = distance in meter

Combining equations and rearranging the terms to express the distance as a function of the remaining variable

$$d = \sqrt{(30 * P * G) / (377 * 10 S)}$$

Changing to units of mW and cm, using P (mW) = P (W) / 1 000, d (cm) = 0.01 * d (m)

$$d = 0.282 * \sqrt{(P * G) / S}$$

Where

d = distance in cm, P = Power in mW, G = Numeric antenna gain, and S = Power density in mW/cm²

4.2 EUT Description

Kind of EUT	3CH Dashcam
Device Category	<input type="checkbox"/> Portable (< 20 cm separation) <input type="checkbox"/> Mobile (> 20 cm separation) <input checked="" type="checkbox"/> Others
Exposure Evaluation Applied	<input checked="" type="checkbox"/> MPE <input type="checkbox"/> SAR <input type="checkbox"/> N/A

4.3 Calculated MPE Safe Distance

According to above equation, the following result was obtained.

Operating Freq. Band (MHz)	Operating Mode	Target Power W/tolerance (dBm)	Max tune up power		Antenna Gain		Safe Distance (cm)	Power Density (mW/cm ²) @ 20 cm Separation	Limit (mW/cm ²)
			(dBm)	(mW)	Log	Linear			
WLAN_2 400 ~ 2 483.5	802.11b	8.92 ± 1.0	9.92	9.82	2.70	1.86	1.21	0.003 6	1.00
	802.11g	7.58 ± 1.0	8.58	7.21			1.03	0.002 7	1.00
	802.11n_HT20	7.67 ± 1.0	8.67	7.36			1.04	0.002 7	1.00

According to above table, for WLAN_2 412 ~ 2 462 MHz Band(802.11n_HT20), (802.11b), (802.11g) safe distance,

$$D = 0.282 * \sqrt{(9.82 * 2.86)/1.00} = 1.21 \text{ cm.}$$

For getting power density at 20 cm separation in above table, following formula was used.

$$S = P * G / (4\pi * R^2) = 9.82 * 1.86 / (4 * \pi * 20^2) = 0.003 6$$

Where:

S = Power Density,

P = Power input to the external antenna (Output power from the EUT antenna port (dBm) – cable loss (dB)),

G = Gain of Transmit Antenna (linear gain), R = Distance from Transmitting Antenna