

# TEST REPORT

# Test Report No. : UL-RPT-RP11913492-2216C V2.0

Manufacturer	: Raspberry Pi (Trading) Ltd
Model No.	: Raspberry Pi 3 Model B+
FCC ID	: 2ABCB-RPI3BP
Technology	: Bluetooth – Low Energy
Test Standard(s)	: FCC Parts 15.207, 15.209(a) & 15.24

- 1. This test report shall not be reproduced in full or partial, without the written approval of UL VS LTD.
- 2. The results in this report apply only to the sample(s) tested.
- 3. The sample tested is in compliance with the above standard(s).
- 4. The test results in this report are traceable to the national or international standards.
- 5. Version 2.0 supersedes all previous versions.

Date of Issue:

06 March 2018

Checked by:

Wilders.

Sarah Williams Senior Test Engineer, Radio Laboratory

**Company Signatory:** 

I.M.

Ian Watch Senior Test Engineer, Radio Laboratory UL VS LTD



This laboratory is accredited by UKAS. The tests reported herein have been performed in accordance with its terms of accreditation.

The *Bluetooth*<sup>®</sup> word mark and logos are owned by the *Bluetooth* SIG, Inc. and any use of such marks by UL VS LTD is under licence. Other trademarks and trade names are those of their respective owners.

ISSUE DATE: 06 MARCH 2018

This page has been left intentionally blank.

# Table of Contents

1. Customer Information	. 4
<ul> <li>2. Summary of Testing</li></ul>	- <b>5</b> 5 6 6
<ul> <li>3. Equipment Under Test (EUT)</li> <li>3.1. Identification of Equipment Under Test (EUT)</li> <li>3.2. Description of EUT</li> <li>3.3. Modifications Incorporated in the EUT</li> <li>3.4. Additional Information Related to Testing</li> <li>3.5. Support Equipment</li> </ul>	. <b>7</b> 7 7 8 8
<ul> <li>4. Operation and Monitoring of the EUT during Testing</li></ul>	. <b>11</b> 11 11
<ul> <li>5. Measurements, Examinations and Derived Results</li> <li>5.1. General Comments</li> <li>5.2. Test Results</li> <li>5.2.1. Transmitter AC Conducted Spurious Emissions</li> <li>5.2.2. Transmitter Minimum 6 dB Bandwidth</li> <li>5.2.3. Transmitter Duty Cycle</li> <li>5.2.4. Transmitter Maximum Peak Output Power</li> <li>5.2.5. Transmitter Radiated Emissions</li> <li>5.2.6. Transmitter Band Edge Radiated Emissions</li> </ul>	12 13 13 13 21 23 26 33
6. Measurement Uncertainty	.36
7. Report Revision History	.37

# **<u>1. Customer Information</u>**

Company Name:	Raspberry Pi (Trading) Ltd
Address:	30 Station Road Cambridge CB1 2JH United Kingdom

# 2. Summary of Testing

#### 2.1. General Information

Specification Reference:	47CFR15.247
Specification Title:	Code of Federal Regulations Volume 47 (Telecommunications): Part 15 Subpart C (Intentional Radiators) - Section 15.247
Specification Reference:	47CFR15.207 and 47CFR15.209
Specification Title:	Code of Federal Regulations Volume 47 (Telecommunications): Part 15 Subpart C (Intentional Radiators) - Sections 15.207 and 15.209
Site Registration:	209735
Location of Testing:	UL VS LTD, Unit 3 Horizon, Wade Road, Kingsland Business Park, Basingstoke, Hampshire, RG24 8AH, United Kingdom
Test Dates:	29 November 2017 to 14 December 2017

# 2.2. Summary of Test Results

FCC Reference (47CFR)	Measurement	Result
Part 15.207	Transmitter AC Conducted Emissions	<b></b>
Part 15.247(a)(2)	Transmitter Minimum 6 dB Bandwidth	<b></b>
Part 15.35(c)	Transmitter Duty Cycle	Note 1
Part 15.247(e)	Transmitter Power Spectral Density	Note 2
Part 15.247(b)(3)	Transmitter Maximum Peak Output Power	<b></b>
Part 15.247(d)/15.209(a)	Transmitter Radiated Emissions	Ø
Part 15.247(d)/15.209(a)	Transmitter Band Edge Radiated Emissions	Ø
Key to Results		
I complied		

#### Note(s):

- 1. The measurement was performed to assist in the calculation of the level of average radiated emissions at the upper band edge.
- 2. In accordance with FCC KDB 558074 Section 10.1, PSD is not required if the maximum conducted output power is less than the PSD limit of 8 dBm / 3 kHz. The PSD level is therefore deemed to be equal to the measured total output power.

# 2.3. Methods and Procedures

Reference:	ANSI C63.10-2013
Title:	American National Standard of Procedures for Compliance Testing of Unlicensed Wireless Devices
Reference:	KDB 558074 D01 DTS Meas Guidance v04 April 5, 2017
Title:	Guidance for Performing Compliance Measurements on Digital Transmission Systems (DTS) Operating Under Section 15.247
Reference:	KDB 174176 D01 Line Conducted FAQ v01r01 June 3, 2015
Title:	AC Power-Line Conducted Emissions Frequently Asked Questions

# 2.4. Deviations from the Test Specification

For the measurements contained within this test report, there were no deviations from, additions to, or exclusions from the test specification identified above.

# 3. Equipment Under Test (EUT)

# 3.1. Identification of Equipment Under Test (EUT)

Brand Name:	Raspberry Pi
Model Name or Number:	Raspberry Pi 3 Model B+
Test Sample Serial Number:	Not marked or stated (Radiated sample)
Hardware Version:	V1.0
Software Version:	4.4
FCC ID:	2ABCB-RPI3BP

Brand Name:	Raspberry Pi
Model Name or Number:	Raspberry Pi 3 Model B+
Test Sample Serial Number:	Not marked or stated (Conducted sample with RF port)
Hardware Version:	V1.0
Software Version:	4.4
FCC ID:	2ABCB-RPI3BP

# 3.2. Description of EUT

The Equipment Under Test was a single board computer. It contains a *Bluetooth* and 2.4 GHz WLAN module powered from an AC/DC power supply. The antenna is integral.

#### 3.3. Modifications Incorporated in the EUT

No modifications were applied to the EUT during testing.

# 3.4. Additional Information Related to Testing

Technology Tested:	Bluetooth Low Energy	(Digital Transmission S	System)
Type of Unit:	Transceiver		
Channel Spacing:	2 MHz	2 MHz	
Modulation:	GFSK		
Data Rate:	1 Mbps	1 Mbps	
Power Supply Requirement(s):	Nominal	5.0 VDC	
Maximum Conducted Output Power:	7.3 dBm		
Antenna Gain:	3.5 dBi		
Transmit Frequency Range:	2402 MHz to 2480 MHz		
Transmit Channels Tested:	Channel ID	Channel Number	Channel Frequency (MHz)
	Bottom	37	2402
	Middle	17	2440
	Тор	39	2480

### 3.5. Support Equipment

The following support equipment was used to exercise the EUT during testing:

Description:	LCD Monitor
Brand Name:	Asus
Model Name or Number:	PA238
Serial Number:	D9LMTF114809

Description:	USB Mouse
Brand Name:	Microsoft
Model Name or Number:	MS1119
Serial Number:	CN-093H7Y-73826-54B-03W0

Description:	USB Keyboard
Brand Name:	Microsoft
Model Name or Number:	600
Serial Number:	0065806454108

Serial Number:

# Support Equipment (continued)

Description:	Power Supply. 230 VAC Input / 5 VDC output		
Brand Name:	Strontronics Ltd		
Model Name or Number:	DSA-12CA-05		
Serial Number:	Not marked or stated		
Description:	16 GB Micro SD card		
Brand Name:	SanDisk		
Model Name or Number:	НСІ		

Description:         HDMI cable. Quantity 1. Length 1.9 metres	
Brand Name:	Not marked or stated
Model Name or Number: Not marked or stated	
Serial Number:	Not marked or stated

Not marked or stated

Description:	Ethernet cable. Quantity 1. Length 1.0 metres	
Brand Name:	Not marked or stated	
Model Name or Number:	Not marked or stated	
Serial Number:	Not marked or stated	

Description:	USB cable. Quantity 2. Length 3.0 metres		
Brand Name:	Not marked or stated		
Model Name or Number:	Not marked or stated		
Serial Number:	Not marked or stated		

Description:	USB Hub		
Brand Name:	Hama		
Model Name or Number:	00078498		
Serial Number:	09825891600		

Description:	Ethernet Router		
Brand Name:	Netgear		
Model Name or Number:	GS605		
Serial Number:	1YG194390218E		

# Support Equipment (continued)

Description: HDMI hub		
Brand Name:	Sumvision	
Model Name or Number:	Cyclone Micro	
Serial Number:	SUM091104017	

Description:	USB dongle	
Brand Name:	Not marked or stated	
Model Name or Number:	Not marked or stated	
Serial Number:	Not marked or stated	

# 4. Operation and Monitoring of the EUT during Testing

#### 4.1. Operating Modes

The EUT was tested in the following operating mode(s):

• Transmitting at maximum power in *Bluetooth* LE mode with modulation, maximum possible data length available and Pseudorandom Bit Sequence 9.

#### 4.2. Configuration and Peripherals

The EUT was tested in the following configuration(s):

- The customer's test application and supplied instructions were used to place the EUT into *Bluetooth LE* test mode. The supplied commands were entered into the console menu on the EUT. Test commands stated in the bt\_testing.sh file located on the /home/pi drive of the EUT were used to configure the EUT to enable a continuous transmission and to select the test channels as required.
- The EUT was powered via an AC/DC switch mode power supply.
- Radiated spurious emissions were performed with the EUT in the X plane (worst case) while connected to its power supply. Tests were performed with the EUT connected to its AC adaptor and USB cable. All other ports were terminated with suitable terminations.
- The LCD monitor was connected to the EUT using a 2 metre long HDMI cable.
- The keyboard and mouse were connected to the USB port on the EUT.
- The EUT conducted sample was used for 6 dB bandwidth, duty cycle, power spectral density and maximum peak output power.
- The EUT radiated sample was used for AC conducted emissions and radiated spurious emissions tests.

# 5. Measurements, Examinations and Derived Results

#### 5.1. General Comments

Measurement uncertainties are evaluated in accordance with current best practice. Our reported expanded uncertainties are based on standard uncertainties, which are multiplied by an appropriate coverage factor to provide a statistical confidence level of approximately 95%. Please refer to *Section 6. Measurement Uncertainty* for details.

In accordance with UKAS requirements all the measurement equipment is on a calibration schedule. All equipment was within the calibration period on the date of testing.

### 5.2. Test Results

#### 5.2.1. Transmitter AC Conducted Spurious Emissions

#### Test Summary:

Test Engineer:	Doug Freegard	Test Date:	14 December 2017
Test Sample Serial Number:	Not marked or stated (Radiated sample)		

FCC Reference:	Part 15.207
Test Method Used:	ANSI C63.10 Section 6.2 / FCC KDB 174176 and notes below

#### **Environmental Conditions:**

Temperature (°C):	22
Relative Humidity (%):	34

#### Note(s):

- 1. The EUT was connected to a DC power supply which supplied the unit with 5.0 VDC. The DC power supply was connected to 120 VAC 60 Hz single phase supply via a LISN.
- 2. In accordance with FCC KDB 174176 Q4, tests were performed with a 240 VAC 60 Hz single phase supply as this was within the voltage range marked on the 5.0 V DC power supply.
- 3. A pulse limiter was fitted between the LISN and the test receiver.
- 4. Pre-scans were performed and markers placed on the highest live and neutral measured levels. Final measurements were performed on the marker frequencies and the results entered into the tables below.

#### Test setup:



ISSUE DATE: 06 MARCH 2018

#### Transmitter AC Conducted Spurious Emissions (continued)

Frequency (MHz)	Line	Level (dBµV)	Limit (dBµV)	Margin (dB)	Result
0.155	Live	58.4	65.8	7.4	Complied
0.177	Live	55.7	64.6	8.9	Complied
0.267	Live	47.7	61.2	13.5	Complied
0.411	Live	39.8	57.6	17.8	Complied
0.627	Live	30.9	56.0	25.1	Complied
11.166	Live	26.2	60.0	33.8	Complied

# Results: Live / Quasi Peak / 120 VAC 60 Hz

# Results: Live / Average / 120 VAC 60 Hz

Frequency (MHz)	Line	Level (dBµV)	Limit (dBµV)	Margin (dB)	Result
0.470	Live	30.8	46.5	15.7	Complied
0.807	Live	17.6	46.0	28.4	Complied
1.037	Live	17.6	46.0	28.4	Complied
1.311	Live	17.2	46.0	28.8	Complied
11.166	Live	19.7	50.0	30.3	Complied
25.058	Live	19.9	50.0	30.1	Complied

### Results: Neutral / Quasi Peak / 120 VAC 60 Hz

Frequency (MHz)	Line	Level (dBµV)	Limit (dBµV)	Margin (dB)	Result
0.195	Neutral	54.0	63.8	9.8	Complied
0.240	Neutral	51.2	62.1	10.9	Complied
0.321	Neutral	46.3	59.7	13.4	Complied
0.398	Neutral	44.7	57.9	13.2	Complied
0.654	Neutral	32.9	56.0	23.1	Complied
11.324	Neutral	31.1	60.0	28.9	Complied

### Results: Neutral / Average / 120 VAC 60 Hz

Frequency (MHz)	Line	Level (dBµV)	Limit (dBµV)	Margin (dB)	Result
0.150	Neutral	32.3	56.0	23.7	Complied
0.465	Neutral	26.8	46.6	19.8	Complied
1.014	Neutral	13.8	46.0	32.2	Complied
6.018	Neutral	17.7	50.0	32.3	Complied
11.382	Neutral	23.6	50.0	26.4	Complied
25.058	Neutral	20.4	50.0	29.6	Complied

# Transmitter AC Conducted Spurious Emissions (continued)

#### Results: 120 VAC 60 Hz



Note: These plots are pre-scans and for indication purposes only. For final measurements, see accompanying tables.

#### Transmitter AC Conducted Spurious Emissions (continued)

Frequency (MHz)	Line	Level (dBµV)	Limit (dBµV)	Margin (dB)	Result		
0.150	Live	52.8	66.0	13.2	Complied		
0.173	Live	51.0	64.8	13.8	Complied		
0.276	Live	43.0	60.9	17.9	Complied		
0.402	Live	35.2	57.8	22.6	Complied		
1.437	Live	29.7	56.0	26.3	Complied		
11.049	Live	27.6	60.0	32.4	Complied		

# Results: Live / Quasi Peak / 240 VAC 60 Hz

# Results: Live / Average / 240 VAC 60 Hz

Frequency (MHz)	Line	Level (dBµV)	Limit (dBµV)	Margin (dB)	Result
0.515	Live	30.3	46.0	15.7	Complied
0.924	Live	22.8	46.0	23.2	Complied
1.464	Live	23.6	46.0	22.4	Complied
2.000	Live	22.7	46.0	23.3	Complied
3.804	Live	22.1	46.0	23.9	Complied
25.058	Live	20.6	50.0	29.4	Complied

### Results: Neutral / Quasi Peak / 240 VAC 60 Hz

Frequency (MHz)	Line	Level (dBµV)	Limit (dBµV)	Margin (dB)	Result
0.150	Neutral	52.9	66.0	13.1	Complied
0.182	Neutral	50.1	64.4	14.3	Complied
0.267	Neutral	43.6	61.2	17.6	Complied
0.425	Neutral	33.9	57.4	23.5	Complied
1.437	Neutral	23.8	56.0	32.2	Complied
11.198	Neutral	29.4	60.0	30.6	Complied

### Results: Neutral / Average / 240 VAC 60 Hz

Frequency (MHz)	Line	Level (dBµV)	Limit (dBµV)	Margin (dB)	Result
0.155	Neutral	28.5	55.8	27.3	Complied
0.515	Neutral	24.7	46.0	21.3	Complied
1.442	Neutral	18.0	46.0	28.0	Complied
2.000	Neutral	16.0	46.0	30.0	Complied
4.502	Neutral	17.5	46.0	28.5	Complied
11.049	Neutral	21.6	50.0	28.4	Complied

# Transmitter AC Conducted Spurious Emissions (continued)

#### Results: 240 VAC 60 Hz



Note: These plots are pre-scans and for indication purposes only. For final measurements, see accompanying tables.

#### **Test Equipment Used:**

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M2013	Thermohygrometer	Testo	608-H1	45046424	20 Jun 2018	12
A649	LISN	Rohde & Schwarz	ESH3-Z5	825562/008	09 Aug 2018	12
A1830	Pulse Limiter	Rohde & Schwarz	ESH3-Z2	100668	09 May 2018	12
M1263	Test Receiver	Rohde & Schwarz	ESIB7	100265	13 Nov 2018	12
A2953	Power Supply	Tacima	SC 5467	Not stated	Calibrated before use	-
M1229	Multimeter	Fluke	179	87640015	12 May 2018	12

### 5.2.2. Transmitter Minimum 6 dB Bandwidth

#### **Test Summary:**

Test Engineer:	Doug Freegard	Test Date:	05 December 2017	
Test Sample Serial Number:	Not marked or stated (Conducted sample with RF port)			

FCC Reference:	Part 15.247(a)(2)
Test Method Used:	FCC KDB 558074 Section 8.1 Option 1

#### **Environmental Conditions:**

Temperature (°C):	25
Relative Humidity (%):	32

#### Note(s):

- 6 dB DTS bandwidth tests were performed using a signal analyser in accordance with FCC KDB 558074 Section 8.1 Option 1 measurement procedure. The signal analyser resolution bandwidth was set to 100 kHz and video bandwidth 300 kHz. A peak detector was used, sweep time was set to auto and the trace mode was Max Hold. The DTS bandwidth was measured at 6 dB down from the peak of the signal.
- 2. The signal analyser was connected to the RF port on the EUT using suitable attenuation and RF cable.

#### Test setup:



ISSUE DATE: 06 MARCH 2018

#### Transmitter Minimum 6 dB Bandwidth (continued)

Results:

Channel	6 dB Bandwidth (kHz)	Limit (kHz)	Margin (kHz)	Result
Bottom	709.100	≥500	209.100	Complied
Middle	709.100	≥500	209.100	Complied
Тор	709.100	≥500	209.100	Complied



#### **Bottom Channel**



**Top Channel** 



Middle Channel

# Transmitter Minimum 6 dB Bandwidth (continued)

### Test Equipment Used:

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M2002	Thermohygrometer	Testo	608-H1	45041825	22 Feb 2018	12
M1873	Signal Analyser	Rohde & Schwarz	FSV30	103074	13 Jun 2018	12
A2527	Attenuator	AtlanTecRF	AN18W5-20	832828#2	Calibrated before use	-
G0606	Signal Generator	Rohde & Schwarz	SMIQ 03B	832870 / 054	16 Feb 2018	12
M199	Power Meter	Rohde & Schwarz	NRVS	827023/075	11 Apr 2018	24
M1267	Power Sensor	Rohde & Schwarz	NRV-Z52	100155	15 Apr 2018	24

### 5.2.3. Transmitter Duty Cycle

#### Test Summary:

Test Engineer:	Doug Freegard	Test Date:	06 December 2017	
Test Sample Serial Number:	Not marked or stated (Conducted sample with RF port)			

FCC Reference:	Part 15.35(c)
Test Method Used:	FCC KDB 558074 Section 6.0

#### **Environmental Conditions:**

Temperature (°C):	25
Relative Humidity (%):	33

#### Note(s):

 In order to assist with the determination of the average level of fundamental and spurious emissions field strength, measurements were made of duty cycle to determine the transmission duration and the silent period time of the transmitter. The transmitter duty cycle was measured using a signal analyser in the time domain and calculated by using the following calculation:

10 log (1 / (On Time / [Period or 100 ms whichever is the lesser]))

 $10 \log (1 / (391.30 \,\mu\text{s} / 623.91 \,\mu\text{s})) = 2.0 \,d\text{B}$ 

#### Test setup:



# Transmitter Duty Cycle (continued)

# Results:

Pulse Duration (ms)	Pulse Duration Period (ms) (ms)		Duty Cycle Correction factor (dB)
0.626	0.391	62.5	2.0

Spect	Spectrum 🔆															
Ref Li	evel	30.00	dBm Of	fset	23.80 d	B 👄 F	RBW 10 №	IHz								
🛛 Att		20	) dB 😐 S1	νT	1.5 m	IS N	/BW 10 M	Ηz								
SGL TR	G:VII	)														
●1Pk M	ЗΧ															
									M1	[1]					6.70	dBm
20 dBm-															623.9	1 µs
20 0011									D2	[1]					0.4	2 dB
10 dBm			_			N	1				<del>D2</del>			8	391.3	0 µs
	-			1							4			Ē	-	_
0 dBm-	-		-			-					-					_
																_ I
-10 dBm	T	RG -10	.000 dBm-													
00 40-																_ I
-20 abr																
20 dam				1												
-30 abii	' I.			Yun	Wellyn	waller					PWV/	www	yan			_ I
-40 dBm	-		_			_									_	_
																- 1
-50 dBm	-		_	_		-										_
																_ I
-60 dBm	-												-		_	_
																- 1
CF 2.4	32 GF	lz	_				691	pts					_		150.0	JS/
Marker								-								
Type	Ref	Trc	Х-	value			r-value	1	Functi	ion		F	unctio	n Resi	ult	1
M1		1		623	.91 µs		6.70 dB	m								
D2	M1	1		39	1.3 µs		0.42 (	iВ								
D3	M1	1		626	.09 µs		0.10	iB								
	Ready 06.12.2017															
11913492																
Date: 6 DE	0 20	17 00-4	0.10													
Date: 0.Dt	-0.20	11 09.4	0.10													

### Test Equipment Used:

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M2002	Thermohygrometer	Testo	608-H1	45041825	22 Feb 2018	12
M1873	Signal Analyser	Rohde & Schwarz	FSV30	103074	13 Jun 2018	12
A2527	Attenuator	AtlanTecRF	AN18W5-20	832828#2	Calibrated before use	-
G0606	Signal Generator	Rohde & Schwarz	SMIQ 03B	832870 / 054	16 Feb 2018	12
M199	Power Meter	Rohde & Schwarz	NRVS	827023/075	11 Apr 2018	24
M1267	Power Sensor	Rohde & Schwarz	NRV-Z52	100155	15 Apr 2018	24

#### 5.2.4. Transmitter Maximum Peak Output Power

#### Test Summary:

Test Engineer:	Doug Freegard	Test Date:	06 December 2017	
Test Sample Serial Number:	Not marked or stated (Conducted sample with RF port)			

FCC Reference:	Part 15.247(b)(3)
Test Method Used:	FCC KDB 558074 Section 9.1.1 and Notes below

#### **Environmental Conditions:**

Temperature (°C):	25
Relative Humidity (%):	32

#### Note(s):

- 1. Conducted power tests were performed using a signal analyser in accordance with FCC KDB 558074 Section 9.1.1 with the RBW > *DTS bandwidth* procedure.
- 2. The signal analyser resolution bandwidth was set to 2 MHz and video bandwidth of 10 MHz. A peak detector was used, sweep time was set to auto and trace mode was Max Hold. The span was set to 6 MHz. A marker was placed at the peak of the signal and the results recorded in the tables below.
- The signal analyser was connected to the RF port on the EUT using suitable attenuation and RF cable. An RF level offset was entered on the signal analyser to compensate for the loss of the attenuator and RF cable.
- 4. The conducted power was added to the declared antenna gain to obtain the EIRP.

#### Test setup:



# Transmitter Maximum Peak Output Power (continued)

## Results:

Channel	Conducted Peak Power (dBm)	Conducted Peak Power Limit (dBm)	Margin (dB)	Result
Bottom	7.2	30.0	22.8	Complied
Middle	7.3	30.0	22.7	Complied
Тор	5.4	30.0	24.6	Complied

Channel	Conducted Peak Power (dBm)	Declared Antenna Gain (dBi)	EIRP (dBm)	De Facto EIRP Limit (dBm)	Margin (dB)	Result
Bottom	7.2	3.5	10.7	36.0	25.3	Complied
Middle	7.3	3.5	10.8	36.0	25.2	Complied
Тор	5.4	3.5	8.9	36.0	27.1	Complied

#### Transmitter Maximum Peak Output Power (continued)



#### **Bottom Channel**





#### Middle Channel

# Top Channel

#### Test Equipment Used:

Asset No.	Instrument	Manufacturer	Туре No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M2002	Thermohygrometer	Testo	608-H1	45041825	22 Feb 2018	12
M1873	Signal Analyser	Rohde & Schwarz	FSV30	103074	13 Jun 2018	12
A2527	Attenuator	AtlanTecRF	AN18W5-20	832828#2	Calibrated before use	-
G0606	Signal Generator	Rohde & Schwarz	SMIQ 03B	832870 / 054	16 Feb 2018	12
M199	Power Meter	Rohde & Schwarz	NRVS	827023/075	11 Apr 2018	24
M1267	Power Sensor	Rohde & Schwarz	NRV-Z52	100155	15 Apr 2018	24

#### 5.2.5. Transmitter Radiated Emissions

#### Test Summary:

Test Engineer:	David Doyle	Test Date:	30 November 2017		
Test Sample Serial Number:	Not marked or stated (Radiated sample)				

FCC Reference:	Parts 15.247(d) & 15.209(a)
Test Method Used:	ANSI C63.10 Sections 6.3 and 6.5
Frequency Range	30 MHz to 1000 MHz

#### **Environmental Conditions:**

Temperature (°C):	23
Relative Humidity (%):	31

#### Note(s):

- 1. The final measured value, for the given emission, in the table below incorporates the calibrated antenna factor and cable loss.
- 2. The preliminary scans showed similar emission levels below 1 GHz, for each channel of operation. Therefore final radiated emissions measurements were performed with the EUT set to the middle channel only.
- 3. All other emissions shown on the pre-scan plots were investigated and found to be ambient, or >20 dB below the applicable limit or below the measurement system noise floor and therefore not recorded.
- 4. Measurements below 1 GHz were performed in a semi-anechoic chamber (Asset Number K0017) at a distance of 3 metres. The EUT was placed at a height of 80 cm above the reference ground plane in the centre of the chamber turntable. Maximum emission levels were determined by height searching the measurement antenna over the range 1 metre to 4 metres.
- 5. Pre-scans were performed and markers placed on the highest measured levels. The test receiver resolution bandwidth was set to 100 kHz and video bandwidth 300 kHz. A peak detector was used, sweep time was set to auto and trace mode was Max Hold.
- 6. Final measurements were performed on the marker frequencies and the results entered into the table below. The test receiver resolution bandwidth was set to 120 kHz, using a CISPR quasi-peak detector and span big enough to see the whole emission.

ISSUE DATE: 06 MARCH 2018

#### **Transmitter Radiated Emissions (continued)**

### Test setup for radiated measurements:

![](_page_26_Figure_6.jpeg)

VERSION 2.0

ISSUE DATE: 06 MARCH 2018

# Transmitter Radiated Emissions (continued)

#### Test setup for radiated measurements (continued):

![](_page_27_Figure_6.jpeg)

Results:	Middle Channel

Frequency	Antenna	Level	Limit	Margin	Result
(MHz)	Polarity	(dBµV/m)	(dBµV/m)	(dB)	
74.261	Horizontal	29.2	40.0	10.8	Complied

![](_page_28_Figure_7.jpeg)

Note: This plot is a pre-scan and for indication purposes only. For final measurements, see accompanying table.

# Test Equipment Used:

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M2003	Thermohygrometer	Testo	608-H1	45046641	22 Feb 2018	12
K0017	3m RSE Chamber	Rainford EMC	N/A	N/A	14 Apr 2018	12
M1995	Test Receiver	Rohde & Schwarz	ESU40	100428	13 Apr 2018	12
A2888	Antenna	Schwarzbeck	VULB 9163	9163-941	25 Apr 2018	12
A2147	Attenuator	AtlanTecRF	AN18-06	09020206-06	25 Apr 2018	12
A2131	Low Pass Filter	AtlanTecRF	AFL-02000	JFB1004-002	27 Feb 2018	12

#### Test Summary:

Test Engineer:	David Doyle	Test Date:	29 November 2017	
Test Sample Serial Number:	Not marked or stated (Radiated sample)			

FCC Reference:	Parts 15.247(d) & 15.209(a)			
Test Method Used:	FCC KDB 558074 Sections 11 & 12 referencing ANSI C63.10 Sections 6.3 and 6.6			
Frequency Range	1 GHz to 25 GHz			

#### **Environmental Conditions:**

Temperature (°C):	23
Relative Humidity (%):	32

#### Note(s):

- 1. The final measured value, for the given emission, in the table below incorporates the calibrated antenna factor and cable loss.
- 2. The emission shown on the 1 GHz to 3 GHz plot is the EUT fundamental.
- 3. No spurious emissions were detected above the noise floor of the measuring receiver therefore the highest peak and average noise floor readings of the measuring receiver were recorded as shown in the tables below.
- 4. Pre-scans above 1 GHz were performed in fully anechoic chamber (Asset Number K0017) at a distance of 3 metres. The EUT was placed at a height of 1.5 metres above the test chamber floor in the centre of the chamber turntable. All measurement antennas were placed at a fixed height of 1.5 metres above the test chamber floor, in line with the EUT.
- 5. Pre-scans were performed and a marker placed on the highest measured level of the appropriate plot. The test receiver resolution bandwidth was set to 1 MHz and video bandwidth 3 MHz. The sweep time was set to auto. Peak and average measurements were performed with their own appropriate detectors during the pre-scan measurements.

#### **Results: Peak / Middle Channel**

Frequency	Antenna	Peak Level	Peak Limit	Margin	Result
(MHz)	Polarity	(dBμV/m)	(dBμV/m)	(dB)	
2609.500	Vertical	54.9	74.0	19.1	Complied

#### Results: Average / Middle Channel

Frequency	Antenna	Average Level	Average Limit	Margin	Result
(MHz)	Polarity	(dBμV/m)	(dBμV/m)	(dB)	
2894.500	Vertical	47.7	54.0	6.3	Complied

![](_page_30_Figure_5.jpeg)

![](_page_30_Figure_6.jpeg)

913492

te: 29.NOV.2017 12:01:34

UL VS LTD

### Test Equipment Used:

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M2003	Thermohygrometer	Testo	608-H1	45046641	22 Feb 2018	12
K0017	3m RSE Chamber	Rainford EMC	N/A	N/A	14 Feb 2018	12
M1995	Test Receiver	Rohde & Schwarz	ESU40	100428	13 Apr 2018	12
A2863	Pre-Amplifier	Agilent	8449B	3008A02100	11 Apr 2018	12
A2891	Pre-Amplifier	Schwarzbeck	BBV 9718	9718-306	11 Apr 2018	12
A2893	Pre-Amplifier	Schwarzbeck	BBV 9721	9721-021	11 Apr 2018	12
A2889	Antenna	Schwarzbeck	BBHA 9120 B	BBHA 9120 B 653	11 Apr 2018	12
A2890	Antenna	Schwarzbeck	HWRD 750	014	11 Apr 2018	12
A2892	Antenna	Schwarzbeck	BBHA 9170	9170-727	11 Apr 2018	12
A2916	Attenuator	AtlanTecRF	AN18W5-10	832827#1	03 Mar 2018	12
A2914	High Pass Filter	AtlanTecRF	AFH-03000	2155	06 Mar 2018	12
A2947	High Pass Filter	AtlanTecRF	AFH-07000	1601900001	18 May 2018	12
M1269	Multimeter	Fluke	179	90250210	02 May 2018	12
S0538	Bench Power Supply	ТТІ	PL154	250135	Calibrated before use	-

#### 5.2.6. Transmitter Band Edge Radiated Emissions

#### **Test Summary:**

Test Engineer:	David Doyle	Test Date:	29 November 2017
Test Sample Serial Number:         Not marked or stated (Radiated sample)			

FCC Reference:	Parts 15.247(d) & 15.209(a)
Test Method Used:	KDB 558074 Section 11 & 12

#### **Environmental Conditions:**

Temperature (°C):	23
Relative Humidity (%):	32

#### Note(s):

- 1. The final measured value, for the given emission, in the table below incorporates the calibrated antenna factor and cable loss.
- The maximum peak conducted output power was previously measured. In accordance with FCC KDB 558074 Section 11.1(a), the lower band edge measurement was performed with a peak detector and the -20 dBc limit applied.
- 3. As the lower band edge is adjacent to a non-restricted band, only peak measurements are required. In accordance with FCC KDB 558074 Section 11.1, the test method in Section 11.3 was followed: the test receiver resolution bandwidth was set to 100 kHz and video bandwidth 300 kHz. A peak detector was used, sweep time was set to auto and trace mode was Max Hold. The test receiver was left to sweep for a sufficient length of time in order to maximise the carrier level and out-of-band emissions. A marker and corresponding reference level line were placed on the peak of the carrier. As the maximum peak conducted output power was measured using a peak detector in accordance with FCC KDB 558074 Section 9.1.1 an out-of-band limit line was placed 20 dB (FCC KDB 558074 Section 11.1(a)) below the peak level. A marker was placed on the band edge spot frequencies. Marker frequency and levels were recorded.
- 4. As the upper band edge falls within a restricted band both peak and average measurements were recorded by placing a marker at the edge of the band. For peak measurements the test receiver resolution bandwidth was set to 1 MHz and the video bandwidth 3 MHz. A peak detector was used, sweep time was set to auto and trace mode was Max Hold. For average measurements the test receiver resolution bandwidth was set to 1 MHz and the video bandwidth 3 MHz. An RMS detector was used, sweep time was set to auto and trace mode was trace averaging over 300 sweeps. A marker was placed on the band edge spot frequencies and a second marker placed on the highest emission level in the adjacent restricted band of operation (where a higher level emission was present). Marker frequencies and levels were recorded.
- 5. There is a restricted band 10 MHz below the lower band edge. The test receiver was set up as follows: the RBW set to 1 MHz, the VBW set to 3 MHz, with the sweep time set to auto couple. Peak and average measurements were performed with peak and RMS detectors respectively. Markers were placed on the highest point on each trace.
- 6. \* -20 dBc limit.

#### Transmitter Band Edge Radiated Emissions (continued)

#### **Results: Peak**

Frequency (MHz)	Antenna Polarity	Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Result
2394.872	Vertical	47.1	82.3*	35.2	Complied
2400.0	Vertical	46.0	82.3*	36.3	Complied
2483.5	Vertical	51.0	74.0	23.0	Complied
2505.776	Vertical	53.3	74.0	20.7	Complied

#### **Results: Average**

Frequency (MHz)	Level (dBµV/m)	Duty Cycle Correction (dB)	Corrected Level (dBµV/m)	Limit (dBµV/m)	Margin (dB)	Result
2483.500	40.5	2.0	42.5	54.0	11.5	Complied

#### Results: 2310 MHz to 2390 MHz Restricted Band / Peak

Frequency	Antenna	Level	Limit	Margin	Result
(MHz)	Polarity	(dBµV/m)	(dBµV/m)	(dB)	
2355.897	Vertical	54.5	74.0	19.5	Complied

#### Results: 2310 MHz to 2390 MHz Restricted Band / Average

Frequency	Antenna	Level	Limit	Margin	Result
(MHz)	Polarity	(dBµV/m)	(dBµV/m)	(dB)	
2376.282	Vertical	41.1	54.0	12.9	Complied

VERSION 2.0

### Transmitter Band Edge Radiated Emissions (continued)

![](_page_34_Figure_5.jpeg)

2310 MHz to 2390 MHz Restricted Band Plot

#### Test Equipment Used:

Asset No.	Instrument	Manufacturer	Type No.	Serial No.	Date Calibration Due	Cal. Interval (Months)
M2003	Thermohygrometer	Testo	608-H1	45046641	22 Feb 2018	12
K0017	3m RSE Chamber	Rainford	N/A	N/A	14 Apr 2018	12
M1995	Test Receiver	Rohde & Schwarz	ESU40	100428	13 Apr 2018	12
A2863	Pre-Amplifier	Agilent	8449B	3008A02100	11 Apr 2018	12
A2889	Antenna	Schwarzbeck	BBHA 9120 B	BBHA 9120 B 653	11 Apr 2018	12
A2916	Attenuator	AtlanTecRF	AN18W5-10	832827#1	03 Mar 2018	12

# 6. Measurement Uncertainty

No measurement or test can ever be perfect and the imperfections give rise to error of measurement in the results. Consequently the result of a measurement is only an approximation to the value measured (the specific quantity subject to measurement) and is only complete when accompanied by a statement of the uncertainty of the approximation.

The expression of uncertainty of a measurement result allows realistic comparison of results with reference values and limits given in specifications and standards.

The uncertainty of the result may need to be taken into account when interpreting the measurement results.

The reported expanded uncertainties below are based on a standard uncertainty multiplied by an appropriate coverage factor such that a confidence level of approximately 95% is maintained. For the purposes of this document "approximately" is interpreted as meaning "effectively" or "for most practical purposes".

Measurement Type	Range	Confidence Level (%)	Calculated Uncertainty
AC Conducted Spurious Emissions	0.15 MHz to 30 MHz	95%	±4.69 dB
Conducted Maximum Peak Output Power	2.4 GHz to 2.4835 GHz	95%	±1.13 dB
Minimum 6 dB Bandwidth	2.4 GHz to 2.4835 GHz	95%	±4.59 %
Duty Cycle	2.4 GHz to 2.4835 GHz	95%	±1.14 %
Radiated Spurious Emissions	30 MHz to 1 GHz	95%	±5.65 dB
Radiated Spurious Emissions	1 GHz to 26.5 GHz	95%	±2.94 dB

The methods used to calculate the above uncertainties are in line with those recommended within the various measurement specifications. Where measurement specifications do not include guidelines for the evaluation of measurement uncertainty the published guidance of the appropriate accreditation body is followed.

# 7. Report Revision History

Version	Revision Details				
Number	Page No(s)	Clause	Details		
1.0	-	-	Initial Version		
2.0	28	-	Test setup diagram added		

--- END OF REPORT ---