



BUREAU
VERITAS

FCC RF Exposure Test Report



VARIANT FCC RF Exposure Test Report

Report No. : W7L-230608W001SA01
Applicant : Borqs BeiJing Ltd.
Address : Tower A, Building B23, Universal Business Park, No. 10 Jiuxianqiao Road,
Chaoyang District Beijing, 100015 China
Product : Ecoport AC LTE-LP
FCC ID : 2ABDK-US08B
Brand : SkyCentrics
Model No. : US08Ba
Serial Model Name: US08B
Standards : FCC Part 2 (Section 2.1091)
KDB 447498 D01 General RF Exposure Guidance v06
Sample Received Date : Jun. 25, 2023
Date of Testing : Jun. 25, 2023 ~ Jun. 29, 2023

CERTIFICATION: The above equipment have been tested by **BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO., LTD.**, and found compliance with the requirement of the above standards. The test record, data evaluation & Equipment Under Test (EUT) configurations represented herein are true and accurate accounts of the measurements of the sample's SAR characteristics under the conditions specified in this report. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product certification, approval, or endorsement by A2LA or any government agencies.

Prepared By :

Jerry Chen

Jerry Chen / Engineer

Approved By :

Luke Lu

Luke Lu / Manager

This report is governed by, and incorporates by reference, the Conditions of Testing as posted at the date of issuance of this report at <http://www.bureauveritas.com/home/about-us/our-business/cps/about-us/terms-conditions/> and is intended for your exclusive use. Any copying or replication of this report to or for any other person or entity, or use of our name or trademark, is permitted only with our prior written permission. This report sets forth our findings solely with respect to the test samples identified herein. The results set forth in this report are not indicative or representative of the quality or characteristics of the lot from which a test sample was taken or any similar or identical product unless specifically and expressly noted. Our report includes all of the tests requested by you and the results thereof based upon the information that you provided to us. Measurement uncertainty is only provided upon request for accredited tests. Statements of conformity are based on simple acceptance criteria without taking measurement uncertainty into account, unless otherwise requested in writing. You have 60 days from date of issuance of this report to notify us of any material error or omission caused by our negligence or if you require measurement uncertainty; provided, however, that such notice shall be in writing and shall specifically address the issue you wish to raise. A failure to raise such issue within the prescribed time shall constitute your unqualified acceptance of the completeness of this report, the tests conducted and the correctness of the report contents.



BUREAU
VERITAS



Table of Contents

RELEASE CONTROL RECORD.....	3
1. DESCRIPTION OF EQUIPMENT UNDER TEST	4
2. MPE(MAXIMUM PERMISSIBLE EXPOSURE) ASSESSMENT	5
2.1 INTRODUCTION.....	5
2.2 RF RADIATION EXPOSURE LIMITS.....	5
2.3 MPE ASSESSMENT METHOD.....	6
2.4 MPE CALCULATION FOR STANDALONE OPERATIONS.....	6
3. INFORMATION ON THE TESTING LABORATORIES.....	9



BUREAU
VERITAS



Certificate # 3939.01

Release Control Record

Report No.	Reason for Change	Date Issued
W7L-230313W001SA01	Initial release	Apr. 03, 2023
W7L-230608W001SA01	Based on the original product change HW&SW version and the location of some components (more details please refer to the discrepancy declaration). This report verify power. The tune up is same as before, so the data doesn't update.	Jun. 29, 2023



BUREAU
VERITAS

FCC RF Exposure Test Report



Description of Equipment Under Test

EUT Type	Ecoport AC LTE-LP
FCC ID	2ABDK-US08B
Brand Name	SkyCentrics
Model Name	US08Ba
Serial Model Name	US08B
Tx Frequency Bands (Unit: MHz)	<p>LTE CAT-M1:</p> <p>LTE Band 2 : 1850.7 MHz ~ 1909.3 MHz LTE Band 4 : 1710.7 MHz ~ 1754.3 MHz LTE Band 5 : 824.7 MHz ~ 848.3 MHz LTE Band 8 : 898.2MHz ~ 899.8MHz LTE Band 12 : 699.7 MHz ~ 715.3 MHz LTE Band 13 : 779.5 MHz ~ 784.5 MHz LTE Band 25 : 1850.7MHz ~ 1914.3MHz LTE Band 26 : 824.7MHz ~ 848.3MHz LTE Band 66 : 1710.7MHz ~ 1779.3MHz LTE Band 85 : 700.5MHz ~ 713.5MHz</p> <p>LTE NB-IOT:</p> <p>LTE Band 2 : 1850.2 MHz ~ 1909.8 MHz LTE Band 4 : 1710.2 MHz ~ 1754.8 MHz LTE Band 5 : 824.2 MHz ~ 848.8 MHz LTE Band 8 : 897.7MHz ~ 900.3MHz LTE Band 12 : 699.2 MHz ~ 715.8 MHz LTE Band 13 : 777.2 MHz ~ 786.8 MHz LTE Band 25 : 1850.2MHz ~ 1914.8MHz LTE Band 66 : 1710.2MHz ~ 1779.8MHz LTE Band 71 : 663.2MHz ~ 697.8MHz LTE Band 85 : 698.2MHz ~ 715.8MHz</p>
Uplink Modulations	LTE : QPSK, 16QAM, BPSK
Antenna Type	WWAN: Internal/External antenna
EUT Stage	Production Unit

Note: 1. The above EUT information is declared by manufacturer and for more detailed features description please refers to the manufacturer's specifications or User's Manual.

2. US08Ba and US08B Difference description:

No	Model ID	Difference Description
1	US08B	Only supports Internal Antenna
2	US08Ba	Supports both Internal Antenna and External Antenna There is an additional Sub board which is connected with main board by RF cable for External antenna assembly.

MPE(Maximum Permissible Exposure) Assessment

2.1 Introduction

According to 47 CFR §2.1091, a mobile device is defined as a transmitting device designed to be used in other than fixed locations and to generally be used in such a way that a separation distance of at least 20 cm is normally maintained between the transmitting antenna and the body of the user or nearby persons. In this context, the term “fixed location” means that the device is physically secured at one location and is not able to be easily moved to another location. Transmitting devices designed to be used by consumers or workers that can be easily re-located, such as wireless devices associated with a personal computer, are considered to be mobile devices if they meet the 20 cm separation requirement. The limits to be used for MPE evaluation are specified in §1.1310. All unlicensed personal communications service (PCS) devices and unlicensed NII devices shall be subject to the limits for general population/uncontrolled exposure.

2.2 RF Radiation Exposure Limits

According to 47 CFR §1.1310, the criteria listed in below table shall be used to evaluate the environmental impact of human exposure to RF radiation as specified in §1.1307(b), except in the case of portable devices which shall be evaluated according to the provisions of §2.1093.

Frequency Range (MHz)	Electric Field Strength (V/m)	Magnetic Field Strength (A/m)	Power Density (mW/cm ²)	Averaging Time (min)
(A) Limits for Occupational / Controlled Exposures				
0.3 – 3.0	614	1.63	100	6
3.0 – 30	1842/f	4.89/f	900/f ²	6
30 – 300	61.4	0.163	1.0	6
300 – 1500	-	-	f/300	6
1500 – 100000	-	-	5	6
(B) Limits for General Population / Uncontrolled Exposures				
0.3 – 1.34	614	1.63	100	30
1.34 – 30	824/f	2.19/f	180/f ²	30
30 – 300	27.5	0.073	0.2	30
300 – 1500	-	-	f/1500	30
1500 – 100000	-	-	1.0	30

Limits for maximum permissible exposure (MPE)

Notes:

- f = frequency in MHz
- Occupational/controlled limits apply in situations in which persons are exposed as a consequence of their employment provided those persons are fully aware of the potential for exposure and can exercise control over their exposure. Limits for occupational/controlled exposure also apply in situations when an individual is transient through a location where occupational/controlled limits apply provided they are made aware of the potential for exposure.
- General population/uncontrolled exposures apply in situations in which the general public may be exposed, or in which persons that are exposed as a consequence of their employment may not be fully aware of the potential for exposure or cannot exercise control over their exposure.



BUREAU
VERITAS



2.3 MPE Assessment Method

Calculations can be made to predict RF field strength and power density levels around typical RF sources. For example, in the case of a single radiating antenna, a prediction for power density in the far-field of the antenna can be made by use of the general Equations below. This equation is generally accurate in the far-field of an antenna but will over-predict power density in the near field, where they could be used for making a "worst case" or conservative prediction.

$$\text{Power Density (S)} = \frac{PG}{4\pi R^2} = \frac{\text{EIRP}}{4\pi R^2}$$

Where

S = Power Density, unit in mW/cm²

P = Power input to the antenna, unit in mW

G = Power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Distance to the center of radiation of the antenna, unit in cm

EIRP = Effective isotropically radiated power

2.4 MPE Calculation for Standalone Operations

The manufacturer expects that the radiated component of this device will not close to the human body during normal usage and the warning statement was also stated in the user instruction. Since the transmitting antenna will be kept at least 20 cm away from the human body, the MPE level is calculated based on this condition and the result is listed in below table.



BUREAU
VERITAS

FCC RF Exposure Test Report



Certificate # 3939.01

CALCULATION FOR MAXIMUM E.I.R.P

US08Ba:

LTE CAT-M1

Band	Antenna Gain (dBi)	Maximum Power (dBm)	Average EIRP (mW)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Power Density / Limit	Result (PASS / FAIL)
LTE Band 2	0.39	22	173.380	0.035	1.000	0.035	Pass
LTE Band 4	-0.55	22	139.637	0.028	1.000	0.028	Pass
LTE Band 5	-2.98	22	79.799	0.016	0.550	0.029	Pass
LTE Band 8	-3.67	22	68.077	0.014	0.599	0.023	Pass
LTE Band 12	-2.81	22	82.985	0.017	0.466	0.035	Pass
LTE Band 13	-2.46	22	89.950	0.018	0.520	0.034	Pass
LTE Band 25	0.39	22	173.380	0.035	1.000	0.035	Pass
LTE Band 26	-2.98	22	79.799	0.016	0.550	0.029	Pass
LTE Band 66	-0.55	22	139.637	0.028	1.000	0.028	Pass
LTE Band 85	-2.81	22	82.985	0.017	0.467	0.035	Pass

LTE NB-IOT

Band	Antenna Gain (dBi)	Maximum Power (dBm)	Average EIRP (mW)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Power Density / Limit	Result (PASS / FAIL)
LTE Band 2	0.39	22	173.380	0.035	1.000	0.035	Pass
LTE Band 4	-0.55	22	139.637	0.028	1.000	0.028	Pass
LTE Band 5	-2.98	22	79.799	0.016	0.549	0.029	Pass
LTE Band 8	-3.67	22	68.077	0.014	0.598	0.023	Pass
LTE Band 12	-2.81	22	82.985	0.017	0.466	0.035	Pass
LTE Band 13	-2.46	22	89.950	0.018	0.518	0.035	Pass
LTE Band 25	0.39	22	173.380	0.035	1.000	0.035	Pass
LTE Band 66	-0.55	22	139.637	0.028	1.000	0.028	Pass
LTE Band 71	-3.37	22	72.946	0.015	0.442	0.033	Pass
LTE Band 85	-2.81	22	82.985	0.017	0.465	0.035	Pass



BUREAU
VERITAS

FCC RF Exposure Test Report



US08B:

LTE CAT-M1

Band	Antenna Gain (dBi)	Maximum Power (dBm)	Average EIRP (mW)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Power Density / Limit	Result (PASS / FAIL)
LTE Band 2	2.02	22	252.348	0.050	1.000	0.050	Pass
LTE Band 4	2.53	22	283.792	0.056	1.000	0.056	Pass
LTE Band 5	-3.94	22	63.973	0.013	0.550	0.023	Pass
LTE Band 8	-5.1	22	48.978	0.010	0.599	0.016	Pass
LTE Band 12	-3.1	22	77.625	0.015	0.466	0.033	Pass
LTE Band 13	-2.19	22	95.719	0.019	0.520	0.037	Pass
LTE Band 25	2.02	22	252.348	0.050	1.000	0.050	Pass
LTE Band 26	-3.94	22	63.973	0.013	0.550	0.023	Pass
LTE Band 66	2.53	22	283.792	0.056	1.000	0.056	Pass
LTE Band 85	-3.1	22	77.625	0.015	0.467	0.033	Pass

LTE NB-IOT

Band	Antenna Gain (dBi)	Maximum Power (dBm)	Average EIRP (mW)	Power Density (mW/cm ²)	Limit (mW/cm ²)	Power Density / Limit	Result (PASS / FAIL)
LTE Band 2	2.02	22	252.348	0.050	1.000	0.050	Pass
LTE Band 4	2.53	22	283.792	0.056	1.000	0.056	Pass
LTE Band 5	-3.94	22	63.973	0.013	0.549	0.023	Pass
LTE Band 8	-5.1	22	48.978	0.010	0.598	0.016	Pass
LTE Band 12	-3.1	22	77.625	0.015	0.466	0.033	Pass
LTE Band 13	-2.19	22	95.719	0.019	0.518	0.037	Pass
LTE Band 25	2.02	22	252.348	0.050	1.000	0.050	Pass
LTE Band 66	2.53	22	283.792	0.056	1.000	0.056	Pass
LTE Band 71	-4.93	22	50.933	0.010	0.442	0.023	Pass
LTE Band 85	-3.1	22	77.625	0.015	0.465	0.033	Pass



BUREAU
VERITAS

FCC RF Exposure Test Report



Information on the Testing Laboratories

We, BV 7LAYERS COMMUNICATIONS TECHNOLOGY (SHENZHEN) CO., LTD., were founded in 2015 to provide our best service in EMC, Radio, Telecom and Safety consultation. Our laboratories are accredited and approved according to ISO/IEC 17025.

If you have any comments, please feel free to contact us at the following:

Add: No. B102, Dazu Chuangxin Mansion, North of Beihuan Avenue, North Area, Hi-Tech Industry Park, Nanshan District, Shenzhen, Guangdong, China

Tel: 86-755-8869-6566

Fax: 86-755-8869-6577

Email: customerservice.sw@bureauveritas.com

Web Site: www.bureauveritas.com

The road map of all our labs can be found in our web site also.

---END---