



FCC 47 CFR PART 15 SUBPART C

TEST REPORT

For

Smart Cloud Camera

Model: SMC-1X

Trade Name: SALIX

Issued to

SALIX TECHNOLOGY CO., LTD.

5F, NO. 16, LANE 77, HSING AI RD., NEI-HU, TAIPEI 114, TAIWAN, R.O.C.

Issued by

Compliance Certification Services Inc.

**No.11, Wugong 6th Rd., Wugu Dist.,
New Taipei City 24891, Taiwan. (R.O.C.)**

<http://www.ccsrf.com>

service@ccsrf.com

Issued Date: March 6, 2015



***Note:** This report shall not be reproduced except in full, without the written approval of Compliance Certification Services Inc. This document may be altered or revised by Compliance Certification Services Inc. personnel only, and shall be noted in the revision section of the document.*



Revision History

Rev.		Issue Date		Revisions	Effect Page	Revised By
00		March 6, 2015		Initial Issue	ALL	Kelly Cheng



TABLE OF CONTENTS

1. TEST RESULT CERTIFICATION.....	4
2. EUT DESCRIPTION	5
3. TEST METHODOLOGY	6
3.1 EUT CONFIGURATION	6
3.2 EUT EXERCISE.....	6
3.3 GENERAL TEST PROCEDURES.....	6
3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS	7
3.5 DESCRIPTION OF TEST MODES	8
4. INSTRUMENT CALIBRATION.....	9
4.1 MEASURING INSTRUMENT CALIBRATION	9
4.2 MEASUREMENT EQUIPMENT USED	9
4.3 MEASUREMENT UNCERTAINTY	10
5. FACILITIES AND ACCREDITATIONS	11
5.1 FACILITIES	11
5.2 EQUIPMENT.....	11
5.3 TABLE OF ACCREDITATIONS AND LISTINGS.....	12
6. SETUP OF EQUIPMENT UNDER TEST	13
6.1 SETUP CONFIGURATION OF EUT.....	13
6.2 SUPPORT EQUIPMENT	13
7. FCC PART 15.247 REQUIREMENTS.....	14
7.1 6DB BANDWIDTH	14
7.2 PEAK POWER.....	25
7.3 AVERAGE POWER	27
7.4 BAND EDGES MEASUREMENT	29
7.5 PEAK POWER SPECTRAL DENSITY	49
7.6 SPURIOUS EMISSIONS.....	60
7.7 RADIATED EMISSIONS	70
7.8 POWERLINE CONDUCTED EMISSIONS.....	84
APPENDIX I PHOTOGRAPHS OF TEST SETUP.....	87



1. TEST RESULT CERTIFICATION

Applicant: SALIX TECHNOLOGY CO., LTD.
5F, NO. 16, LANE 77, HSING AI RD., NEI-HU, TAIPEI 114,
TAIWAN, R.O.C.

Equipment Under Test: Smart Cloud Camera

Trade Name: SALIX

Model: SMC-1

Date of Test: March 2~ 3, 2015

APPLICABLE STANDARDS	
STANDARD	TEST RESULT
FCC 47 CFR Part 15 Subpart C	No non-compliance noted

We hereby certify that:

The above equipment was tested by Compliance Certification Services Inc. The test data, data evaluation, test procedures, and equipment configurations shown in this report were made in accordance with the procedures given in ANSI C63.4: 2009 and the energy emitted by the sample EUT tested as described in this report is in compliance with the requirements of FCC Rules Part 15.207, 15.209, 15.247.

The test results of this report relate only to the tested sample EUT identified in this report.

Approved by:

Reviewed by:

Miller Lee
Section Manager
Compliance Certification Services Inc.

Angel Cheng
Section Manager
Compliance Certification Services Inc.



2. EUT DESCRIPTION

Product	Smart Cloud Camera
Trade Name	SALIX
Model Number	SMC-1
Model Discrepancy	N/A
Received Date	January 21, 2015
Power Rating	VDC from Power Adapter SALIX / PA-2 I/P: 100-240V, 50-60Hz, 0.15A O/P: 5V, 1A
Frequency Range	2412 ~ 2462 MHz
Transmit Power	IEEE 802.11b mode: 17.47dBm IEEE 802.11g mode: 21.93 dBm IEEE 802.11n HT 20 mode: 21.51 dBm
Modulation Technique	IEEE 802.11b mode: DSSS (1, 2, 5.5 and 11 Mbps) IEEE 802.11g mode: OFDM (6, 9, 12, 18, 24, 36, 48 and 54 Mbps) IEEE 802.11n HT 20 mode: OFDM (6.5, 13, 19.5, 26, 39, 52, 58.5, 65.0Mbps)
Number of Channels	IEEE 802.11b/g mode: 11 Channels IEEE 802.11n HT 20 mode: 11 Channels
Antenna Specification	ethertronics / Salix SMC-1B PCB Antenna / Gain: -2.5dBi

Remark:

1. The sample selected for test was engineering sample that approximated to production product and was provided by manufacturer.
2. This submittal(s) (test report) is intended for FCC ID: **2ABDZ61SMC01** filing to comply with Section 15.207, 15.209 and 15.247 of the FCC Part 15, Subpart C Rules.



3. TEST METHODOLOGY

The tests documented in this report were performed in accordance with ANSI C63.4: 2009 and FCC CFR 47 Part 15.207, 15.209, 15.247, KDB558074.

3.1 EUT CONFIGURATION

The EUT configuration for testing is installed on RF field strength measurement to meet the Commissions requirement and operating in a manner that intends to maximize its emission characteristics in a continuous normal application.

3.2 EUT EXERCISE

The EUT was operated in the engineering mode to fix the TX frequency that was for the purpose of the measurements.

According to its specifications, the EUT must comply with the requirements of the Section 15.207, 15.209 and 15.247 under the FCC Rules Part 15 Subpart C.

3.3 GENERAL TEST PROCEDURES

Conducted Emissions

The EUT is placed on the turntable, which is 0.8 m above ground plane. According to the requirements in Section 13.1.4.1 of ANSI C63.4 Conducted emissions from the EUT measured in the frequency range between 0.15 MHz and 30MHz using CISPR Quasi-peak and average detector modes.

Radiated Emissions

The EUT is placed on a turn table, which is 0.8 m above ground plane. The turntable shall rotate 360 degrees to determine the position of maximum emission level. EUT is set 3m away from the receiving antenna, which varied from 1m to 4m to find out the highest emission. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical. In order to find out the maximum emissions, exploratory radiated emission measurements were made according to the requirements in Section 13.1.4.1 of ANSI C63.4.



3.4 FCC PART 15.205 RESTRICTED BANDS OF OPERATIONS

- (a) Except as shown in paragraph (d) of this section, only spurious emissions are permitted in any of the frequency bands listed below:

MHz	MHz	MHz	GHz
0.090 - 0.110	16.42 - 16.423	399.9 - 410	4.5 - 5.15
¹ 0.495 - 0.505	16.69475 - 16.69525	608 - 614	5.35 - 5.46
2.1735 - 2.1905	16.80425 - 16.80475	960 - 1240	7.25 - 7.75
4.125 - 4.128	25.5 - 25.67	1300 - 1427	8.025 - 8.5
4.17725 - 4.17775	37.5 - 38.25	1435 - 1626.5	9.0 - 9.2
4.20725 - 4.20775	73 - 74.6	1645.5 - 1646.5	9.3 - 9.5
6.215 - 6.218	74.8 - 75.2	1660 - 1710	10.6 - 12.7
6.26775 - 6.26825	108 - 121.94	1718.8 - 1722.2	13.25 - 13.4
6.31175 - 6.31225	123 - 138	2200 - 2300	14.47 - 14.5
8.291 - 8.294	149.9 - 150.05	2310 - 2390	15.35 - 16.2
8.362 - 8.366	156.52475 -	2483.5 - 2500	17.7 - 21.4
8.37625 - 8.38675	156.52525	2655 - 2900	22.01 - 23.12
8.41425 - 8.41475	156.7 - 156.9	3260 - 3267	23.6 - 24.0
12.29 - 12.293	162.0125 - 167.17	3332 - 3339	31.2 - 31.8
12.51975 - 12.52025	167.72 - 173.2	3345.8 - 3358	36.43 - 36.5
12.57675 - 12.57725	240 - 285	3600 - 4400	(²)
13.36 - 13.41	322 - 335.4		

¹ Until February 1, 1999, this restricted band shall be 0.490-0.510 MHz.

² Above 38.6

- (b) Except as provided in paragraphs (d) and (e), the field strength of emissions appearing within these frequency bands shall not exceed the limits shown in Section 15.209. At frequencies equal to or less than 1000 MHz, compliance with the limits in Section 15.209 shall be demonstrated using measurement instrumentation employing a CISPR quasi-peak detector. Above 1000 MHz, compliance with the emission limits in Section 15.209 shall be demonstrated based on the average value of the measured emissions. The provisions in Section 15.35 apply to these measurements.



3.5 DESCRIPTION OF TEST MODES

The EUT (model: SMC-1) had been tested under operating condition.

Software used to control the EUT for staying in continuous transmitting mode was programmed.

After verification, all tests were carried out with the worst case test modes as shown below except radiated spurious emission below 1GHz and power line conducted emissions below 30MHz, which worst case was in normal link mode only.

IEEE 802.11b mode:

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 1Mbps data rate were chosen for full testing.

IEEE 802.11g mode:

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 6Mbps data rate were chosen for full testing.

IEEE 802.11n HT 20 mode:

Channel Low (2412MHz), Channel Mid (2437MHz) and Channel High (2462MHz) with 6.5Mbps data rate were chosen for full testing.

The field strength of spurious emission was measured in the following position: EUT stand-up position (Z axis), lie-down position (X, Y axis). The worst emission was found in lie-down position (Y axis) and the worst case was recorded.



4. INSTRUMENT CALIBRATION

4.1 MEASURING INSTRUMENT CALIBRATION

The measuring equipment, which was utilized in performing the tests documented herein, has been calibrated in accordance with the manufacturer's recommendations for utilizing calibration equipment, which is traceable to recognized national standards.

4.2 MEASUREMENT EQUIPMENT USED

Equipment Used for Emissions Measurement

Remark: Each piece of equipment is scheduled for calibration once a year.

Conducted Emissions Test Site				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	US42510252	11/23/2015
Thermostatic/Hygrosatic Chamber	TAICHY	MHG-150LF	930619	10/07/2015
DC Power Supply	ABM	8301HD	D011531	N.C.R
Power Meter	Anritsu	ML2495A	1012009	06/03/2015
Power Sensor	Anritsu	MA2411A	0917072	06/03/2015

Wugu 966 Chamber A				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
Spectrum Analyzer	Agilent	E4446A	US42510268	01/24/2015
EMI Test Receiver	R&S	ESCI	100064	05/30/2015
Bilog Antenna	Sunol Sciences	JB3	A030105	08/19/2015
Horn Antenna	EMCO	3117	00055165	02/04/2015
Turn Table	CCS	CC-T-1F	N/A	N.C.R
Antenna Tower	CCS	CC-A-1F	N/A	N.C.R
Controller	CCS	CC-C-1F	N/A	N.C.R
Test S/W	EZ-EMC (CCS-3A1RE)			

Conducted Emission Room # B				
Name of Equipment	Manufacturer	Model	Serial Number	Calibration Due
EMI Test Receiver	R&S	ESCI	101073	09/18/2015
LISN	R&S	ENV216	101054	05/18/2015
LISN	SCHWARZBECK	NSLK 8127	8127-541	11/25/2015
Capacitive Voltage Probe	FCC	F-CVP-1	100185	03/09/2015
Test S/W	CCS-3A1-CE			



4.3 MEASUREMENT UNCERTAINTY

PARAMETER	UNCERTAINTY
Powerline Conducted Emission	+/- 1.2575
3M Semi Anechoic Chamber / <200M	+/- 4.0138
3M Semi Anechoic Chamber / 200M~1000M	+/- 3.9483
3M Semi Anechoic Chamber / 1G~8G	+/- 2.5975
3M Semi Anechoic Chamber / 8G~18G	+/- 2.6112
3M Semi Anechoic Chamber / 18G~26G	+/- 2.7389
3M Semi Anechoic Chamber / 26G~40G	+/- 2.9683

Remark: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of $k=2$.



5. FACILITIES AND ACCREDITATIONS

5.1 FACILITIES

All measurement facilities used to collect the measurement data are located at

☒ No.199, Chunghsen Road, Hsintien City, Taipei Hsien, Taiwan, R.O.C.

Tel: 886-2-2217-0894 / Fax: 886-2-2217-1029

☒ No.11, Wugong 6th Rd., Wugu Dist., New Taipei City 24891, Taiwan. (R.O.C.)

Tel: 886-2-2299-9720 / Fax: 886-2-2298-4045

☐ No.81-1, Lane 210, Bade 2nd Rd., Lujhu Township, Taoyuan County 33841, TAIWAN, R.O.C.

Tel: 886-3-324-0332 / Fax: 886-3-324-5235

The sites are constructed in conformance with the requirements of ANSI C63.7, ANSI C63.4 and CISPR Publication 22.

5.2 EQUIPMENT

Radiated emissions are measured with one or more of the following types of linearly polarized antennas: tuned dipole, biconical, log periodic, bi-log, and/or ridged waveguide, horn. Spectrum analyzers with pre-selectors and quasi-peak detectors are used to perform radiated measurements.




Conducted emissions are measured with Line Impedance Stabilization Networks and EMI Test Receivers.

Calibrated wideband preamplifiers, coaxial cables, and coaxial attenuators are also used for making measurements.

All receiving equipment conforms to CISPR Publication 16-1, "Radio Interference Measuring Apparatus and Measurement Methods."



5.3 TABLE OF ACCREDITATIONS AND LISTINGS

Country	Agency	Scope of Accreditation	Logo
USA	FCC	3M Semi Anechoic Chamber (FCC MRA: TW1039) to perform FCC Part 15 measurements	 FCC MRA: TW1039
Taiwan	TAF	LP0002, RTTE01, FCC Method-47 CFR Part 15 Subpart C, D, E, RSS-210, RSS-310 IDA TS SRD, AS/NZS 4268, AS/NZS 4771, TS 12.1 & 12.2, ETSI EN 300 440-1, ETSI EN 300 440-2, ETSI EN 300 328, ETSI EN 300 220-1, ETSI EN 300 220-2, ETSI EN 301 893, ETSI EN 301 489-1/3/7/17 FCC OET Bulletin 65 + Supplement C, EN 50360, EN 50361, EN 50371, RSS 102, EN 50383, EN 50385, EN 50392, IEC 62209, CNS 14958-1, CNS 14959 FCC Method -47 CFR Part 15 Subpart B IEC / EN 61000-3-2, IEC / EN 61000-3-3, IEC / EN 61000-4-2/3/4/5/6/8/11	
Canada	Industry Canada	3M Semi Anechoic Chamber (IC 2324G-1 / IC 2324G-2) to perform	 IC 2324G-1 IC 2324G-2

* No part of this report may be used to claim or imply product endorsement by A2LA or any agency of the US Government.



6. SETUP OF EQUIPMENT UNDER TEST

6.1 SETUP CONFIGURATION OF EUT

See test photographs attached in Appendix II for the actual connections between EUT and support equipment.

6.2 SUPPORT EQUIPMENT

No	Device Type	Brand	Model	Series No.	FCC ID	Data Cable	Power Cord
1.	Notebook PC	HP	dv6-1332TX	CNF9491GPS	PD9112BNHU	N/A	AC I/P: Unshielded, 1.8m DC O/P: Unshielded, 1.8m with a core
2	Notebook PC	IBM	7663 (T61)	L3E9812	N/A	N/A	AC I/P: Unshielded, 1.8m DC O/P: Unshielded, 1.8m with a core

Remark:

- 1. All the equipment/cables were placed in the worst-case configuration to maximize the emission during the test.*
- 2. Grounding was established in accordance with the manufacturer's requirements and conditions for the intended use.*




7. FCC PART 15.247 REQUIREMENTS

7.1 6DB BANDWIDTH

LIMIT

According to §15.247(a)(2), systems using digital modulation techniques may operate in the 902 - 928 MHz, 2400 - 2483.5 MHz, and 5725 - 5850 MHz bands. The minimum 6dB bandwidth shall be at least 500 kHz.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the spectrum analyzer. Set the RBW=100kHz the emission bandwidth, VBW $\geq 3 \times$ RBW, Detector = Peak, Trace mode = max hold, Sweep = auto couple. Measure the maximum width of the emission that is constrained by the frequencies associated with the two amplitude points (upper and lower) that are attenuated by 6dB relative to the maximum level measured in the fundamental emission.

TEST RESULTS

No non-compliance noted

**Test Data****Test mode: IEEE 802.11b mode**

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (kHz)	Result
Low	2412	8.25	>500	PASS
Mid	2437	8.25		PASS
High	2462	8.25		PASS

Test mode: IEEE 802.11g mode

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (kHz)	Result
Low	2412	16.0834	>500	PASS
Mid	2437	16		PASS
High	2462	16		PASS


Test mode: IEEE 802.11n HT 20 mode

Channel	Frequency (MHz)	6dB Bandwidth (MHz)	Limit (kHz)	Result
Low	2412	17.3333	>500	PASS
Mid	2437	17.25		PASS
High	2462	17.25		PASS



IEEE 802.11b mode

6dB Bandwidth (CH Low)




No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2407.8333	1.72	1.85	-0.13
2	2411.5000	7.85	1.85	6.00
3	2416.0833	1.75	1.85	-0.10

No.		Δ Frequency(MHz)	Δ Level(dB)
1	mk3-mk1	8.25	0.03



6dB Bandwidth (CH Mid)




No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2432.8333	1.31	1.44	-0.13
2	2436.5000	7.44	1.44	6.00
3	2441.0833	1.41	1.44	-0.03

No.		Δ Frequency(MHz)	Δ Level(dB)
1	mk3-mk1	8.25	0.1



6dB Bandwidth (CH High)




No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2457.8333	1.16	1.31	-0.15
2	2461.4167	7.31	1.31	6.00
3	2466.0833	1.26	1.31	-0.05

No.		Δ Frequency(MHz)	Δ Level(dB)
1	mk3-mk1	8.25	0.1



IEEE 802.11g mode

6dB Bandwidth (CH Low)




No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2403.8333	-0.83	-0.01	-0.82
2	2413.0000	5.99	-0.01	6.00
3	2419.9167	-0.14	-0.01	-0.13

No.		Δ Frequency(MHz)	Δ Level(dB)
1	mk3-mk1	16.0834	0.69



6dB Bandwidth (CH Mid)




No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2429.0000	-0.10	0.06	-0.16
2	2437.9167	6.06	0.06	6.00
3	2445.0000	-0.63	0.06	-0.69

No.		Δ Frequency(MHz)	Δ Level(dB)
1	mk3-mk1	16	-0.53



6dB Bandwidth (CH High)




No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2453.9167	-0.29	-0.22	-0.07
2	2461.0833	5.78	-0.22	6.00
3	2469.9167	-0.52	-0.22	-0.30

No.		Δ Frequency(MHz)	Δ Level(dB)
1	mk3-mk1	16	-0.23



IEEE 802.11n HT 20 mode

6dB Bandwidth (CH Low)




No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2403.2500	-0.88	-0.47	-0.41
2	2411.2500	5.53	-0.47	6.00
3	2420.5833	-0.61	-0.47	-0.14

No.		Δ Frequency(MHz)	Δ Level(dB)
1	mk3-mk1	17.3333	0.27



6dB Bandwidth (CH Mid)




No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2428.3333	-1.12	-1.04	-0.08
2	2436.0000	4.96	-1.04	6.00
3	2445.5833	-1.21	-1.04	-0.17

No.		Δ Frequency(MHz)	Δ Level(dB)
1	mk3-mk1	17.25	-0.09



6dB Bandwidth (CH High)



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2453.3333	-0.84	-0.75	-0.09
2	2461.0000	5.25	-0.75	6.00
3	2470.5833	-1.09	-0.75	-0.34

No.		Δ Frequency(MHz)	Δ Level(dB)
1	mk3-mk1	17.25	-0.25




7.2 PEAK POWER

LIMIT

The maximum peak output power of the intentional radiator shall not exceed the following:

1. According to §15.247(b)(3), for systems using digital modulation in the bands of 902-928 MHz, 2400-2483.5 MHz, and 5725-5850 MHz: 1 Watt.
2. According to §15.247(b)(4), the conducted output power limit specified in paragraph (b) of this section is based on the use of antennas with directional gains that do not exceed 6 dBi. Except as shown in paragraph (c) of this section, if transmitting antennas of directional gain greater than 6 dBi are used, the conducted output power from the intentional radiator shall be reduced below the stated values in paragraphs (b)(1), (b)(2), and (b)(3) of this section, as appropriate, by the amount in dB that the directional gain of the antenna exceeds 6 dBi.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the Power Meter. The Power Meter is set to the peak power detection.

TEST RESULTS

No non-compliance noted

**Test Data****Test mode: IEEE 802.11b mode**

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2412	*17.47	0.0558	1.00	PASS
Mid	2437	17.03	0.0505		PASS
High	2462	17.23	0.0528		PASS

Test mode: IEEE 802.11g mode

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2412	*21.93	0.1560	1.00	PASS
Mid	2437	21.36	0.1368		PASS
High	2462	21.63	0.1455		PASS

Test mode: IEEE 802.11n HT 20 mode

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)	Limit (W)	Result
Low	2412	21.46	0.1400	1.00	PASS
Mid	2437	21.32	0.1355		PASS
High	2462	*21.51	0.1416		PASS




7.3 AVERAGE POWER

LIMIT

None; for reporting purposes only.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to the Power Meter. The Power Meter is set to the average power detection.



TEST RESULTS

No non-compliance noted

Test Data

Test mode: IEEE 802.11b mode

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)
Low	2412	14.51	0.0282
Mid	2437	14.02	0.0252
High	2462	14.17	0.0261

Test mode: IEEE 802.11g mode

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)
Low	2412	12.72	0.0187
Mid	2437	12.32	0.0171
High	2462	12.33	0.0171

Test mode: IEEE 802.11n HT 20 mode

Channel	Frequency (MHz)	Output Power (dBm)	Output Power (W)
Low	2412	12.02	0.0159
Mid	2437	11.56	0.0143
High	2462	11.68	0.0147




7.4 BAND EDGES MEASUREMENT

LIMIT


According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

Test Configuration

For Radiated



For Conducted





TEST PROCEDURE

For Radiated

1. The EUT is placed on a turntable, which is 0.8m above the ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emission.
4. Set the spectrum analyzer in the following setting in order to capture the lower and upper band-edges of the emission:
 - (a) PEAK: RBW=1MHz / VBW=3MHz / Sweep=AUTO
 - (b) AVERAGE: RBW=1MHz / VBW= 10Hz / Sweep=AUTO
5. Repeat the procedures until all the PEAK and AVERAGE versus POLARIZATION are measured.

For Conducted

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz.


TEST RESULTS

Refer to attach spectrum analyzer data chart.



Band Edges (IEEE 802.11b mode / CH Low)


Polarity: Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)	
1	2385.680	64.61	-3.81	60.80	74.00	-13.20	100	236	peak
2	2385.680	56.36	-3.81	52.55	54.00	-1.45	100	236	AVG



Polarity: Horizontal




No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)	
1	2385.280	60.18	-3.81	56.37	74.00	-17.63	100	230	peak
2	2385.280	50.99	-3.81	47.18	54.00	-6.82	100	230	AVG



Band Edges (IEEE 802.11b mode / CH High)


Polarity: Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)	Remark
1	2485.909	54.95	-3.25	51.70	74.00	-22.30	100	9	peak
2	2485.909	43.44	-3.25	40.19	54.00	-13.81	100	9	AVG



Polarity: Horizontal




No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)	Remark
1	2487.245	53.58	-3.24	50.34	74.00	-23.66	100	288	peak
2	2487.245	41.99	-3.24	38.75	54.00	-15.25	100	288	AVG



Band Edges (IEEE 802.11g mode / CH Low)


Polarity: Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)	
1	2388.320	73.11	-3.79	69.32	74.00	-4.68	100	277	peak
2	2388.320	55.64	-3.79	51.85	54.00	-2.15	100	277	AVG



Polarity: Horizontal




No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)	
1	2389.840	67.79	-3.77	64.02	74.00	-9.98	100	17	peak
2	2389.840	51.41	-3.77	47.64	54.00	-6.36	100	17	AVG



Band Edges (IEEE 802.11g mode / CH High)


Polarity: Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)	
1	2483.533	61.43	-3.27	58.16	74.00	-15.84	100	320	peak
2	2483.533	45.64	-3.27	42.37	54.00	-11.63	100	320	AVG



Polarity: Horizontal




No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)	
1	2483.682	63.23	-3.27	59.96	74.00	-14.04	100	105	peak
2	2483.682	45.99	-3.27	42.72	54.00	-11.28	100	105	AVG



Band Edges (IEEE 802.11n HT 20 mode / CH Low)


Polarity: Vertical



No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)	
1	2388.800	76.39	-3.78	72.61	74.00	-1.39	100	219	peak
2	2388.800	56.22	-3.78	52.44	54.00	-1.56	100	219	AVG



Polarity: Horizontal




No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)	
1	2388.000	68.32	-3.79	64.53	74.00	-9.47	100	171	peak
2	2388.000	52.71	-3.79	48.92	54.00	-5.08	100	171	AVG



Band Edges (IEEE 802.11n HT 20 mode / CH High)


Polarity: Vertical



No.	Frequency (MHz)	Reading (dBuV)	Correct Factor(dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Height (cm)	Degree (°)	Remark
1	2483.517	66.09	-3.27	62.82	74.00	-11.18	100	277	peak
2	2483.517	45.89	-3.27	42.62	54.00	-11.38	100	277	AVG



Polarity: Horizontal




No.	Frequency	Reading	Correct	Result	Limit	Margin	Height	Degree	Remark
	(MHz)	(dBuV)	Factor(dB/m)	(dBuV/m)	(dBuV/m)	(dB)	(cm)	(°)	
1	2483.698	63.11	-3.27	59.84	74.00	-14.16	100	105	peak
2	2483.698	44.50	-3.27	41.23	54.00	-12.77	100	105	AVG



Conducted Band Edge

IEEE 802.11b


(CH Low)



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2396.0000	-35.49	-12.24	-23.25
2	2411.5000	7.76	-12.24	20.00



(CH High)




No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2461.5000	6.76	-13.24	20.00
2	2489.0000	-48.40	-13.24	-35.16



IEEE 802.11g


(CH Low)



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2399.1250	-31.61	-17.18	-14.43
2	2413.2500	2.82	-17.18	20.00



(CH High)




No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2463.2500	2.31	-17.69	20.00
2	2483.5000	-43.93	-17.69	-26.24



IEEE 802.11n HT 20 mode


(CH Low)



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2399.7500	-33.11	-17.65	-15.46
2	2413.2500	2.35	-17.65	20.00



(CH High)



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2463.2500	1.54	-18.46	20.00
2	2483.8750	-45.42	-18.46	-26.96




7.5 PEAK POWER SPECTRAL DENSITY

LIMIT

1. According to §15.247(e), for digitally modulated systems, the power spectral density conducted from the intentional radiator to the antenna shall not be greater than 8 dBm in any 3 kHz band during any time interval of continuous transmission.
2. According to §15.247(f), the digital modulation operation of the hybrid system, with the frequency hopping turned off, shall comply with the power density requirements of paragraph (d) of this section.

Test Configuration



TEST PROCEDURE

The transmitter output is connected to a spectrum analyzer. Set the RBW = 100 kHz, VBW \geq 300 kHz, span to 1.5 times the DTS bandwidth, Detector = peak, Trace mode = max hold, Sweep = auto couple. Use the peak marker function to determine the maximum amplitude level within the RBW. If measured value exceeds limit, reduce RBW (no less than 3 kHz).



TEST RESULTS

No non-compliance noted

Test Data

Test mode: IEEE 802.11b mode

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	2412	3.73	8.00	PASS
Mid	2437	3.00		PASS
High	2462	4.68		PASS

Test mode: IEEE 802.11g mode

Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	2412	-1.65	8.00	PASS
Mid	2437	-1.46		PASS
High	2462	-2.52		PASS

Test mode: IEEE 802.11n HT 20 mode


Channel	Frequency (MHz)	PPSD (dBm)	Limit (dBm)	Result
Low	2412	-2.17	8.00	PASS
Mid	2437	-1.95		PASS
High	2462	-2.43		PASS



Test Plot

IEEE 802.11b mode


PPSD (CH Low)



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2410.4750	3.73	8.00	-4.27




PPSD (CH Mid)



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2437.7000	3.00	8.00	-5.00



PPSD (CH High)




No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2461.4750	4.68	8.00	-3.32



IEEE 802.11g mode


PPSD (CH Low)



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2412.6000	-1.65	8.00	-9.65




PPSD (CH Mid)



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2436.7333	-1.46	8.00	-9.46



PPSD (CH High)




No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2460.7333	-2.52	8.00	-10.52



IEEE 802.11n HT 20 mode


PPSD (CH Low)



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2411.3333	-2.17	8.00	-10.17




PPSD (CH Mid)



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2436.3333	-1.95	8.00	-9.95



PPSD (CH High)



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2461.3333	-2.43	8.00	-10.43




7.6 SPURIOUS EMISSIONS

7.6.1 Conducted Measurement

LIMIT

According to §15.247(d), in any 100 kHz bandwidth outside the frequency bands in which the spread spectrum intentional radiator is operating, the radio frequency power that is produced by the intentional radiator shall be at least 20 dB below that in the 100 kHz bandwidth within the band that contains the highest level of the desired power, based on either an RF conducted or a radiated measurement, provided the transmitter demonstrates compliance with the peak conducted power limits. In addition, radiated emissions which fall in the restricted bands, as defined in §15.205(a), must also comply with the radiated emission limits specified in 15.209(a) (see Section 15.205(c)).

Test Configuration



TEST PROCEDURE

Conducted RF measurements of the transmitter output were made to confirm that the EUT antenna port conducted emissions meet the specified limit and to identify any spurious signals that require further investigation or measurements on the radiated emissions site.

The transmitter output is connected to the spectrum analyzer. The resolution bandwidth is set to 100 kHz. The video bandwidth is set to 100 kHz.

Measurements are made over the 30MHz to 26GHz range with the transmitter set to the lowest, middle, and highest channels.

TEST RESULTS


No non-compliance noted



Test Plot

IEEE 802.11b mode


CH Low



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2377.1800	-45.46	-12.61	-32.85
2	7246.3300	-38.15	-12.61	-25.54




CH Mid



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	1228.5600	-50.06	-12.63	-37.43
2	7321.2400	-43.03	-12.63	-30.40



CH High




No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	1228.5600	-51.06	-12.91	-38.15
2	7396.1500	-44.29	-12.91	-31.38



IEEE 802.11g mode


CH Low



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2377.1800	-40.88	-17.72	-23.16
2	7246.3300	-42.93	-17.72	-25.21




CH Mid



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2327.2400	-51.86	-17.61	-34.25
2	7321.2400	-45.87	-17.61	-28.26



CH High




No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2302.2700	-53.22	-17.08	-36.14
2	24975.0300	-49.23	-17.08	-32.15



IEEE 802.11n HT 20 mode


CH Low



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2377.1800	-42.94	-17.68	-25.26
2	7246.3300	-45.30	-17.68	-27.62




CH Mid



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2327.2400	-52.39	-17.90	-34.49
2	7321.2400	-48.74	-17.90	-30.84



CH High



No.	Frequency(MHz)	Result(dBm)	Limit(dBm)	Margin(dBm)
1	2302.2700	-52.94	-17.80	-35.14
2	7371.1800	-50.05	-17.80	-32.25



7.7 RADIATED EMISSIONS

LIMIT

1. According to §15.209(a), except as provided elsewhere in this Subpart, the emissions from an intentional radiator shall not exceed the field strength levels specified in the following table:

Frequency (MHz)	Field Strength (μV/m)	Measurement Distance (m)
0.009 - 0.490	2400/F(kHz)	300
0.490 - 1.705	24000/F(kHz)	30
1.705 – 30.0	30	30
30-88	100	3
88-216	150	3
216-960	200	3
Above 960	500	3

Remark: Except as provided in paragraph (g), fundamental emissions from intentional radiators operating under this Section shall not be located in the frequency bands 54-72 MHz, 76-88 MHz, 174-216 MHz or 470-806 MHz. However, operation within these frequency bands is permitted under other sections of this Part, e.g., Sections 15.231 and 15.241.


2. In the emission table above, the tighter limit applies at the band edges.

Frequency (MHz)	Field Strength (μV/m at 3-meter)	Field Strength (dBμV/m at 3-meter)
0.009 - 0.490	2400/F(kHz) +80	20LOG((2400/F(kHz))+80)
0.490 - 1.705	24000/F(kHz) +40	20LOG((24000/F(kHz))+40)
1.705 – 30.0	30	69.54
30-88	100	40
88-216	150	43.5
216-960	200	46
Above 960	500	54




Test Configuration

9kHz ~ 30MHz




30MHz ~ 1GHz





Above 1 GHz





TEST PROCEDURE

1. The EUT is placed on a turntable, which is 0.8m above ground plane.
2. The turntable shall be rotated for 360 degrees to determine the position of maximum emission level.
3. EUT is set 3m away from the receiving antenna, which is varied from 1m to 4m to find out the highest emissions.
4. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
5. And also, each emission was to be maximized by changing the polarization of receiving antenna both horizontal and vertical.
6. Set the spectrum analyzer in the following setting as:
Below 1GHz:
RBW=100kHz / VBW=300kHz / Sweep=AUTO
Above 1GHz:
(a) PEAK: RBW=1MHz / VBW=3MHz / Sweep=AUTO
(b) AVERAGE: RBW=1MHz / VBW=10Hz / Sweep=AUTO
7. Repeat above procedures until the measurements for all frequencies are complete.

**TEST RESULTS****Below 1GHz****Operation Mode:** Normal Link**Test Date:** March 3, 2015**Temperature:** 27°C**Tested by:** Andy Shi**Humidity:** 53% RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction Factor (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
156.1000	54.10	-18.16	35.94	43.50	-7.56	peak	V
252.1300	48.21	-18.25	29.96	46.00	-16.04	peak	V
494.6300	44.59	-11.92	32.67	46.00	-13.33	peak	V
626.5500	48.55	-9.87	38.68	46.00	-7.32	peak	V
759.4400	39.29	-7.79	31.50	46.00	-14.50	peak	V
891.3600	39.61	-6.27	33.34	46.00	-12.66	peak	V
59.1000	57.06	-23.85	33.21	40.00	-6.79	peak	H
240.4900	57.51	-18.60	38.91	46.00	-7.09	peak	H
408.3000	50.53	-13.79	36.74	46.00	-9.26	peak	H
560.5900	46.13	-10.90	35.23	46.00	-10.77	peak	H
693.4800	47.90	-8.86	39.04	46.00	-6.96	peak	H
890.3900	42.60	-6.28	36.32	46.00	-9.68	peak	H

Remark:

1. No emission found between lowest internal used/generated frequency to 30MHz (9kHz~30MHz)
2. Radiated emissions measured in frequency range from 30 MHz to 1000MHz were made with an instrument using peak/quasi-peak detector mode.
3. Quasi-peak test would be performed if the peak result were greater than the quasi-peak limit or as required by the applicant.
4. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
5. $\text{Margin (dB)} = \text{Result (dBuV/m)} - \text{Limit (dBuV/m)}$.

**Above 1 GHz****Operation Mode:** TX / IEEE 802.11b / CH Low**Test Date:** March 3, 2015**Temperature:** 27°C**Tested by:** Andy Shi**Humidity:** 53 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1536.000	51.25	-7.34	43.91	74.00	-30.09	peak	V
7235.000	40.88	10.64	51.52	74.00	-22.48	peak	V
NA							
1536.000	55.38	-7.34	48.04	74.00	-25.96	peak	H
3620.000	44.36	-0.40	43.96	74.00	-30.04	peak	H
7235.000	40.96	10.64	51.60	74.00	-22.40	peak	H
NA							

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. $\text{Margin (dB)} = \text{Result (dBuV/m)} - \text{limit (dBuV/m)}$.

**Operation Mode:** TX / IEEE 802.11b / CH Mid**Test Date:** March 3, 2015**Temperature:** 27°C**Tested by:** Andy Shi**Humidity:** 53 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1536.000	56.15	-7.34	48.81	74.00	-25.19	peak	V
7310.000	44.81	10.71	55.52	74.00	-18.48	peak	V
7310.000	42.25	10.71	52.96	54.00	-1.04	AVG	V
NA							
1536.000	58.20	-7.34	50.86	74.00	-23.14	peak	H
7310.000	41.63	10.71	52.34	74.00	-21.66	peak	H
7310.000	39.84	10.71	50.55	54.00	-3.45	AVG	H
NA							

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. $\text{Margin (dB)} = \text{Result (dBuV/m)} - \text{limit (dBuV/m)}$.

**Operation Mode:** TX / IEEE 802.11b / CH High**Test Date:** March 3, 2015**Temperature:** 27°C**Tested by:** Andy Shi**Humidity:** 53 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1536.000	55.62	-7.34	48.28	74.00	-25.72	peak	V
7385.000	45.02	10.79	55.81	74.00	-18.19	peak	V
7385.000	41.39	10.79	52.18	54.00	-1.82	AVG	V
NA							
1536.000	57.24	-7.34	49.90	74.00	-24.10	peak	H
7385.000	38.50	10.79	49.29	74.00	-24.71	peak	H
NA							

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser; with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. $\text{Margin (dB)} = \text{Result (dBuV/m)} - \text{limit (dBuV/m)}$.

**Operation Mode:** TX / IEEE 802.11g / CH Low**Test Date:** March 3, 2015**Temperature:** 27°C**Tested by:** Andy Shi**Humidity:** 53 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Pol. (H/V)
1536.000	56.82	-7.34	49.48	74.00	-24.52	peak	V
3315.000	44.78	-1.35	43.43	74.00	-30.57	peak	V
7235.000	38.05	10.64	48.69	74.00	-25.31	peak	V
NA							
1536.000	57.52	-7.34	50.18	74.00	-23.82	peak	H
7230.000	38.89	10.64	49.53	74.00	-24.47	peak	H
NA							

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser; with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. $\text{Margin (dB)} = \text{Result (dBuV/m)} - \text{limit (dBuV/m)}$.

**Operation Mode:** TX / IEEE 802.11g / CH Mid**Test Date:** March 3, 2015**Temperature:** 27°C**Tested by:** Andy Shi**Humidity:** 53 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Pol. (H/V)
1536.000	53.91	-7.34	46.57	74.00	-27.43	peak	V
7310.000	44.99	10.71	55.70	74.00	-18.30	peak	V
7310.000	38.66	10.71	49.37	54.00	-4.63	AVG	V
NA							
1536.000	56.84	-7.34	49.50	74.00	-24.50	peak	H
7300.000	41.11	10.70	51.81	74.00	-22.19	peak	H
NA							

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin>20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. $\text{Margin (dB)} = \text{Result (dBuV/m)} - \text{limit (dBuV/m)}$.

**Operation Mode:** TX / IEEE 802.11g / CH High**Test Date:** March 3, 2015**Temperature:** 27°C**Tested by:** Andy Shi**Humidity:** 53 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Pol. (H/V)
1536.000	57.32	-7.34	49.98	74.00	-24.02	peak	V
7395.000	46.26	10.80	57.06	74.00	-16.94	peak	V
7395.000	37.03	10.80	47.83	54.00	-6.17	AVG	V
NA							
1536.000	57.44	-7.34	50.10	74.00	-23.90	peak	H
7385.000	38.67	10.79	49.46	74.00	-24.54	peak	H
NA							

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. $\text{Margin (dB)} = \text{Result (dBuV/m)} - \text{limit (dBuV/m)}$.

**Operation Mode:** TX / IEEE 802.11n HT 20 mode / CH Low**Test Date:** March 3, 2015**Temperature:** 27°C**Tested by:** Andy Shi**Humidity:** 53 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1536.000	52.08	-7.34	44.74	74.00	-29.26	peak	V
7240.000	39.56	10.65	50.21	74.00	-23.79	peak	V
NA							
1536.000	51.93	-7.34	44.59	74.00	-29.41	peak	H
7235.000	39.65	10.64	50.29	74.00	-23.71	peak	H
NA							

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. $\text{Margin (dB)} = \text{Result (dBuV/m)} - \text{limit (dBuV/m)}$.

**Operation Mode:** TX / IEEE 802.11n HT 20 mode / CH Mid**Test Date:** March 3, 2015**Temperature:** 27°C**Tested by:** Andy Shi**Humidity:** 53 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant. Pol. (H/V)
1536.000	57.64	-7.34	50.30	74.00	-23.70	peak	V
7315.000	44.76	10.72	55.48	74.00	-18.52	peak	V
7315.000	39.89	10.72	50.61	54.00	-3.39	AVG	V
NA							
1536.000	59.00	-7.34	51.66	74.00	-22.34	peak	H
7300.000	39.91	10.70	50.61	74.00	-23.39	peak	H
NA							

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. Peak Margin (dB) = Peak result (dBuV/m) – Peak limit (dBuV/m).
Average Margin (dB) = Peak result (dBuV/m) – Average limit (dBuV/m).

**Operation Mode:** TX / IEEE 802.11n HT 20 mode / CH High**Test Date:** March 3, 2015**Temperature:** 27°C**Tested by:** Andy Shi**Humidity:** 53 % RH**Polarity:** Ver. / Hor.

Frequency (MHz)	Reading (dBuV)	Correction (dB/m)	Result (dBuV/m)	Limit (dBuV/m)	Margin (dB)	Remark	Ant.Pol. (H/V)
1722.000	50.74	-6.35	44.39	74.00	-29.61	peak	V
7385.000	46.49	10.79	57.28	74.00	-16.72	peak	V
7385.000	38.23	10.79	49.02	54.00	-4.98	AVG	V
NA							
1536.000	57.09	-7.34	49.75	74.00	-24.25	peak	H
7385.000	38.86	10.79	49.65	74.00	-24.35	peak	H
NA							

Remark:

1. Measuring frequencies from 1 GHz to the 10th harmonic of highest fundamental frequency.
2. Radiated emissions measured in frequency above 1000MHz were made with an instrument using peak/average detector mode.
3. Average test would be performed if the peak result were greater than the average limit or as required by the applicant.
4. Data of measurement within this frequency range shown " --- " in the table above means the reading of emissions are attenuated more than 20dB below the permissible limits or the field strength is too small to be measured.
5. Measurements above show only up to 6 maximum emissions noted, or would be lesser, with " N/A " remark, if no specific emissions from the EUT are recorded (ie: margin > 20dB from the applicable limit) and considered that's already beyond the background noise floor.
6. $\text{Margin (dB)} = \text{Result (dBuV/m)} - \text{limit (dBuV/m)}$.



7.8 POWERLINE CONDUCTED EMISSIONS

LIMIT

According to §15.207(a), except as shown in paragraphs (b) and (c) of this section, for an intentional radiator that is designed to be connected to the public utility (AC) power line, the radio frequency voltage that is conducted back onto the AC power line on any frequency or frequencies within the band 150 kHz to 30 MHz shall not exceed the limits in the following table, as measured using a 50 μ H/50 ohms line impedance stabilization network (LISN). Compliance with the provisions of this paragraph shall be based on the measurement of the radio frequency voltage between each power line and ground at the power terminal. The lower limit applies at the boundary between the frequency ranges.

Frequency Range (MHz)	Limits (dB μ V)	
	Quasi-peak	Average
0.15 to 0.50	66 to 56*	56 to 46*
0.50 to 5	56	46
5 to 30	60	50

* Decreases with the logarithm of the frequency.

Test Configuration

See test photographs attached in Appendix 1 for the actual connections between EUT and support equipment.

TEST PROCEDURE

1. The EUT was placed on a table, which is 0.8m above ground plane.
2. Maximum procedure was performed on the six highest emissions to ensure EUT compliance.
3. Repeat above procedures until all frequency measured were complete.

**TEST RESULTS**

The initial step in collecting conducted data is a spectrum analyzer peak scan of the measurement range. Significant peaks are then marked as shown on the following data page, and these signals are then quasi-peaked.

Test Data

Operation Mode: Normal Link **Test Date:** March 2, 2015
Temperature: 26°C **Tested by:** Terry Chang
Humidity: 60% RH

Freq. (MHz)	QP Reading (dBuV)	AV Reading (dBuV)	Corr. factor (dB/m)	QP Result (dBuV/m)	AV Result (dBuV/m)	QP Limit (dBuV)	AV Limit (dBuV)	QP Margin (dB)	AV Margin (dB)	Note
0.2060	41.43	21.83	9.62	51.05	31.45	63.37	53.37	-12.32	-21.92	L1
0.2580	34.69	18.74	9.62	44.31	28.36	61.50	51.50	-17.19	-23.14	L1
0.3140	33.13	20.61	9.62	42.75	30.23	59.86	49.86	-17.11	-19.63	L1
0.3460	27.13	9.36	9.62	36.75	18.98	59.06	49.06	-22.31	-30.08	L1
0.4580	28.79	15.13	9.62	38.41	24.75	56.73	46.73	-18.32	-21.98	L1
11.1980	25.11	15.43	9.86	34.97	25.29	60.00	50.00	-25.03	-24.71	L1
0.1500	32.95	8.69	9.66	42.61	18.35	66.00	56.00	-23.39	-37.65	L2
0.1660	28.97	8.14	9.66	38.63	17.80	65.16	55.16	-26.53	-37.36	L2
0.1900	43.24	27.00	9.67	52.91	36.67	64.04	54.04	-11.13	-17.37	L2
0.3100	32.83	20.79	9.67	42.50	30.46	59.97	49.97	-17.47	-19.51	L2
0.3300	32.47	20.03	9.67	42.14	29.70	59.45	49.45	-17.31	-19.75	L2
12.5000	35.96	23.30	9.92	45.88	33.22	60.00	50.00	-14.12	-16.78	L2


Remark:

1. Measuring frequencies from 0.15 MHz to 30MHz.
2. The emissions measured in frequency range from 0.15 MHz to 30MHz were made with an instrument using Quasi-peak detector and average detector.
3. The IF bandwidth of SPA between 0.15MHz and 30MHz was 10 kHz; the IF bandwidth of Test Receiver between 0.15MHz and 30MHz was 9 kHz;
4. L1 = Line One (Live Line) / L2 = Line Two (Neutral Line)



Test Plots

Conducted emissions (Line 1)



Conducted emissions (Line 2)

